Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY tel. +39 0584 383694 fax +39 0584 395182 www.cecchi.it info@cecchi.it

C-SYSTEMS 10 10 CFS comp. B FAST - SAFETY DATA SHEET march 2018- n° batch 099-AH rev.1/18



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : 10 10 CFS B Fast

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the : Adhesive

Substance/Mixture

1.3 Details of the supplier of the safety data sheet

Cecchi Gustavo & C. srl - Via M. Coppino 253,

55049 Viareggio (LU) ITALY www.cecchi.it - info@cecchi.it

Information in case of emergency: +39 0584 383694 - info@cecchi.it

From monday to friday office hours 8:30 – 12:30, 14:00 – 18:30

1.3 Emergency telephone number

+39 0584 383694

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Acute toxicity, Category 4 H302: Harmful if swallowed.

Skin corrosion, Category 1B H314: Causes severe skin burns and eye damage.

Serious eye damage, Category 1 H318: Causes serious eye damage.

Skin sensitisation, Category 1 H317: May cause an allergic skin reaction.

Chronic aquatic toxicity, Category 3 H412: Harmful to aquatic life with long lasting

effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms





Signal word Danger

Hazard statements : H302 Harmful if swallowed.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it

C-SYSTEMS 10 10 CFS comp. B FAST - SAFETY DATA SHEET march 2018- n° batch 099-AH rev.1/18

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.
H412 Harmful to aquatic life with long lasting

effects.

Precautionary statements : **Prevention**:

P261 Avoid breathing dust/ fume/ gas/ mist/

vapours/ spray.

P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/

eye protection/ face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off

immediately all contaminated clothing.

Rinse skin with water/shower.

P304 + P340 + P310 IF INHALED: Remove person tofresh

air and keep comfortable for breathing.

Immediately call a POISON

CENTER/doctor.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously

with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a

POISON CENTER/doctor.

Hazardous components which must be listed on the label:

4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with 3-aminomethyl-3,5,5

Amines, polyethylenepoly-, triethylenetetramine fraction

3-aminomethyl-3,5,5-trimethylcyclohexylamine

m-phenylenebis(methylamine)

2-piperazin-1-ylethylamine

2,4,6-tris(dimethylaminomethyl)phenol

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Amine Solution

Hazardous components

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY tel. +39 0584 383694 fax +39 0584 395182 www.cecchi.it info@cecchi.it



www.cecchi.it info@cecchi.it c-systems 10 10 CFS comp. B FAST – SAFETY DATA SHEET march 2018– n° batch 099-AH rev.1/18

Chemical name	CAS-No.	Classification	Concentration
	EC-No. Registration number	(REGULATION (EC) No 1272/2008)	(%)
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with 3-aminomethyl-3,5,5	38294-64-3	Acute Tox.4; H302 Acute Tox.4; H312 Skin Corr.1B; H314 Skin Sens.1; H317 Aquatic Chronic3; H412	>= 30 - < 50
benzyl alcohol	100-51-6 202-859-9 01-2119492630-38	Acute Tox.4; H302 Acute Tox.4; H332 Eye Irrit.2; H319	>= 25 - < 30
Amines, polyethylenepoly-, triethylenetetramine fraction	90640-67-8 292-588-2 01-2119487919-13	Acute Tox.4; H302 Acute Tox.4; H312 Skin Corr.1B; H314 Skin Sens.1B; H317 Aquatic Chronic3; H412	>= 5 - < 7
3-aminomethyl-3,5,5- trimethylcyclohexylamine	2855-13-2 220-666-8 01-2119514687-32	Acute Tox.4; H312 Acute Tox.4; H302 Skin Corr.1B; H314 Skin Sens.1; H317 Aquatic Chronic3; H412	>= 3 - < 5
m-phenylenebis(methylamine)	1477-55-0 216-032-5 01-2119480150-50	Acute Tox.4; H302 Acute Tox.4; H332 Skin Corr.1B; H314 Skin Sens.1B; H317 Aquatic Chronic3; H412	>= 2,5 - < 3
salicylic acid	69-72-7 200-712-3 01-2119472428-31	Acute Tox.4; H302 Eye Dam.1; H318	>= 1 - < 3
2-piperazin-1-ylethylamine	140-31-8 205-411-0 01-2119471486-30	Acute Tox.4; H302 Skin Corr.1B; H314 Skin Sens.1; H317 Aquatic Chronic3; H412 Acute Tox.3; H311 1; H318	>= 1 - < 2,5
2,4,6- tris(dimethylaminomethyl)phenol	90-72-2 202-013-9 01-2119560597-27	1C; H314 1; H318 Skin Sens.1B; H317	>= 1 - < 3
Toluene-4-sulphonic acid, monohydrate	6192-52-5	Skin Irrit.2; H315 Eye Irrit.2; H319 STOT SE3; H335	>= 1 - < 5

For explanation of abbreviations see section 16.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it

C-SYSTEMS 10 10 CFS comp. B FAST - SAFETY DATA SHEET march 2018- n° batch 099-AH rev.1/18



SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Show this safety data sheet to the doctor in attendance.

Keep warm and in a quiet place.

Take off all contaminated clothing immediately.

If inhaled : Move to fresh air.

Keep patient warm and at rest.

If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

If breathing is irregular or stopped, administer artificial

respiration.

In case of skin contact : Wash off immediately with soap and plenty of water.

Do NOT use solvents or thinners. If on clothes, remove clothes. Burns must be treated by a physician.

In case of eye contact : Rinse immediately with plenty of water, also under the eyelids,

for at least 15 minutes.

If eye irritation persists, consult a specialist. If easy to do, remove contact lens, if worn.

If swallowed : Do NOT induce vomiting.

If a person vomits when lying on his back, place him in the

recovery position.

Call a physician immediately.

Give small amounts of water to drink.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Burn

superficial burning sensation

Redness Severe irritation

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : The first aid procedure should be established in consultation

with the doctor responsible for industrial medicine.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Carbon dioxide (CO2)

Foam Dry powder Water mist

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it

C-SYSTEMS 10 10 CFS comp. B FAST - SAFETY DATA SHEET march 2018- n° batch 099-AH rev.1/18

Unsuitable extinguishing

media

: None known.

5.2 Special hazards arising from the substance or mixture

Specific hazards during

firefighting

: The pressure in sealed containers can increase under the

influence of heat.

Cool closed containers exposed to fire with water spray. Hazardous decomposition products formed under fire

conditions.

5.3 Advice for firefighters

Special protective equipment

for firefighters

: In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

Further information : In the event of fire and/or explosion do not breathe fumes.

Use extinguishing measures that are appropriate to local

circumstances and the surroundingenvironment. Immediately evacuate personnel to safe areas.

Prevent fire extinguishing water from contaminating surface

water or the ground water system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Refer to protective measures listed in sections 7 and 8.

Evacuate personnel to safe areas. Use personal protective equipment.

Ensure adequate ventilation.

Inform the responsible authorities in case of gas leakage, or of

entry into waterways, soil or drains.

6.2 Environmental precautions

Environmental precautions : Do not allow uncontrolled discharge of product into the

environment.

Try to prevent the material from entering drains or water

courses.

Local authorities should be advised if significant spillages

cannot be contained.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silicagel,

acid binder, universal binder, sawdust).

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to

local / national regulations (see section 13).

Pick up and transfer to properly labelled containers.



Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it

C-SYSTEMS 10 10 CFS comp. B FAST - SAFETY DATA SHEET march 2018- n° batch 099-AH rev.1/18



6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Provide sufficient air exchange and/or exhaust in work rooms.

Do not breathe vapours or spray mist.

Avoid inhalation, ingestion and contact with skin and eyes.

Wear personal protective equipment.

Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is

being used.

Advice on protection against

fire and explosion

: Keep away from open flames, hot surfaces and sources of

ignition.

: Provide adequate ventilation. Wash hands and face before Hygiene measures

breaks and immediately after handling the product.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: Keep containers tightly closed in a dry, cool and wellventilated place. Keep in properly labelled containers. To maintain product quality, do not store in heat or direct sunlight.

Further information on storage conditions

: Protect from moisture.

Advice on common storage : Keep away from isocyanates.

Do not store near acids.

Keep away from oxidizing agents.

Other data : Stable at normal ambient temperature and pressure.

7.3 Specific end use(s)

Specific use(s) : Consult the technical guidelines for the use of this

substance/mixture.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Contains no substances with occupational exposure limit values.

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

benzyl alcohol : End Use: Workers

Exposure routes: Inhalation

Potential health effects: Short-term exposure, Systemic effects

Value: 450 mg/m3 End Use: Workers

Exposure routes: Inhalation

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it

C-SYSTEMS 10 10 CFS comp. B FAST - SAFETY DATA SHEET march 2018- n° batch 099-AH rev.1/18



Potential health effects: Long-term exposure, Systemic effects

Value: 90 mg/m3 End Use: Workers

Exposure routes: Skin contact

Potential health effects: Short-term exposure, Systemic effects

Value: 47 mg/kg End Use: Workers

Exposure routes: Skin contact

Potential health effects: Long-term exposure, Systemic effects

Value: 9,5 mg/kg End Use: Consumers Exposure routes: Ingestion

Potential health effects: Short-term exposure, Systemic effects

Value: 25 mg/kg End Use: Consumers Exposure routes: Ingestion

Potential health effects: Long-term exposure, Systemic effects

Value: 5 mg/kg End Use: Consumers Exposure routes: Inhalation

Potential health effects: Short-term exposure, Systemic effects

Value: 40,55 mg/m3 End Use: Consumers Exposure routes: Inhalation

Potential health effects: Long-term exposure, Systemic effects

Value: 8,11 mg/m3 End Use: Consumers

Exposure routes: Skin contact

Potential health effects: Short-term exposure, Systemic effects

Value: 28,5 mg/kg End Use: Consumers

Exposure routes: Skin contact

Potential health effects: Long-term exposure, Systemic effects

Value: 5,7 mg/kg End Use: Workers

Amines, polyethylenepoly-, : End Use: Workers

triethylenetetramine fraction Exposure routes: Skin contact

Potential health effects: Long-term systemic effects

Value: 0,57 mg/kg End Use: Workers

Exposure routes: Inhalation

Potential health effects: Long-term systemic effects

Value: 1 mg/m3

End Use: Consumer use Exposure routes: Skin contact

Potential health effects: Long-term systemic effects

Value: 0,25 mg/kg End Use: Consumers Exposure routes: Inhalation

Potential health effects: Long-term systemic effects

Value: 0,29 mg/m3 End Use: Workers

Exposure routes: Inhalation

Potential health effects: Short-term exposure

Value: 5380 mg/m3 : End Use: Workers

Exposure routes: Skin contact

2-piperazin-1-ylethylamine

7 / 20

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it

C-SYSTEMS 10 10 CFS comp. B FAST - SAFETY DATA SHEET march 2018- n° batch 099-AH rev.1/18



Potential health effects: Short-term exposure, Systemic effects

Value: 20 mg/kg End Use: Workers

Exposure routes: Skin contact

Potential health effects: Short-term exposure, Local effects

Value: 0,04 mg/cm2 End Use: Workers

Exposure routes: Skin contact

Potential health effects: Long-term systemic effects

Value: 3,3 mg/kg End Use: Workers

Exposure routes: Inhalation

Potential health effects: Long-term systemic effects

Value: 3,6 mg/m3 End Use: Workers

Exposure routes: Skin contact

Potential health effects: Long-term local effects

Value: 0,006 mg/cm2 End Use: Consumers

Exposure routes: Skin contact

Potential health effects: Short-term exposure, Systemic effects

Value: 10 mg/kg End Use: Consumers Exposure routes: Inhalation

Potential health effects: Short-term exposure, Systemic effects

Value: 5,3 mg/m3 End Use: Consumers Exposure routes: Ingestion

Potential health effects: Short-term exposure, Systemic effects

Value: 1,5 mg/kg End Use: Workers

Exposure routes: Inhalation

Potential health effects: Short-term exposure, Systemic effects

Value: 21,4 mg/m3 End Use: Consumers

Exposure routes: Skin contact

Potential health effects: Short-term exposure, Local effects

Value: 0,02 mg/cm2 End Use: Consumers

Exposure routes: Skin contact

Potential health effects: Long-term systemic effects

Value: 1,7 mg/kg End Use: Consumers Exposure routes: Inhalation

Potential health effects: Long-term systemic effects

Value: 0,9 mg/m3 End Use: Consumers Exposure routes: Ingestion

Potential health effects: Long-term systemic effects

Value: 0,3 mg/kg End Use: Consumers

Exposure routes: Skin contact

Potential health effects: Long-term local effects

Value: 0,003 mg/cm2

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it

C-SYSTEMS 10 10 CFS comp. B FAST – SAFETY DATA SHEET march 2018– n° batch 099-AH rev.1/18

benzyl alcohol : Fresh water

Value: 1 mg/l Marine water Value: 0,1mg/l Fresh water sediment Value: 5,27 mg/kg Marine sediment

Soil

Value: 0,456 mg/kg Sewage treatment plant

Value: 39 mg/l Intermittent releases Value: 2,3 mg/l

Value: 0,527 mg/kg

Amines, polyethylenepoly-, triethylenetetramine fraction

: Sewage treatment plant

Value: 4,25 mg/l Fresh water Value: 0,135 mg/l Fresh water sediment Value: 2,08 mg/kg Marine water Value: 0,0027 mg/l Marine sediment Value: 0,123 mg/kg

Soil

Value: 1,67 mg/kg Intermittent releases Value: 0,2 mg/l : Fresh water

3-aminomethyl-3,5,5-trimethylcyclohexylamine

Value: 0,06 mg/l Marine water Value: 0,006 mg/l Intermittent releases Value: 0,23 mg/l Fresh water sediment Value: 5,784 mg/kg Marine sediment Value: 0,578 mg/kg Sewage treatment plant

Value: 3,18 mg/l

Soil

Value: 1,121 mg/kg

2-piperazin-1-ylethylamine

: Fresh water
Value: 0,058 mg/l
Marine water
Value: 0,0058 mg/l
Intermittent releases
Value: 0,58 mg/l
Fresh water sediment
Value: 215 mg/kg
Marine sediment
Value: 21,5 mg/kg

Soil

Value: 42,9 mg/kg Sewage treatment plant

Value: 250 mg/l



Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY tel. +39 0584 383694 fax +39 0584 395182 www.cecchi.it info@cecchi.it c-systems 10 10 CFS comp. B FAST – SAFETY DATA SHEET march 2018– n° batch 099-AH rev.1/18 С

8.2 Exposure controls

Engineering measures

Effective exhaust ventilation system effective ventilation in all processing areas

Personal protective equipment

Eye protection : Safety glasses with side-shields conforming to EN166

Do not wear contact lenses.

Ensure that eyewash stations and safety showers are close to

the workstation location.

Hand protection

Material : Chemical resistant gloves made of butyl rubber or nitrile

rubber category III according to EN374.

Skin and body protection : Protective suit

Respiratory protection : Use respirator when performing operations involving potential

exposure to vapour of the product.

The filter class for the respirator must be suitable for the

maximum expected contaminant concentration

(gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-

contained breathing apparatus must be used. Respirator with a vapour filter (EN 141)

Protective measures : Avoid contact with skin.

Wear suitable protective equipment.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : liquid

Colour : amber

Odour : ammoniacal

Odour Threshold : not determined

pH : not determined

Melting point/freezing point : Not applicable

: > 150 °C

Flash point : 100 °C

Evaporation rate : not determined

Upper explosion limit : Not applicable

Lower explosion limit : Not applicable

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182 www.cecchi.it info@cecchi.it C-SYSTEMS 10 10 CFS comp. B FAST – SAFETY DATA SHEET march 2018– n° batch 099-AH rev.1/18



Vapour pressure : Not applicable

Relative vapour density : not determined

Density : 1,02 g/cm3

Bulk density : not determined

Solubility(ies)

Solubility in other solvents : not determined

Partition coefficient: n-

octanol/water

: No data available

Auto-ignition temperature : Not applicable

Thermal decomposition : Method: No data available

Viscosity

: 450 - 650 mPa.s Viscosity, dynamic

Viscosity, kinematic : not determined

Explosive properties : Not applicable

Oxidizing properties : Not applicable

9.2 Other information

Surface tension : not determined

Sublimation point : Not applicable

SECTION 10: Stability and reactivity

10.1 Reactivity

Stable under recommended storage conditions.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Reacts with the following substances:

Acids

Strong oxidizing agents

10.4 Conditions to avoid

Conditions to avoid : No decomposition if used as directed.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it

C-SYSTEMS 10 10 CFS comp. B FAST – SAFETY DATA SHEET march 2018– n° batch 099-AH rev.1/18



Materials to avoid : Strong acids

Strong oxidizing agents

10.6 Hazardous decomposition products

Hazardous decomposition

products

: This product may release the following:

Nitrogen oxides (NOx) Carbon monoxide

Carbon dioxide (CO2)

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product:

Acute oral toxicity : Remarks: No data available

Acute toxicity estimate: 595,57 mg/kg

Method: Calculation method

: Acute toxicity estimate : > 5 mg/l Acute inhalation toxicity

Exposure time: 4 h

Test atmosphere: dust/mist Method: Calculation method

: Acute toxicity estimate : > 2.000 mg/kg Acute dermal toxicity

Method: Calculation method

Components:

benzyl alcohol:

: LC50 (Rat, male and female): > 4.178 mg/l Acute inhalation toxicity

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

GLP: yes

Amines, polyethylenepoly-, triethylenetetramine fraction:

: LD50 (Rat, male and female): 1.716 mg/kg Acute oral toxicity

Method: OECD Test Guideline 401

GLP: yes

Acute dermal toxicity : LD50 (Rabbit, male and female): 1.465 mg/kg

Method: OECD Test Guideline 402

GLP: yes

3-aminomethyl-3,5,5-trimethylcyclohexylamine:

Acute oral toxicity : Acute toxicity estimate : 500 mg/kg

Method: Converted acute toxicity point estimate

Acute dermal toxicity : Acute toxicity estimate : 1.100mg/kg

12 / 20



Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it

C-SYSTEMS 10 10 CFS comp. B FAST – SAFETY DATA SHEET march 2018– n° batch 099-AH rev.1/18

Method: Converted acute toxicity point estimate

2-piperazin-1-ylethylamine:

Acute oral toxicity : LD50 (Rat, male): 2.097 mg/kg

Acute dermal toxicity : LD50 (Rabbit, male): 866 mg/kg

2,4,6-tris(dimethylaminomethyl)phenol:

: Acute toxicity estimate : 500 mg/kg Acute oral toxicity

Method: Converted acute toxicity point estimate

Skin corrosion/irritation

Product:

Remarks: No data available

Components:

benzyl alcohol: Species: Rabbit

Method: OECD Test Guideline 404

Result: No skin irritation

GLP: ves

Amines, polyethylenepoly-, triethylenetetramine fraction:

Species: Rabbit

Method: OECD Test Guideline 404

Result: Corrosive

GLP: yes

2-piperazin-1-ylethylamine:

Species: Rabbit Result: Corrosive

Serious eye damage/eye irritation

Product:

Remarks: No data available

Components:

benzyl alcohol: Species: Rabbit

Method: OECD Test Guideline 405 Result: Eye irritation

GLP: yes

Amines, polyethylenepoly-, triethylenetetramine fraction:

Species: Rabbit

Method: OECD Test Guideline 405 Result: Risk of serious damage to eyes.

GLP: yes

2-piperazin-1-ylethylamine:

Species: Rabbit

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY tel. +39 0584 383694 fax +39 0584 395182 www.cecchi.it info@cecchi.it c-systems 10 10 CFS comp. B FAST – SAFETY DATA SHEET march 2018– n° batch 099-AH rev.1/18



Result: Risk of serious damage to eyes.

Respiratory or skin sensitisation

Product:

Remarks: No data available

Components:

Amines, polyethylenepoly-, triethylenetetramine fraction:

Test Type: Buehler Test Species: Guinea pig

Method: OECD Test Guideline 406

Result: May cause sensitisation by skin contact.

GLP: yes

2-piperazin-1-ylethylamine:

Test Type: Maximisation Test Exposure routes: Dermal Species: Guinea pig

Method: OECD Test Guideline 406

Result: May cause sensitisation by skin contact.

Germ cell mutagenicity

Carcinogenicity

Reproductive toxicity

STOT - single exposure

STOT - repeated exposure

Repeated dose toxicity

Product:

Remarks: No data available

Aspiration toxicity

Components:

3-aminomethyl-3,5,5-trimethylcyclohexylamine:

No aspiration toxicity classification

Further information

Product:

Remarks: No data available

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it

C-SYSTEMS 10 10 CFS comp. B FAST - SAFETY DATA SHEET march 2018- n° batch 099-AH rev.1/18



SECTION 12: Ecological information

12.1 Toxicity

Product:

Toxicity to fish : Remarks: No data available

Toxicity to daphnia and other

aquatic invertebrates

: Remarks: No data available

Components:

benzyl alcohol:

Toxicity to daphnia and other

aquatic invertebrates

: EC50 (Daphnia magna (Water flea)): 230 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

GLP: yes

: ErC50 (Pseudokirchneriella subcapitata (green algae)): 770 Toxicity to algae

mg/l

Exposure time: 72 h Test Type: static test

Method: OECD Test Guideline 201

GLP: yes

Amines, polyethylenepoly-, triethylenetetramine fraction:

aquatic invertebrates

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 31,1 mg/l

Exposure time: 48 h Test Type: static test

Method: Directive 67/548/EEC, Annex V, C.2.

GLP: yes

: ErC50 (Selenastrum capricornutum (green algae)): 20 mg/l Toxicity to algae

> Exposure time: 72 h Test Type: semi-static test Method: OECD Test Guideline 201

GLP: yes

3-aminomethyl-3,5,5-trimethylcyclohexylamine:

Toxicity to fish : LC50 (Leuciscus idus (Golden orfe)): 110 mg/l

> Exposure time: 96 h Test Type: semi-static test

Method: Directive 67/548/EEC, Annex V, C.1.

GLP: yes

Toxicity to daphnia and other

aquatic invertebrates

: EC50 (Daphnia magna (Water flea)): 23 mg/l

Exposure time: 48 h Test Type: static test

Method: OECD Test Guideline 202

GLP: yes

Toxicity to algae : ErC50 (Scenedesmus capricornutum (fresh water algae)):>

50 mg/l

Exposure time: 72 h

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it

C-SYSTEMS 10 10 CFS comp. B FAST - SAFETY DATA SHEET march 2018- n° batch 099-AH rev.1/18

Test Type: static test

Method: Directive 67/548/EEC, Annex V, C.3.

GLP: yes

Toxicity to daphnia and other

aquatic invertebrates (Chronic toxicity)

: NOEC: 3 mg/l Exposure time: 21 d

Species: Daphnia magna (Water flea)

Test Type: semi-static test

GLP: yes

2-piperazin-1-ylethylamine:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 2.190 mg/l

Exposure time: 96 h Test Type: static test

Toxicity to daphnia and other

aquatic invertebrates

: EC50 (Daphnia magna (Water flea)): 58 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

GLP: yes

Toxicity to algae : ErC50 (Selenastrum capricornutum (green algae)): >1.000

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

GLP: yes

12.2 Persistence and degradability

Product:

Biodegradability : Remarks: No data available

Components:

3-aminomethyl-3,5,5-trimethylcyclohexylamine:

Biodegradability : Test Type: aerobic

Result: Not readily biodegradable.

Method: Directive 67/548/EEC Annex V, C.4.A.

GLP: yes

2-piperazin-1-ylethylamine:

Biodegradability : Result: Not readily biodegradable.

Method: OECD Test Guideline 301F

GLP: yes

12.3 Bioaccumulative potential_

Product:

Bioaccumulation : Remarks: No data available

Components:

3-aminomethyl-3,5,5-trimethylcyclohexylamine:

Partition coefficient: n- : log Pow: 0,99

octanol/water Method: OECD Test Guideline 107

16 / 20



Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it

C-SYSTEMS 10 10 CFS comp. B FAST - SAFETY DATA SHEET march 2018- n° batch 099-AH rev.1/18

GLP: yes

2-piperazin-1-ylethylamine:

Partition coefficient: n-

octanol/water

: log Pow: -1,48 (20 °C)

12.4 Mobility in soil

Components:

2-piperazin-1-ylethylamine:

Distribution among : Medium:Soil environmental compartments Koc: 37000

12.5 Results of PBT and vPvB assessment

Product:

: This substance/mixture contains no components considered Assessment

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher...

12.6 Other adverseeffects

Product:

Additional ecological

information

: Remarks: An environmental hazard cannot be excluded in the

event of unprofessional handling or disposal.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : In accordance with local and national regulations.

> Container hazardous when empty. Do not dispose of with domestic refuse. Do not mix waste streams during collection.

Contaminated packaging : Empty containers should be taken to an approved waste

handling site for recycling or disposal.

SECTION 14: Transport information

14.1 UN number

ADR/RID/ADN : UN2735 **IMDG** : UN2735 **IATA** : UN2735

14.2 UN proper shipping name

: AMINES, LIQUID, CORROSIVE, N.O.S. ADR/RID/ADN

(BADGE-IPDA adduct)



Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it

C-SYSTEMS 10 10 CFS comp. B FAST – SAFETY DATA SHEET march 2018– n° batch 099-AH rev.1/18

IMDG : AMINES, LIQUID, CORROSIVE, N.O.S.

(BADGE-IPDA adduct)

IATA : Amines, liquid, corrosive, n.o.s.

(BADGE-IPDA adduct)

14.3 Transport hazard class(es)

ADR/RID/ADN : 8 **IMDG** : 8 **IATA** : 8

14.4 Packing group

ADR/RID/ADN

: 111 Packing group Classification Code : C7 Hazard Identification Number: 80 Labels

IMDG

Packing group : 111 Labels : 8 EmS Code : F-A, S-B

Remarks : IMDG Code segregation group 18 - Alkalis

IATA

Packing instruction (cargo : 856

aircraft)

: 852 Packing instruction

(passenger aircraft)

Packing group : 111 : 8 Labels

14.5 Environmental hazards

ADR/RID/ADN

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on : Not applicable





Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it

C-SYSTEMS 10 10 CFS comp. B FAST - SAFETY DATA SHEET march 2018- n° batch 099-AH rev.1/18

the market and use of certain dangerous substances, preparations and articles (Annex XVII)

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

: This product does not contain substances of very high concern

(Regulation (EC) No

: Not applicable

1907/2006 (REACH), Article 57).

REACH - List of substances subject to authorisation

(Annex XIV)

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Not applicable

15.2 Chemical safety assessment

Not applicable

SECTION 16: Other information

Full text of H-Statements

H302 : Harmful if swallowed.
H311 : Toxic in contact with skin.
H312 : Harmful in contact with skin.

H314 : Causes severe skin burns and eye damage.

H315 : Causes skin irritation.

H317 : May cause an allergic skin reaction.
H318 : Causes serious eye damage.
H319 : Causes serious eye irritation.

H332 : Harmful if inhaled.

H335 : May cause respiratory irritation.

H412 : Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox. : Acute toxicity

Aquatic Chronic : Chronic aquatic toxicity Eye Dam. : Serious eye damage

Eye Irrit. : Eye irritation
Skin Corr. : Skin corrosion
Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitisation

STOT SE : Specific target organ toxicity - single exposure

Further information

Training advice : Provide adequate information, instruction and training for

operators.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.



Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY tel. +39 0584 383694 fax +39 0584 395182 www.cecchi.it info@cecchi.it c-systems 10 10 CFs comp. B FAST – SAFETY DATA SHEET march 2018– n° batch 099-AH rev.1/18

