



CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it

10 3 component A - Safety Data Sheet - august 2018 - batch 249-AH - rev.1/17

Safety Data Sheet

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name 10 3 component A

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Casting Resin

1.3 Details of the supplier of the safety data sheet Manufacturer/Supplier:

Cecchi Gustavo & C. srl - Via M. Coppino 253,
55049 Viareggio (LU) ITALY www.cecchi.it - info@cecchi.it

1.4 Emergency telephone number:

+39 0584/383694 - info@cecchi.it
From monday to friday office hours 8:30 – 12:30, 14:00 – 18:30

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Skin corrosion , Category 1	H314: Causes severe skin burns and eye damage.
Serious eye damage , Category 1	H318: Causes serious eye damage.
Skin sensitisation , Category 1	H317: May cause an allergic skin reaction.
Reproductive toxicity , Category 1A	H360: May damage fertility or the unborn child.
Chronic aquatic toxicity , Category 2	H411: Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :

Signal word : **Danger**

Hazard statements : **H314 Causes severe skin burns and eye damage.**
H317 May cause an allergic skin reaction.



CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it

10 3 component A - Safety Data Sheet - august 2018 - batch 249-AH - rev.1/17

H360 May damage fertility or the unborn child.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**

P201 Obtain special instructions before use.
P280 Wear protective gloves/protective clothing/
eye protection/ face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor.
P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.

Hazardous components which must be listed on the label:

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight =< 700)

1,3-Propanediol, 2-ethyl-2-(hydroxymethyl)-, polymer with (chloromethyl)oxirane

Bisphenol-F-epichlorohydrin resin, MM=<700

oxirane, mono[(C12-14-alkyloxy)methyl]derivs

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Modified epoxy resin

Hazardous components

Chemical name	CAS-No. EC-No. Registration number	Classification (REGULATION (EC) No 1272/2008)	Concentration (%)
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight	25068-38-6 01-2119456619-26	Eye Irrit.2; H319 Skin Irrit.2; H315 Skin Sens.1; H317	>= 50 - <= 100



CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it

10 3 component A - Safety Data Sheet - august 2018 - batch 249-AH - rev.1/17

=< 700)		Aquatic Chronic2; H411	
1,3-Propanediol, 2-ethyl-2-(hydroxymethyl)-, polymer with (chloromethyl)oxirane	30499-70-8	Skin Corr.1; H314 Eye Dam.1; H318 Skin Sens.1; H317 Aquatic Chronic2; H411 Repr.1; H360	>= 12,5 - < 20
Bisphenol-F-epichlorohydrin resin, MM=<700	9003-36-5 01-2119454392-40	Skin Irrit.2; H315 Eye Irrit.2; H319 Skin Sens.1; H317 Aquatic Chronic2; H411	>= 10 - < 12,5
oxirane, mono[(C12-14-alkyloxy)methyl]derivs	Not Assigned 271-846-8 01-2119485289-22	Skin Irrit.2; H315 Skin Sens.1; H317	>= 3 - < 5

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Keep warm and in a quiet place.
Show this safety data sheet to the doctor in attendance.
Take off all contaminated clothing immediately.
- If inhaled : Move to fresh air.
Keep patient warm and at rest.
If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
If breathing is irregular or stopped, administer artificial respiration.
- In case of skin contact : Wash off immediately with soap and plenty of water.
Do NOT use solvents or thinners.
If on clothes, remove clothes.
If skin irritation persists, call a physician.
- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
If eye irritation persists, consult a specialist.
If easy to do, remove contact lens, if worn.
- If swallowed : Keep at rest.
Do not induce vomiting without medical advice.
Keep respiratory tract clear.
If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : irritant effects
Redness



CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it

10 3 component A - Safety Data Sheet - august 2018 - batch 249-AH - rev.1/17

sensitising effects

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : The first aid procedure should be established in consultation with the doctor responsible for industrial medicine.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Foam
Sand
Carbon dioxide (CO₂)
Water mist

Unsuitable extinguishing media : Water spray jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : The pressure in sealed containers can increase under the influence of heat.
Cool closed containers exposed to fire with water spray.

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.

Further information : In the event of fire and/or explosion do not breathe fumes.
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Immediately evacuate personnel to safe areas.
Prevent fire extinguishing water from contaminating surface water or the ground water system.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Refer to protective measures listed in sections 7 and 8.
Evacuate personnel to safe areas.
Use personal protective equipment.
Ensure adequate ventilation.
Inform the responsible authorities in case of gas leakage, or of entry into waterways, soil or drains.

6.2 Environmental precautions

Environmental precautions : Do not allow uncontrolled discharge of product into the



CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it

10 3 component A - Safety Data Sheet - august 2018 - batch 249-AH - rev.1/17

environment.

Try to prevent the material from entering drains or water courses.

Local authorities should be advised if significant spillages cannot be contained.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).
Pick up and transfer to properly labelled containers.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Provide sufficient air exchange and/or exhaust in work rooms.
Avoid inhalation, ingestion and contact with skin and eyes.
Wear personal protective equipment.
Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

Advice on protection against fire and explosion : Keep away from open flames, hot surfaces and sources of ignition.

Hygiene measures : Provide adequate ventilation. Wash hands and face before breaks and immediately after handling the product.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep containers tightly closed in a dry, cool and well-ventilated place. Keep in properly labelled containers.

Advice on common storage : Keep away from oxidizing agents, strongly acid or alkaline materials and amines.
Keep product and empty container away from heat and sources of ignition.
Keep away from food and drink.

Other data : Stable at normal ambient temperature and pressure.

7.3 Specific end use(s)

Specific use(s) : Consult the technical guidelines for the use of this substance/mixture.



CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it

10 3 component A - Safety Data Sheet - august 2018 - batch 249-AH - rev.1/17

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Contains no substances with occupational exposure limit values.

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight =< 700)	: End Use: Workers Exposure routes: Skin contact Potential health effects: Acute systemic effects, Long-term systemic effects Value: 8,33 mg/kg End Use: Workers Exposure routes: Inhalation Potential health effects: Acute systemic effects, Long-term local effects Value: 12,25 mg/m ³ End Use: Consumers Exposure routes: Skin contact Potential health effects: Acute systemic effects, Long-term systemic effects Value: 3,571 mg/kg End Use: Consumers Exposure routes: Ingestion Potential health effects: Acute systemic effects, Long-term systemic effects Value: 0,75 mg/kg
oxirane, mono[(C12-14- alkyloxy)methyl]derivs	: End Use: Workers Exposure routes: Skin contact Potential health effects: Long-term systemic effects Value: 3,9 mg/kg End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term systemic effects Value: 13,8 mg/m ³

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight =< 700)	: Fresh water Value: 0,006 mg/l Marine water Value: 0,0006 mg/l Intermittent releases Value: 0,018 mg/l Sewage treatment plant Value: 10 mg/l Fresh water sediment Value: 0,996 mg/kg Marine sediment Value: 0,0996 mg/kg Soil Value: 0,196 mg/kg
oxirane, mono[(C12-14- alkyloxy)methyl]derivs	: Sewage treatment plant Value: 10 mg/l



CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it

10 3 component A - Safety Data Sheet - august 2018 - batch 249-AH - rev.1/17

Fresh water
Value: 0,0072 mg/l
Marine water
Value: 0,00072 mg/l
Fresh water sediment
Value: 66,77 mg/kg
Marine sediment
Value: 6,677 mg/kg
Soil
Value: 80,12 mg/kg

8.2 Exposure controls

Engineering measures

Effective exhaust ventilation system
effective ventilation in all processing areas

Personal protective equipment

Eye protection : Do not wear contact lenses.
Safety glasses with side-shields conforming to EN166
Ensure that eyewash stations and safety showers are close to the workstation location.

Hand protection

Material : Chemical resistant gloves made of butyl rubber or nitrile rubber category III according to EN374.

Skin and body protection : Protective suit

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. In the case of vapour formation use a respirator with an approved filter.
Respirator with a vapour filter (EN 141)
Apply technical measures to comply with the occupational exposure limits.
This should be achieved by a good general extraction and -if practically feasible- by the use of a local exhaust ventilation.

Protective measures : Avoid contact with skin.
Wear suitable protective equipment.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : liquid
Colour : light yellow
Odour : slight
Odour Threshold : not determined



CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it

10 3 component A - Safety Data Sheet - august 2018 - batch 249-AH - rev.1/17

pH	: not determined
Melting point/freezing point	: Not applicable
Boiling point/boiling range	: > 200 °C
Flash point	: 150 °C
Evaporation rate	: not determined
Upper explosion limit	: Not applicable
Lower explosion limit	: Not applicable
Vapour pressure	: Not applicable
Relative vapour density	: not determined
Density	: 1,15 g/cm ³ (25 °C)
Bulk density	: not determined
Solubility(ies) Solubility in other solvents	: not determined
Partition coefficient: n- octanol/water	: No data available
Auto-ignition temperature	: Not applicable
Thermal decomposition	: Method: No data available
Viscosity Viscosity, dynamic	: 1.200 - 1.800 mPa.s (25 °C)
Viscosity, kinematic	: not determined
Explosive properties	: Not applicable
Oxidizing properties	: Not applicable

9.2 Other information

Surface tension	: not determined
Sublimation point	: Not applicable



CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it

10 3 component A - Safety Data Sheet - august 2018 - batch 249-AH - rev.1/17

SECTION 10: Stability and reactivity

10.1 Reactivity

Stable under recommended storage conditions.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Reacts with the following substances:
Bases
Strong oxidizing agents
Avoid amines.

10.4 Conditions to avoid

Conditions to avoid : No decomposition if used as directed.

10.5 Incompatible materials

Materials to avoid : Incompatible with oxidizing agents.

10.6 Hazardous decomposition products

Hazardous decomposition products : This product may release the following:
Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product:

Acute oral toxicity : Remarks: No data available

Components:

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight =< 700):

Acute oral toxicity : LD50 (Rat, female): > 2.000mg/kg
Method: OECD Test Guideline 420
GLP: yes

Acute dermal toxicity : LD50 (Rat, male and female): > 2.000 mg/kg
Method: OECD Test Guideline 402
GLP: yes

Skin corrosion/irritation

Product:

Remarks: No data available



CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it

10 3 component A - Safety Data Sheet - august 2018 - batch 249-AH - rev.1/17

Components:

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight =< 700):

Species: Rabbit

Exposure time: 4 h

Method: OECD Test Guideline 404

Result: Skin irritation

GLP: yes

Serious eye damage/eye irritation

Product:

Remarks: No data available

Respiratory or skin sensitisation

Product:

Remarks: No data available

Components:

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight =< 700):

Test Type: Mouse Local Lymph Node assay (LLNA)

Species: Mouse

Method: OECD Test Guideline 429

Result: May cause sensitisation by skin contact.

GLP: yes

Germ cell mutagenicity

Carcinogenicity

Reproductive toxicity

STOT - single exposure

Product:

Remarks: Not applicable

STOT - repeated exposure

Repeated dose toxicity

Product:

Remarks: No data available

Aspiration toxicity

Components:

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight =< 700):



CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it

10 3 component A - Safety Data Sheet - august 2018 - batch 249-AH - rev.1/17

No aspiration toxicity classification

Further information

Product:

Remarks: No data available

SECTION 12: Ecological information

12.1 Toxicity

Product:

Toxicity to fish : Remarks: No data available

Toxicity to daphnia and other aquatic invertebrates : Remarks: No data available

Components:

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight =< 700):

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia (water flea)): 1,7 mg/l
Exposure time: 48 h
Test Type: static test
Method: OECD Test Guideline 202
GLP: yes

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 0,3 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Test Type: semi-static test
Method: OECD Test Guideline 211
GLP: yes

12.2 Persistence and degradability

Product:

Biodegradability : Remarks: No data available

Components:

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight =< 700):

Biodegradability : Result: Not readily biodegradable.
Method: OECD Test Guideline 301F
GLP: yes

12.3 Bioaccumulative potential

Product:

Bioaccumulation : Remarks: No data available



CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it

10 3 component A - Safety Data Sheet - august 2018 - batch 249-AH - rev.1/17

Components:

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight =< 700):

Partition coefficient:n-octanol/water : log Pow: 3,242 (25 °C)
pH: 7,1
Method: OECD Test Guideline 117
GLP: yes

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Other adverse effects

Product:

Additional ecological information : Remarks: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : In accordance with local and national regulations.
Container hazardous when empty.
Do not dispose of with domestic refuse.
Do not mix waste streams during collection.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.

SECTION 14: Transport information

14.1 UN number

ADR/RID/ADN : UN1760

IMDG : UN1760

IATA : UN1760

14.2 UN proper shipping name

ADR/RID/ADN : CORROSIVE LIQUID, N.O.S.
(Reaction mass of 1-(2,3-epoxypropoxy)-2,2-bis ((2,3-epoxypropoxy)methyl) butane and 1-(2,3-epoxypropoxy)-2-((2,3-epoxypropoxy)methyl, Epoxy resin)



CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it

10 3 component A - Safety Data Sheet - august 2018 - batch 249-AH - rev.1/17

IMDG	: CORROSIVE LIQUID, N.O.S. (Reaction mass of 1-(2,3-epoxypropoxy)-2,2-bis ((2,3-epoxypropoxy)methyl) butane and 1-(2,3-epoxypropoxy)-2-((2,3-epoxypropoxy)methyl, Epoxy resin)
IATA	: Corrosive liquid, n.o.s. (Reaction mass of 1-(2,3-epoxypropoxy)-2,2-bis ((2,3-epoxypropoxy)methyl) butane and 1-(2,3-epoxypropoxy)-2-((2,3-epoxypropoxy)methyl, Epoxy resin)

14.3 Transport hazard class(es)

ADR/RID/ADN	: 8
IMDG	: 8
IATA	: 8

14.4 Packing group

ADR/RID/ADN	
Packing group	: III
Classification Code	: C9
Hazard Identification Number	: 80
Labels	: 8
Tunnel restriction code	: E
IMDG	
Packing group	: III
Labels	: 8
EmS Code	: F-A, S-B
IATA	
Packing instruction (cargo aircraft)	: 856
Packing instruction (passenger aircraft)	: 852
Packing group	: III
Labels	: 8

14.5 Environmental hazards

ADR/RID/ADN	
Environmentally hazardous	: yes
IMDG	
Marine pollutant	: yes

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.



CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it

10 3 component A - Safety Data Sheet - august 2018 - batch 249-AH - rev.1/17

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Not applicable

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57).

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

		Quantity 1	Quantity 2
E2	ENVIRONMENTAL HAZARDS	200 t	500 t

15.2 Chemical safety assessment

Not applicable

SECTION 16: Other information

Full text of H-Statements

H314 : Causes severe skin burns and eye damage.
H315 : Causes skin irritation.
H317 : May cause an allergic skin reaction.
H318 : Causes serious eye damage.
H319 : Causes serious eye irritation.
H360 : May damage fertility or the unborn child.
H411 : Toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Aquatic Chronic : Chronic aquatic toxicity
Eye Dam. : Serious eye damage
Eye Irrit. : Eye irritation
Repr. : Reproductive toxicity
Skin Corr. : Skin corrosion
Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitisation

Further information

Training advice : Provide adequate information, instruction and training for operators.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific



CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it

10 3 component A - Safety Data Sheet - august 2018 - batch 249-AH - rev.1/17

material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.