

## Safety data sheet

### Section 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

**Product name: NAUTILUS EPOXY FAST FINE FILLER component A**

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Use of substance / mixture:** Filler for industrial or professional application. For information regarding additional possible application please email us or dial the indicated phone number as shown below. We will connect you with our responsible technical personnel.

#### 1.3 Details of the supplier of the safety data sheet Manufacturer/Supplier:

Cecchi Gustavo & C. srl - Via M. Coppino 253,  
55049 Viareggio (LU) ITALY www.cecchi.it - info@cecchi.it

#### 1.4 Emergency telephone number:

+39 0584/383694 - info@cecchi.it  
From monday to friday office hours 8:30 – 12:30, 14:00 – 18:30

### Section 2: Hazards identification

#### 2.1. Classification of the substance or mixture

**Classification under CLP:** Aquatic Chronic 2: H411; Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317

**Most important adverse effects:** Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation.  
Toxic to aquatic life with long lasting effects.

#### 2.2. Label elements

##### Label elements:

**Hazard statements:** H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H411: Toxic to aquatic life with long lasting effects.

**Hazard pictograms:** GHS07: Exclamation mark

GHS09: Environmental



## CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS EPOXY FAST FINE FILLER component A – SAFETY DATA SHEET - march 2018 - n°batch 809008 - rev. 1/2018

**Signal words:** Warning

**Precautionary statements:** P102: Keep out of reach of children.

P273: Avoid release to the environment.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P302+352: IF ON SKIN: Wash with plenty of water/.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P333+313: If skin irritation or rash occurs: Get medical advice/attention.

P337+313: If eye irritation persists: Get medical.

P363: Wash contaminated clothing before reuse.

P391: Collect spillage.

### 2.3. Other hazards

**PBT:** This product is not identified as a PBT/vPvB substance.

## Section 3: Composition/information on ingredients

### 3.2. Mixtures

#### Hazardous ingredients:

BISPHENOL A-(EPICHLORHYDRIN) {REACTION PRODUCT} - REACH registered number(s): 01-2119456619-26

| EINECS    | CAS        | PBT / WEL | CLP Classification   | Percent |
|-----------|------------|-----------|--|---------|
| 500-033-5 | 25068-38-6 | -         | Eye Irrit. 2: H319; Skin Irrit. 2: H315;<br>Skin Sens. 1: H317; Aquatic Chronic 2:<br>H411 | 40-60%  |

BISPHENOL F-EPICHLORHYDRINHARZE - REACH registered number(s): 01-2119454392-40

|           |            |   |  |        |
|-----------|------------|---|--|--------|
| 500-006-8 | 28064-14-4 | - | Skin Irrit. 2: H315; Skin Sens. 1B:<br>H317; Aquatic Chronic 2: H411 | 10-20% |
|-----------|------------|---|--|--------|

1,4-BIS(2,3-EPOXYPROPOXY) BUTANE - REACH registered number(s): 01-2119494060-45

|           |           |   |   |        |
|-----------|-----------|---|---|--------|
| 219-371-7 | 2425-79-8 | - | Acute Tox. 4: H332; Acute Tox. 4: H312;<br>Eye Irrit. 2: H319; Skin Irrit. 2: H315;<br>Skin Sens. 1: H317 | 10-20% |
|-----------|-----------|---|---|--------|

## Section 4: First aid measures

### 4.1. Description of first aid measures

**Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

**Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.

**Ingestion:** Wash out mouth with water. Consult a doctor.

**Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

[cont...]

## CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS EPOXY FAST FINE FILLER component A – SAFETY DATA SHEET - march 2018 - n°batch 809008 - rev. 1/2018

### 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

**Ingestion:** There may be soreness and redness of the mouth and throat.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

### 4.3. Indication of any immediate medical attention and special treatment needed

## Section 5: Fire-fighting measures

### 5.1. Extinguishing media

**Immediate / special treatment:** Eye bathing equipment should be available on the premises.

**Extinguishing media:** Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

### 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** In combustion emits toxic fumes.

### 5.3. Advice for fire-fighters

**Advice for fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

## Section 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions:** Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid.

### 6.2. Environmental precautions

**Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding.

### 6.3. Methods and material for containment and cleaning up

**Clean-up procedures:** Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

### 6.4. Reference to other sections

**Reference to other sections:** Refer to section 8 of SDS.

## Section 7: Handling and storage

## CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS EPOXY FAST FINE FILLER component A – SAFETY DATA SHEET - march 2018 - n°batch 809008 - rev. 1/2018

### 7.1. Precautions for safe handling

**Handling requirements:** Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Do not handle in a confined space. Avoid the formation or spread of mists in the air.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage conditions:** Store in a cool, well ventilated area. Keep container tightly closed. The floor of the storage room must be impermeable to prevent the escape of liquids.

**Suitable packaging:** Coated steel.

### 7.3. Specific end use(s)

## Section 8: Exposure controls/personal protection

### 8.1. Control parameters

**Specific end use(s):** No data available.

**Workplace exposure limits:** No data available.

### DNEL/PNEC Values

### 8.2. Exposure controls

**DNEL / PNEC** No data available.

**Engineering measures:** Ensure there is sufficient ventilation of the area. The floor of the storage room must be impermeable to prevent the escape of liquids.

**Respiratory protection:** Self-contained breathing apparatus must be available in case of emergency.

**Hand protection:** Nitrile gloves. Breakthrough time of the glove material > 8 hours. Rubber gloves- thickness: 0,4 mm

**Eye protection:** Safety glasses. Ensure eye bath is to hand.

**Skin protection:** Protective clothing.

**Environmental:** Ensure all engineering measures mentioned in section 7 of SDS are in place.

## Section 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

**State:** Liquid

**Colour:** White

**Solubility in water:** Not miscible

**Also soluble in:** Most organic solvents.

**Viscosity:** Viscous

**Boiling point/range°C:** n.V.

**Melting point/range°C:** n.V.

**Flammability limits %: lower:** n.V.

**upper:** n.V.

**Flash point°C:** 147

**Part.coeff. n-octanol/water:** n.V.

**Autoflammability°C:** n.a.

**Vapour pressure:** n.V.

**Relative density:** 0,5-0,7 g/ml

**pH:** n.a.

**VOC g/l:** ENTFÄLLT

**CECCHI GUSTAVO & C.**

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS EPOXY FAST FINE FILLER component A – SAFETY DATA SHEET - march 2018 - n°batch 809008 - rev. 1/2018

**9.2. Other information****Other information:** No data available.**Section 10: Stability and reactivity****10.1. Reactivity****10.2. Chemical stability****Reactivity:** Stable under recommended transport or storage conditions.**Chemical stability:** Stable under normal conditions.**10.3. Possibility of hazardous reactions****Hazardous reactions:** Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

**10.4. Conditions to avoid****Conditions to avoid:** Heat.**10.5. Incompatible materials****10.6. Hazardous decomposition products****Materials to avoid:** Strong oxidising agents. Strong acids.**Haz. decomp. products:** In combustion emits toxic fumes.**Section 11: Toxicological information****11.1. Information on toxicological effects****Hazardous ingredients:****BISPHENOL A-(EPICHLORHYDRIN) {REACTION PRODUCT}**

|     |     |      |       |       |
|-----|-----|------|-------|-------|
| ORL | MUS | LD50 | 15600 | mg/kg |
| ORL | RAT | LD50 | 11400 | mg/kg |
| SKN | RBT | LD50 | >20   | ml/kg |

**1,4-BIS(2,3-EPOXYPROPOXY) BUTANE**

|     |     |      |      |       |
|-----|-----|------|------|-------|
| ORL | MUS | LD50 | 1100 | µg/kg |
| ORL | RAT | LD50 | 1134 | mg/kg |

**Toxicity values:** No data available.**Symptoms / routes of exposure****Skin contact:** There may be irritation and redness at the site of contact.**Eye contact:** There may be irritation and redness. The eyes may water profusely.**Ingestion:** There may be soreness and redness of the mouth and throat.**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

**CECCHI GUSTAVO & C.**

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY  
tel. +39 0584 383694 fax +39 0584 395182  
www.cecchi.it info@cecchi.it



NAUTILUS EPOXY FAST FINE FILLER component A – SAFETY DATA SHEET - march 2018 - n°batch 809008 - rev. 1/2018

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

**Section 12: Ecological information****12.1. Toxicity****12.2. Persistence and degradability**

**Ecotoxicity values:** No data available.

**Persistence and degradability:** Not biodegradable.

**12.3. Bioaccumulative potential****12.4. Mobility in soil**

**Bioaccumulative potential:** Bioaccumulation potential.

**Mobility:** Readily absorbed into soil.

**12.5. Results of PBT and vPvB assessment****12.6. Other adverse effects**

**PBT identification:** This product is not identified as a PBT/vPvB substance.

**Other adverse effects:** Toxic to aquatic organisms. Toxic to soil organisms.

**Section 13: Disposal considerations****13.1. Waste treatment methods**

**Disposal operations:** Transfer to a suitable container and arrange for collection by specialised disposal company.

**Waste code number:** 08 04 09

**Disposal of packaging:** Dispose of in a regulated landfill site or other method for hazardous or toxic wastes.

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

**Section 14: Transport information****14.1. UN number**

**UN number:** UN3082

**14.2. UN proper shipping name**

**Shipping name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,  
(BISPHENOL A-(EPICHLORHYDRIN) {REACTION PRODUCT}; 1,4-BIS[(VINILOXY)  
METHYL]CYCLOHEXANE)

**14.3. Transport hazard class(es)**

**Transport class:** 9

**14.4. Packing group**

**Packing group:** III

## CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY  
tel. +39 0584 383694 fax +39 0584 395182  
www.cecchi.it info@cecchi.it



NAUTILUS EPOXY FAST FINE FILLER component A – SAFETY DATA SHEET - march 2018 - n°batch 809008 - rev. 1/2018

### 14.5. Environmental hazards

Environmentally hazardous: Yes

Marine pollutant: Yes

### 14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: E

Transport category: 3

## Section 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### 15.2. Chemical Safety Assessment

**Chemical safety assessment:** A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

## Section 16: Other information

### Other information

**Other information:** This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830.

\* indicates text in the SDS which has changed since the last revision.

**Phrases used in s.2 and s.3:** H312: Harmful in contact with skin.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H332: Harmful if inhaled.

H411: Toxic to aquatic life with long lasting effects.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.