



Safety data sheet

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: NAUTILUS EPOXY FAST FINE FILLER component B

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Filler for industrial or professional application. For information regarding additional possible application please email us or dial the indicated phone number as shown below. We will connect you with our responsible technical personnel.

1.3 Details of the supplier of the safety data sheet Manufacturer/Supplier:

Cecchi Gustavo & C. srl - Via M. Coppino 253,
55049 Viareggio (LU) ITALY www.cecchi.it - info@cecchi.it

1.4 Emergency telephone number:

+39 0584/383694 - info@cecchi.it

From monday to friday office hours 8:30 – 12:30, 14:00 – 18:30

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Acute Tox. 4: H302; Aquatic Chronic 4: H413; Muta. 2: H341; Skin Corr. 1B: H314; Skin Sens. 1: H317

Most important adverse effects: Harmful if swallowed. Causes severe skin burns and eye damage. May cause an allergic skin reaction. Suspected of causing genetic defects xxxx. May cause long lasting harmful effects to aquatic life.

2.2. Label elements

Label elements:

Hazard statements: H302: Harmful if swallowed.

H314: Causes severe skin burns and eye damage.

H317: May cause an allergic skin reaction.

H341: Suspected of causing genetic defects xxxx.

H413: May cause long lasting harmful effects to aquatic life.

Hazard pictograms: GHS05: Corrosion

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS EPOXY FAST FINE FILLER component B – SAFETY DATA SHEET - march 2018 - n°batch 809006 - rev. 1/2018

GHS07: Exclamation mark

GHS08: Health hazard

**Signal words:** Danger**Precautionary statements:** P102: Keep out of reach of children.

P273: Avoid release to the environment.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P301+312: IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.

P301+330+331: IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

P302+352: IF ON SKIN: Wash with plenty of water/.

P303+361+353: IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+313: IF exposed or concerned: Get medical.

P333+313: If skin irritation or rash occurs: Get medical advice/attention.

P363: Wash contaminated clothing before reuse.

P405: Store locked up.

2.3. Other hazards**Section 3: Composition/information on ingredients****3.2. Mixtures****PBT:** This product is not identified as a PBT/vPvB substance.**Hazardous ingredients:**

ALIPHATISCHES POLYAMIN - REACH registered number(s): Nicht bestimmt

EINECS	CAS	PBT / WEL	CLP Classification	Percent
-	-	-	Aquatic Chronic 4: H413	20-40%

M-XYLYLENDIAMIN - REACH registered number(s): 01-2119480150-50

-	1477-55-0	-	Acute Tox. 4: H302; Aquatic Chronic 3: H412; Skin Corr. 1B: H314; Skin Sens. 1: H317; Acute Tox. 4: H332	1-10%
---	-----------	---	--	-------

BENZYL ALCOHOL - REACH registered number(s): 01-2119492630-38

202-859-9	100-51-6	-	Acute Tox. 4: H332; Acute Tox. 4: H302	1-10%
-----------	----------	---	--	-------

[cont...]

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it

**NAUTILUS EPOXY FAST FINE FILLER component B** – SAFETY DATA SHEET - march 2018 - n°batch 809006 - rev. 1/2018

PHENOL - REACH registered number(s): 01-2119471329-32

203-632-7	108-95-2	-	Muta. 2: H341; Acute Tox. 3: H331; Acute Tox. 3: H311; Acute Tox. 3: H301; STOT RE 2: H373; Skin Corr. 1B: H314	1-10%
-----------	----------	---	--	-------

2,4,6-TRIS(DIMETHYLAMINOMETHYL)PHENOL - REACH registered number(s): 01-2119560597-27

202-013-9	90-72-2	-	Acute Tox. 4: H302; Eye Irrit. 2: H319; Skin Irrit. 2: H315	1-10%
-----------	---------	---	--	-------

N-OCTYLAMIN - REACH registered number(s): 01-2119474880-31

-	111-86-4	-	Flam. Liq. 3: H226; Acute Tox. 3: H301; Acute Tox. 4: H332; STOT SE 3: H335; Skin Corr. 1A: H314; Aquatic Acute 1: H400; Aquatic Chronic 2: H411; Acute Tox. 3: H311	0,10-1%
---	----------	---	--	---------

Section 4: First aid measures**4.1. Description of first aid measures****Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin.

Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Transfer to hospital if there are burns or symptoms of poisoning.

Eye contact: Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.**Ingestion:** Wash out mouth with water. Do not induce vomiting. Give 1 cup of water to drink every 10 minutes. If unconscious, check for breathing and apply artificial respiration if necessary. If unconscious and breathing is OK, place in the recovery position. Transfer to hospital as soon as possible.**Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. If unconscious and breathing is OK, place in the recovery position. If conscious, ensure the casualty sits or lies down. If breathing becomes bubbly, have the casualty sit and provide oxygen if available. Transfer to hospital as soon as possible.**4.2. Most important symptoms and effects, both acute and delayed****Skin contact:** Blistering may occur. Progressive ulceration will occur if treatment is not immediate.**Eye contact:** Corneal burns may occur. May cause permanent damage.**Ingestion:** Corrosive burns may appear around the lips. Blood may be vomited. There may be bleeding from the mouth or nose.**Inhalation:** There may be shortness of breath with a burning sensation in the throat. Exposure may cause coughing or wheezing.**4.3. Indication of any immediate medical attention and special treatment needed**

[cont...]

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS EPOXY FAST FINE FILLER component B – SAFETY DATA SHEET - march 2018 - n°batch 809006 - rev. 1/2018

Section 5: Fire-fighting measures**5.1. Extinguishing media**

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Corrosive. In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Personal precautions: Notify the police and fire brigade immediately. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Clean-up should be dealt with only by qualified personnel familiar with the specific substance. Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections**Section 7: Handling and storage****7.1. Precautions for safe handling**

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Coated steel.

7.3. Specific end use(s)**Section 8: Exposure controls/personal protection**

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS EPOXY FAST FINE FILLER component B – SAFETY DATA SHEET - march 2018 - n°batch 809006 - rev. 1/2018

8.1. Control parameters**Hazardous ingredients:****PHENOL****Workplace exposure limits:****Respirable dust**

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	2 ppm	4 ppm	-	-

DNEL/PNEC Values**DNEL / PNEC** No data available.**8.2. Exposure controls****Engineering measures:** Ensure there is sufficient ventilation of the area.**Respiratory protection:** Self-contained breathing apparatus must be available in case of emergency.**Hand protection:** Nitrile gloves. Breakthrough time of the glove material > 8 hours. Rubber gloves-
thickness: 0,4 mm**Eye protection:** Tightly fitting safety goggles. Ensure eye bath is to hand.**Skin protection:** Impermeable protective clothing.**Environmental:** Ensure all engineering measures mentioned in section 7 of SDS are in place.**Section 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties****State:** Liquid**Odour:** Aromatic**Solubility in water:** Not miscible**Also soluble in:** Most organic solvents.**Viscosity:** Viscous**Boiling point/range°C:** n.V.**Flammability limits %: lower:** n.V.**Flash point°C:** > 100**Autoflammability°C:** n.a.**Relative density:** 1,78 g/cm3**Melting point/range°C:** n.V.**upper:** n.V.**Part.coeff. n-octanol/water:** n.V.**Vapour pressure:** n.V.**VOC g/l:** Entfällt**9.2. Other information****Section 10: Stability and reactivity****10.1. Reactivity****10.2. Chemical stability****Other information:** No data available.

[cont...]

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS EPOXY FAST FINE FILLER component B – SAFETY DATA SHEET - march 2018 - n°batch 809006 - rev. 1/2018

Chemical stability: Stable under normal conditions.**10.3. Possibility of hazardous reactions****10.4. Conditions to avoid****Conditions to avoid:** Heat.**10.5. Incompatible materials****10.6. Hazardous decomposition products****Materials to avoid:** Strong oxidising agents. Strong acids.**Haz. decomp. products:** In combustion emits toxic fumes.**Section 11: Toxicological information****11.1. Information on toxicological effects****Hazardous ingredients:****BENZYL ALCOHOL**

IVN	RAT	LD50	53	mg/kg
ORL	MUS	LD50	1360	mg/kg
ORL	RAT	LD50	1230	mg/kg

PHENOL

ORL	MUS	LD50	270	mg/kg
ORL	RAT	LD50	317	mg/kg
SCU	RAT	LD50	460	mg/kg

2,4,6-TRIS(DIMETHYLAMINOMETHYL)PHENOL

ORL	RAT	LD50	1200	mg/kg
SKN	RAT	LD50	1280	mg/kg

Toxicity values: No data available.**Symptoms / routes of exposure****Skin contact:** Blistering may occur. Progressive ulceration will occur if treatment is not immediate.**Eye contact:** Corneal burns may occur. May cause permanent damage.**Ingestion:** Corrosive burns may appear around the lips. Blood may be vomited. There may be bleeding from the mouth or nose.**Inhalation:** There may be shortness of breath with a burning sensation in the throat. Exposure may cause coughing or wheezing.**Section 12: Ecological information****12.1. Toxicity****Ecotoxicity values:** No data available.

[cont...]

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS EPOXY FAST FINE FILLER component B – SAFETY DATA SHEET - march 2018 - n°batch 809006 - rev. 1/2018

12.2. Persistence and degradability**Persistence and degradability:** Biodegradable.**12.3. Bioaccumulative potential****12.4. Mobility in soil****Bioaccumulative potential:** No bioaccumulation potential.**Mobility:** Readily absorbed into soil.**12.5. Results of PBT and vPvB assessment****12.6. Other adverse effects****PBT identification:** This product is not identified as a PBT/vPvB substance.**Other adverse effects:** Negligible ecotoxicity.**Section 13: Disposal considerations****13.1. Waste treatment methods****Disposal operations:** Transfer to a suitable container and arrange for collection by specialised disposal company.**Waste code number:** 08 05 01**Disposal of packaging:** Dispose of in a regulated landfill site or other method for hazardous or toxic wastes.**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.**Section 14: Transport information****14.1. UN number****UN number:** UN1759**14.2. UN proper shipping name****Shipping name:** CORROSIVE SOLID,
(M-XYLYLENDIAMIN)**14.3. Transport hazard class(es)****14.4. Packing group****Transport class:** 8**Packing group:** II**14.5. Environmental hazards****14.6. Special precautions for user****Environmentally hazardous:** No**Marine pollutant:** No**Tunnel code:** E**Transport category:** 2

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS EPOXY FAST FINE FILLER component B – SAFETY DATA SHEET - march 2018 - n°batch 809006 - rev. 1/2018

Section 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****Specific regulations:** Not applicable.**15.2. Chemical Safety Assessment****Chemical safety assessment:** A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.**Section 16: Other information****Other information****Other information:** This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H226: Flammable liquid and vapour.

H301: Toxic if swallowed.

H302: Harmful if swallowed.

H311: Toxic in contact with skin.

H314: Causes severe skin burns and eye damage.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H331: Toxic if inhaled.

H332: Harmful if inhaled.

H335: May cause respiratory irritation.

H341: Suspected of causing genetic defects <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

H373: May cause damage to organs <or state all organs affected, if known> through prolonged or repeated exposure <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

H400: Very toxic to aquatic life.

H411: Toxic to aquatic life with long lasting effects.

H412: Harmful to aquatic life with long lasting effects.

H413: May cause long lasting harmful effects to aquatic life.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.