

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS ENAMEL Component B - SAFETY DATA SHEET - march 2017 - n°batch 065-AH - rev. 1/2018

Safety data sheet

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name

NAUTILUS ENAMEL Component B

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use

MARINA/NAUTICA

| Identified Uses | Industrial | Professional | Consumer |
|--|-------------------------------------|-------------------------------------|----------|
| Prodotto verniciante per nautica - marina | - | <input checked="" type="checkbox"/> | - |
| Prodotto verniciante per usi industriali | <input checked="" type="checkbox"/> | - | - |
| Prodotto verniciante per uso professionale | - | <input checked="" type="checkbox"/> | - |

Uses Advised Against

CONSUMATORE: FAI-DA-TE

1.3 Details of the supplier of the safety data sheet Manufacturer/Supplier:

Cecchi Gustavo & C. srl - Via M. Coppino 253,
55049 Viareggio (LU) ITALY www.cecchi.it - info@cecchi.it

1.4 Emergency telephone number:

+39 0584/383694 - info@cecchi.it

From monday to friday office hours 8:30 - 12:30, 14:00 - 18:30

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of EC Regulation 1907/2006 and subsequent amendments. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

| | | |
|--|------|--|
| Flammable liquid, category 2 | H225 | Highly flammable liquid and vapour. |
| Acute toxicity, category 4 | H332 | Harmful if inhaled. |
| Specific target organ toxicity - repeated exposure, category 2 | H373 | May cause damage to organs through prolonged or repeated exposure. |
| Eye irritation, category 2 | H319 | Causes serious eye irritation. |
| Skin irritation, category 2 | H315 | Causes skin irritation. |
| Specific target organ toxicity - single exposure, category 3 | H335 | May cause respiratory irritation. |
| Skin sensitization, category 1 | H317 | May cause an allergic skin reaction. |

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS ENAMEL Component B - SAFETY DATA SHEET - march 2017 - n°batch 065-AH - rev. 1/2018



Signal words:

Danger

Hazard statements:

| | |
|--------|--|
| H225 | Highly flammable liquid and vapour. |
| H332 | Harmful if inhaled. |
| H373 | May cause damage to organs through prolonged or repeated exposure. |
| H319 | Causes serious eye irritation. |
| H315 | Causes skin irritation. |
| H335 | May cause respiratory irritation. |
| H317 | May cause an allergic skin reaction. |
| EUH204 | Contains isocyanates. May produce an allergic reaction. |
| EUH208 | Contains: 4-TOLUENSOLFONILISOCIANATO, HEXAMETHYLENE-DI-ISOCYANATE |
| | May produce an allergic reaction. |

Precautionary statements:

| | |
|-----------|--|
| P210 | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. |
| P233 | Keep container tightly closed. |
| P261 | Avoid breathing dust / fume / gas / mist / vapours / spray. |
| P280 | Wear protective gloves / eye protection / face protection. |
| P312 | Call a POISON CENTRE / doctor / . . . if you feel unwell. |
| P370+P378 | In case of fire: use . . . to extinguish. |

| | |
|-----------|--|
| Contains: | XYLENE (MIXTURE OF ISOMERS) ESAMETILEN, 1,6-DIISOCIANATO, OMOPOLIMERO ETHYLBENZENE 4-TOLUENSOLFONILISOCIANATO |
|-----------|--|

Product not intended for uses provided for by Dir. 2004/42/CE.

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

SECTION 3. Composition/information on ingredients

3.1. Substances

Information not relevant

3.2. Mixtures

Contains:

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS ENAMEL Component B - SAFETY DATA SHEET - march 2017 - n°batch 065-AH - rev. 1/2018

| Identification | x = Conc. % | Classification 1272/2008 (CLP) |
|---|----------------|--|
| ESAMETILEN, 1,6-DIISOCIANATO, OMOPOLIMERO CAS 28182-81-2 EC 500-060-2 INDEX - Reg. no. 01-2119488934-20-0000 | 50 ≤ x < 70 | Acute Tox. 4 H332, STOT SE 3 H335, Skin Sens. 1 H317 |
| 2-METHOXY-1-METHYLETHYL ACETATE CAS 108-65-6 EC 203-603-9 INDEX 607-195-00-7 Reg. no. 01-2119475791-29-XXXX | 10 ≤ x < 20 | Flam. Liq. 3 H226 |
| XYLENE (MIXTURE OF ISOMERS) CAS 1330-20-7 EC 215-535-7 INDEX 601-022-00-9 Reg. no. 01-2119488216-32-XXXX | 10 ≤ x < 20 | Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Aquatic Chronic 3 H412, Note C |
| ETHYLBENZENE CAS 100-41-4 EC 202-849-4 INDEX 601-023-00-4 | 1,5 ≤ x < 2,5 | Flam. Liq. 2 H225, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373 |
| HEXAMETHYLENE-DI-ISOCYANATE CAS 822-06-0 EC 212-485-8 INDEX 615-011-00-1 Reg. no. 01-2119457571-37-0000 | 0,2 ≤ x < 0,25 | Acute Tox. 1 H330, Acute Tox. 4 H302, Skin Corr. 1C H314, STOT SE 3 H335, Resp. Sens. 1 H334, Skin Sens. 1 H317, Note 2 |
| 4-TOLUENSOLFONILISOCIANATO CAS 4083-64-1 EC 223-810-8 INDEX 615-012-00-7 | 0,2 ≤ x < 0,25 | Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Resp. Sens. 1 H334, EUH014 |

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS ENAMEL Component B - SAFETY DATA SHEET - march 2017 - n°batch 065-AH - rev. 1/2018

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products. The product is combustible and, when the powder is released into the air in sufficient concentrations and in the presence of a source of ignition, it can create explosive mixtures with air. Fires may start or get worse by leakage of the solid product from the container, when it reaches high temperatures or through contact with sources of ignition.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS ENAMEL Component B - SAFETY DATA SHEET - march 2017 - n°batch 065-AH - rev. 1/2018

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

Send away individuals who are not suitably equipped. Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. If the product is flammable, use explosion-proof equipment. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Vapours may catch fire and an explosion may occur; vapour accumulation is therefore to be avoided by leaving windows and doors open and ensuring good cross ventilation. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. When performing transfer operations involving large containers, connect to an earthing system and wear antistatic footwear. Vigorous stirring and flow through the tubes and equipment may cause the formation and accumulation of electrostatic charges. In order to avoid the risk of fires and explosions, never use compressed air when handling. Open containers with caution as they may be pressurised. Do not eat, drink or smoke during use. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS ENAMEL Component B - SAFETY DATA SHEET - march 2017 - n°batch 065-AH - rev. 1/2018

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Store in a well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

Storage class TRGS 510 (Germany):

3

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory References:

| | | |
|-----|----------------|--|
| DEU | Deutschland | MAK-und BAT-Werte-Liste 2012 |
| ESP | España | INSHT - Límites de exposición profesional para agentes químicos en España 2015 |
| FRA | France | JORF n°0109 du 10 mai 2012 page 8773 texte n° 102 |
| GBR | United Kingdom | EH40/2005 Workplace exposure limits |
| ITA | Italia | Decreto Legislativo 9 Aprile 2008, n.81 |
| NLD | Nederland | Databank of the social and Economic Concil of Netherlands (SER) Values, AF 2011:18 |
| POL | Polska | ROZPORZĄDZENIE MINISTRA PRACY I POLITYKI SPOŁECZNEJ z dnia 16 grudnia 2011r |
| PRT | Portugal | Ministério da Economia e do Emprego Consolida as prescrições mínimas em matéria de protecção dos trabalhadores contra os riscos para a segurança e a saúde devido à exposição a agentes químicos no trabalho - Diaro da Republica I 26; 2012-02-06 |
| EU | OEL EU | Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 91/322/EEC. |
| | TLV-ACGIH | ACGIH 2016 |

2-METHOXY-1-METHYLETHYL ACETATE

Threshold Limit Value

| Type | Country | TWA/8h | | STEL/15min | | |
|------|---------|--------|-----|------------|-----|------|
| | | mg/m3 | ppm | mg/m3 | ppm | |
| AGW | DEU | 270 | 50 | 270 | 50 | |
| MAK | DEU | 270 | 50 | 270 | 50 | |
| VLA | ESP | 275 | 50 | 550 | 100 | SKIN |
| VLEP | FRA | 275 | 50 | 550 | 100 | SKIN |
| WEL | GBR | 274 | 50 | 548 | 100 | |
| VLEP | ITA | 275 | 50 | 550 | 100 | SKIN |
| OEL | NLD | 550 | | | | |

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it

**NAUTILUS ENAMEL Component B - SAFETY DATA SHEET - march 2017 - n°batch 065-AH - rev. 1/2018**

| | | | | | | |
|-----|-----|-----|----|-----|-----|------|
| NDS | POL | 260 | | 520 | | |
| VLE | PRT | 275 | 50 | 550 | 100 | SKIN |
| OEL | EU | 275 | 50 | 550 | 100 | SKIN |

Predicted no-effect concentration - PNEC

| | | |
|--|--------|-------|
| Normal value in fresh water | 0,635 | mg/l |
| Normal value in marine water | 0,0635 | mg/l |
| Normal value for fresh water sediment | 3,29 | mg/kg |
| Normal value for marine water sediment | 0,329 | mg/kg |
| Normal value of STP microorganisms | 100 | mg/l |
| Normal value for the terrestrial compartment | 0,29 | mg/kg |

Health - Derived no-effect level - DNEL / DMEL

| Route of exposure | Effects on consumers | Effects on workers |
|-------------------|----------------------|-----------------------|
| Oral | VND | 1,67 mg/kg |
| Inhalation | VND | 33 mg/m ³ |
| Skin | VND | 54,8 mg/kg |
| | VND | 275 mg/m ³ |
| | VND | 153,5 mg/kg |

XYLENE (MIXTURE OF ISOMERS)**Threshold Limit Value**

| Type | Country | TWA/8h | | STEL/15min | | |
|-----------|---------|-------------------|-----|-------------------|-----|------|
| | | mg/m ³ | ppm | mg/m ³ | ppm | |
| AGW | DEU | 440 | 100 | 880 | 200 | SKIN |
| MAK | DEU | 440 | 100 | 880 | 200 | SKIN |
| VLA | ESP | 221 | 50 | 442 | 100 | SKIN |
| VLEP | FRA | 221 | 50 | 442 | 100 | SKIN |
| WEL | GBR | 220 | 50 | 441 | 100 | |
| VLEP | ITA | 221 | 50 | 442 | 100 | SKIN |
| OEL | NLD | 210 | | 442 | | SKIN |
| NDS | POL | 100 | | | | |
| OEL | EU | 221 | 50 | 442 | 100 | SKIN |
| TLV-ACGIH | | 434 | 100 | 651 | 150 | |

Predicted no-effect concentration - PNEC

| | | |
|--|-------|-------|
| Normal value in fresh water | 0,327 | mg/l |
| Normal value in marine water | 0,327 | mg/l |
| Normal value for fresh water sediment | 12,46 | mg/kg |
| Normal value for marine water sediment | 12,46 | mg/kg |
| Normal value of STP microorganisms | 6,58 | mg/l |
| Normal value for the terrestrial compartment | 2,31 | mg/kg |

ETHYLBENZENE**Threshold Limit Value**

| Type | Country | TWA/8h | | STEL/15min | | |
|------|---------|-------------------|-----|-------------------|-----|------|
| | | mg/m ³ | ppm | mg/m ³ | ppm | |
| AGW | DEU | 440 | 100 | 880 | 200 | SKIN |
| MAK | DEU | 88 | 20 | 176 | 40 | SKIN |

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS ENAMEL Component B - SAFETY DATA SHEET - march 2017 - n°batch 065-AH - rev. 1/2018

| | | | | | | |
|-----------|-----|------|-----|-----|-----|------|
| VLA | ESP | 441 | 100 | 884 | 200 | SKIN |
| VLEP | FRA | 88,4 | 20 | 442 | 100 | SKIN |
| WEL | GBR | 441 | 100 | 552 | 125 | SKIN |
| VLEP | ITA | 442 | 100 | 884 | 200 | SKIN |
| OEL | NLD | 215 | | 430 | | SKIN |
| NDS | POL | 200 | | 400 | | |
| VLE | PRT | 442 | 100 | 884 | 200 | SKIN |
| OEL | EU | 442 | 100 | 884 | 200 | SKIN |
| TLV-ACGIH | | 87 | 20 | | | |

HEXAMETHYLENE-DI-ISOCYANATE

Threshold Limit Value

| Type | Country | TWA/8h | | STEL/15min | |
|-----------|---------|--------|-------|------------|-------|
| | | mg/m3 | ppm | mg/m3 | ppm |
| AGW | DEU | 0,035 | 0,005 | 0,035 | 0,005 |
| MAK | DEU | 0,035 | 0,005 | 0,035 | 0,005 |
| VLA | ESP | 0,035 | 0,005 | | |
| VLEP | FRA | 0,075 | 0,01 | 0,15 | 0,02 |
| WEL | GBR | 0,02 | | 0,07 | |
| NDS | POL | 0,04 | | 0,08 | |
| TLV-ACGIH | | 0,034 | 0,005 | | |

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

TLV of solvent mixture: 2,8 mg/m3

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

Exposure levels must be kept as low as possible to avoid significant build-up in the organism. Manage personal protective equipment so as to guarantee maximum protection (e.g. reduction in replacement times).

HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS ENAMEL Component B - SAFETY DATA SHEET - march 2017 - n°batch 065-AH - rev. 1/2018

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, wear a mask with a type AX filter, whose limit of use will be defined by the manufacturer (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|--|-----------------------------------|
| Appearance | liquid |
| Colour | colourless |
| Odour | characteristic of solvent |
| Odour threshold | Not available |
| pH | Not available |
| Melting point / freezing point | Not available |
| Initial boiling point | > 35 °C |
| Boiling range | Not available |
| Flash point | 21 ≤ T ≤ 23 °C |
| Evaporation Rate | Not available |
| Flammability of solids and gases | Not available |
| Lower inflammability limit | Not available |
| Upper inflammability limit | Not available |
| Lower explosive limit | Not available |
| Upper explosive limit | Not available |
| Vapour pressure | Not available |
| Vapour density | Not available |
| Relative density | 1,03 |
| Solubility | immiscible with water |
| Partition coefficient: n-octanol/water | Not available |
| Auto-ignition temperature | Not available |
| Decomposition temperature | Not available |
| Viscosity | >20,5 mm ² /sec (40°C) |
| Explosive properties | Not available |
| Oxidising properties | Not available |

9.2. Other information

| | |
|------------------------------|--------------------------|
| Total solids (250°C / 482°F) | 60,44 % |
| VOC (Directive 2010/75/EC) : | 39,56 % - 408,94 g/litre |
| VOC (volatile carbon) : | 28,79 % - 297,59 g/litre |

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS ENAMEL Component B - SAFETY DATA SHEET - march 2017 - n°batch 065-AH - rev. 1/2018

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

2-METHOXY-1-METHYLETHYL ACETATE

Stable in normal conditions of use and storage.

With the air it may slowly develop peroxides that explode with an increase in temperature.

HEXAMETHYLENE-DI-ISOCYANATE

Decomposes at 255°C/491°F. Polymerises at temperatures above 200°C/392°F.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

2-METHOXY-1-METHYLETHYL ACETATE

May react violently with: oxidising substances, strong acids, alkaline metals.

XYLENE (MIXTURE OF ISOMERS)

XYLENE (MIXTURE OF ISOMERS): stable, but may develop violent reactions in the presence of strong oxidising agents such as sulphuric and nitric acids and perchlorates. May form explosive mixtures with the air.

ETHYLBENZENE

Reacts violently with: strong oxidants. Attacks various types of plastic materials. May form explosive mixtures with: air.

HEXAMETHYLENE-DI-ISOCYANATE

May form explosive mixtures with: alcohols, bases. May react violently with: alcohols, amines, strong bases, oxidising agents, strong acids, water.

10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

HEXAMETHYLENE-DI-ISOCYANATE

Avoid exposure to: high temperatures, moisture.

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS ENAMEL Component B - SAFETY DATA SHEET - march 2017 - n°batch 065-AH - rev. 1/2018

10.5. Incompatible materials

2-METHOXY-1-METHYLETHYL ACETATE

Incompatible with: oxidising substances, strong acids, alkaline metals.

HEXAMETHYLENE-DI-ISOCYANATE

Incompatible with: alcohols, carboxylic acids, amines, strong bases.

10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

ETHYLBENZENE

May develop: methane, styrene, hydrogen, ethane.

HEXAMETHYLENE-DI-ISOCYANATE

May develop: nitric oxide, hydrogen cyanide.

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

4-TOLUENSOLFONILISOCIANATO

TOSSICITA' ACUTA PER OCCHI E PELLE.

11.1. Information on toxicological effects

XYLENE (MIXTURE OF ISOMERS)

XYLENE (MIXTURE OF ISOMERS): has a toxic effect on the CNS (encephalopathies). Irritating to the skin, conjunctivae, cornea and respiratory apparatus.

Metabolism, toxicokinetics, mechanism of action and other information

2-METHOXY-1-METHYLETHYL ACETATE

The main route of entry is the skin, whereas the respiratory route is less important due to the low vapour pressure of the product.

Information on likely routes of exposure

2-METHOXY-1-METHYLETHYL ACETATE

WORKERS: inhalation; contact with the skin.

ETHYLBENZENE

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; contact with the skin of products containing the substance.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

2-METHOXY-1-METHYLETHYL ACETATE

Above 100 ppm causes irritation of the eye, nose and oropharynx mucous membranes. At 1000 ppm, disturbance of equilibrium and severe eye irritation

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS ENAMEL Component B - SAFETY DATA SHEET - march 2017 - n°batch 065-AH - rev. 1/2018

can be noticed. Clinical and biological examinations carried out on exposed volunteers revealed no anomalies. Acetate produces greater skin and eye irritation with direct contact. No chronic effects on humans have been reported (INCR, 2010).

ETHYLBENZENE

As the counterparts of benzene, may have an acute effect on the central nervous system, with depression, narcosis, often preceded by dizziness and associated with headache (IspeSl). Is irritating for skin, conjunctiva and respiratory tract.

Interactive effects

Information not available

ACUTE TOXICITY

LC50 (Inhalation - vapours) of the mixture:> 20 mg/l

LC50 (Inhalation - mists / powders) of the mixture:2,1 mg/l

LD50 (Oral) of the mixture:Not classified (no significant component)

LD50 (Dermal) of the mixture:>2000 mg/kg

2-METHOXY-1-METHYLETHYL ACETATE

LD50 (Oral) 8530 mg/kg Rat

LD50 (Dermal) > 5000 mg/kg Rat

LC50 (Inhalation)

ETHYLBENZENE

LD50 (Oral) 3500 mg/kg Rat

LD50 (Dermal) 15354 mg/kg Rabbit

LC50 (Inhalation)

HEXAMETHYLENE-DI-ISOCYANATE

LC50 (Inhalation)

XYLENE (MIXTURE OF ISOMERS)

LD50 (Oral) 3523 mg/kg Rat

LD50 (Dermal) 4350 mg/kg Rabbit

LC50 (Inhalation)

4-TOLUENSOLFONILISOCIANATO

LD50 (Oral) > 2600 mg/kg Ratto

SKIN CORROSION / IRRITATION

Causes skin irritation

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye irritation

RESPIRATORY OR SKIN SENSITISATION

Sensitising for the skinMay produce an allergic reaction.Contains:4-TOLUENSOLFONILISOCIANATO

HEXAMETHYLENE-DI-ISOCYANATE

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

ETHYLBENZENE

Classified in Group 2B (possible human carcinogen) by the International Agency for Research on Cancer (IARC) - (IARC, 2000).

Classified in Group D (not classifiable as a human carcinogen) by the US Environmental Protection Agency (EPA) - (US EPA file on-line 2014).

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

May cause respiratory irritation

STOT - REPEATED EXPOSURE

May cause damage to organs

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class Viscosity: >20,5 mm²/sec (40°C)

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS ENAMEL Component B - SAFETY DATA SHEET - march 2017 - n°batch 065-AH - rev. 1/2018

SECTION 12. Ecological information

No specific data are available for this product. Handle it according to good working practices. Avoid littering. Do not contaminate soil and waterways. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation. Please take all the proper measures to reduce harmful effects on aquifers.

12.1. Toxicity

| | |
|---|--------------------------------------|
| 2-METHOXY-1-METHYLETHYL ACETATE | |
| LC50 - for Fish | > 100 mg/l/96h Oncorhynchus mykiss |
| EC50 - for Crustacea | > 408 mg/l/48h Daphnia magna |
| EC50 - for Algae / Aquatic Plants | > 100 mg/l/72h |
| Chronic NOEC for Fish | 47,5 mg/l Oncorhynchus mykiss |
| Chronic NOEC for Crustacea | > 99 mg/l Daphnia magna |
| Chronic NOEC for Algae / Aquatic Plants | > 999 mg/l Selenastrum capricornutum |

| | |
|-----------------------------|------------------------------------|
| XYLENE (MIXTURE OF ISOMERS) | |
| LC50 - for Fish | > 4,2 mg/l/96h Oncorhynchus mykiss |
| EC50 - for Crustacea | > 2,93 mg/l/48h Daphnia Magna |

12.2. Persistence and degradability

| | |
|---------------------------------|--------------|
| 2-METHOXY-1-METHYLETHYL ACETATE | |
| Solubility in water | > 10000 mg/l |
| Rapidly degradable | |

| | |
|---------------------|-------------------|
| ETHYLBENZENE | |
| Solubility in water | 1000 - 10000 mg/l |
| Rapidly degradable | |

HEXAMETHYLENE-DI-ISOCYANATE
NOT rapidly degradable

| | |
|--|-----------------|
| XYLENE (MIXTURE OF ISOMERS) | |
| Solubility in water | 100 - 1000 mg/l |
| Degradability: information not available | |

12.3. Bioaccumulative potential

2-METHOXY-1-METHYLETHYL ACETATE

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS ENAMEL Component B - SAFETY DATA SHEET - march 2017 - n°batch 065-AH - rev. 1/2018

Partition coefficient: n-octanol/water 1,2

ETHYLBENZENE

Partition coefficient: n-octanol/water 3,6

HEXAMETHYLENE-DI-ISOCYANATE

Partition coefficient: n-octanol/water 3,2

BCF 3,2

XYLENE (MIXTURE OF ISOMERS)

Partition coefficient: n-octanol/water 3,12

BCF 25,9

12.4. Mobility in soil

XYLENE (MIXTURE OF ISOMERS)

Partition coefficient: soil/water 2,73

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

14.1. UN number

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS ENAMEL Component B - SAFETY DATA SHEET - march 2017 - n°batch 065-AH - rev. 1/2018


ADR / RID, IMDG, 1263
IATA:

14.2. UN proper shipping name

ADR / RID: PAINT or PAINT
RELATED
MATERIAL
IMDG: PAINT or PAINT
RELATED
MATERIAL
IATA: PAINT or PAINT
RELATED
MATERIAL

14.3. Transport hazard class(es)

ADR / RID: Class: 3 Label: 3
IMDG: Class: 3 Label: 3
IATA: Class: 3 Label: 3



14.4. Packing group

ADR / RID, IMDG, III
IATA:

14.5. Environmental hazards

ADR / RID: NO
IMDG: NO
IATA: NO

14.6. Special precautions for user

| | | | |
|------------|--|-------------------------------|--------------------------------------|
| ADR / RID: | HIN - Kemler: 30 | Limited Quantities: 5 L | Tunnel restriction code: (D/E) |
| IMDG: | Special Provision: - EMS: F-E, <u>S-E</u> | Limited Quantities: 5 L | |
| IATA: | Cargo: | Maximum quantity: 220 L | Packaging instructions: 366 |
| | Pass.: | Maximum quantity: 60 L | Packaging instructions: 355 |
| | Special Instructions: | A3, A72, A192 | |

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS ENAMEL Component B - SAFETY DATA SHEET - march 2017 - n°batch 065-AH - rev. 1/2018

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EC: P5c

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product
Point 3 - 40

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage greater than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

German regulation on the classification of substances hazardous to water (VwVwS 2005)

WGK 2: Hazard to waters

15.2. Chemical safety assessment

A chemical safety assessment has been performed for the following contained substances

2-METHOXY-1-METHYLETHYL ACETATE

XYLENE (MIXTURE OF ISOMERS)

**SECTION 16. Other information**

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

| | |
|--------------------------|--|
| Flam. Liq. 2 | Flammable liquid, category 2 |
| Flam. Liq. 3 | Flammable liquid, category 3 |
| Acute Tox. 1 | Acute toxicity, category 1 |
| Acute Tox. 4 | Acute toxicity, category 4 |
| Asp. Tox. 1 | Aspiration hazard, category 1 |
| STOT RE 2 | Specific target organ toxicity - repeated exposure, category 2 |
| Skin Corr. 1C | Skin corrosion, category 1C |
| Eye Irrit. 2 | Eye irritation, category 2 |
| Skin Irrit. 2 | Skin irritation, category 2 |
| STOT SE 3 | Specific target organ toxicity - single exposure, category 3 |
| Resp. Sens. 1 | Respiratory sensitization, category 1 |
| Skin Sens. 1 | Skin sensitization, category 1 |
| Aquatic Chronic 3 | Hazardous to the aquatic environment, chronic toxicity, category 3 |
| H225 | Highly flammable liquid and vapour. |
| H226 | Flammable liquid and vapour. |
| H330 | Fatal if inhaled. |
| H302 | Harmful if swallowed. |
| H312 | Harmful in contact with skin. |
| H332 | Harmful if inhaled. |
| H304 | May be fatal if swallowed and enters airways. |
| H373 | May cause damage to organs through prolonged or repeated exposure. |
| H314 | Causes severe skin burns and eye damage. |
| H319 | Causes serious eye irritation. |
| H315 | Causes skin irritation. |
| H335 | May cause respiratory irritation. |
| H334 | May cause allergy or asthma symptoms or breathing difficulties if inhaled. |
| H317 | May cause an allergic skin reaction. |
| H412 | Harmful to aquatic life with long lasting effects. |
| EUH014 | Reacts violently with water. |
| EUH204 | Contains isocyanates. May produce an allergic reaction. |

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS ENAMEL Component B - SAFETY DATA SHEET - march 2017 - n°batch 065-AH - rev. 1/2018

- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EU) 1907/2006 (REACH) of the European Parliament
 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
 3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
 4. Regulation (EU) 2015/830 of the European Parliament
 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- The Merck Index. - 10th Edition
 - Handling Chemical Safety
 - INRS - Fiche Toxicologique (toxicological sheet)
 - Patty - Industrial Hygiene and Toxicology
 - N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
 - IFA GESTIS website
 - ECHA website
 - Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.