

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY
tel. +39 0584 383694 fax +39 0584 395182
www.cecchi.it info@cecchi.it



SPINNAKER GOLD FASHION MAT – Safety Data Sheet - january 2019 - batch 017-Ai - rev.1/16

SPINNAKER GOLD FASHION MAT

* SECTION 1 Identification of the substance/preparation and of the company/undertaking

1.1 Product identifier

Trade name: **SPINNAKER GOLD FASHION MAT**

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product category PC9a Coatings and paints, thinners, paint removers

Process category PROC10 Roller application or brushing

Environmental release category

ERC10b Wide dispersive outdoor use of long-life articles and materials with high or intended release (including abrasive processing)

ERC2 Formulation of preparations

Application of the substance / the mixture

See our technical datasheet for application of this product.

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Cecchi Gustavo & C. srl - Via M. Coppino 253, 55049 Viareggio (LU) ITALY www.cecchi.it - info@cecchi.it

1.4 Emergency telephone number:

: +39 0584/383694 - info@cecchi.it

From monday to friday office hours 8:30 – 12:30, 14:00 – 18:30

* SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms



GHS02

Signal word Warning

Hazard statements

H226 Flammable liquid and vapour.

Precautionary statements

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

Contains cobaltbis(2-ethylhexanoat), 2-butanone oxime. May cause an allergic reaction.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY
tel. +39 0584 383694 fax +39 0584 395182
www.cecchi.it info@cecchi.it



SPINNAKER GOLD FASHION MAT – Safety Data Sheet - january 2019 - batch 017-Ai - rev.1/16

* SECTION 3: Composition/information on ingredients

3.2 Chemical characterisation: Mixtures

Description:

Resin mixture

Solvent mixture with additives

Mixture of synthetic binders, matting agent, additives
and organic solvents

Mixture of synthetic binders, matting agent, additives and organic solvents

Dangerous components:		
CAS: 64742-48-9 EINECS: 265-150-3 Index number: 649-327-00-6 Reg.nr.: 01-2119463258-33	Naphtha (petroleum), hydrotreated heavy Flam. Liq. 3, H226 Asp. Tox. 1, H304	25-50%
CAS: 107-98-2 EINECS: 203-539-1 Index number: 603-064-00-3 Reg.nr.: 01-2119457435-35	1-methoxy-2-propanol Flam. Liq. 3, H226 STOT SE 3, H336	<= 2.5%
CAS: 127519-17-9 ELINCS: 407-000-3 Index number: 607-281-00-4 Reg.nr.: 01-0000015648-61	A mixture of branched and linear C7-C9 alkyl 3-[3-(2H-benzotriazol-2-yl)- 5-(1,1- dimethyl-ethyl)-4-hydroxyphenyl] propionates	<=0,5%
CAS: 96-29-7 EINECS: 202-496-6 Index number: 616-014-00-0 Reg.nr.: 01-2119539477-28	2-butanone oxime Carc. 2, H351 Eye Dam. 1, H318 Acute Tox. 4, H312; Skin Sens. 1, H317	<=0.5%
CAS: 136-52-7 EINECS: 205-250-6 Reg.nr.: 01-2119524678-29	cobalt bis(2-ethylhexanoate) Repr. 2, H361 Aquatic Acute 1, H400; Aquatic Chronic 1, H410 Skin Sens. 1, H317	<=0.5%

Additional information:

Note P: The substance does not have to be classified as a carcinogen or mutagen as can be shown that the substance contains less than 0.1% (w / w) benzene (EINECS No 200-753-7.). This note applies only to certain complex oil-derived substances in Part 3

* SECTION 4: First aid measures

4.1 Description of first aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact: Generally the product does not irritate the skin.

After eye contact: Rinse opened eye for several minutes under running water.

After swallowing: If symptoms persist consult doctor.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

* SECTION 5: Firefighting measures

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY
tel. +39 0584 383694 fax +39 0584 395182
www.cecchi.it info@cecchi.it



SPINNAKER GOLD FASHION MAT – Safety Data Sheet - january 2019 - batch 017-Ai - rev.1/16

5.1 Extinguishing media

Suitable extinguishing agents:

CO₂, sand, extinguishing powder. Do not use water.

For safety reasons unsuitable extinguishing agents:

Water

Water with full jet

5.2 Special hazards arising from the substance or mixture

No further relevant information available.

5.3 Advice for firefighters

Protective equipment: No special measures required.

* SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Do not flush with water or aqueous cleansing agents

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

* SECTION 7: Handling and storage

7.1 Precautions for safe handling Keep away from heat and direct sunlight.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles: No special requirements.

Information about storage in one common storage facility: Not required.

Further information about storage conditions: Keep container tightly sealed.

7.3 Specific end use(s) No further relevant information available

* SECTION 8: Exposure controls/personal protection

Additional information about design of technical facilities:

No further data; see item 7.

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

107-98-2 1-methoxy-2-propanol		
Inhalative	(Tgg)time weighted average 15 min. / Exposure time	563 mg/m ³ (Algemene bevolking/ General population)
	(Tgg)time weighted average 8 hours / Exposure time	375 mg/m ³ (Algemene bevolking/ General population)
107-98-2 1-methoxy-2-propanol		
WEL	Short-term value: 560 mg/m ³ , 150 ppm Long-term value: 375 mg/m ³ , 100 ppm	



	Sk	
DNELs		
64742-48-9 naphta (petroleum), hydrotreated heavy		
Dermal	Long-term - systemic effects, worker	300 mg/kg bw/day (Werker/Worker)
Inhalative	Long-term - systemic effects, worker	1500 mg/m3 (Werker/Worker)
96-29-7 2-butanone oxime		
Inhalative	Acute - systemic effects, worker	320-1000 mg/m3 (Fish Acute Toxicity Study)

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Personal protective equipment:

General protective and hygienic measures:

Wash hands before breaks and at the end of work.

Respiratory protection:

Not necessarily with good ventilation, however, use a filter AX when ventilation is inadequate!

Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradationMaterial of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the permanent contact gloves made of the following materials are suitable:

nitrile rubber;

recommended glove thickness > 0.45mm. permeability / permeation time: > 480 min. according to EN 374.

As protection from splashes gloves made of the following materials are suitable:

Cloroprene; handglove thickness > 0.7mm, penetration time > 60min. according EN374.

Nitrilrubber; handglove thickness > 0.3mm, penetration time > 60min. according EN374.

Eye protection:

Tightly sealed goggles

* SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Appearance:

Form:

Fluid

Colour:

According to product specification

Odour:

Characteristic

Odour threshold:

Not determined.

pH-value:

Not determined.

Change in condition

Melting point/Melting range:

Undetermined.

Boiling point/Boiling range:

150 °C

Flash point:

> 42 °C

Flammability (solid, gaseous):

Not applicable.

Ignition temperature:

240.0 °C

Decomposition temperature:

Not determined.

Self-igniting:

Product is not selfigniting.

Danger of explosion:

Product is not explosive. However, formation of explosive air/vapour



mixtures are possible.

Explosion limits:	
Lower:	0.6 Vol %
Upper:	7.0 Vol %
Vapour pressure at 20 °C:	1.0 hPa
Density at 20 °C:	0.92854 g/cm ³
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/water):	Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic at 20 °C:	35 s (ISO 6 mm)
Solvent content:	
Organic solvents:	51.0 %
VOC content:	51.0 %
	VOC content:
	473.6 g/l / 3.95 lb/gl
Solids content:	51.9 % (SC % 1h150 C)
9.2 Other information	No further relevant information available.

*** SECTION 10: Stability and reactivity**

10.1 Reactivity No further relevant information available.

10.2 Chemical stability

Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

10.3 Possibility of hazardous reactions No dangerous reactions known.

10.4 Conditions to avoid No further relevant information available.

10.5 Incompatible materials: No further relevant information available.

10.6 Hazardous decomposition products:

No dangerous decomposition products known.

*** SECTION 11: Toxicological information**

11.1 Information on toxicological effects

Acute toxicity:

LD/LC50 values relevant for classification:

64742-48-9 naphta (petroleum), hydrotreated heavy		
Oral	LD50	>5000 mg/kg bw (rat)
Dermal	LD50	>5000 mg/kg bw (rabbit) ((24h))
Inhalative	LD50	>5000 mg/m ³ (vapour) (rat) ((8h))
107-98-2 1-methoxy-2-propanol		
Oral	LD50	5660 mg/kg bw (rat)
Dermal	LD50	13000 mg/kg bw (rabbit)
Inhalative	LC50/4 h	6 mg/l (rat)
64742-95-6 petroleum, nafta, licht aromatisch		
Oral	LD50	3592 mg/kg (rat)
Dermal	LD50 (Konijn)	3160 mg/kg (rabbit)
Inhalative	LC50 (rat)	>6193 mg/m ³ (rat)
96-29-7 2-butanone oxime		
Oral	LD50	3700 mg/kg bw (rat)
Dermal	LD50	200-2000 mg/kg bw (rat)
Inhalative	LC50/4 h	20 mg/l (rat)
95-63-6 1,2,4-trimethylbenzene		
Oral	LD50	5000 mg/kg bw (rat)
136-52-7 cobalt bis(2-ethylhexanoate)		

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY
tel. +39 0584 383694 fax +39 0584 395182
www.cecchi.it info@cecchi.it



SPINNAKER GOLD FASHION MAT – Safety Data Sheet - january 2019 - batch 017-Ai - rev.1/16

Oral	LD50	>5000 mg/kg (rat)
Dermal	LD50 (Konijn)	5000 mg/kg (rabbit)

Primary irritant effect:

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Serious eye damage/irritation

Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

Based on available data, the classification criteria are not met.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

* SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity:	
64742-48-9 naphta (petroleum), hydrotreated heavy	
EL50 (48h)	>1000 mg/l ((Daphnia magna-OECD 202))
EbL50 (72h)	>1000 mg/l (Pseudokirchneriella subcapitata-OECD 201)
ErL (72h)	>1000 mg/l (Pseudokirchneriella subcapitata-OECD 201)
LL50 (96h)	>1000 mg/l ((Onorhynchus mykiss OECD 203))
NOELR (72h)	3 mg/l ((Pseudo. subcapitata-biomass-OECD 201)) 100 mg/l ((Pseudo. subcap. growth rate OECD 201))
96-29-7 2-butanone oxime	
EC50	630 mg/l (other waterspecies 1) (BACTERIA; TOXICITEITSTEST)
EC50 (48 hours)	500 mg/l (daphnia magna) 750 mg/l (Daphnia similis Acute Toxicity Study) (DAPHNIA MAGNA)
EC50 (72 hours)	83 mg/l (other waterspecies 2) (SCENEDESMUS SUBSPICATUS)
LC50 (48 hours)	750 mg/l (other waterspecies 1)
LC50 (96 hours)	320-1000 mg/l (fish 1) (LEUCISCUS IDUS; STATISCH SYSTEM) 48 mg/l (fish 2) (LEPOSMIS MACEOCHIRUS; STATISCH SYSTEM)
136-52-7 cobalt bis(2-ethylhexanoate)	
EC50	0.1-1 mg/l (Algae, Growth inhibition test) 0.1-1 mg/l (daphnia magna)
LC50	0.1-1 mg/l (Fish Acute Toxicity Study)

12.2 Persistence and degradability No further relevant information available.

12.3 Bioaccumulative potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

Additional ecological information:

General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

12.5 Results of PBT and vPvB assessment

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY
tel. +39 0584 383694 fax +39 0584 395182
www.cecchi.it info@cecchi.it



SPINNAKER GOLD FASHION MAT – Safety Data Sheet - january 2019 - batch 017-Ai - rev.1/16

PBT: Not applicable.

vPvB: Not applicable.

12.6 Other adverse effects No further relevant information available.

* SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

European waste catalogue

08 00 00	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS
08 01 00	wastes from MFSU and removal of paint and varnish
08 01 11*	waste paint and varnish containing organic solvents or other dangerous substances

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

* SECTION 14: Transport information

14.1 UN-Number

ADR, IMDG, IATA UN1263

14.2 UN proper shipping name

ADR 1263 PAINT (not viscous)
IMDG, IATA PAINT

14.3 Transport hazard class(es)

ADR
Class 3 (F1) Flammable liquids.
Label 3
IMDG, IATA
Class 3 Flammable liquids.
Label 3

14.4 Packing group

ADR, IMDG, IATA III

14.5 Environmental hazards:

Marine pollutant: No

14.6 Special precautions for user

Warning: Flammable liquids.
Danger code (Kemler): 30
EMS Number: F-E,S-E

14.7 Transport in bulk according to

Annex II of MARPOL73/78 and the IBC Code Not applicable.

Transport/Additional information:

ADR

Limited quantities (LQ) 5L

Excepted quantities (EQ) Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

Transport category 3

Tunnel restriction code D/E

IMDG

Limited quantities (LQ) 5L

Excepted quantities (EQ) Code: E1

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY
tel. +39 0584 383694 fax +39 0584 395182
www.cecchi.it info@cecchi.it



SPINNAKER GOLD FASHION MAT – Safety Data Sheet - january 2019 - batch 017-Ai - rev.1/16

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

Remarks: ≤30 1: -

UN "Model Regulation": UN1263, PAINT (not viscous), 3, III

* SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

National regulations:

Technical instructions (air):

Class	Share in %
-------	------------

I	≤ 0.5
---	-------

NK	50-100
----	--------

Waterhazard class:

Water hazard class 1 (Self-assessment): slightly hazardous for water.

15.2 Chemical safety assessment:

A Chemical Safety Assessment has not been carried out.

* SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H336 May cause drowsiness or dizziness.

H351 Suspected of causing cancer.

H361 Suspected of damaging fertility or the unborn child.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids, Hazard Category 3

Acute Tox. 4: Acute toxicity, Hazard Category 4

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY
tel. +39 0584 383694 fax +39 0584 395182
www.cecchi.it info@cecchi.it



SPINNAKER GOLD FASHION MAT – Safety Data Sheet - january 2019 - batch 017-Ai - rev.1/16

Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

Carc. 2: Carcinogenicity, Hazard Category 2

Repr. 2: Reproductive toxicity, Hazard Category 2

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

Asp. Tox. 1: Aspiration hazard, Hazard Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - AcuteHazard, Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - Chronic Hazard, Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2

* Data compared to the previous version altered.

GB