Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it

SPINNAKER MAHOGANY - SAFETY DATA SHEET batch may 2017 n° 159-AG – rev.2/15



# SPINNAKER MAHOGANY

### \* SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: SPINNAKER MAHOGANY

1.2 Relevant identified uses of the substance or mixture and uses advised against stain

Product category PC9a Coatings and paints, thinners, paint removers

Process category PROC10 Roller application or brushing

Environmental release category

ERC10b Wide dispersive outdoor use of long-life articles and materials with high or intended

release (including abrasive processing)

ERC2 Formulation of preparations

Application of the substance / the mixture

See our technical datasheet for application of this product.

Stain for coloring bare wood and/or varnishes
1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

CECCHI GUSTAVO & C. SRL.

Via M.Coppino, 253 55049 VIAREGGIO (LU) ITALY TEL. +39 0584 383694 FAX +39 0584 395182

1.4 Emergency telephone number:

+39 0584/383694 From monday to friday office hours 8:30 - 12:30, 14:00 - 18:30 - info@cecchi.it

#### \* SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.

GHS08 health hazard

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

GHS09 environment

Aquatic Chronic 2

GHS07

H411 Toxic to aquatic life with long lasting effects.

STOT SE 3 2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms









H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

GHS02

GHS07

Signal word Danger Hazard-determining components of labelling:

Solvent naphtha (petroleum), light arom.

Hazard statements

H226 Flammable liquid and vapour.

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

H304 May be fatal if swallowed and enters airways.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P271 Use only outdoors or in a well-ventilated area.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it

SPINNAKER MAHOGANY - SAFETY DATA SHEET batch may 2017 n° 159-AG – rev.2/15



P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable. vPvB: Not applicable

## \* SECTION 3: Composition/information on ingredients

3.2 Chemical characterisation: Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:

| CAS: 64742-95-6<br>EINECS: 265-199-0<br>Index number: 649-356-00-4<br>Reg.nr.: 01-2119486773-24 | Solvent naphtha (petroleum), light arom. Flam. Liq. 3, H226 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 STOT SE 3, H335-H336 | 50-100% |
|---|--|---------|
| CAS: 107-98-2<br>EINECS: 203-539-1<br>Index number: 603-064-00-3<br>Reg.nr.: 01-2119457435-35   | 1-methoxy-2-propanol<br>Flam. Liq. 3, H226<br>STOT SE 3, H336  | 2,5-10% |

#### Additional information:

Note P: The substance does not have to be classified as a carcinogen or mutagen as can be shown that the substance contains less than 0.1% (w / w) benzene (EINECS No 200-753-7.). This note applies only to certain complex oil-derived substances in Part 3.

For the wording of the listed risk phrases refer to section 16.

#### \* SECTION 4: First aid measures

4.1 Description of first aid measures

After inhalation:

In case of unconsciousness place patient stably in side position for transportation.

After skin contact: Immediately wash with water and soap and rinse thoroughly.

After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing: If symptoms persist consult doctor.

- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

### \* SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture

No further relevant information available.

5.3 Advice for firefighters

Protective equipment: No special measures required.

## \* SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures. Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it

SPINNAKER MAHOGANY - SAFETY DATA SHEET batch may 2017 n° 159-AG - rev.2/15



Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## \* SECTION 7: Handling and storage

7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles: No special requirements.

Information about storage in one common storage facility: Not required.

Further information about storage conditions: Keep container tightly sealed.

7.3 Specific end use(s) No further relevant information available.

## \* SECTION 8: Exposure controls/personal protection

Additional information about design of technical facilities:

No further data; see item 7.

8.1 Control parameters

| 107-98-2 1-methoxy-2-propanol |                                      |  |  |  |
|-------------------------------|--------------------------------------|--|--|--|
| Inhalative                    | (Tgg)time weighted average 15        | 563 mg/m3                                |  |  |
|                               | min. / Exposure time                 | (Algemene bevolking /General population) |  |  |
|                               | (Tgg)time weighted average 8         | 375 mg/m3 (Algemene                      |  |  |
|                               | hours / Exposure time                | bevolking /General population)           |  |  |
| 107-98-2 1-methoxy-2-propanol |                                      |  |  |  |
| WEL                           | Short-term value: 560 mg/m3, 150 ppm |  |  |  |
|                               | Long-term value: 375 mg/m3, 100 ppm  |  |  |  |
|                               | Sk                                   |  |  |  |

107-98-2 1-methoxy-2-propanol

WEL Short-term value: 560 mg/m3, 150 ppm Long-term value: 375 mg/m3, 100 ppm

Sk

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Personal protective equipment:

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter AX

Protection of hands:

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it

**SPINNAKER MAHOGANY -** SAFETY DATA SHEET batch may 2017  $n^{\circ}$  159-AG – rev.2/15



Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the permanent contact gloves made of the following materials are suitable: nitrile rubber; recommended glove thickness> 0.45mm, permeability / permeation time;> 480 min, according to EN 374.

As protection from splashes gloves made of the following materials are suitable:

PVC gloves

Nitrile

Glove thickness> 0.45 mm, breakthrough time> 30 min. to EN374 Not suitable are gloves made of the following materials: None

Eye protection:

Tightly sealed goggles

### \* SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

**General Information** 

Appearance:

Form: Fluid

Colour: According to product specification

Odour: Characteristic
Odour threshold: Not determined.
pH-value: Not determined.

Change in condition

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: 120 °C Flash point: 31 °C

Flammability (solid, gaseous): Not applicable.

Ignition temperature: 270 °C

Decomposition temperature: Not determined.

Self-igniting: Product is not selfigniting.

Danger of explosion: Product is not explosive. However, formation of explosive air/vapour

mixtures are possible.

Explosion limits:

Lower: 0.7 Vol % Upper: 7.5 Vol %

Vapour pressure at 20 °C: 5 hPa
Density at 20 °C: 0.9 g/cm3
Relative density Not determined.
Vapour density Not determined.
Evaporation rate Not determined.

Solubility in / Miscibility with water: Not miscible or difficult to mix.

Partition coefficient (n-octanol/water): Not determined.

Viscosity:

Dynamic: Not determined. Kinematic at 20 °C: 10 s (DIN 53211/4)

Solvent content:

Organic solvents: 97.2 % VOC content: 97.2 %

VOC content:

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it

SPINNAKER MAHOGANY - SAFETY DATA SHEET batch may 2017 n° 159-AG - rev.2/15



874.4 g/l / 7.30 lb/gl

Solids content: 2.8 %

9.2 Other information No further relevant information available.

#### \* SECTION 10: Stability and reactivity

10.1 Reactivity No further relevant information available.

10.2 Chemical stability

Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.

10.6 Hazardous decomposition products:

No dangerous decomposition products known.

#### \* SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity:

| LD/LC50 values relevant for   | or classification:                   |                         |  |  |
|-------------------------------|--------------------------------------|-------------------------|--|--|
| 64742-95-6 Solvent naphth     | na (petroleum), light arom. (Note-P) |                         |  |  |
| Oral                          | LD50                                 | 3592 mg/kg (rat)        |  |  |
| Dermal                        | LD50 (Konijn)                        | 3160 mg/kg (rabbit)     |  |  |
| Inhalative                    | LC50 (rat)                           | >6193 mg/m3 (rat)       |  |  |
| 107-98-2 1-methoxy-2-propanol |                                      |                         |  |  |
| Oral                          | LD50                                 | 5660 mg/kg bw (rat)     |  |  |
| Dermal                        | LD50                                 | 13000 mg/kg bw (rabbit) |  |  |
| Inhalative                    | LC50/4 h                             | 6 mg/l (rat)            |  |  |

Primary irritant effect:

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Serious eye damage/irritation

Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

Based on available data, the classification criteria are not met.

CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation. May cause drowsiness or dizziness.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

May be fatal if swallowed and enters airways.

### \* SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity: No further relevant information available.

- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.

Ecotoxical effects:

Remark: Toxic for fish

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it

### SPINNAKER MAHOGANY - SAFETY DATA SHEET batch may 2017 n° 159-AG - rev.2/15



Additional ecological information:

General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

12.5 Results of PBT and vPvB assessment

PBT: Not applicable. vPvB: Not applicable.

12.6 Other adverse effects No further relevant information available.

#### \* SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

European waste catalogue

|           | Europouri Muoto Gataloguo                                    |  |  |
|-----------|--|--|--|
| 08 00 00  | WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE     |  |  |
|           | (MFSU) OF  |  |  |
|           | COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS),           |  |  |
|           | ADHESIVES,   |  |  |
|           | SEALANTS AND PRINTING INKS                                   |  |  |
| 08 01 00  | wastes from MFSU and removal of paint and varnish            |  |  |
| 08 01 11* | waste paint and varnish containing organic solvents or other |  |  |
|           | dangerous substances   |  |  |

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

# \* SECTION 14: Transport information

14.1 UN-Number

ADR, IMDG, IATA UN1263

14.2 UN proper shipping name

ADR 1263 PAINT RELATED MATERIAL, ENVIRONMENTALLY HAZARDOUS

IMDG, IATA PAINT RELATED MATERIAL

14.3 Transport hazard class(es)

**ADR** 

Class 3 Flammable liquids.

Label

IMDG, IATA

Class 3 Flammable liquids.

Label 3

14.4 Packing group

ADR, IMDG, IATA III

14.5 Environmental hazards:

Marine pollutant: No

Special marking (ADR): Symbol (fish and tree) 14.6 Special precautions for user Warning: Flammable liquids.

Danger code (Kemler): 30
EMS Number: F-E,S-E

14.7 Transport in bulk according to

Annex II of Marpol and the IBC Code Not applicable.

Transport/Additional information:

**ADR** 

Limited quantities (LQ) 5L Excepted quantities (EQ) Code: E1

Maximum net quantity per inner packaging: 30 ml

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it

SPINNAKER MAHOGANY - SAFETY DATA SHEET batch may 2017 n° 159-AG - rev.2/15



Maximum net quantity per outer packaging:1000 ml

Tunnel restriction code D

**IMDG** 

Limited quantities (LQ) 5L

Excepted quantities (EQ) Code: E1

Maximum net quantity per inner packaging:30 ml Maximum net quantity per outer packaging:1000 ml

UN "Model Regulation": UN1263, PAINT RELATED MATERIAL, ENVIRONMENTALLY HAZARDOUS, 3, III

### \* SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the

substance or mixture

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

National regulations:

Technical instructions (air):

Class Share in % NK 50-100

Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.

15.2 Chemical safety assessment:

A Chemical Safety Assessment has not been carried out.

#### \* SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids, Hazard Category 3

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

Asp. Tox. 1: Aspiration hazard, Hazard Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2

\* Data compared to the previous version altered