

## C-SYSTEMS 10 10 UV PROTECTION component A

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Trade name: **C-SYSTEMS 10 10 UV PROTECTION component A**

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture: Casting Resin

#### 1.3 Details of the supplier of the safety data sheet

Company Cecchi Gustavo & C. srl - Via M. Coppino 253,  
55049 Viareggio (LU) ITALY www.cecchi.it - info@cecchi.it

Information in case of emergency: +39 0584 383694 - info@cecchi.it

From monday to friday office hours 8:30 – 12:30, 14:00 – 18:30

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Skin irritation , Category 2	H315: Causes skin irritation.
Serious eye damage , Category 1	H318: Causes serious eye damage.
Skin sensitisation , Category 1	H317: May cause an allergic skin reaction.
Chronic aquatic toxicity , Category 2	H411: Toxic to aquatic life with long lasting effects.

#### 2.2 Label elements

##### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements :

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H411 Toxic to aquatic life with long lasting effects.

##### Precautionary statements : Prevention:

P261 Avoid breathing dust/ fume/ gas/ mist/vapours/ spray.

P273 Avoid release to the environment.

P280 Wear eye protection/ face protection.

##### Response:

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

P362 + P364 Take off contaminated clothing and wash it before reuse.

Hazardous components which must be listed on the label:

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight =< 700)

1,4-bis(2,3-epoxypropoxy)butane

bisphenol-F-epichlorohydrin resin, MM=<700

oxirane, mono[(C12-14-alkyloxy)methyl]derivs

bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate

#### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### SECTION 3: Composition/information on ingredients

#### 3.2 Mixtures

Chemical nature : Modified epoxy resin

**Hazardous components**

Chemical Name	CAS-No. EC-No. Registration number	Classification (REGULATION (EC) No	Concentration (%)
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700)	25068-38-6 01-2119456619-26	Eye Irrit. 2; H319 Skin Irrit. 2; H315 Skin Sens. 1; H317 Aquatic Chronic 2; H411	>= 50 - <= 100
1,4-bis(2,3-epoxypropoxy)butane	2425-79-8 219-371-7 01-2119494060-45	Acute Tox.4; H312 Eye Dam.1; H318 Acute Tox.4; H302 Skin Sens.1; H317 Aquatic Chronic3; H412	>= 12,5 - < 20
Bisphenol-F-epichlorohydrin resin, MM=<700	9003-36-5 01-2119454392-40	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 Aquatic Chronic 2; H411	>= 7 - < 10
oxirane, mono[(C12-14- alkyloxy)methyl]derivs	Not Assigned 271-846-8 01-2119485289-22	Skin Irrit. 2; H315 Skin Sens. 1; H317	>= 1 - < 3
bis(1,2,2,6,6-pentamethyl-4- piperidyl) sebacate	41556-26-7 255-437-1	Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 0,1 - < 0,25

For explanation of abbreviations see section 16.

**SECTION 4: First aid measures****4.1 Description of first aid measures**

General advice : Keep warm and in a quiet place.  
Show this safety data sheet to the doctor in attendance.  
Take off all contaminated clothing immediately.

If inhaled : Move to fresh air.  
Keep patient warm and at rest.  
If unconscious place in recovery position and seek medical advice.  
If symptoms persist, call a physician.  
If breathing is irregular or stopped, administer artificial respiration.

In case of skin contact : Wash off immediately with soap and plenty of water.  
Do NOT use solvents or thinners.  
If on clothes, remove clothes.  
If skin irritation persists, call a physician.

In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.  
If eye irritation persists, consult a specialist.  
If easy to do, remove contact lens, if worn.

If swallowed : Keep at rest.  
Do not induce vomiting without medical advice.  
Keep respiratory tract clear.  
If symptoms persist, call a physician.

## CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY  
tel. +39 0584 383694 fax +39 0584 395182  
www.cecchi.it info@cecchi.it



C-SYSTEMS 10 10 UV PROTECTION comp. A - SAFETY DATA SHEET - may 2017- n° batch 136-AG rev.1/17

### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms : irritant effects

Redness

sensitising effects

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : The first aid procedure should be established in consultation with the doctor responsible for industrial medicine.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media :

Foam

Sand

Carbon dioxide (CO<sub>2</sub>)

Water mist

Unsuitable extinguishing media:

Water spray jet

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting

: The pressure in sealed containers can increase under the influence of heat.

Cool closed containers exposed to fire with water spray.

### 5.3 Advice for firefighters

Special protective equipment for firefighters:

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

Further information : In the event of fire and/or explosion do not breathe fumes.

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Immediately evacuate personnel to safe areas.

Prevent fire extinguishing water from contaminating surface water or the ground water system.

Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Refer to protective measures listed in sections 7 and 8.

Evacuate personnel to safe areas.

Use personal protective equipment.

Ensure adequate ventilation.

Inform the responsible authorities in case of gas leakage, or of entry into waterways, soil or drains.

### 6.2 Environmental precautions

Environmental precautions : Do not allow uncontrolled discharge of product into the environment.

Try to prevent the material from entering drains or water courses.

Local authorities should be advised if significant spillages cannot be contained.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Pick up and transfer to properly labelled containers.

### 6.4 Reference to other sections

For personal protection see section 8.

## CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY  
tel. +39 0584 383694 fax +39 0584 395182  
www.cecchi.it info@cecchi.it



C-SYSTEMS 10 10 UV PROTECTION comp. A - SAFETY DATA SHEET - may 2017- n° batch 136-AG rev.1/17

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

Advice on safe handling :

Provide sufficient air exchange and/or exhaust in work rooms.

Avoid inhalation, ingestion and contact with skin and eyes.

Wear personal protective equipment.

Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

Advice on protection against fire and explosion:

Keep away from open flames, hot surfaces and sources of ignition.

Hygiene measures :

Provide adequate ventilation. Wash hands and face before breaks and immediately after handling the product.

#### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers:

Keep containers tightly closed in a dry, cool and wellventilated place. Keep in properly labelled containers.

Advice on common storage : Keep away from oxidizing agents, strongly acid or alkaline materials and amines.

Keep product and empty container away from heat and sources of ignition.

Keep away from food and drink.

Other data : Stable at normal ambient temperature and pressure.

#### 7.3 Specific end use(s)

Specific use(s) : Consult the technical guidelines for the use of this substance/mixture.

### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

Contains no substances with occupational exposure limit values.

#### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

reaction product: bisphenol-A-  
(epichlorhydrin); epoxy resin  
(number average molecular  
weight =< 700)

: End Use: Workers

Exposure routes: Skin contact

Potential health effects: Acute systemic effects, Long-term  
systemic effects

Value: 8,33 mg/kg

End Use: Workers

Exposure routes: Inhalation

Potential health effects: Acute systemic effects, Long-term local  
effects

Value: 12,25 mg/m<sup>3</sup>

End Use: Consumers

Exposure routes: Skin contact

Potential health effects: Acute systemic effects, Long-term  
systemic effects

Value: 3,571 mg/kg

End Use: Consumers

Exposure routes: Ingestion

Potential health effects: Acute systemic effects, Long-term  
systemic effects

Value: 0,75 mg/kg

oxirane, mono[(C12-14-  
alkyloxy)methyl]derivs

: End Use: Workers

Exposure routes: Skin contact

## CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY  
tel. +39 0584 383694 fax +39 0584 395182  
www.cecchi.it info@cecchi.it



**C-SYSTEMS 10 10 UV PROTECTION comp. A** - SAFETY DATA SHEET - may 2017- n° batch 136-AG rev.1/17

Potential health effects: Long-term systemic effects

Value: 3,9 mg/kg

End Use: Workers

Exposure routes: Inhalation

Potential health effects: Long-term systemic effects

Value: 13,8 mg/m<sup>3</sup>

**Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:**

reaction product: bisphenol-A-  
(epichlorhydrin); epoxy resin  
(number average molecular  
weight =< 700)

: Fresh water

Value: 0,006 mg/l

Marine water

Value: 0,0006 mg/l

Intermittent releases

Value: 0,018 mg/l

Sewage treatment plant

Value: 10 mg/l

Fresh water sediment

Value: 0,996 mg/kg

Marine sediment

Value: 0,0996 mg/kg

Soil

Value: 0,196 mg/kg

oxirane, mono[(C12-14-  
alkyloxy)methyl]derivs

: Sewage treatment plant

Value: 10 mg/l

Fresh water

Value: 0,0072 mg/l

Marine water

Value: 0,00072 mg/l

Fresh water sediment

Value: 66,77 mg/kg

Marine sediment

Value: 6,677 mg/kg

Soil

Value: 80,12 mg/kg

### 8.2 Exposure controls

#### Engineering measures

Effective exhaust ventilation system

effective ventilation in all processing areas

#### Personal protective equipment

Eye protection : Do not wear contact lenses.

Safety glasses with side-shields conforming to EN166

Ensure that eyewash stations and safety showers are close to  
the workstation location.

Hand protection

Material : Chemical resistant gloves made of butyl rubber or nitrile  
rubber category III according to EN 374.

Skin and body protection : Protective suit

Respiratory protection : Use respiratory protection unless adequate local exhaust  
ventilation is provided or exposure assessment demonstrates  
that exposures are within recommended exposure guidelines.

In the case of vapour formation use a respirator with an  
approved filter.

## CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY  
tel. +39 0584 383694 fax +39 0584 395182  
www.cecchi.it info@cecchi.it



C-SYSTEMS 10 10 UV PROTECTION comp. A - SAFETY DATA SHEET - may 2017- n° batch 136-AG rev.1/17

Respirator with a vapour filter (EN 141)

Apply technical measures to comply with the occupational exposure limits.

This should be achieved by a good general extraction and -if practically feasible- by the use of a local exhaust ventilation.

Protective measures : Avoid contact with skin.

Wear suitable protective equipment.

### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

Appearance :	liquid
Colour :	light yellow
Odour :	slight
Odour Threshold :	not determined
pH :	not determined
Melting point/freezing point :	Not applicable
Boiling point/boiling range :	> 200 °C
Flash point :	150 °C
Evaporation rate :	not determined
Upper explosion limit :	Not applicable
Lower explosion limit :	Not applicable
Vapour pressure :	Not applicable
Relative vapour density :	not determined
Density :	1,15 g/cm <sup>3</sup> (25 °C)
Bulk density :	not determined
Solubility(ies)	
Solubility in other solvents :	not determined
Partition coefficient: noctanol/ water:	No data available
Auto-ignition temperature :	Not applicable
Thermal decomposition : Method:	No data available
Viscosity	
Viscosity, dynamic :	800 - 1.200 mPa.s (25 °C)
Viscosity, kinematic :	not determined
Explosive properties :	Not applicable
Oxidizing properties :	Not applicable

#### 9.2 Other information

Surface tension :	not determined
Sublimation point :	Not applicable

### 10: Stability and reactivity

#### 10.1 Reactivity

Stable under recommended storage conditions.

#### 10.2 Chemical stability

No decomposition if stored and applied as directed.

#### 10.3 Possibility of hazardous reactions

Hazardous reactions : Reacts with the following substances:

Bases

Strong oxidizing agents

Avoid amines.

#### 10.4 Conditions to avoid

Conditions to avoid : No decomposition if used as directed.

#### 10.5 Incompatible materials

## CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY  
tel. +39 0584 383694 fax +39 0584 395182  
www.cecchi.it info@cecchi.it



C-SYSTEMS 10 10 UV PROTECTION comp. A - SAFETY DATA SHEET - may 2017- n° batch 136-AG rev.1/17

Materials to avoid : Incompatible with oxidizing agents.

### 10.6 Hazardous decomposition products

Hazardous decomposition products: This product may release the following:  
Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Acute toxicity

##### Product:

Acute oral toxicity : Acute toxicity estimate : > 2.000 mg/kg

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate : > 20 mg/l

Exposure time: 4 h

Test atmosphere: vapour

Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : > 2.000 mg/kg

Method: Calculation method

##### Components:

**reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight =< 700):**

Acute oral toxicity : LD50 (Rat, female): > 2.000 mg/kg

Method: OECD Test Guideline 420

GLP: yes

Acute dermal toxicity : LD50 (Rat, male and female): > 2.000 mg/kg

Method: OECD Test Guideline 402

GLP: yes

#### Skin corrosion/irritation

##### Product:

Remarks: No data available

##### Components:

**reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight =< 700):**

Species: Rabbit

Exposure time: 4 h

Method: OECD Test Guideline 404

Result: Skin irritation

GLP: yes

#### Serious eye damage/eye irritation

##### Product:

Remarks: No data available

#### Respiratory or skin sensitisation

##### Product:

Remarks: No data available

##### Components:

**reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight =< 700):**

Test Type: Mouse Local Lymph Node assay (LLNA)

Species: Mouse

Method: OECD Test Guideline 429

Result: May cause sensitisation by skin contact.

GLP: yes

**bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate:**

Species: Guinea pig

Method: OECD Test Guideline 406

Result: positive

#### Germ cell mutagenicity

## CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY  
tel. +39 0584 383694 fax +39 0584 395182  
www.cecchi.it info@cecchi.it



C-SYSTEMS 10 10 UV PROTECTION comp. A - SAFETY DATA SHEET - may 2017- n° batch 136-AG rev.1/17

### **Carcinogenicity**

#### **Reproductive toxicity**

##### **STOT - single exposure**

###### **Product:**

Remarks: Not applicable

##### **STOT - repeated exposure**

##### **Repeated dose toxicity**

###### **Product:**

Remarks: No data available

#### **Aspiration toxicity**

##### **Components:**

**reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight =< 700):**

No aspiration toxicity classification

#### **Further information**

##### **Product:**

Remarks: No data available

## **SECTION 12: Ecological information**

### **12.1 Toxicity**

#### **Product:**

Toxicity to fish : Remarks: No data available

Toxicity to daphnia and other aquatic invertebrates

: Remarks: No data available

#### **Components:**

**reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight =< 700):**

Toxicity to daphnia and other aquatic invertebrates

: EC50 (Daphnia (water flea)): 1,7 mg/l

Exposure time: 48 h

Test Type: static test

Method: OECD Test Guideline 202

GLP: yes

Toxicity to daphnia and other aquatic invertebrates

(Chronic toxicity)

: NOEC: 0,3 mg/l

Exposure time: 21 d

Species: Daphnia magna (Water flea)

Test Type: semi-static test

Method: OECD Test Guideline 211

GLP: yes

### **12.2 Persistence and degradability**

#### **Product:**

Biodegradability : Remarks: No data available

#### **Components:**

**reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight =< 700):**

Biodegradability : Result: Not readily biodegradable.

Method: OECD Test Guideline 301F

GLP: yes

### **12.3 Bioaccumulative potential**

#### **Product:**

Bioaccumulation : Remarks: No data available

#### **Components:**



## CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY  
tel. +39 0584 383694 fax +39 0584 395182  
www.cecchi.it info@cecchi.it



C-SYSTEMS 10 10 UV PROTECTION comp. A - SAFETY DATA SHEET - may 2017- n° batch 136-AG rev.1/17

### reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight =< 700):

Partition coefficient: noctanol/  
water

: log Pow: 3,242 (25 °C)

pH: 7,1

Method: OECD Test Guideline 117

GLP: yes

#### 12.4 Mobility in soil

No data available

#### 12.5 Results of PBT and vPvB assessment

##### Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

#### 12.6 Other adverse effects

##### Product:

Additional ecological  
information

: Remarks: An environmental hazard cannot be excluded

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

Product : In accordance with local and national regulations.

Container hazardous when empty.

Do not dispose of with domestic refuse.

Do not mix waste streams during collection.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.

### SECTION 14: Transport information

#### 14.1 UN number

ADR/RID/ADN : UN 3082

IMDG : UN 3082

IATA : UN 3082

#### 14.2 UN proper shipping name

ADR/RID/ADN : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,  
N.O.S.  
(Epoxy resin)

IMDG : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,  
N.O.S.  
(Epoxy resin)

IATA : Environmentally hazardous substance, liquid, n.o.s.  
(Epoxy resin)

#### 14.3 Transport hazard class(es)

ADR/RID/ADN : 9

IMDG : 9

IATA : 9

#### 14.4 Packing group

##### ADR/RID/ADN

Packing group : III

Classification Code : M6

Hazard Identification Number : 90

Labels : 9

Tunnel restriction code : E

Remarks : ADR: These substances when carried in single or combination packagings containing a net

## CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY  
tel. +39 0584 383694 fax +39 0584 395182  
www.cecchi.it info@cecchi.it



**C-SYSTEMS 10 10 UV PROTECTION comp. A** - SAFETY DATA SHEET - may 2017- n° batch 136-AG rev.1/17

quantity per single or inner packaging of 5 l or less for liquids or having a net mass per single or inner packaging of 5 kg or less for solids, are not subject to any other provisions of ADR provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

### IMDG

Packing group : III

Labels : 9

EmS Code : F-A, S-F

Remarks : IMDG: Marine pollutants packaged in single or combination packagings containing a net quantity per single or inner packaging of 5 l or less for liquids or having a net mass per single or inner packaging of 5 kg or less for solids are not subject to any other provisions of this Code relevant to marine pollutants provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8. In the case of marine pollutants also meeting the criteria for inclusion in another hazard class all provisions of this Code relevant to any additional hazards continue to apply.

### IATA

Packing instruction (cargo aircraft) : 964

Packing instruction (passenger aircraft) : 964

Packing group : III

Labels : 9

Remarks : IATA: These substances when transported in single or combination packagings containing a net quantity per single or inner packaging of 5 L or less for liquids or having a net mass of 5 kg or less for solids, are not subject to any other provisions of these Regulations provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.

### 14.5 Environmental hazards

#### ADR/RID/ADN

Environmentally hazardous : yes

#### IMDG

Marine pollutant : yes

### 14.6 Special precautions for user

Not applicable

### 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Not applicable REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : This product does not contain

substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57).

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

	Quantity 1	Quantity 2
E2 ENVIRONMENTAL HAZARDS	200 t	500 t

### 15.2 Chemical Safety Assessment

Not applicable

## SECTION 16: Other information

### Full text of H-Statements

H302 : Harmful if swallowed.

H312 : Harmful in contact with skin.

H315 : Causes skin irritation.

H317 : May cause an allergic skin reaction.

H318 : Causes serious eye damage.

## CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY  
tel. +39 0584 383694 fax +39 0584 395182  
www.cecchi.it info@cecchi.it



**C-SYSTEMS 10 10 UV PROTECTION comp. A** - SAFETY DATA SHEET - may 2017- n° batch 136-AG rev.1/17

H319 : Causes serious eye irritation.

H332 : Harmful if inhaled.

H400 : Very toxic to aquatic life.

H410 : Very toxic to aquatic life with long lasting effects.

H411 : Toxic to aquatic life with long lasting effects.

H412 : Harmful to aquatic life with long lasting effects.

### **Full text of other abbreviations**

Acute Tox. : Acute toxicity

Aquatic Acute : Acute aquatic toxicity

Aquatic Chronic : Chronic aquatic toxicity

Eye Dam. : Serious eye damage

Eye Irrit. : Eye irritation

Skin Irrit. : Skin irritation

Skin Sens. : Skin sensitisation

### **Further information**

Training advice : Provide adequate information, instruction and training for operators.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.