Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it

SPINNAKER WOOD PROTECTION - Safety Data Sheet - january 2019 - batch 019-Ai - rev.1/15



SPINNAKER WOOD PROTECTION

* SECTION 1 Identification of the substance/preparation and of the company/undertaking

1.1 Product identifier

Trade name: SPINNAKER WOOD PROTECTION

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product category PC9a Coatings and paints, thinners, paint removers PROC10 Roller application or brushing

Environmental release category ERC2 Formulation of preparations

Application of the substance / the mixture

See our technical datasheet for application of this product.

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Cecchi Gustavo & C. srl - Via M. Coppino 253,

55049 Viareggio (LU) ITALY www.cecchi.it - info@cecchi.it

1.4 Emergency telephone number:+39 0584/383694 - info@cecchi.it

From monday to friday office hours 8:30 – 12:30, 14:00 – 18:30

* SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

GHS02 flame

Flam. Lig. 3 H226 Flammable liquid and vapour.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms



GHS02

Signal word Warning

Hazard statements

H226 Flammable liquid and vapour.

Precautionary statements

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P501 Dispose of contents/container in accordance with local/regional/ national/international regulations. Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

Contains cobaltbis(2-ethylhexanoat), 2-butanone oxime. May cause an allergic reaction.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable. vPvB: Not applicable.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it

SPINNAKER WOOD PROTECTION - Safety Data Sheet - january 2019 - batch 019-Ai - rev.1/15



* SECTION 3: Composition/information on ingredients

3.2 Chemical characterisation: Mixtures

Description: Resin mixture

Solvent mixture with additives

Dangerous components:		
CAS: 64742-48-9	Naphtha (petroleum),	50-100%
EINECS: 265-150-3	hydrotreated heavy	
Index number: 649-327-00-6	Flam. Liq. 3, H226	
Reg.nr.: 01-2119463258-33	Asp. Tox. 1, H304	
CAS: 96-29-7	2-butanone oxime	<=0.5%
EINECS: 202-496-6	Carc. 2, H351	
Index number: 616-014-00-0	Eye Dam. 1, H318	
Reg.nr.: 01-2119539477-28	Acute Tox. 4, H312; Skin Sens. 1,	
_	H317	

Additional information:

Note P: The substance does not have to be classified as a carcinogen or mutagen as can be shown that the substance contains less than 0.1% (w / w) benzene (EINECS No 200-753-7.). This note applies only to certain complex oil-derived substances in Part 3.

For the wording of the listed risk phrases refer to section 16.

* SECTION 4: First aid measures

4.1 Description of first aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints. After skin contact: Generally the product does not irritate the skin.

After eye contact: Rinse opened eye for several minutes under running water.

After swallowing: Seek medical treatment.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

* SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture

No further relevant information available.

5.3 Advice for firefighters

Protective equipment: No special measures required.

* SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it

SPINNAKER WOOD PROTECTION - Safety Data Sheet - january 2019 - batch 019-Ai - rev.1/15

See Section 13 for disposal information.

* SECTION 7: Handling and storage

7.1 Precautions for safe handling

Work only in fume cupboard.

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles: No special requirements.

Information about storage in one common storage facility: Not required.

Further information about storage conditions: Keep container tightly sealed.

7.3 Specific end use(s) No further relevant information available.

* SECTION 8: Exposure controls/personal protection

Additional information about design of technical facilities:

No further data; see item 7.

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

64742-82-1 Naphtha (petroleum), hydrodesulfurized heavy (Note-P)			
Dermal	Long-term - systemic effects,	300 mg/kg bw/day (Werker/	
	worker	Worker)	
Inhalative	Long-term - systemic effects, worker	1500 mg/m3 (Werker/Worker)	
96-29-7 2-butanone oxime			
Inhalative	Acute - systemic effects, worker	320-1000 mg/m3 (Fish Acute Toxicity Study)	

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Personal protective equipment:

General protective and hygienic measures:

Do not eat, drink, smoke or sniff while working.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter AX

Protection of hands:

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but

also on further marks of quality and varies from manufacturer to manufacturer.

As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.



Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it

SPINNAKER WOOD PROTECTION - Safety Data Sheet - january 2019 - batch 019-Ai - rev.1/15

For the permanent contact gloves made of the following materials are suitable: nitrile rubber; recommended glove thickness> 0.45mm. permeability / permeation time:> 480 min. according to EN 374.

As protection from splashes gloves made of the following materials are suitable: Cloropene; handglove thickness >0.7mm, penetration time >60min. according EN374. Nitrilrubber; handglove thickness >0.3mm, penetration time >60min. according EN374. Eye protection:

Eye protection.

Tightly sealed goggles

Body protection: Use protective suit.

* SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Appearance:

Form: Fluid

Colour: According to product specification

Odour: Characteristic
Odour threshold: Not determined.
pH-value: Not determined.

Change in condition

Melting point/Melting range:

Boiling point/Boiling range:

Undetermined.

Undetermined.

Value of the point of the point

Flammability (solid, gaseous): Not applicable.

Ignition temperature: 240 °C

Decomposition temperature: Not determined.

Self-igniting: Product is not selfigniting.

Danger of explosion: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

Explosion limits: Lower: 0.6 Vol % Upper: 7.0 Vol %

Vapour pressure at 20 °C: 1 hPa

Density at 20 °C: 0.894 g/cm3 (ISO 2811)

Relative density Not determined.

Vapour density Not determined.

Evaporation rate Not determined.

Solubility in / Miscibility with water: Not miscible or difficult to mix.

Partition coefficient (n-octanol/water): Not determined.

Viscosity:

Dynamic: Not determined. Kinematic at 20 °C: 25 s (DIN 53211/4)

Solvent content:

Organic solvents: 56.4 % VOC content: 56.9 %

VOC content: 504.2 g/l / 4.21 lb/gl Solids content: 41.7 % (VB% 1h 150C) 9.2 Other information No further relevant information available.

* SECTION 10: Stability and reactivity

10.1 Reactivity No further relevant information available.

10.2 Chemical stability

Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

10.3 Possibility of hazardous reactions No dangerous reactions known.

10.4 Conditions to avoid No further relevant information available.

10.5 Incompatible materials: No further relevant information available.

10.6 Hazardous decomposition products:

No dangerous decomposition products known.



Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it

SPINNAKER WOOD PROTECTION - Safety Data Sheet - january 2019 - batch 019-Ai - rev.1/15



* SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

LD/LC50 values relevant for classification:

64742-48-9 Naphtha (petroleum), hydrotreated heavy			
Oral	LD50	>5000 mg/kg bw (rat)	
Dermal	LD50	>5000 mg/kg bw (rabbit) ((24h))	
Inhalative	LD50	>5000 mg/m3 (vapour) (rat) ((8h))	
96-29-7 2-butanone oxime			
Oral	LD50	3700 mg/kg bw (rat)	
Dermal	LD50	200-2000 mg/kg bw (rat)	
Inhalative		20 mg/l (rat)	
95-63-6 1,2,4-trimethylbenzene			
Oral	LD50	5000 mg/kg bw (rat)	

Primary irritant effect:

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Serious eye damage/irritation

Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

Based on available data, the classification criteria are not met.

CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

* SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity:

64742-48-9 Naphtha (petroleum), hydrotreated heavy		
EL50 (48h)	>1000 mg/l ((Daphnia magna-OECD 202))	
EbL50 (72h)	>1000 mg/l (Pseudokirchneriella subcapitata-OECD 201)	
ErL (72h)	>1000 mg/l (Pseudokirchneriella subcapitata-OECD 201)	
LL50 (96h)	>1000 mg/l ((Onorhynchus mykiss OECD 203))	
NOELR (72h)	3 mg/l ((Pseudo. subcapitata-biomass-OECD 201))	
	100 mg/l ((Pseudo. subcap. growth rate OECD 201))	
96-29-7 2-butanone oxime		
EC50	630 mg/l (other waterspecies 1) (BACTERIA; TOXICITEITSTEST)	
EC50 (48 hours)	500 mg/l (daphnia magna)	
	750 mg/l (Daphnia similis Acute Toxicity Study) (DAPHNIA	
	MAGNA)	
EC50 (72 hours)	83 mg/l (other waterspecies 2) (SCENEDESMUS SUBSPICATUS)	
LC50 (48 hours)	750 mg/l (other waterspecies 1)	
LC50 (96 hours)	320-1000 mg/l (fish 1) (LEUCISCUS IDUS; STATISCH SYSTEM)	
	48 mg/l (fish 2) (LEPOSMIS MACEOCHIRUS; STATISCH SYSTEM)	

^{12.2} Persistence and degradability No further relevant information available.

^{12.3} Bioaccumulative potential No further relevant information available.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it

SPINNAKER WOOD PROTECTION - Safety Data Sheet - january 2019 - batch 019-Ai - rev.1/15

12.4 Mobility in soil No further relevant information available.

Additional ecological information:

General notes:

Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

12.5 Results of PBT and vPvB assessment

PBT: Not applicable. vPvB: Not applicable.

12.6 Other adverse effects No further relevant information available.

* SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

European waste catalogue

08 00 00 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES,

SEALANTS AND PRINTING INKS

08 01 00 wastes from MFSU and removal of paint and varnish

08 01 11* waste paint and varnish containing organic solvents or other dangerous substances

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

* SECTION 14: Transport information

14.1 UN-Number

UN1263 ADR, IMDG, IATA

14.2 UN proper shipping name

ADR **1263 PAINT** IMDG, IATA PAINT

14.3 Transport hazard class(es)

ADR, IMDG, IATA

Class 3 Flammable liquids.

Label

14.4 Packing group

Ш ADR, IMDG, IATA

14.5 Environmental hazards:

Marine pollutant: No

14.6 Special precautions for user Warning: Flammable liquids.

Danger code (Kemler): 30 EMS Number: F-E.S-E

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable.

Transport/Additional information:

ADR

Limited quantities (LQ) 5L Excepted quantities (EQ) Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml



Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it

SPINNAKER WOOD PROTECTION - Safety Data Sheet - january 2019 - batch 019-Ai - rev.1/15

Transport category

Tunnel restriction code D/E

IMDG

Limited quantities (LQ) 5L Excepted quantities (EQ) Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml UN "Model Regulation": UN1263, PAINT, 3, III

* SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

National regulations:

Technical instructions (air):

Class Share in % I <=0.5 NK 50-100 Waterhazard class:

Water hazard class 3 (Self-assessment): extremely hazardous for water.

15.2 Chemical safety assessment:

A Chemical Safety Assessment has not been carried out.

* SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H351 Suspected of causing cancer.

H411 Toxic to aquatic life with long lasting effects.

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids, Hazard Category 3



Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY tel. +39 0584 383694 fax +39 0584 395182 www.cecchi.it info@cecchi.it



SPINNAKER WOOD PROTECTION - Safety Data Sheet - january 2019 - batch 019-Ai - rev.1/15

Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1 Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

Carc. 2: Carcinogenicity, Hazard Category 2

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

Asp. Tox. 1: Aspiration hazard, Hazard Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2

* Data compared to the previous version altered.