

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS TEAK OIL W.B. – Technical Data Sheet

NAUTILUS TEAK OIL W.B. Water based wood oil

Nautilus Teak Oil W.B. is a water-based oil for teak and other unpainted woods. It has a slightly amber color to enhance the wood grain.

Dries quickly and is ready to use. It is advisable to mix it well before and also during the application.

CARATTERISTICHE

Product type	oil for water for teak and natural wood
Color	light amber
Dilution	do not dilute
Density	1,02 g/ml
Solid Content	ca. 17 w/w%
Viscosity	12 sec (4mm/DIN cup)
Shelf life (+12 a +30°C)	24/36 months in new sealed containers, cool and ventilated place. Limited storage after opening
Packaging	1 L

TECHNICAL DATA

Theoretical coverage	15 m ² /L
Smell	Light
Gloss grade	satin
Dust dry	1h a 20°C
Sandable	24 h a 20°C
Recoatable	2h at 20°C or day after
Temperature	from +12°C to +30°C
Umidity	max 80% daily average
Flash point	not applicable

SURFACE PREPARATION AND APPLICATION

Protective treatment specifically designed for decks. Also suitable for chairs, tables, gazebos, kept natural. Clean the teak perfectly with Nautilus Teak & Wood Cleaner before application, making sure that the color of the wood is uniform, free of stains or old residues.

Nautilus Teak Oil W.B. it is water based, does not attack the deck caulking. Lightly amber-colored to emphasize the grain and beauty of teak. Ideal for maintaining natural wood.

Avoid application in direct sun and / or with too hot surface.

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS TEAK OIL W.B. – Technical Data Sheet

Instructions for Use

Clean the deck perfectly with Nautilus Teak & Wood Cleaner; if necessary wash several times.

Make sure the teak has no traces of moisture and has a uniform color.

Mix Nautilus Teak Oil W.B. before and during use.

Apply uniformly by roller following the direction of the vein, using the brush in narrow spaces to saturate well the porosity of the wood.

After about 20 minutes wipe with paper or rag to even out and remove any excess, in order not to create a surface film.

After 2 hours (at 20 ° C) or the following day apply the second coat in the same way.

When the protection needs to be repeated, wash it off first with Nautilus Teak & Wood Cleaner.

Brushes and rollers can be washed with soap and water.

After opening the jar, use it quickly.

For more information www.cecchi.it or call at our offices.

SAFETY PRECAUTIONS

Before using paint products, it is mandatory to view the safety data sheets and / or phrases and risk symbols on the label.

Security data sheet are also available online at www.cecchi.it

For further information do not hesitate to contact our Technical Department.

GENERAL NOTES

The information contained in this technical data sheet is based on our best knowledge. However, they cannot be considered binding as a guarantee, given that methods, places of use and application conditions are beyond our control. Therefore we decline any responsibility for an improper use of the product as the application recommendations reported in this sheet are to be considered of a general nature. In cases of doubt it is advisable to carry out preliminary tests. Cecchi Gustavo & C. reserves the right to modify or update this technical data sheet without prior notice. Customers are kindly requested to check that they are in possession of the current edition.