

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS Polishing Antifouling Plus – SCHEDA TECNICA

NAUTILUS Polishing Antifouling Plus

- High quality antifouling, soluble matrix, bright colours.
- Compliant with CE's regulations, suitable for cruising at high speed up to 30 knots. It is indicated for sailing boats. The slow erosion prevents the accumulation of the applied layers year after year and it offers a better smoothness of the hull.
- Suitable for use on all substrates, including Aluminum surfaces. The reduced VOC allows to decrease the solvent' emissions in the environment.

Applications and use

- Stir well until product is mixed to a uniform consistency before application. Make sure that the surface is dried and cleaned. Apply two coats at least, reinforcing on the waterline and most exposed areas. The third coat gives a protection up to 18 months. If necessary, add 4-5% of NAUTILUS Antifouling Thinner.
- In good conditions: in case of application of previous products, we recommend to make a test of compatibility and then apply directly. If it is necessary to seal old antifouling coats, we suggest to apply a layer of Nautilus Classic Primer before Polishing Antifouling Plus.

DRYING/OVERCOATING INFORMATION				
DRYING TIME				
	5°C	15°C	23°C	35°C
Immersion	24 hrs	24 hrs	8 hrs	6 hrs
Dustdry	2 hrs	1,5 hrs	1,5 hrs	21hrs

Note: Note: Max immersion range is at all temperatures – 6 months. If the max immersion range exceed, use high pressure water wash or wet sanding with 180-240 grit paper. Please, follow the same procedure if haulage is necessary during the season.

Overcoating								
Substrate Temperature								
	5°C		15°C		23°C		35°C	
Overcoated by	Min	Max	Min	Max	Min	Max	Min	Max
Same product	24 hrs	No defined	16 hrs	No defined	6 hrs	No defined	4 hrs	No defined

For preventative interventions or restoring osmosis problems, for epoxy cycles (C-System 10 10 CFS) and specific applications, we recommend to consult the other products of the same range, your Dealer or our offices.

For applications of varnished products please, respect security instructions in compliance with the local laws.

For further information, please contact the nearest Dealer or our offices or refer to our website

www.cecchi.it