

ET 108 component B

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Relevant identified uses of the substance or mixture and uses advised against

Trade name: **ET 108 component B**

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture: Adhesive

1.3 Details of the supplier of the safety data sheet

Company Cecchi Gustavo & C. srl - Via M. Coppino 253,
55049 Viareggio (LU) ITALY www.cecchi.it - info@cecchi.it

Information in case of emergency: +39 0584 383694 - info@cecchi.it

From monday to friday office hours 8:30 – 12:30, 14:00 – 18:30

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Skin corrosion , Category 1B H314: Causes severe skin burns and eye damage.

Skin sensitisation , Category 1 H317: May cause an allergic skin reaction.

Chronic aquatic toxicity , Category 2 H411: Toxic to aquatic life with long lasting effects.

Classification (67/548/EEC, 1999/45/EC)

Corrosive R34: Causes burns.

Harmful R22: Harmful if swallowed.

Sensitising R43: May cause sensitisation by skin contact.

Dangerous for the environment R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements :

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/spray.

P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/eye protection/ face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Takeoff immediately all contaminated clothing.

Rinse skin with water/ shower.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER or doctor/ physician.

Hazardous components which must be listed on the label:

Polyamide polymer

Amines, polyethylenepoly-, triethylenetetramine fraction

3,6-diazaoctanethylenediamin

3,6,9-triazaundecamethylenediamine

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

**SECTION 3: Composition/information on ingredients****3.2 Mixtures**

Chemical nature : Aliphatic Amine

Hazardous components

Chemical Name	CAS-No. EC-No. Registration number	Classification (REGULATION (EC) No 1272/2008)	Concentration (%)
Polyamide polymer	68082-29-1	Skin Irrit.2; H315 Eye Dam.1; H318 Skin Sens.1; H317 Aquatic Chronic2; H411	>= 50 - <= 100
Fatty acids, C18-unsatd., dimers, polymers with tall-oil fatty acids, tetraethylenepentamine and triethylenetetramine	68071-65-8	Acute Tox.4; H312 Aquatic Chronic3; H412 Eye Irrit.2; H319	>= 20 - < 25
Amines, polyethylenepoly-, triethylenetetramine fraction	90640-67-8 292-588-2 01-2119487919- 13	Acute Tox.4; H302 Acute Tox.4; H312 Skin Corr.1B; H314 Skin Sens.1B; H317 Aquatic Chronic3; H412	>= 5 - < 7
3,6-diazaoctanethylenediamin	112-24-3 203-950-6 01-2119487919- 13	Acute Tox.4; H312 Skin Corr.1B; H314 Skin Sens.1; H317 Aquatic Chronic3; H412 Acute Tox.4; H302 Eye Dam.1; H318	>= 0,5 - < 1
3,6,9- triazoundecamethylenediamine	112-57-2 203-986-2 /	Acute Tox.4; H312 Acute Tox.4; H302 Skin Corr.1B; H314 Skin Sens.1; H317 Aquatic Chronic2; H411	>= 0,5 - < 1

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY
tel. +39 0584 383694 fax +39 0584 395182
www.cecchi.it info@cecchi.it



C-SYSTEMS ET108 comp B - SAFETY DATA SHEET august 2019 - batch n° 246-A9 - rev.1/17

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Show this safety data sheet to the doctor in attendance.

Keep warm and in a quiet place.

Take off all contaminated clothing immediately.

If inhaled : Move to fresh air.

Keep patient warm and at rest.

If unconscious place in recovery position and seek medical advice.

If symptoms persist, call a physician.

If breathing is irregular or stopped, administer artificial respiration.

In case of skin contact : Wash off immediately with soap and plenty of water.

Do NOT use solvents or thinners.

If on clothes, remove clothes.

Burns must be treated by a physician.

In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

If eye irritation persists, consult a specialist.

If easy to do, remove contact lens, if worn.

If swallowed : Do NOT induce vomiting.

If a person vomits when lying on his back, place him in the recovery position.

Call a physician immediately.

Give small amounts of water to drink.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : corrosive effects

Burn

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : The first aid procedure should be established in consultation with the doctor responsible for industrial medicine.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Carbon dioxide (CO₂)

Foam

Dry powder

Water mist

Unsuitable extinguishing media

: None known.

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting

: The pressure in sealed containers can increase under the influence of heat.

Cool closed containers exposed to fire with water spray.

Hazardous decomposition products formed under fire conditions.

5.3 Advice for firefighters

Special protective equipment for firefighters

: In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

Further information : In the event of fire and/or explosion do not breathe fumes.

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Immediately evacuate personnel to safe areas.

Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures



Personal precautions : Refer to protective measures listed in sections 7 and 8.

Evacuate personnel to safe areas.

Use personal protective equipment.

Ensure adequate ventilation.

Inform the responsible authorities in case of gas leakage, or of entry into waterways, soil or drains.

6.2 Environmental precautions

Environmental precautions : Do not allow uncontrolled discharge of product into the environment.

Try to prevent the material from entering drains or water courses.

Local authorities should be advised if significant spillages cannot be contained.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local/ national regulations (see section 13). Pick up and transfer to properly labelled containers.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Provide sufficient air exchange and/or exhaust in work rooms.

Do not breathe vapours or spray mist.

Avoid inhalation, ingestion and contact with skin and eyes.

Wear personal protective equipment.

Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

Advice on protection against fire and explosion

: Keep away from open flames, hot surfaces and sources of ignition.

Hygiene measures : Provide adequate ventilation. Wash hands and face before breaks and immediately after handling the product.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: Keep containers tightly closed in a dry, cool and wellventilated place. Keep in properly labelled containers.

To maintain product quality, do not store in heat or direct sunlight.

Further information on storage conditions: Protect from moisture.

Advice on common storage : Keep away from isocyanates.

Do not store near acids.

Keep away from oxidizing agents.

Other data : Stable at normal ambient temperature and pressure.

7.3 Specific end use(s)

Specific use(s) : Consult the technical guidelines for the use of this substance/mixture.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Silica, amorphous, fumed, cryst.-free	112945-52-5	TWA (inhalable dust)	6 mg/m ³ (Silica)	GB EH40
Further information	For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/3 General methods for sampling and gravimetric analysis of respirable and inhalable dust, The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m-3 8-hour TWA of inhalable dust or 4 mg.m-3 8-hour TWA of respirable dust.			



	<p>This means that any dust will be subject to COSHH if people are exposed above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limit., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/3., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure should be used</p>			
		TWA (Respirable dust)	2,4 mg/m ³ (Silica)	GB EH40
Further information	<p>For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/3 General methods for sampling and gravimetric analysis of respirable and inhalable dust, The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m⁻³ 8-hour TWA of inhalable dust or 4 mg.m⁻³ 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limit., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/3., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure should be used</p>			

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Amines, polyethylenepoly-, triethylenetetramine fraction
 : End Use: Workers
 Exposure routes: Skin contact
 Potential health effects: Long-term systemic effects
 Value: 0,57 mg/kg
 End Use: Workers
 Exposure routes: Inhalation
 Potential health effects: Long-term systemic effects
 Value: 1 mg/m³
 End Use: Consumer use
 Exposure routes: Skin contact
 Potential health effects: Long-term systemic effects
 Value: 0,25 mg/kg
 End Use: Consumers
 Exposure routes: Inhalation

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY
tel. +39 0584 383694 fax +39 0584 395182
www.cecchi.it info@cecchi.it



C-SYSTEMS ET108 comp B - SAFETY DATA SHEET august 2019 - batch n° 246-A9 - rev.1/17

Potential health effects: Long-term systemic effects

Value: 0,29 mg/m³

End Use: Workers

Exposure routes: Inhalation

Potential health effects: Short-term exposure

Value: 5380 mg/m³

Silica, amorphous, fumed,
cryst.-free

: End Use: Workers

Exposure routes: Inhalation

Potential health effects: Long-term local effects

Value: 4 mg/m³

3,6-diazaoctanethylenediamin : End Use: Workers

Exposure routes: Inhalation

Potential health effects: Short-term exposure, Systemic effects

Value: 5380 mg/m³

End Use: Workers

Exposure routes: Skin contact

Potential health effects: Long-term systemic effects

Value: 0,57 mg/kg

End Use: Workers

Exposure routes: Inhalation

Potential health effects: Long-term systemic effects

Value: 1 mg/m³

End Use: Workers

Exposure routes: Skin contact

Potential health effects: Long-term local effects

Value: 0,028 mg/cm²

End Use: Consumers

Exposure routes: Skin contact

Potential health effects: Short-term exposure, Systemic effects

Value: 8 mg/kg

End Use: Consumers

Exposure routes: Inhalation

Potential health effects: Short-term exposure, Systemic effects

Value: 1600 mg/m³

End Use: Consumers

Exposure routes: Ingestion

Potential health effects: Short-term exposure, Systemic effects

Value: 20 mg/kg

End Use: Consumers

Exposure routes: Skin contact

Potential health effects: Local effects, Short-term exposure

Value: 1 mg/cm²

End Use: Consumers

Exposure routes: Skin contact

Potential health effects: Long-term systemic effects

Value: 0,25 mg/kg

End Use: Consumers

Exposure routes: Inhalation

Potential health effects: Long-term systemic effects

Value: 0,29 mg/m³

End Use: Consumers

Exposure routes: Ingestion

Potential health effects: Long-term systemic effects

Value: 0,41 mg/kg

End Use: Consumers

Exposure routes: Skin contact

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY
tel. +39 0584 383694 fax +39 0584 395182
www.cecchi.it info@cecchi.it



C-SYSTEMS ET108 comp B - SAFETY DATA SHEET august 2019 - batch n° 246-A9 - rev.1/17

Potential health effects: Long-term local effects

Value: 0,43 mg/cm²

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Amines, polyethylenepoly-,
triethylenetetramine fraction

: Sewage treatment plant

Value: 4,25 mg/l

Fresh water

Value: 0,135 mg/l

Fresh water sediment

Value: 2,08 mg/kg

Marine water

Value: 0,0027 mg/l

Marine sediment

Value: 0,123 mg/kg

Soil

Value: 1,67 mg/kg

Intermittent releases

Value: 0,2 mg/l

3,6-diazaoctanethylenediamin : Fresh water

Value: 0,19 mg/l

Marine water

Value: 0,038 mg/l

Fresh water sediment

Value: 95,9 mg/kg

Marine sediment

Value: 19,2 mg/kg

Soil

Value: 19,1 mg/kg

Sewage treatment plant

Value: 4,25 mg/l

8.2 Exposure controls

Engineering measures

Effective exhaust ventilation system

effective ventilation in all processing areas

Personal protective equipment

Eye protection : Safety glasses with side-shields conforming to EN166

Do not wear contact lenses.

Ensure that eyewash stations and safety showers are close to the workstation location.

Hand protection

Material : Chemical resistant gloves made of butyl rubber or nitrile rubber category III according to EN 374.

Skin and body protection : Protective suit

Respiratory protection : Use respirator when performing operations involving potential exposure to vapour of the product.

The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.

Respirator with a vapour filter (EN 141)

Protective measures : Avoid contact with skin.

Wear suitable protective equipment.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : liquid

Colour : amber

Odour : ammoniacal

Odour Threshold : not determined

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY
tel. +39 0584 383694 fax +39 0584 395182
www.cecchi.it info@cecchi.it



C-SYSTEMS ET108 comp B - SAFETY DATA SHEET august 2019 - batch n° 246-A9 - rev.1/17

pH :	not determined
Melting point/freezing point :	Not applicable
Boiling point/boiling range :	> 200 °C
Flash point :	150 °C
Evaporation rate :	not determined
Upper explosion limit :	Not applicable
Lower explosion limit :	Not applicable
Vapour pressure :	Not applicable
Relative vapour density :	not determined
Density :	1 g/cm ³ (25 °C)
Bulk density :	not determined
Solubility(ies)	
Solubility in other solvents :	not determined
Partition coefficient: noctanol/ water:	No data available
Auto-ignition temperature :	Not applicable
Thermal decomposition :	Method: No data available
Viscosity	
Viscosity, dynamic :	300.000 - 450.000 mPa.s (25 °C)
Viscosity, kinematic :	not determined
Explosive properties :	Not applicable
Oxidizing properties :	Not applicable

9.2 Other information

Surface tension :	not determined
Sublimation point :	Not applicable

SECTION 10: Stability and reactivity

10.1 Reactivity

Stable under recommended storage conditions.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Reacts with the following substances:

Acids

Strong oxidizing agents

10.4 Conditions to avoid

Conditions to avoid : No decomposition if used as directed.

10.5 Incompatible materials

Materials to avoid : Strong acids

Strong oxidizing agents

10.6 Hazardous decomposition products

Hazardous decomposition products

: This product may release the following:

Nitrogen oxides (NO_x)

Carbon monoxide

Carbon dioxide (CO₂)

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product:

Acute oral toxicity : Acute toxicity estimate : > 2.000 mg/kg

Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : > 2.000 mg/kg

Method: Calculation method

Components:

Amines, polyethylenepoly-, triethylenetetramine fraction:

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY
tel. +39 0584 383694 fax +39 0584 395182
www.cecchi.it info@cecchi.it



C-SYSTEMS ET108 comp B - SAFETY DATA SHEET august 2019 - batch n° 246-A9 - rev.1/17

Acute oral toxicity : LD50 (Rat, male and female): 1.716 mg/kg
Method: OECD Test Guideline 401
GLP: yes
Acute dermal toxicity : LD50 (Rabbit, male and female): 1.465 mg/kg
Method: OECD Test Guideline 402
GLP: yes
3,6-diazaoctanethylenediamin:
Acute oral toxicity : LD50 (Rat, male): 1.716 mg/kg
Method: OECD Test Guideline 401
GLP: yes
Acute dermal toxicity : LD50 (Rabbit): 1.465 mg/kg
Method: OECD Test Guideline 402
GLP: yes
3,6,9-triazaundecamethylenediamine:
Acute oral toxicity : Acute toxicity estimate : 500 mg/kg
Method: Converted acute toxicity point estimate
Acute dermal toxicity : Acute toxicity estimate : 1.100 mg/kg
Method: Converted acute toxicity point estimate
Skin corrosion/irritation
Product:
Remarks: Acute dermal irritation/corrosion
Components:
Amines, polyethylenepoly-, triethylenetetramine fraction:
Species: Rabbit
Method: OECD Test Guideline 404
Result: Corrosive
GLP: yes
3,6-diazaoctanethylenediamin:
Method: OECD Test Guideline 435
Result: Corrosive
Serious eye damage/eye irritation
Product:
Remarks: Severe eye irritation
Components:
Amines, polyethylenepoly-, triethylenetetramine fraction:
Species: Rabbit
Method: OECD Test Guideline 405
Result: Risk of serious damage to eyes.
GLP: yes
3,6-diazaoctanethylenediamin:
Species: Rabbit
Method: OECD Test Guideline 405
Result: Risk of serious damage to eyes.
GLP: yes
Respiratory or skin sensitisation
Product:
Remarks: No data available
Components:
Amines, polyethylenepoly-, triethylenetetramine fraction:
Test Type: Buehler Test
Species: Guinea pig
Method: OECD Test Guideline 406
Result: May cause sensitisation by skin contact.
GLP: yes
3,6-diazaoctanethylenediamin:
Test Type: Buehler Test
Exposure routes: Dermal
Species: Guinea pig

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY
tel. +39 0584 383694 fax +39 0584 395182
www.cecchi.it info@cecchi.it



C-SYSTEMS ET108 comp B - SAFETY DATA SHEET august 2019 - batch n° 246-A9 - rev.1/17

Method: OECD Test Guideline 406

Result: May cause sensitisation by skin contact.

GLP: yes

Germ cell mutagenicity

Carcinogenicity

Reproductive toxicity

STOT - single exposure

STOT - repeated exposure

Repeated dose toxicity

Product:

Remarks: No data available

Aspiration toxicity

Further information

Product:

Remarks: No data available

SECTION 12: Ecological information

12.1 Toxicity

Product:

Toxicity to fish : Remarks: No data available

Toxicity to daphnia and other aquatic invertebrates

: Remarks: No data available

Components:

Amines, polyethylenepoly-, triethylenetetramine fraction:

Toxicity to daphnia and other aquatic invertebrates

: EC50 (Daphnia magna (Water flea)): 31,1 mg/l

Exposure time: 48 h

Test Type: static test

Method: Directive 67/548/EEC, Annex V, C.2.

GLP: yes

Toxicity to algae : ErC50 (Selenastrum capricornutum (green algae)): 20 mg/l

Exposure time: 72 h

Test Type: semi-static test

Method: OECD Test Guideline 201

GLP: yes

3,6-diazaoctanethylenediamin:

Toxicity to daphnia and other aquatic invertebrates

: EC50 (Daphnia magna (Water flea)): 31,1 mg/l

Exposure time: 48 h

Test Type: static test

GLP: yes

Toxicity to algae : ErC50 (Selenastrum capricornutum (green algae)): Exposure time: 72 h

Test Type: semi-static test

Method: OECD Test Guideline 201

GLP: yes

12.2 Persistence and degradability

Product:

Biodegradability : Remarks: No data available

Components:

3,6-diazaoctanethylenediamin:

Biodegradability : Test Type: aerobic

Result: Not readily biodegradable.

Method: OECD Test Guideline 301D

GLP: yes

12.3 Bioaccumulative potential

Product:

Bioaccumulation : Remarks: No data available

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY
tel. +39 0584 383694 fax +39 0584 395182
www.cecchi.it info@cecchi.it



C-SYSTEMS ET108 comp B - SAFETY DATA SHEET august 2019 - batch n° 246-A9 - rev.1/17

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Other adverse effects

Product:

Additional ecological information

: Remarks: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : : In accordance with local and national regulations.

Container hazardous when empty.

Do not dispose of with domestic refuse.

Do not mix waste streams during collection.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.

SECTION 14: Transport information

14.1 UN number

ADR/RID/ADN : UN 2735

IMDG : UN 2735

IATA : UN 2735

14.2 UN proper shipping name

ADR/RID/ADN : AMINES, LIQUID, CORROSIVE, N.O.S.
(Polyamide polymer)

IMDG : AMINES, LIQUID, CORROSIVE, N.O.S.
(Polyamide polymer)

IATA : Amines, liquid, corrosive, n.o.s.
(Polyamide polymer)

14.3 Transport hazard class(es)

ADR/RID/ADN : 8

IMDG : 8

IATA : 8

14.4 Packing group

ADR/RID/ADN

Packing group : III

Classification Code : C7

Hazard Identification Number : 80

Labels : 8

IMDG

Packing group : III

Labels : 8

EmS Code : F-A, S-B

Remarks : IMDG Code segregation group 18 - Alkalis

IATA

Packing instruction (cargo aircraft) : 856

Packing instruction (passenger aircraft) : 852

Packing group : III

Labels : 8

14.5 Environmental hazards

ADR/RID/ADN

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY
tel. +39 0584 383694 fax +39 0584 395182
www.cecchi.it info@cecchi.it



C-SYSTEMS ET108 comp B - SAFETY DATA SHEET august 2019 - batch n° 246-A9 - rev.1/17

Environmentally hazardous : yes

IMDG

Marine pollutant : yes

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII): Not applicable

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).

: This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57).

REACH - List of substances subject to authorisation (Annex XIV)

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

	Quantity 1	Quantity 2
E2 ENVIRONMENTAL HAZARDS	200 t	500 t

15.2 Chemical safety assessment

Not applicable

SECTION 16: Other information

Full text of H-Statements

H302 : Harmful if swallowed.

H312 : Harmful in contact with skin.

H314 : Causes severe skin burns and eye damage.

H315 : Causes skin irritation.

H317 : May cause an allergic skin reaction.

H318 : Causes serious eye damage.

H319 : Causes serious eye irritation.

H411 : Toxic to aquatic life with long lasting effects.

H412 : Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox. : Acute toxicity

Aquatic Chronic : Chronic aquatic toxicity

Eye Dam. : Serious eye damage

Eye Irrit. : Eye irritation

Skin Corr. : Skin corrosion

Skin Irrit. : Skin irritation

Skin Sens. : Skin sensitisation

Further information

Training advice : Provide adequate information, instruction and training for operators.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.