

## CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS ENAMEL RAL 9016 Component A - SAFETY DATA SHEET - october 2019 - n°batch 296-Ai - rev. 1/2019

# Safety Data Sheet

## SECTION 1. Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Product name

NAUTILUS ENAMEL RAL 9016 Component A

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use

MARINA / NAUTICA

Identified Uses	Industrial	Professional	Consumer
Paint product for furniture	-	✓	-
Paint product for boating - marine	-	✓	-
Paint product for industrial uses	✓	-	-
Paint product for professional use	-	✓	-

### Uses Advised Against

CONSUMATORE: FAI-DA-TE

### 1.3 Details of the supplier of the safety data sheet Manufacturer/Supplier:

Cecchi Gustavo & C. srl - Via M. Coppino 253,  
55049 Viareggio (LU) ITALY www.cecchi.it - [info@cecchi.it](mailto:info@cecchi.it)

### 1.4 Emergency telephone number:

+39 0584/383694 - [info@cecchi.it](mailto:info@cecchi.it)

From monday to friday office hours 8:30 - 12:30, 14:00 - 18:30

## SECTION 2. Hazards identification

### 2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2015/830. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Flammable liquid, category 3

H226

Flammable liquid and vapour.

Specific target organ toxicity - single exposure, category 3

H336

May cause drowsiness or dizziness.

### 2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:

## CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS ENAMEL RAL 9016 Component A - SAFETY DATA SHEET - october 2019 - n°batch 296-Ai - rev. 1/2019



Signal words:

Warning

Hazard statements:

**H226** Flammable liquid and vapour.  
**H336** May cause drowsiness or dizziness.  
**EUH208** Contains: ACIDI GRASSI, TALLOLIO, COMPOSTI CON OLEILAMMINA, FATTY ACIDS ,C-18,UNSATD,TRIMERS,COMP.D WITH 9-OCTADECEN-1-AMINE,(Z)  
May produce an allergic reaction.

Precautionary statements:

**P210** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
**P370+P378** In case of fire: use . . . to extinguish.  
**P501** Dispose of contents / container to . . .  
**P261** Avoid breathing dust / fume / gas / mist / vapours / spray.  
**P280** Wear personal protective equipment / face protection.  
**P312** Call a POISON CENTRE / doctor / . . . if you feel unwell.

**Contains:** 2-METHOXY-1-METHYLETHYL ACETATE  
N-BUTYL ACETATE

Product not intended for uses provided for by Dir. 2004/42/CE.

### 2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

## SECTION 3. Composition/information on ingredients

### 3.2. Mixtures

Contains:

Identification	x = Conc. %	Classification 1272/2008 (CLP)
<b>2-METHOXY-1-METHYLETHYL ACETATE</b>		
CAS 108-65-6	$13 \leq x < 16$	Flam. Liq. 3 H226, STOT SE 3 H336
EC 203-603-9		
INDEX 607-195-00-7		
Reg. no. 01-2119475791-29-XXXX		
<b>N-BUTYL ACETATE</b>		
CAS 123-86-4	$4 \leq x < 5$	Flam. Liq. 3 H226, STOT SE 3 H336, EUH066
EC 204-658-1		

## CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS ENAMEL RAL 9016 Component A - SAFETY DATA SHEET - october 2019 - n°batch 296-Ai - rev. 1/2019

INDEX 607-025-00-1

Reg. no. 01-2119485493-29-XXXX

### ETHYL,3-ETHOXY PROPIONATE

CAS 763-69-9  $4 \leq x < 5$  Flam. Liq. 3 H226, EUH066

EC 212-112-9

INDEX -

### XYLENE (MIXTURE OF ISOMERS)

CAS 1330-20-7  $1 \leq x < 2$  Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Aquatic Chronic 3 H412, Classification note according to Annex VI to the CLP Regulation: C

EC 215-535-7

INDEX 601-022-00-9

Reg. no. 01-2119488216-32-XXXX

### FATTY ACIDS, C-18, UNSATD, TRIMERS, COMPD, WITH 9-OCTADECEN-1-AMINE, (Z)

CAS 147900-93-4  $0,1 \leq x < 0,4$  Acute Tox. 4 H302, STOT RE 2 H373, Skin Sens. 1B H317, Aquatic Chronic 2 H411

EC 604-612-4

INDEX -

Reg. no. 01-2119971821-33-0000

### ACIDI GRASSI, TALLOLIO, COMPOSTI CON OLEILAMMINA

CAS 85711-55-3  $0,05 \leq x < 0,1$  STOT RE 2 H373, Eye Dam. 1 H318, Skin Sens. 1A H317

EC 288-315-1

INDEX -

Reg. no. 01-2119974148-28-0000

### PHOSPHORIC ACID

CAS 7664-38-2  $0 \leq x < 0,05$  Skin Corr. 1B H314, Eye Dam. 1 H318, Classification note according to Annex VI to the CLP Regulation: B

EC 231-633-2

INDEX 015-011-00-6

Reg. no. 01-2119485924-24

The full wording of hazard (H) phrases is given in section 16 of the sheet.

## SECTION 4. First aid measures

### 4.1. Description of first aid measures

**EYES:** Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

**SKIN:** Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention immediately. Wash contaminated clothing before using it again.

**INHALATION:** Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately.

**INGESTION:** Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

### 4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

## CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS ENAMEL RAL 9016 Component A - SAFETY DATA SHEET - october 2019 - n°batch 296-Ai - rev. 1/2019

### 4.3. Indication of any immediate medical attention and special treatment needed

Information not available

## SECTION 5. Firefighting measures

### 5.1. Extinguishing media

#### SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

#### UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

### 5.2. Special hazards arising from the substance or mixture

#### HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

### 5.3. Advice for firefighters

#### GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

#### SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

## SECTION 6. Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

Send away individuals who are not suitably equipped. Use explosion-proof equipment. Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site.

### 6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

### 6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

### 6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

## CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS ENAMEL RAL 9016 Component A - SAFETY DATA SHEET - october 2019 - n°batch 296-Ai - rev. 1/2019

## SECTION 7. Handling and storage

### 7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat. Avoid leakage of the product into the environment.

### 7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store in a well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

Storage class TRGS 510 (Germany):  
3

### 7.3. Specific end use(s)

Information not available

## SECTION 8. Exposure controls/personal protection

### 8.1. Control parameters

Regulatory References:

DEU	Deutschland	TRGS 900 (Fassung 31.1.2018 ber.) - Liste der Arbeitsplatzgrenzwerte und Kurzzeitwerte
ESP	España	INSHT - Límites de exposición profesional para agentes químicos en España 2017
FRA	France	JORF n°0109 du 10 mai 2012 page 8773 texte n° 102
GBR	United Kingdom	EH40/2005 Workplace exposure limits
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
NLD	Nederland	Databank of the social and Economic Council of Netherlands (SER) Values, AF 2011:18
POL	Polska	ROZPORZĄDZENIE MINISTRA PRACY I POLITYKI SPOŁECZNEJ z dnia 7 czerwca 2017 r
PRT	Portugal	Ministério da Economia e do Emprego Consolida as prescrições mínimas em matéria de protecção dos trabalhadores contra os riscos para a segurança e a saúde devido à exposição a agentes químicos no trabalho - Diário da República I 26; 2012-02-06
ROU	România	Monitorul Oficial al României 44; 2012-01-19
EU	OEL EU	Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2018

### TITANIUM DIOXIDE

#### Threshold Limit Value

Type	Country	TWA/8h		STEL/15min	
		mg/m3	ppm	mg/m3	ppm
VLA	ESP	10			
VLEP	FRA	10			
WEL	GBR	4			
NDS	POL	10			INHAL
TLV	ROU	10		15	
TLV-ACGIH		10			

**CECCHI GUSTAVO & C.**

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it

**NAUTILUS ENAMEL RAL 9016 Component A - SAFETY DATA SHEET - october 2019 - n°batch 296-Ai - rev. 1/2019**

Predicted no-effect concentration - PNEC		
Normal value in fresh water	0,184	mg/l
Normal value in marine water	0,0184	mg/l
Normal value for fresh water sediment	100	mg/kg/d
Normal value for marine water sediment	1000	mg/kg/d
Normal value for water, intermittent release	0,193	mg/l
Normal value of STP microorganisms	100	mg/l
Normal value for the terrestrial compartment	100	mg/kg/d

Health - Derived no-effect level - DNEL / DMEL								
Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral		700 mg/kg bw/d		NPI		NPI		NPI
Inhalation	NPI	NPI	NPI	NPI	NPI	NPI	10 mg/m3	NPI
Skin	NPI	NPI	NPI	NPI	NPI	NPI	NPI	NPI

2-METHOXY-1-METHYLETHYL ACETATE						
Threshold Limit Value						
Type	Country	TWA/8h		STEL/15min		
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	270	50	270	50	
MAK	DEU	270	50	270	50	
VLA	ESP	275	50	550	100	SKIN
VLEP	FRA	275	50	550	100	SKIN
WEL	GBR	274	50	548	100	
VLEP	ITA	275	50	550	100	SKIN
OEL	NLD	550				
NDS	POL	260		520		
VLE	PRT	275	50	550	100	SKIN
TLV	ROU	275	50	550	100	SKIN
OEL	EU	275	50	550	100	SKIN

Predicted no-effect concentration - PNEC		
Normal value in fresh water	0,635	mg/l
Normal value in marine water	0,0635	mg/l
Normal value for fresh water sediment	3,29	mg/kg
Normal value for marine water sediment	0,329	mg/kg
Normal value of STP microorganisms	100	mg/l
Normal value for the terrestrial compartment	0,29	mg/kg

Health - Derived no-effect level - DNEL / DMEL								
Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			VND	1,67 mg/kg				
Inhalation			VND	33 mg/m3			VND	275 mg/m3
Skin			VND	54,8 mg/kg			VND	153,5 mg/kg

**CECCHI GUSTAVO & C.**

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS ENAMEL RAL 9016 Component A - SAFETY DATA SHEET - october 2019 - n°batch 296-Ai - rev. 1/2019

<b>N-BUTYL ACETATE</b>								
<b>Threshold Limit Value</b>								
Type	Country	TWA/8h		STEL/15min				
		mg/m3	ppm	mg/m3	ppm			
AGW	DEU	300	62	600	124			
VLA	ESP	724	150	965	200			
VLEP	FRA	710	150	940	200			
WEL	GBR	724	150	966	200			
OEL	NLD	150						
NDS	POL	240		720				
TLV	ROU	715	150	950	200			
TLV-ACGIH			50		150			
Predicted no-effect concentration - PNEC								
Normal value in fresh water				0,18	mg/l			
Normal value in marine water				0,018	mg/l			
Normal value for fresh water sediment				0,981	mg/kg			
Normal value for marine water sediment				0,0981	mg/kg			
Normal value for water, intermittent release				0,36	mg/l			
Normal value of STP microorganisms				35,6	mg/l			
Normal value for the terrestrial compartment				0,0903	mg/kg			
<b>Health - Derived no-effect level - DNEL / DMEL</b>								
Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Inhalation	859.7 mg/m3	859,7 mg/m3	102,34 mg/m3		960 mg/m3	960 mg/m3	480 mg/m3	480 mg/m3
<b>ETHYL,3-ETHOXY PROPIONATE</b>								
<b>Threshold Limit Value</b>								
Type	Country	TWA/8h		STEL/15min				
		mg/m3	ppm	mg/m3	ppm			
AGW	DEU	610	100	610	100			
MAK	DEU	610	100	610	100	SKIN		
Predicted no-effect concentration - PNEC								
Normal value in fresh water				0,0609	mg/l			
Normal value in marine water				0,00609	mg/l			
Normal value for fresh water sediment				0,419	mg/kg pc/giorno			
Normal value for marine water sediment				0,0419	mg/l			
Normal value for water, intermittent release				0,609	mg/l			
Normal value of STP microorganisms				50	mg/l			
<b>Health - Derived no-effect level - DNEL / DMEL</b>								
Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			1,2 mg/m3	1,2 mg/m3				





**CECCHI GUSTAVO & C.**

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS ENAMEL RAL 9016 Component A - SAFETY DATA SHEET - october 2019 - n°batch 296-Ai - rev. 1/2019

Oral	NPI	12	12 µg/kg bw/d				
Skin	NPI		12 µg/kg bw/d	NPI	NPI	12	24 µg/kg bw/d

**ACIDI GRASSI, TALLOLIO, COMPOSTI CON OLEILAMMINA**

Predicted no-effect concentration - PNEC

Normal value in fresh water	NPI
Normal value for water, intermittent release	NPI
Normal value of STP microorganisms	NPI
Normal value for the food chain (secondary poisoning)	470 µg/kg food
Normal value for the atmosphere	NPI

**Health - Derived no-effect level - DNEL / DMEL**

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral		NPI		12 µg/kg bw/day				
Skin		NPI		12 µg/kg bw/day		NPI		24 µg/kg bw/day

**PHOSPHORIC ACID****Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min	
		mg/m3	ppm	mg/m3	ppm
AGW	DEU	2		4	INHAL
MAK	DEU	2		4	INHAL
VLA	ESP	1		2	
VLEP	FRA	1	0,2	2	0,5
WEL	GBR	1		2	
VLEP	ITA	1		2	
OEL	NLD	1		2	
NDS	POL	1		2	
VLE	PRT	1		2	
TLV	ROU	1		2	
OEL	EU	1		2	
TLV-ACGIH		1		3	

**Health - Derived no-effect level - DNEL / DMEL**

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Inhalation			0,73 mg/m3		2 mg/m3		1 mg/m3	

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

## CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS ENAMEL RAL 9016 Component A - SAFETY DATA SHEET - october 2019 - n°batch 296-Ai - rev. 1/2019

### 8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

#### HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

#### SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion.

#### EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

#### RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

#### ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

## SECTION 9. Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Appearance	dense liquid
Colour	white
Odour	characteristic of solvent
Odour threshold	Not available
pH	Not available
Melting point / freezing point	Not available
Initial boiling point	Not available
Boiling range	Not available
Flash point	23 ≤ T ≤ 60 °C
Evaporation Rate	Not available
Flammability of solids and gases	Not available
Lower flammability limit	Not available
Upper flammability limit	Not available
Lower explosive limit	Not available
Upper explosive limit	Not available
Vapour pressure	Not available
Vapour density	Not available
Relative density	1,44
Solubility	immiscible with water

## CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS ENAMEL RAL 9016 Component A - SAFETY DATA SHEET - october 2019 - n°batch 296-Ai - rev. 1/2019

Partition coefficient: n-octanol/water	Not available
Auto-ignition temperature	Not available
Decomposition temperature	Not available
Viscosity	>20,5 mm <sup>2</sup> /sec (40°C)
Explosive properties	Not available
Oxidising properties	Not available

### 9.2. Other information

Total solids (250°C / 482°F)	73,93 %		
VOC (Directive 2010/75/EC) :	25,54 %	-	366,48 g/litre
VOC (volatile carbon) :	15,47 %	-	221,95 g/litre

## SECTION 10. Stability and reactivity

### 10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

#### 2-METHOXY-1-METHYLETHYL ACETATE

Stable in normal conditions of use and storage.

With the air it may slowly develop peroxides that explode with an increase in temperature.

#### N-BUTYL ACETATE

Decomposes on contact with: water.

#### PHOSPHORIC ACID

Decomposes at temperatures above 200°C/392°F.

### 10.2. Chemical stability

The product is stable in normal conditions of use and storage.

### 10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

#### 2-METHOXY-1-METHYLETHYL ACETATE

May react violently with: oxidising substances, strong acids, alkaline metals.

#### N-BUTYL ACETATE

Risk of explosion on contact with: strong oxidising agents. May react dangerously with: alkaline hydroxides, potassium tert-butoxide. Forms explosive mixtures with: air.

## CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS ENAMEL RAL 9016 Component A - SAFETY DATA SHEET - october 2019 - n°batch 296-Ai - rev. 1/2019

### XYLENE (MIXTURE OF ISOMERS)

XYLENE (MIXTURE OF ISOMERS): stable, but may develop violent reactions in the presence of strong oxidising agents such as sulphuric and nitric acids and perchlorates. May form explosive mixtures with the air.

### PHOSPHORIC ACID

Risk of explosion on contact with: nitromethane. May react dangerously with: alkalis, sodium borohydride.

#### 10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

### N-BUTYL ACETATE

Avoid exposure to: moisture, sources of heat, naked flames.

#### 10.5. Incompatible materials

### 2-METHOXY-1-METHYLETHYL ACETATE

Incompatible with: oxidising substances, strong acids, alkaline metals.

### N-BUTYL ACETATE

Incompatible with: water, nitrates, strong oxidants, acids, alkalis, zinc.

### PHOSPHORIC ACID

Incompatible with: metals, strong alkalis, aldehydes, organic sulphides, peroxides.

#### 10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

### PHOSPHORIC ACID

May develop: phosphoryl oxides.

## SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using

## CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS ENAMEL RAL 9016 Component A - SAFETY DATA SHEET - october 2019 - n°batch 296-Ai - rev. 1/2019

the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

### 11.1. Information on toxicological effects

XYLENE (MIXTURE OF ISOMERS)

XYLENE (MIXTURE OF ISOMERS): has a toxic effect on the CNS (encephalopathies). Irritating to the skin, conjunctivae, cornea and respiratory apparatus.

#### Metabolism, toxicokinetics, mechanism of action and other information

2-METHOXY-1-METHYLETHYL ACETATE

The main route of entry is the skin, whereas the respiratory route is less important due to the low vapour pressure of the product.

#### Information on likely routes of exposure

2-METHOXY-1-METHYLETHYL ACETATE

WORKERS: inhalation; contact with the skin.

N-BUTYL ACETATE

WORKERS: inhalation; contact with the skin.

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

2-METHOXY-1-METHYLETHYL ACETATE

Above 100 ppm causes irritation of the eye, nose and oropharynx mucous membranes. At 1000 ppm, disturbance of equilibrium and severe eye irritation can be noticed. Clinical and biological examinations carried out on exposed volunteers revealed no anomalies. Acetate produces greater skin and eye irritation with direct contact. No chronic effects on humans have been reported (INCR, 2010).

N-BUTYL ACETATE

In humans, the substance's vapours cause irritation of the eyes and nose. In the event of repeated exposure, skin irritation, dermatitis (dryness and cracking of the skin) and keratitis appear.

#### Interactive effects

N-BUTYL ACETATE

A case of acute intoxication been reported involving a 33 year old worker while cleaning a tank with a preparation containing xylenes, butyl acetate and ethylene glycol acetate. The person had irritation of the conjunctiva and upper respiratory tract, drowsiness and motor coordination disorders, which disappeared within 5 hours. The symptoms are attributed to poisoning by mixed xylenes and butyl acetate, with a possible synergistic effect responsible for the neurological effects. Cases of vacuolar keratitis are reported in workers exposed to a mixture of butyl acetate and isobutanol vapours, but with uncertainty concerning the responsibility of a particular solvent (INRC, 2011).

#### ACUTE TOXICITY

LC50 (Inhalation) of the mixture:

> 20 mg/l

LD50 (Oral) of the mixture:

Not classified (no significant component)

## CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



**NAUTILUS ENAMEL RAL 9016 Component A** - SAFETY DATA SHEET - october 2019 - n°batch 296-Ai - rev. 1/2019

LD50 (Dermal) of the mixture:  
>2000 mg/kg

### PHOSPHORIC ACID

LD50 (Oral) 1530 mg/kg Rat

LD50 (Dermal) 2740 mg/kg Rabbit

LC50 (Inhalation) > 0,85 mg/l/1h Rat

### 2-METHOXY-1-METHYLETHYL ACETATE

LD50 (Oral) 8500 mg/kg Rat

LD50 (Dermal) > 3160 mg/kg Rat

LC50 (Inhalation) 6193 mg/m<sup>3</sup>/4h Ratto

### N-BUTYL ACETATE

LD50 (Oral) > 6400 mg/kg Rat

LD50 (Dermal) > 5000 mg/kg Rabbit

LC50 (Inhalation) 21,1 mg/l/4h Rat

### XYLENE (MIXTURE OF ISOMERS)

LD50 (Oral) 3500 mg/kg Rat

LD50 (Dermal) 4350 mg/kg Rabbit

LC50 (Inhalation) 26 mg/l/4h Rat

### FATTY ACIDS ,C-18,UNSATD,TRIMERS,COMPD,WITH 9-OCTADECEN-1-AMINE,(Z)

LD50 (Oral) > 1570 mg/kg ratto

### SKIN CORROSION / IRRITATION

Does not meet the classification criteria for this hazard class

### SERIOUS EYE DAMAGE / IRRITATION

Does not meet the classification criteria for this hazard class

---

## CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS ENAMEL RAL 9016 Component A - SAFETY DATA SHEET - october 2019 - n°batch 296-Ai - rev. 1/2019

### RESPIRATORY OR SKIN SENSITISATION

May produce an allergic reaction. Contains: ACIDI GRASSI, TALLOLIO, COMPOSTI CON OLEILAMMINA  
FATTY ACIDS ,C-18,UNSATD,TRIMERS,COMPD,WITH 9-OCTADECEN-1-AMINE,(Z)

### GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

### CARCINOGENICITY

Does not meet the classification criteria for this hazard class

### REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

### STOT - SINGLE EXPOSURE

May cause drowsiness or dizziness

### STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

### ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class Viscosity: >20,5 mm<sup>2</sup>/sec (40°C)

## SECTION 12. Ecological information

No specific data are available for this product. Handle it according to good working practices. Avoid littering. Do not contaminate soil and waterways. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation. Please take all the proper measures to reduce harmful effects on aquifers.

### 12.1. Toxicity

#### 2-METHOXY-1-METHYLETHYL ACETATE

LC50 - for Fish	> 100 mg/l/96h Oncorhynchus mykiss
EC50 - for Crustacea	> 408 mg/l/48h Daphnia magna
EC50 - for Algae / Aquatic Plants	> 100 mg/l/72h
Chronic NOEC for Fish	47,5 mg/l Oncothynchus mykiss
Chronic NOEC for Crustacea	> 99 mg/l Daphnia magna
Chronic NOEC for Algae / Aquatic Plants	> 999 mg/l Selenastrum capricornutum

#### XYLENE (MIXTURE OF ISOMERS)

LC50 - for Fish	> 4,2 mg/l/96h Oncorhynchus mykiss
-----------------	------------------------------------

## CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS ENAMEL RAL 9016 Component A - SAFETY DATA SHEET - october 2019 - n°batch 296-Ai - rev. 1/2019

EC50 - for Crustacea > 2,93 mg/l/48h Daphnia Magna

### 12.2. Persistence and degradability

#### PHOSPHORIC ACID

Solubility in water > 850000 mg/l

Degradability: information not available

#### 2-METHOXY-1-METHYLETHYL ACETATE

Solubility in water > 10000 mg/l

Rapidly degradable

#### ETHYL,3-ETHOXY PROPIONATE

Solubility in water > 10000 mg/l

Rapidly degradable

#### N-BUTYL ACETATE

Solubility in water 1000 - 10000 mg/l

#### XYLENE (MIXTURE OF ISOMERS)

Solubility in water 100 - 1000 mg/l

Degradability: information not available

### 12.3. Bioaccumulative potential

#### 2-METHOXY-1-METHYLETHYL ACETATE

Partition coefficient: n-octanol/water 1,2

#### ETHYL,3-ETHOXY PROPIONATE

Partition coefficient: n-octanol/water 1,47

#### N-BUTYL ACETATE

Partition coefficient: n-octanol/water 2,3

BCF 15,3

#### XYLENE (MIXTURE OF ISOMERS)

Partition coefficient: n-octanol/water 3,12

BCF 25,9

### 12.4. Mobility in soil

#### N-BUTYL ACETATE

Partition coefficient: soil/water < 3



## CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS ENAMEL RAL 9016 Component A - SAFETY DATA SHEET - october 2019 - n°batch 296-Ai - rev. 1/2019

XYLENE (MIXTURE OF ISOMERS)

Partition coefficient: soil/water 2,73

### 12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

### 12.6. Other adverse effects

Information not available

## SECTION 13. Disposal considerations

### 13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

## SECTION 14. Transport information

### 14.1. UN number

ADR / RID, IMDG, 1263  
IATA:

### 14.2. UN proper shipping name

ADR / RID: PAINT or PAINT RELATED MATERIAL  
IMDG: PAINT or PAINT RELATED MATERIAL  
IATA: PAINT or PAINT RELATED MATERIAL

### 14.3. Transport hazard class(es)

ADR / RID: Class: 3 Label: 3  
IMDG: Class: 3 Label: 3  
IATA: Class: 3 Label: 3



### 14.4. Packing group

## CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS ENAMEL RAL 9016 Component A - SAFETY DATA SHEET - october 2019 - n°batch 296-Ai - rev. 1/2019

ADR / RID, IMDG, III  
IATA:

### 14.5. Environmental hazards

ADR / RID: NO  
IMDG: NO  
IATA: NO

### 14.6. Special precautions for user

ADR / RID:	HIN - Kemler: 30	Limited Quantities: 5 L	Tunnel restriction code: (D/E)
IMDG:	Special Provision: - EMS: F-E, <u>S-E</u>	Limited Quantities: 5 L	
IATA:	Cargo:	Maximum quantity: 220 L	Packaging instructions: 366
	Pass.:	Maximum quantity: 60 L	Packaging instructions: 355
	Special Instructions:	A3, A72, A192	

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Information not relevant

## SECTION 15. Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EC: P5c

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product  
Point 3 - 40

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage greater than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

## CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS ENAMEL RAL 9016 Component A - SAFETY DATA SHEET - october 2019 - n°batch 296-Ai - rev. 1/2019

### Substances subject to the Rotterdam Convention:

None

### Substances subject to the Stockholm Convention:

None

### Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

### German regulation on the classification of substances hazardous to water (AwSV, vom 18. April 2017)

WGK 2: Hazard to waters

## 15.2. Chemical safety assessment

A chemical safety assessment has been performed for the following contained substances

2-METHOXY-1-METHYLETHYL ACETATE

N-BUTYL ACETATE

XYLENE (MIXTURE OF ISOMERS)

## SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

<b>Flam. Liq. 3</b>	Flammable liquid, category 3
<b>Acute Tox. 4</b>	Acute toxicity, category 4
<b>Asp. Tox. 1</b>	Aspiration hazard, category 1
<b>STOT RE 2</b>	Specific target organ toxicity - repeated exposure, category 2
<b>Skin Corr. 1B</b>	Skin corrosion, category 1B
<b>Eye Dam. 1</b>	Serious eye damage, category 1
<b>Eye Irrit. 2</b>	Eye irritation, category 2
<b>Skin Irrit. 2</b>	Skin irritation, category 2
<b>STOT SE 3</b>	Specific target organ toxicity - single exposure, category 3
<b>Skin Sens. 1A</b>	Skin sensitization, category 1A
<b>Skin Sens. 1B</b>	Skin sensitization, category 1B
<b>Aquatic Chronic 2</b>	Hazardous to the aquatic environment, chronic toxicity, category 2
<b>Aquatic Chronic 3</b>	Hazardous to the aquatic environment, chronic toxicity, category 3
<b>H226</b>	Flammable liquid and vapour.
<b>H302</b>	Harmful if swallowed.

## CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS ENAMEL RAL 9016 Component A - SAFETY DATA SHEET - october 2019 - n°batch 296-Ai - rev. 1/2019

H312	Harmful in contact with skin.
H332	Harmful if inhaled.
H304	May be fatal if swallowed and enters airways.
H373	May cause damage to organs through prolonged or repeated exposure.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H335	May cause respiratory irritation.
H317	May cause an allergic skin reaction.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

### LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

### GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
4. Regulation (EU) 2015/830 of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament

## CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



**NAUTILUS ENAMEL RAL 9016 Component A** - SAFETY DATA SHEET - october 2019 - n°batch 296-Ai - rev. 1/2019

11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament

12. Regulation (EU) 2016/1179 (IX Atp. CLP)

13. Regulation (EU) 2017/776 (X Atp. CLP)

- The Merck Index. - 10th Edition

- Handling Chemical Safety

- INRS - Fiche Toxicologique (toxicological sheet)

- Patty - Industrial Hygiene and Toxicology

- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition

- IFA GESTIS website

- ECHA website

- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

Changes to previous review:

The following sections were modified:

02 / 03 / 04 / 07 / 08 / 09 / 10 / 11 / 12 / 13 / 15.