

## CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY  
tel. +39 0584 383694 fax +39 0584 395182  
www.cecchi.it info@cecchi.it



SPINNAKER POLYURETHANE 2 comp.A - SAFETY DATA SHEET - february 2020 - batch n° 061-B0 - rev.1/16

# SPINNAKER POLYURETHANE 2 comp. A

## \* SECTION 1: Identification of the substance/mixture and of the company/undertaking

### · 1.1 Product identifier

Trade name: SPINNAKER POLYURETHANE 2 comp.A

### · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance / the mixture base component of a two-component high gloss yacht varnish

### · 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

CECCHI GUSTAVO & C. SRL.

Via M.Coppino, 253 55049 VIAREGGIO (LU) ITALY

TEL. +39 0584 383694 FAX +39 0584 395182

### · 1.4 Emergency telephone number:

+39 0584/383694 From monday to friday office hours 8:30 – 12:30, 14:00 – 18:30 - [info@cecchi.it](mailto:info@cecchi.it)

## \* SECTION 2: Hazards identification

### · 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

GHS02 flame

Flam. Liq. 3

H226 Flammable liquid and vapour.

Aquatic Chronic 3

H412 Harmful to aquatic life with long lasting effects.

### · 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

### · Hazard pictograms



· Signal word Warning

· Hazard statements

H226 Flammable liquid and vapour.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P501 Dispose of contents/container in accordance with local/regional/ national/international regulations.

· Additional information: For professional use only.

### · 2.3 Other hazards

· Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

## \* SECTION 3: Composition/information on ingredients

### · 3.2 Chemical characterisation: Mixtures

· Description:

Resin mixture

Solvent mixture with additives

**CECCHI GUSTAVO & C.**

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY  
 tel. +39 0584 383694 fax +39 0584 395182  
 www.cecchi.it info@cecchi.it



**SPINNAKER POLYURETHANE 2 comp.A** - SAFETY DATA SHEET - february 2020 - batch n° 061-B0 - rev.1/16

CAS: 108-65-6 EINECS: 203-603-9 Index number: 607-195-00-7 Reg.nr.: 01-2119475791-29	2-methoxy-1-methylethyl acetate Flam. Liq. 3, H226	25-50%
CAS: 1330-20-7 EINECS: 215-535-7 Index number: 601-022-00-9 Reg.nr.: 01-2119488216-32	xylene Flam. Liq. 3, H226 Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	2,5-10%
CAS: 78-93-3 EINECS: 201-159-0 Index number: 606-002-00-3 Reg.nr.: 01-2119457290-43	butanone Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336	2,5-10%
ELINCS: 400-830-7 Index number: 607-176-00-3 Reg.nr.: 01-2119396032-43	Mixture of alpha-3-(3-(2Hbenzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-omegahydroxypoly(oxyethylene) and alpha-3-(3-(2H-benzotriazol-2-yl)-5-tertbutyl-4-hydroxyphenyl)propionyl-omega-3-(3-(2H-benzotriazol-2-yl)-5-tertbutyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene) Aquatic Chronic 2, H411 Skin Sens. 1, H317	<=1%
CAS: 41556-26-7 EINECS: 255-437-1 Reg.nr.: 01-2119491304-40	bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacat Aquatic Acute 1, H400; Aquatic Chronic 1, H410 Skin Sens. 1, H317	<=1%
CAS: 82919-37-7 EINECS: 280-060-7 Reg.nr.: niet van toepassing	methyl-1,2,3,6,6-pentamethyl-4-piperidylsebacat Aquatic Acute 1, H400; Aquatic Chronic 1, H410 Skin Sens. 1,	<=0,3%

· Additional information:

For the wording of the listed risk phrases refer to section 16.

**\* SECTION 4: First aid measures**

· 4.1 Description of first aid measures

- After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Generally the product does not irritate the skin.
- After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- After swallowing: Seek medical treatment.

· 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

- 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

**\* SECTION 5: Firefighting measures**

· 5.1 Extinguishing media

· Suitable extinguishing agents:

CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- For safety reasons unsuitable extinguishing agents: Water with full jet

· 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- 5.3 Advice for firefighters

## CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY  
tel. +39 0584 383694 fax +39 0584 395182  
www.cecchi.it info@cecchi.it



SPINNAKER POLYURETHANE 2 comp.A - SAFETY DATA SHEET - february 2020 - batch n° 061-B0 - rev.1/16

· Protective equipment: Wear fully protective suit.

### \* SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### \* SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Keep away from heat and direct sunlight.

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

· Requirements to be met by storerooms and receptacles:

Store only in the original receptacle.

· Information about storage in one common storage facility: Not required.

· Further information about storage conditions: Keep container tightly sealed.

· 7.3 Specific end use(s) No further relevant information available.

### \* SECTION 8: Exposure controls/personal protection

· Additional information about design of technical facilities:

No further data; see item 7.

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

108-65-6 2-methoxy-1-methylethyl acetate		
Inhalative	(Tgg)time weighted average 8 hours / Exposure time	550 mg/m3 (Algemene bevolking/ General population)
1330-20-7 xylene		
Inhalative	(Tgg)time weighted average 15 min. / Exposure time	442 mg/m3 (Algemene bevolking/ General population)
	(Tgg)time weighted average 8 hours / Exposure time	210 mg/m3 (Algemene bevolking/ General population)
78-93-3 butanone		
Inhalative	(Tgg)time weighted average 15 min. / Exposure time	900 mg/m3 (Algemene bevolking/ General population)
	(Tgg)time weighted average 8 hours / Exposure time	590 mg/m3 (Algemene bevolking/

**CECCHI GUSTAVO & C.**

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY  
 tel. +39 0584 383694 fax +39 0584 395182  
 www.cecchi.it info@cecchi.it



**SPINNAKER POLYURETHANE 2 comp.A** - SAFETY DATA SHEET - february 2020 - batch n° 061-B0 - rev.1/16

		General population)
108-65-6 2-methoxy-1-methylethyl acetate		
WEL	Short-term value: 548 mg/m <sup>3</sup> , 100 ppm Long-term value: 274 mg/m <sup>3</sup> , 50 ppm Sk	
1330-20-7 xylene		
WEL	Short-term value: 441 mg/m <sup>3</sup> , 100 ppm Long-term value: 220 mg/m <sup>3</sup> , 50 ppm Sk; BMGV	
78-93-3 butanone		
WEL	Short-term value: 899 mg/m <sup>3</sup> , 300 ppm Long-term value: 600 mg/m <sup>3</sup> , 200 ppm Sk, BMGV	
· DNELs		
1330-20-7 xylene		
Dermal	Long-term - local effects, worker	
Inhalative	Acute - systemic effects, worker	289 mg/m <sup>3</sup> (Werker/Worker)
	Acute-local effects, worker	289 mg/m <sup>3</sup> (Werker/Worker)
	Long-term - local effects, worker	77 mg/m <sup>3</sup> (Werker/Worker)

· PNECs	
1330-20-7 xylene	
Aquatic compartment - freshwater	0.327 mg/L (not specified)
Aquatic compartment - marine water	0.327 mg/L (not specified)
Aquatic compartment - sediment in freshwater	12.46 mg/kg sed dw (not specified)
Aquatic compartment - sediment in marine water	12.46 mg/kg sed dw (not specified)
Aquatic compartment - water, intermittent releases	0.327 mg/L (not specified)
Sewage treatment plant	6.58 mg/L (not specified)
Terrestrial compartment - soil	2.31 mg/kg dw (not specified)
Ingredients with biological limit values:	
1330-20-7 xylene	
BMGV	650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid
78-93-3 butanone	
BMGV	70 µmol/L Medium: urine Sampling time: post shift Parameter: butan-2-one

· Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

· Personal protective equipment:

· General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter AX



- Protection of hands:

## Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

- For the permanent contact gloves made of the following materials are suitable: Butyl rubber, glove thickness 0.7 mm,> 480 min breakthrough time / permeation to EN374.

- As protection from splashes gloves made of the following materials are suitable:

(recommended: at least protection index 2, corresponding> 30 minutes permeability time / Permeation according to EN 374) chloroprene rubber (CR) - 0.5 mm thickness nitrile rubber (NBR) - 0.4 mm thickness

- Eye protection:

Tightly sealed goggles

**\* SECTION 9: Physical and chemical properties**

- 9.1 Information on basic physical and chemical properties

- General Information

- Appearance:

Form:	Fluid
Colour:	According to product specification
· Odour:	Characteristic
· Odour threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	146 °C
· Flash point:	42 °C
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	315 °C
· Decomposition temperature:	Not determined.
· Self-igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits:	
Lower:	1.5 Vol %
Upper:	10.8 Vol %
· Vapour pressure at 20 °C:	3.4 hPa
· Density at 20 °C:	1.07 g/cm <sup>3</sup>
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility withwater:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic at 20 °C:	40 s (ISO 4 mm)
· Solvent content:	
Organic solvents:	61.0 %
VOC content:	61.0 %
VOC content:	

## CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY  
tel. +39 0584 383694 fax +39 0584 395182  
www.cecchi.it info@cecchi.it



SPINNAKER POLYURETHANE 2 comp.A - SAFETY DATA SHEET - february 2020 - batch n° 061-B0 - rev.1/16

652.4 g/l / 5.44 lb/gl

Solids content: 39.3 % (VB% 1h150 C)

· 9.2 Other information No further relevant information available.

### \* SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

· Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

· 10.3 Possibility of hazardous reactions No dangerous reactions known.

· 10.4 Conditions to avoid No further relevant information available.

· 10.5 Incompatible materials: No further relevant information available.

· 10.6 Hazardous decomposition products:

No dangerous decomposition products known.

### \* SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

· Acute toxicity

· LD/LC50 values relevant for classification:		
108-65-6 2-methoxy-1-methylethyl acetate		
Oral	LD50	8532 mg/kg bw (rat)
Inhalative	LC50/4 h	35.7 mg/l (rat)
1330-20-7 xylene		
Oral	LD50	
Dermal	LD50	
78-93-3 butanone		
Oral	LD50	3300 mg/kg bw (rat)
Dermal	LD50	5000 mg/kg bw (rabbit)

· Primary irritant effect:

· Skin corrosion/irritation

Based on available data, the classification criteria are not met.

· Serious eye damage/irritation

Based on available data, the classification criteria are not met.

· Respiratory or skin sensitisation

Based on available data, the classification criteria are not met.

· CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

· Germ cell mutagenicity

Based on available data, the classification criteria are not met.

· Carcinogenicity

Based on available data, the classification criteria are not met.

· Reproductive toxicity

Based on available data, the classification criteria are not met.

· STOT-single exposure

Based on available data, the classification criteria are not met.

· STOT-repeated exposure

Based on available data, the classification criteria are not met.

· Aspiration hazard

Based on available data, the classification criteria are not met.

## CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY  
tel. +39 0584 383694 fax +39 0584 395182  
www.cecchi.it info@cecchi.it



SPINNAKER POLYURETHANE 2 comp.A - SAFETY DATA SHEET - february 2020 - batch n° 061-B0 - rev.1/16

### \* SECTION 12: Ecological information

- 12.1 Toxicity
- Aquatic toxicity:

108-65-6 2-methoxy-1-methylethyl acetate	
EC50	408-500 mg/l (daphnia magna) (48 uur/hour)
IC 50	>1000 mg/l (Algae, Growth inhibition test) (72 uur/hour)
LC50	100-180 mg/l (Fish Acute Toxicity Study) (96 uur/hour)
1330-20-7 xylene	
EC50	1 mg/l (daphnia magna) (48 uur/hour)
LC50	13.5-2.6 mg/l (Fish Acute Toxicity Study) (96 uur/hour)
· 12.2 Persistence and degradability No further relevant information available.	
· 12.3 Bioaccumulative potential	
1330-20-7 xylene	
Log Kow	3 (not specified)

- 12.4 Mobility in soil No further relevant information available.
- Additional ecological information:
- General notes:  
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water  
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- 12.5 Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

### \* SECTION 13: Disposal considerations

- 13.1 Waste treatment methods
- Recommendation  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- European waste catalogue

08 00 00	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS
08 01 00	wastes from MFSU and removal of paint and varnish
08 01 11*	waste paint and varnish containing organic solvents or other dangerous substances

- Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.

### \* SECTION 14: Transport information

- 14.1 UN-Number
- ADR, IMDG, IATA UN1263
- 14.2 UN proper shipping name
- ADR 1263 PAINT
- IMDG, IATA PAINT
- 14.3 Transport hazard class(es)
- ADR, IMDG, IATA
- Class 3 Flammable liquids.
- Label 3
- 14.4 Packing group

## CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY  
tel. +39 0584 383694 fax +39 0584 395182  
www.cecchi.it info@cecchi.it



SPINNAKER POLYURETHANE 2 comp.A - SAFETY DATA SHEET - february 2020 - batch n° 061-B0 - rev.1/16

- ADR, IMDG, IATA III
- 14.5 Environmental hazards:
- Marine pollutant: No
- 14.6 Special precautions for user Warning: Flammable liquids.
- Danger code (Kemler): 30
- EMS Number: F-E,S-E
- 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable.
- Transport/Additional information:
- ADR
- Limited quantities (LQ) 5L
- Excepted quantities (EQ) Code: E1
- Maximum net quantity per inner packaging: 30 ml
- Maximum net quantity per outer packaging: 1000 ml
- Transport category 3
- Tunnel restriction code D/E
- IMDG
- Limited quantities (LQ) 5L
- Excepted quantities (EQ) Code: E1
- Maximum net quantity per inner packaging: 30 ml
- Maximum net quantity per outer packaging: 1000 ml
- UN "Model Regulation": UN1263, PAINT, 3, III

### \* SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Directive 2012/18/EU
- Named dangerous substances - ANNEX I None of the ingredients is listed.
- National regulations:
- Technical instructions (air):  
Class Share in %  
NK 50-100
- Waterhazard class:  
Water hazard class 1 (Self-assessment): slightly hazardous for water.
- 15.2 Chemical safety assessment:  
A Chemical Safety Assessment has not been carried out.

### \* SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Relevant phrases  
H225 Highly flammable liquid and vapour.  
H226 Flammable liquid and vapour.  
H312 Harmful in contact with skin.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H332 Harmful if inhaled.  
H336 May cause drowsiness or dizziness.  
H400 Very toxic to aquatic life.  
H410 Very toxic to aquatic life with long lasting effects.  
H411 Toxic to aquatic life with long lasting effects.
- Abbreviations and acronyms:  
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)  
ICAO: International Civil Aviation Organisation

## CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY  
tel. +39 0584 383694 fax +39 0584 395182  
www.cecchi.it info@cecchi.it



**SPINNAKER POLYURETHANE 2 comp.A** - SAFETY DATA SHEET - february 2020 - batch n° 061-B0 - rev.1/16

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids, Hazard Category 2

Flam. Liq. 3: Flammable liquids, Hazard Category 3

Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

Aquatic Acute 1: Hazardous to the aquatic environment - Acute Hazard, Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - Chronic Hazard, Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3

· \* Data compared to the previous version altered.