

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



EPOXY THINNER - Safety data sheet - september 2020 - n° batch 295-B0 - rev.1/17

Safety data sheet

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name **EPOXY THINNER**
Chemical name and synonym **MISCELA DI SOLVENTI**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use **DILUENTE PER VERNICI.**

Identified Uses	Industrial	Professional	Consumer
Diluizione, sgrassaggio, preparazione di talune superfici	✓	✓	✓

1.3. Details of the supplier of the safety data sheet

Name **CECCHI GUSTAVO & C. S.R.L.**
Full address **Via Coppino 253**
District and Country **55049 VIAREGGIO (LU)**
Italy
Tel. +39 0584 383694
Fax +39 0584 395182

e-mail address of the competent person responsible for the Safety Data Sheet

info@cecchi.it

1.4. Emergency telephone number

For urgent inquiries refer to **+39 0584 383694**

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of EC Regulation 1907/2006 and subsequent amendments. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Flammable liquid, category 2	H225	Highly flammable liquid and vapour.
Acute toxicity, category 4	H332	Harmful if inhaled.
Aspiration hazard, category 1	H304	May be fatal if swallowed and enters airways.
Specific target organ toxicity - repeated exposure, category 2	H373	May cause damage to organs through prolonged or repeated exposure.
Serious eye damage, category 1	H318	Causes serious eye damage.
Skin irritation, category 2	H315	Causes skin irritation.
Specific target organ toxicity - single exposure, category 3	H335	May cause respiratory irritation.
Specific target organ toxicity - single exposure, category 3	H336	May cause drowsiness or dizziness.

2.2. Label elements

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



EPOXY THINNER - Safety data sheet - september 2020 - n° batch 295-B0 - rev.1/17

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words:

Danger

Hazard statements:

H225	Highly flammable liquid and vapour.
H332	Harmful if inhaled.
H304	May be fatal if swallowed and enters airways.
H373	May cause damage to organs through prolonged or repeated exposure.
H318	Causes serious eye damage.
H315	Causes skin irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.

Precautionary statements:

P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280	Wear protective gloves / eye protection / face protection.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P331	Do NOT induce vomiting.
P501	Dispose of contents / container to . . .

Contains:	XYLENE (MIXTURE OF ISOMERS) ISOBUTYL ALCOHOL 4-METHYLPENTAN-2-ONE ETHYLBENZENE
------------------	---

Product not intended for uses provided for by Dir. 2004/42/CE.

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

SECTION 3. Composition/information on ingredients

3.1. Substances

Information not relevant

3.2. Mixtures

Contains:

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



EPOXY THINNER - Safety data sheet - september 2020 - n° batch 295-B0 - rev.1/17

The full wording of hazard (H) phrases is given in section 16 of the sheet.

Identification	x = Conc. %	Classification 1272/2008 (CLP)
XYLENE (MIXTURE OF ISOMERS)		
CAS 1330-20-7	$30 \leq x < 40$	Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Note C
EC 215-535-7		
INDEX 601-022-00-9		
Reg. no. 01-2119488216-32-XXXX		
4-METHYLPENTAN-2-ONE		
CAS 108-10-1	$20 \leq x < 30$	Flam. Liq. 2 H225, Acute Tox. 4 H332, Eye Irrit. 2 H319, STOT SE 3 H335, EUH066
EC 203-550-1		
INDEX 606-004-00-4		
Reg. no. 01-2119473980-30		
ISOBUTYL ALCOHOL		
CAS 78-83-1	$10 \leq x < 20$	Flam. Liq. 3 H226, Eye Dam. 1 H318, Skin Irrit. 2 H315, STOT SE 3 H335, STOT SE 3 H336
EC 201-148-0		
INDEX 603-108-00-1		
Reg. no. 01-2119484609-23		
4-HYDROXY-4-METHYLPENTAN-2-ONE		
CAS 123-42-2	$10 \leq x < 20$	Flam. Liq. 3 H226, Eye Irrit. 2 H319
EC 204-626-7		
INDEX 603-016-00-1		
ETHYLBENZENE		
CAS 100-41-4	$7.5 \leq x < 10$	Flam. Liq. 2 H225, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373
EC 202-849-4		
INDEX 601-023-00-4		
N-BUTYL ACETATE		
CAS 123-86-4	$2.5 \leq x < 5$	Flam. Liq. 3 H226, STOT SE 3 H336, EUH066
EC 204-658-1		
INDEX 607-025-00-1		
Reg. no. 01-2119485493-29-XXXX		

SECTION 4. First aid measures

4.1. Description of first aid measures

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



EPOXY THINNER - Safety data sheet - september 2020 - n° batch 295-B0 - rev.1/17

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



EPOXY THINNER - Safety data sheet - september 2020 - n° batch 295-B0 - rev.1/17

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

Send away individuals who are not suitably equipped. Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. If the product is flammable, use explosion-proof equipment. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Vapours may catch fire and an explosion may occur; vapour accumulation is therefore to be avoided by leaving windows and doors open and ensuring good cross ventilation. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. When performing transfer operations involving large containers, connect to an earthing system and wear antistatic footwear. Vigorous stirring and flow through the tubes and equipment may cause the formation and accumulation of electrostatic charges. In order to avoid the risk of fires and explosions, never use compressed air when handling. Open containers with caution as they may be pressurised. Do not eat, drink or smoke during use. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



EPOXY THINNER - Safety data sheet - september 2020 - n° batch 295-B0 - rev.1/17

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Store in a well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

Storage class TRGS 510 (Germany):

3

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory References:

DEU	Deutschland	MAK-und BAT-Werte-Liste 2012
ESP	España	INSHT - Límites de exposición profesional para agentes químicos en España 2015
FRA	France	JORF n°0109 du 10 mai 2012 page 8773 texte n° 102
GBR	United Kingdom	EH40/2005 Workplace exposure limits
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
NLD	Nederland	Databank of the social and Economic Concil of Netherlands (SER) Values, AF 2011:18
POL	Polska	ROZPORZĄDZENIE MINISTRA PRACY I POLITYKI SPOŁECZNEJ z dnia 16 grudnia 2011r
PRT	Portugal	Ministério da Economia e do Emprego Consolida as prescrições mínimas em matéria de protecção dos trabalhadores contra os riscos para a segurança e a saúde devido à exposição a agentes químicos no trabalho - Diaro da Republica I 26; 2012-02-06
EU	OEL EU	Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2016

XYLENE (MIXTURE OF ISOMERS)

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	440	100	880	200	SKIN
MAK	DEU	440	100	880	200	SKIN
VLA	ESP	221	50	442	100	SKIN
VLEP	FRA	221	50	442	100	SKIN
WEL	GBR	220	50	441	100	
VLEP	ITA	221	50	442	100	SKIN
OEL	NLD	210		442		SKIN
NDS	POL	100				

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



EPOXY THINNER - Safety data sheet - september 2020 - n° batch 295-B0 - rev.1/17

OEL	EU	221	50	442	100	SKIN
TLV-ACGIH		434	100	651	150	

Predicted no-effect concentration - PNEC

Normal value in fresh water	0.327	mg/l
Normal value in marine water	0.327	mg/l
Normal value for fresh water sediment	12.46	mg/kg
Normal value for marine water sediment	12.46	mg/kg
Normal value of STP microorganisms	6.58	mg/l
Normal value for the terrestrial compartment	2.31	mg/kg

4-METHYLPENTAN-2-ONE**Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	83	20	166	40	SKIN
MAK	DEU	83	20	166	40	SKIN
VLA	ESP	83	20	208	50	
VLEP	FRA	83	20	208	50	
WEL	GBR	208	50	416	100	SKIN
VLEP	ITA	83	20	208	50	
OEL	NLD	104		208		
NDS	POL	83		200		
VLE	PRT	83	20	208	50	
OEL	EU	83	20	208	50	
TLV-ACGIH		82	20	307	75	

ISOBUTYL ALCOHOL**Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min	
		mg/m3	ppm	mg/m3	ppm
AGW	DEU	310	100	310	100
MAK	DEU	310	100	310	100
VLA	ESP	154	50		
VLEP	FRA	150	50		
WEL	GBR	154	50	231	75
OEL	NLD	150			
NDS	POL	100		200	
TLV-ACGIH		152	50		

Predicted no-effect concentration - PNEC

Normal value in fresh water	0.4	mg/l
Normal value in marine water	0.04	mg/l
Normal value for fresh water sediment	1.52	mg/kg d.w.
Normal value for marine water sediment	0.152	mg/kg d.w.
Normal value for water, intermittent release	11	mg/l
Normal value of STP microorganisms	10	mg/l
Normal value for the terrestrial compartment	0.0699	mg/kg d.w.

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers		Effects on workers					
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral							25 mg/kg d.w.	VND
Inhalation			310 mg/m3	VND			55 mg/m3	VND

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



EPOXY THINNER - Safety data sheet - september 2020 - n° batch 295-B0 - rev.1/17

4-HYDROXY-4-METHYLPENTAN-2-ONE

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	96	20	192	40	SKIN
MAK	DEU	96	20	192	40	SKIN
VLA	ESP	241	50			
VLEP	FRA	240	50			
WEL	GBR	241	50	362	75	
OEL	NLD	120				SKIN
NDS	POL	240				
TLV-ACGIH		238	50			

ETHYLBENZENE

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	440	100	880	200	SKIN
MAK	DEU	88	20	176	40	SKIN
VLA	ESP	441	100	884	200	SKIN
VLEP	FRA	88.4	20	442	100	SKIN
WEL	GBR	441	100	552	125	SKIN
VLEP	ITA	442	100	884	200	SKIN
OEL	NLD	215		430		SKIN
NDS	POL	200		400		
VLE	PRT	442	100	884	200	SKIN
OEL	EU	442	100	884	200	SKIN
TLV-ACGIH		87	20			

N-BUTYL ACETATE

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		
		mg/m3	ppm	mg/m3	ppm	
MAK	DEU	480	100	960	200	
VLA	ESP	724	150	965	200	
VLEP	FRA	710	150	940	200	
WEL	GBR	724	150	966	200	
OEL	NLD	150				
NDS	POL	200		950		
TLV-ACGIH			50		150	

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



EPOXY THINNER - Safety data sheet - september 2020 - n° batch 295-B0 - rev.1/17

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

Exposure levels must be kept as low as possible to avoid significant build-up in the organism. Manage personal protective equipment so as to guarantee maximum protection (e.g. reduction in replacement times).

HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion.

EYE PROTECTION

Wear a hood visor or protective visor combined with airtight goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, wear a mask with a type AX filter, whose limit of use will be defined by the manufacturer (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	liquid
Colour	colourless
Odour	characteristic of solvent
Odour threshold	Not available
pH	Not available
Melting point / freezing point	Not available
Initial boiling point	> 35 °C
Boiling range	Not available
Flash point	< 23 °C
Evaporation Rate	Not available
Flammability of solids and gases	Not available

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



EPOXY THINNER - Safety data sheet - september 2020 - n° batch 295-B0 - rev.1/17

Lower inflammability limit	Not available
Upper inflammability limit	Not available
Lower explosive limit	Not available
Upper explosive limit	Not available
Vapour pressure	10.81 mmHg
Vapour density	Not available
Relative density	0.85
Solubility	10% BY WT IN WATER
Partition coefficient: n-octanol/water	Not available
Auto-ignition temperature	Not available
Decomposition temperature	Not available
Viscosity	T.F. 3 a 40°C < 30"
Explosive properties	Not available
Oxidising properties	Not available

9.2. Other information

VOC (Directive 2010/75/EC) :	100.00 % - 849.47 g/litre
VOC (volatile carbon) :	77.17 % - 655.52 g/litre

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

4-METHYLPENTAN-2-ONE

Reacts violently with: light metals. Attacks various types of plastic materials.

4-HYDROXY-4-METHYLPENTAN-2-ONE

Decomposes at temperatures above 90°C/194°F.

N-BUTYL ACETATE

Decomposes on contact with: water.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

XYLENE (MIXTURE OF ISOMERS)

XYLENE (MIXTURE OF ISOMERS): stable, but may develop violent reactions in the presence of strong oxidising agents such as sulphuric and nitric acids and perchlorates. May form explosive mixtures with the air.

4-METHYLPENTAN-2-ONE

May react violently with: oxidising agents. Forms peroxides with: air. Forms explosive mixtures with: hot air.

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



EPOXY THINNER - Safety data sheet - september 2020 - n° batch 295-B0 - rev.1/17

4-HYDROXY-4-METHYLPENTAN-2-ONE

Risk of explosion on contact with: air,sources of heat.May react dangerously with: alkaline metals,amines,oxidising agents,acids.

ETHYLBENZENE

Reacts violently with: strong oxidants.Attacks various types of plastic materials.May form explosive mixtures with: air.

N-BUTYL ACETATE

Risk of explosion on contact with: strong oxidising agents.May react dangerously with: alkaline hydroxides,potassium tert-butoxide.Forms explosive mixtures with: air.

10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

4-METHYLPENTAN-2-ONE

Avoid exposure to: sources of heat.

4-HYDROXY-4-METHYLPENTAN-2-ONE

Avoid exposure to: light,sources of heat,naked flames.

N-BUTYL ACETATE

Avoid exposure to: moisture,sources of heat,naked flames.

10.5. Incompatible materials

4-METHYLPENTAN-2-ONE

Incompatible with: oxidising substances,reducing substances.

N-BUTYL ACETATE

Incompatible with: water,nitrates,strong oxidants,acids,alkalis,zinc.

10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

ETHYLBENZENE

May develop: methane,styrene,hydrogen,ethane.

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



EPOXY THINNER - Safety data sheet - september 2020 - n° batch 295-B0 - rev.1/17

11.1. Information on toxicological effects

XYLENE (MIXTURE OF ISOMERS)

XYLENE (MIXTURE OF ISOMERS): has a toxic effect on the CNS (encephalopathies). Irritating to the skin, conjunctivae, cornea and respiratory apparatus.

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

ETHYLBENZENE

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; contact with the skin of products containing the substance.

4-HYDROXY-4-METHYLPENTAN-2-ONE

WORKERS: inhalation; contact with the skin.

N-BUTYL ACETATE

WORKERS: inhalation; contact with the skin.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

ETHYLBENZENE

As the counterparts of benzene, may have an acute effect on the central nervous system, with depression, narcosis, often preceded by dizziness and associated with headache (Ispehl). Is irritating for skin, conjunctiva and respiratory tract.

4-HYDROXY-4-METHYLPENTAN-2-ONE

Acute toxicity causes irritation of the eyes, nose and throat in humans at 100 ppm (476 mg/kg) and pulmonary disorders at 400 ppm. No chronic effects on humans have been reported. The substance may have a depressive effect on the respiratory centres and cause death from respiratory failure.

N-BUTYL ACETATE

In humans, the substance's vapours cause irritation of the eyes and nose. In the event of repeated exposure, skin irritation, dermatitis (dryness and cracking of the skin) and keratitis appear.

Interactive effects

N-BUTYL ACETATE

A case of acute intoxication been reported involving a 33 year old worker while cleaning a tank with a preparation containing xylenes, butyl acetate and ethylene glycol acetate. The person had irritation of the conjunctiva and upper respiratory tract, drowsiness and motor coordination disorders, which disappeared within 5 hours. The symptoms are attributed to poisoning by mixed xylenes and butyl acetate, with a possible synergistic effect responsible for the neurological effects. Cases of vacuolar keratitis are reported in workers exposed to a mixture of butyl acetate and isobutanol vapours, but with uncertainty concerning the responsibility of a particular solvent (INRC, 2011).

ACUTE TOXICITY

LC50 (Inhalation) of the mixture: 14.40 mg/l

LD50 (Oral) of the mixture: Not classified (no significant component)

LD50 (Dermal) of the mixture: >2000 mg/kg

ISOBUTYL ALCOHOL

2460 mg/kg Rat

LD50 (Oral)

2460 mg/kg Rabbit

LD50 (Dermal)

19.2 mg/l/4h Rat

LC50 (Inhalation)

ETHYLBENZENE

3500 mg/kg Rat

LD50 (Oral)

15354 mg/kg Rabbit

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



EPOXY THINNER - Safety data sheet - september 2020 - n° batch 295-B0 - rev.1/17

LD50 (Dermal)
17.2 mg/l/4h Rat
LC50 (Inhalation)

4-HYDROXY-4-METHYLPENTAN-2-ONE
4000 mg/kg Rat
LD50 (Oral)

4-METHYLPENTAN-2-ONE
2080 mg/kg Rat
LD50 (Oral)
> 16000 mg/kg Rabbit
LD50 (Dermal)
> 8.2 mg/l/4h Rat
LC50 (Inhalation)

N-BUTYL ACETATE
> 6400 mg/kg Rat
LD50 (Oral)
> 5000 mg/kg Rabbit
LD50 (Dermal)
21.1 mg/l/4h Rat
LC50 (Inhalation)

XYLENE (MIXTURE OF ISOMERS)
3523 mg/kg Rat
LD50 (Oral)
4350 mg/kg Rabbit
LD50 (Dermal)
26 mg/l/4h Rat
LC50 (Inhalation)

SKIN CORROSION / IRRITATION

Causes skin irritation

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye damage

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

ETHYLBENZENE

Classified in Group 2B (possible human carcinogen) by the International Agency for Research on Cancer (IARC) - (IARC, 2000).

Classified in Group D (not classifiable as a human carcinogen) by the US Environmental Protection Agency (EPA) - (US EPA file on-line 2014).

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

May cause respiratory irritation May cause drowsiness or dizziness

STOT - REPEATED EXPOSURE

May cause damage to organs

ASPIRATION HAZARD

Toxic for aspiration

SECTION 12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

12.1. Toxicity

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



EPOXY THINNER - Safety data sheet - september 2020 - n° batch 295-B0 - rev.1/17

ISOBUTYL ALCOHOL

LC50 - for Fish > 1.43 mg/l/96h Pimephales promelas

EC50 - for Crustacea > 1.1 mg/l/48h Daphnia pulex

XYLENE (MIXTURE OF ISOMERS)

LC50 - for Fish > 4.2 mg/l/96h Oncorhynchus mykiss

EC50 - for Crustacea > 2.93 mg/l/48h Daphnia Magna

12.2. Persistence and degradability

ISOBUTYL ALCOHOL

Solubility in water 1000 - 10000 mg/l

Rapidly degradable

ETHYLBENZENE

Solubility in water 1000 - 10000 mg/l

Rapidly degradable

4-HYDROXY-4-METHYLPENTAN-2-ONE

Solubility in water 1000 - 10000 mg/l

Rapidly degradable

4-METHYLPENTAN-2-ONE

Solubility in water > 10000 mg/l

Degradability: information not available

Rapidly degradable

N-BUTYL ACETATE

Solubility in water 1000 - 10000 mg/l

XYLENE (MIXTURE OF ISOMERS)

Solubility in water 100 - 1000 mg/l

Degradability: information not available

12.3. Bioaccumulative potential

ISOBUTYL ALCOHOL

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



EPOXY THINNER - Safety data sheet - september 2020 - n° batch 295-B0 - rev.1/17

Partition coefficient: n-octanol/water	1
ETHYLBENZENE	
Partition coefficient: n-octanol/water	3.6
4-HYDROXY-4-METHYLPENTAN-2-ONE	
Partition coefficient: n-octanol/water	-0.09
4-METHYLPENTAN-2-ONE	
Partition coefficient: n-octanol/water	1.9
N-BUTYL ACETATE	
Partition coefficient: n-octanol/water	2.3
BCF	15.3
XYLENE (MIXTURE OF ISOMERS)	
Partition coefficient: n-octanol/water	3.12
BCF	25.9

12.4. Mobility in soil

ISOBUTYL ALCOHOL	
Partition coefficient: soil/water	0.31
4-METHYLPENTAN-2-ONE	
Partition coefficient: soil/water	2.008
N-BUTYL ACETATE	
Partition coefficient: soil/water	< 3
XYLENE (MIXTURE OF ISOMERS)	
Partition coefficient: soil/water	2.73

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects

Information not available

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



EPOXY THINNER - Safety data sheet - september 2020 - n° batch 295-B0 - rev.1/17

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

14.1. UN number

ADR / RID, IMDG, 1263
IATA:

14.2. UN proper shipping name

ADR / RID: PAINT or PAINT
RELATED
MATERIAL
IMDG: PAINT or PAINT
RELATED
MATERIAL
IATA: PAINT or PAINT
RELATED
MATERIAL

14.3. Transport hazard class(es)

ADR / RID: Class: 3 Label: 3

IMDG: Class: 3 Label: 3

IATA: Class: 3 Label: 3



14.4. Packing group

ADR / RID, IMDG, II
IATA:

14.5. Environmental hazards

ADR / RID: NO

IMDG: NO

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



EPOXY THINNER - Safety data sheet - september 2020 - n° batch 295-B0 - rev.1/17

IATA: NO

14.6. Special precautions for user

ADR / RID:	HIN - Kemler: 33	Limited Quantities: 5 L	Tunnel restriction code: (D/E)
IMDG:	Special Provision: 640C EMS: F-E, <u>S-E</u>	Limited Quantities: 5 L	
IATA:	Cargo:	Maximum quantity: 60 L	Packaging instructions: 364
	Pass.:	Maximum quantity: 5 L	Packaging instructions: 353
	Special Instructions:	A3, A72, A192	

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EC: P5c

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product Point 3 - 40

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage greater than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



EPOXY THINNER - Safety data sheet - september 2020 - n° batch 295-B0 - rev.1/17

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

German regulation on the classification of substances hazardous to water (VwVwS 2005)

WGK 2: Hazard to waters

15.2. Chemical safety assessment

A chemical safety assessment has been performed for the following contained substances

XYLENE (MIXTURE OF ISOMERS)

4-METHYLPENTAN-2-ONE

ISOBUTYL ALCOHOL

N-BUTYL ACETATE

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 2	Flammable liquid, category 2
Flam. Liq. 3	Flammable liquid, category 3
Acute Tox. 4	Acute toxicity, category 4
Asp. Tox. 1	Aspiration hazard, category 1
STOT RE 2	Specific target organ toxicity - repeated exposure, category 2
Eye Dam. 1	Serious eye damage, category 1
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
STOT SE 3	Specific target organ toxicity - single exposure, category 3
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H312	Harmful in contact with skin.
H332	Harmful if inhaled.
H304	May be fatal if swallowed and enters airways.
H373	May cause damage to organs through prolonged or repeated exposure.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H335	May cause respiratory irritation.

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



EPOXY THINNER - Safety data sheet - september 2020 - n° batch 295-B0 - rev.1/17

H336 May cause drowsiness or dizziness.
EUH066 Repeated exposure may cause skin dryness or cracking.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EU) 1907/2006 (REACH) of the European Parliament
 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
 3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
 4. Regulation (EU) 2015/830 of the European Parliament
 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- The Merck Index. - 10th Edition
 - Handling Chemical Safety
 - INRS - Fiche Toxicologique (toxicological sheet)
 - Patty - Industrial Hygiene and Toxicology
 - N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
 - IFA GESTIS website
 - ECHA website
 - Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



EPOXY THINNER - Safety data sheet - september 2020 - n° batch 295-B0 - rev.1/17

Changes to previous review:

The following sections were modified:

01 / 02 / 03 / 04 / 06 / 07 / 08 / 09 / 10 / 11 / 12 / 14 / 15 / 16.