

## C-SYSTEMS ET108 component A

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : ET 108  
component A

UFI:  
VP20-MOTJ-Q00D-56JU

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the : Protective Coating  
Substance/Mixture

#### 1.3 Details of the supplier of the safety data sheet

Company Cecchi Gustavo & C. srl - Via M. Coppino 253,  
55049 Viareggio (LU) ITALY www.cecchi.it - info@cecchi.it

Information in case of emergency: +39 0584 383694 - info@cecchi.it

From monday to friday office hours 8:30 – 12:30, 14:00 – 18:30

---

### SECTION 2: Hazards identification



#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Chronic aquatic toxicity, Category 2	H411: Toxic to aquatic life with long lasting effects.

#### 2.2 Label elements

##### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms	:	 
Signal word	:	Warning
Hazard statements	:	H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H411 Toxic to aquatic life with long lasting effects.

Precautionary statements	<b>Prevention:</b>	
	P261	Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
	P273	Avoid release to the environment.
	P280	Wear protective gloves/ eye protection/ face protection.
	<b>Response:</b>	
	P333 + P313	If skin irritation or rash occurs: Get medical advice/ attention.
P337 + P313	If eye irritation persists: Get medical advice/ attention.	
P362 + P364	Take off contaminated clothing and wash it before reuse.	

Hazardous components which must be listed on the label:

bis[4-(2,3-epoxypropoxy)phenyl]propane  
 Reaction product of Epichlorohydrin/Bisphenol-A  
 1,6-bis(2,3-epoxypropoxy)hexane

**2.3 Other hazards**

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

**SECTION 3: Composition/information on ingredients**

**3.2 Mixtures**

Chemical nature : Modified epoxy resin

**Hazardous components**

Chemical name	CAS-No. EC-No. Registration number	Classification (REGULATION (EC) No 1272/2008)	Concentration (%)
bis[4-(2,3-epoxypropoxy)phenyl]propane	1675-54-3 216-823-5 01-2119456619-26	Eye Irrit.2; H319 Skin Irrit.2; H315 Skin Sens.1; H317 Aquatic Chronic2; H411	>= 50 - <= 100
Reaction product of Epichlorohydrin/Bisphenol-A	25036-25-3	Skin Irrit.2; H315 Eye Irrit.2; H319 Skin Sens.1; H317	>= 10 - < 12,5
1,6-bis(2,3-epoxypropoxy)hexane	933999-84-9 240-260-4 01-2119463471-41	Skin Irrit.2; H315 Eye Irrit.2; H319 Skin Sens.1; H317 Aquatic Chronic3; H412	>= 3 - < 5
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	2530-83-8 219-784-2 01-2119513212-58	Eye Dam.1; H318	>= 1 - < 3

For explanation of abbreviations see section 16.

---

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- General advice : Keep warm and in a quiet place.  
Show this safety data sheet to the doctor in attendance.  
Take off all contaminated clothing immediately.
- If inhaled : Move to fresh air.  
Keep patient warm and at rest.  
If unconscious, place in recovery position and seek medical advice.  
If symptoms persist, call a physician.  
If breathing is irregular or stopped, administer artificial respiration.
- In case of skin contact : Wash off immediately with soap and plenty of water.  
Do NOT use solvents or thinners.  
If on clothes, remove clothes.  
If skin irritation persists, call a physician.
- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids,  
for at least 15 minutes.  
If eye irritation persists, consult a specialist.  
If easy to do, remove contact lens, if worn.
- If swallowed : Keep at rest.  
Do not induce vomiting without medical advice.  
Keep respiratory tract clear.  
If symptoms persist, call a physician.

### 4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : irritant effects  
Redness  
sensitising effects

### 4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : The first aid procedure should be established in consultation  
with the doctor responsible for industrial medicine.

---

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

- Suitable extinguishing media : Foam  
Sand  
Carbon dioxide (CO<sub>2</sub>)  
Water mist



Unsuitable extinguishing media : Water spray jet

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : The pressure in sealed containers can increase under the influence of heat.  
Cool closed containers exposed to fire with water spray.

### 5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.  
Use personal protective equipment.

Further information : In the event of fire and/or explosion do not breathe fumes.  
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Immediately evacuate personnel to safe areas.  
Prevent fire extinguishing water from contaminating surface water or the ground water system.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Refer to protective measures listed in sections 7 and 8.  
Evacuate personnel to safe areas.  
Use personal protective equipment.  
Ensure adequate ventilation.  
Inform the responsible authorities in case of gas leakage, or of entry into waterways, soil or drains.

### 6.2 Environmental precautions

Environmental precautions : Do not allow uncontrolled discharge of product into the environment.  
Try to prevent the material from entering drains or water courses.  
Local authorities should be advised if significant spillages cannot be contained.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).  
Pick up and transfer to properly labelled containers.

**6.4 Reference to other sections**

For personal protection see section 8.

**SECTION 7: Handling and storage****7.1 Precautions for safe handling**

- Advice on safe handling : Provide sufficient air exchange and/or exhaust in work rooms. Avoid inhalation, ingestion and contact with skin and eyes. Wear personal protective equipment. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
- Advice on protection against fire and explosion : Keep away from open flames, hot surfaces and sources of ignition.
- Hygiene measures : Provide adequate ventilation. Wash hands and face before breaks and immediately after handling the product.

**7.2 Conditions for safe storage, including any incompatibilities**

- Requirements for storage areas and containers : Keep containers tightly closed in a dry, cool and well-ventilated place. Keep in properly labelled containers.
- Advice on common storage : Keep away from oxidizing agents, strongly acid or alkaline materials and amines. Keep product and empty container away from heat and sources of ignition. Keep away from food and drink.
- Other data : Stable at normal ambient temperature and pressure.

**7.3 Specific end use(s)**

- Specific use(s) : Consult the technical guidelines for the use of this substance/mixture.

**SECTION 8: Exposure controls/personal protection****8.1 Control parameters****Occupational Exposure Limits**

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Silica, amorphous, fumed, cryst.-free	112945-52-5	TWA (inhalable dust)	6 mg/m <sup>3</sup> (Silica)	GB EH40
Further information	For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/3 General methods for sampling and gravimetric analysis of respirable and inhalable dust, The COSHH definition of a substance hazardous to health includes dust of any			



	<p>kind when present at a concentration in air equal to or greater than 10 mg.m-3 8-hour TWA of inhalable dust or 4 mg.m-3 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limit., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/3., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure should be used</p>			
	<table border="1"> <tr> <td data-bbox="583 854 827 911">TWA (Respirable dust)</td> <td data-bbox="831 854 1166 911">2,4 mg/m3 (Silica)</td> <td data-bbox="1170 854 1349 911">GB EH40</td> </tr> </table>	TWA (Respirable dust)	2,4 mg/m3 (Silica)	GB EH40
TWA (Respirable dust)	2,4 mg/m3 (Silica)	GB EH40		
Further information	<p>For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/3 General methods for sampling and gravimetric analysis of respirable and inhalable dust, The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m-3 8-hour TWA of inhalable dust or 4 mg.m-3 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limit., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/3., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure should be used</p>			

**Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:**

- |                                       |                                                                                                                                                     |
|---------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------|
| 1,6-bis(2,3-epoxypropoxy)hexane       | : End Use: Workers<br>Exposure routes: Skin contact<br>Potential health effects: Long-term systemic effects<br>Value: 2,8 mg/kg<br>End Use: Workers |
|                                       | Exposure routes: Inhalation<br>Potential health effects: Long-term systemic effects<br>Value: 4,9 mg/m3                                             |
| Silica, amorphous, fumed, cryst.-free | : End Use: Workers<br>Exposure routes: Inhalation<br>Potential health effects: Long-term local effects                                              |

[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Value: 4 mg/m <sup>3</sup> : End Use: Workers Exposure routes: Skin contact Potential health effects: Acute systemic effects Value: 21 mg/kg Exposure routes: Inhalation Potential health effects: Acute systemic effects Value: 147 mg/m <sup>3</sup> End Use: Workers Potential health effects: Long-term systemic effects Value: 21 mg/kg End Use: Workers Potential health effects: Long-term systemic effects Value: 147 mg/m <sup>3</sup>
----------------------------------------------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

**Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:**

1,6-bis(2,3-epoxypropoxy)hexane	: Sewage treatment plant Value: 1 mg/l Fresh water Value: 0,0115 mg/l Fresh water sediment Value: 0,283 mg/kg Marine water Value: 0,00115 mg/l Marine sediment Value: 0,0283 mg/kg Soil Value: 0,223 mg/kg
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	: Sewage treatment plant Value: 10 mg/l Fresh water Value: 1 mg/l Marine water Value: 0,1 mg/l Intermittent releases Value: 1 mg/l Fresh water sediment Value: 0,79 mg/kg Soil Value: 0,13 mg/kg

**8.2 Exposure controls****Engineering measures**

Effective exhaust ventilation system  
 effective ventilation in all processing areas

**Personal protective equipment**

Eye protection	: Do not wear contact lenses. Safety glasses with side-shields conforming to EN166 Ensure that eyewash stations and safety showers are close to the workstation location.
----------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Hand protection Material	: Protective gloves complying with EN 374.
-----------------------------	--------------------------------------------



Skin and body protection	: Protective suit
Respiratory protection	: Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. In the case of vapour formation use a respirator with an approved filter. Respirator with a vapour filter (EN 141) Apply technical measures to comply with the occupational exposure limits. This should be achieved by a good general extraction and -if practically feasible- by the use of a local exhaust ventilation.
Protective measures	: Avoid contact with skin. Wear suitable protective equipment.

---

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Appearance	: liquid
Colour	: light yellow
Odour	: slight
Odour Threshold	: not determined
pH	: not determined
Melting point/freezing point	: Not applicable
Boiling point/boiling range	: > 200 °C
Flash point	: 150 °C
Evaporation rate	: not determined
Upper explosion limit	: Not applicable
Lower explosion limit	: Not applicable
Vapour pressure	: Not applicable
Relative vapour density	: not determined
Density	: 1,17 g/cm <sup>3</sup> (25 °C)
Bulk density	: not determined
Solubility(ies) Solubility in other solvents	: not determined





Partition coefficient: n-octanol/water	:	No data available
Ignition temperature	:	Not applicable
Auto-ignition temperature	:	Not applicable
Thermal decomposition	:	Method: No data available
Viscosity		
Viscosity, dynamic	:	140.000 - 210.000 mPa.s (25 °C)
Viscosity, kinematic	:	not determined
Explosive properties	:	Not applicable
Oxidizing properties	:	Not applicable

**9.2 Other information**

Surface tension	:	not determined
Sublimation point	:	Not applicable

---

**SECTION 10: Stability and reactivity****10.1 Reactivity**

Stable under recommended storage conditions.

**10.2 Chemical stability**

No decomposition if stored and applied as directed.

**10.3 Possibility of hazardous reactions**

Hazardous reactions	:	Reacts with the following substances: Bases Strong oxidizing agents Avoid amines.
---------------------	---	--------------------------------------------------------------------------------------------

**10.4 Conditions to avoid**

Conditions to avoid	:	No decomposition if used as directed.
---------------------	---	---------------------------------------

**10.5 Incompatible materials**

Materials to avoid	:	Incompatible with oxidizing agents.
--------------------	---	-------------------------------------

**10.6 Hazardous decomposition products**

## CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



C-SYSTEMS ET108 component A - SAFETY DATA SHEET january 2021 - batch n° 035-Bi - rev.1/18

Hazardous decomposition products : This product may release the following:  
Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

---

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Acute toxicity

##### Product:

Acute oral toxicity : Remarks: No data available

##### Components:

##### **1,6-bis(2,3-epoxypropoxy)hexane:**

Acute oral toxicity : LD50 (Rat): 2.900 mg/kg  
Method: OECD Test Guideline 401  
GLP: yes

Acute dermal toxicity : LD50 (Rabbit): > 2.000 mg/kg  
Method: OECD Test Guideline 402  
GLP: yes

##### **[3-(2,3-epoxypropoxy)propyl]trimethoxysilane:**

Acute inhalation toxicity : LC50 (Rat, male and female): > 5,3 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: OECD Test Guideline 403  
GLP: yes

Acute dermal toxicity : LD50 (Rabbit, male): 4.250 mg/kg  
Method: OECD Test Guideline 402

#### Skin corrosion/irritation

##### Product:

Remarks: No data available

##### Components:

##### **[3-(2,3-epoxypropoxy)propyl]trimethoxysilane:**

Species: Rabbit  
Method: OECD Test Guideline 404  
Result: No skin irritation

#### Serious eye damage/eye irritation

##### Product:

Remarks: No data available

##### Components:



**[3-(2,3-epoxypropoxy)propyl]trimethoxysilane:**

Species: Rabbit

Method: OECD Test Guideline 405

Result: Risk of serious damage to eyes.

**Respiratory or skin sensitisation**

**Product:**

Remarks: No data available

**Components:**

**[1,6-bis(2,3-epoxypropoxy)hexane]:**

Test Type: Mouse Local Lymph Node assay (LLNA)

Exposure routes: Dermal

Species: Mouse

Method: OECD Test Guideline 429

Result: May cause sensitisation by skin contact.

GLP: yes

**[3-(2,3-epoxypropoxy)propyl]trimethoxysilane:**

Test Type: Buehler Test

Species: Guinea pig

Method: OECD Test Guideline 406

Result: Does not cause skin sensitisation.

GLP: yes

**Germ cell mutagenicity**

**Carcinogenicity**

**Reproductive toxicity**

**STOT - single exposure**

**Product:**

Remarks: Not applicable

**STOT - repeated exposure**

**Repeated dose toxicity**

**Product:**

Remarks: No data available

**Aspiration toxicity**

**Further information**

**Product:**

Remarks: No data available

## SECTION 12: Ecological information

### 12.1 Toxicity

**Product:**

Toxicity to fish : Remarks: No data available

Toxicity to daphnia and other aquatic invertebrates : Remarks: No data available

**Components:****1,6-bis(2,3-epoxypropoxy)hexane:**Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 30 mg/l  
Exposure time: 96 h  
Test Type: semi-static test  
Method: OECD Test Guideline 203  
GLP: yesToxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 39 mg/l  
Exposure time: 48 h  
Test Type: static test  
Method: OECD Test Guideline 202  
GLP: yes**[3-(2,3-epoxypropoxy)propyl]trimethoxysilane:**Toxicity to fish : LC50 (Cyprinus carpio (Carp)): 55 mg/l  
Exposure time: 96 h  
Test Type: semi-static test  
Method: Directive 67/548/EEC, Annex V, C.1.Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: > 100 mg/l  
Exposure time: 21 d  
Species: Daphnia magna (Water flea)  
Test Type: semi-static test  
Method: OECD Test Guideline 211  
GLP: yes

### 12.2 Persistence and degradability.

**Product:**

Biodegradability : Remarks: No data available

**Components:****1,6-bis(2,3-epoxypropoxy)hexane:**Biodegradability : Test Type: aerobic  
Result: Inherently biodegradable.  
Method: OECD Test Guideline 301D  
GLP: yes**[3-(2,3-epoxypropoxy)propyl]trimethoxysilane:**

## CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



C-SYSTEMS ET108 component A - SAFETY DATA SHEET january 2021 - batch n° 035-Bi - rev.1/18

Biodegradability : Test Type: aerobic

Result: Not readily biodegradable.

Method: Directive 67/548/EEC Annex V, C.4.A.

GLP: yes

### 12.3 Bioaccumulative potential

#### Product:

Bioaccumulation : Remarks: No data available

#### Components:

##### **1,6-bis(2,3-epoxypropoxy)hexane:**

Partition coefficient: n-octanol/water : log Pow: 0,822 (20 °C)  
pH: 6 - 8  
Method: OECD Test Guideline 107  
GLP: yes

### 12.4 Mobility in soil

#### Components:

##### **1,6-bis(2,3-epoxypropoxy)hexane:**

Distribution among environmental compartments : log Koc: 2,98  
Method: OECD Test Guideline 121

### 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

### 12.6 Other adverse effects

#### Product:

Additional ecological information : Remarks: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : In accordance with local and national regulations.  
Container hazardous when empty.  
Do not dispose of with domestic refuse.  
Do not mix waste streams during collection.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.

**SECTION 14: Transport information****14.1 UN number**

**ADR/RID/ADN** : UN 3082  
**IMDG** : UN 3082  
**IATA** : UN 3082

**14.2 UN proper shipping name**

**ADR/RID/ADN** : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,  
N.O.S.  
(bis[4-(2,3-epoxypropoxy)phenyl]propane)  
**IMDG** : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,  
N.O.S.  
(bis[4-(2,3-epoxypropoxy)phenyl]propane)  
**IATA** : Environmentally hazardous substance, liquid, n.o.s.  
(bis[4-(2,3-epoxypropoxy)phenyl]propane)

**14.3 Transport hazard class(es)**

**ADR/RID/ADN** : 9  
**IMDG** : 9  
**IATA** : 9

**14.4 Packing group**

**ADR/RID/ADN**  
Packing group : III  
Classification Code : M6  
Hazard Identification Number : 90  
Labels : 9  
Remarks : ADR: These substances when carried in single or combination packagings containing a net quantity per single or inner packaging of 5 l or less for liquids or having a net mass per single or inner packaging of 5 kg or less for solids, are not subject to any other provisions of ADR provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

**IMDG**

Packing group : III  
Labels : 9  
EmS Code : F-A, S-F  
Remarks : IMDG: Marine pollutants packaged in single or combination packagings containing a net quantity per single or inner packaging of 5 l or less for liquids or having a net mass per single or inner packaging of 5 kg or less for solids are not subject to any other provisions of this Code relevant to marine pollutants provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8. In the case of marine pollutants also meeting the criteria for inclusion in

## CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



C-SYSTEMS ET108 component A - SAFETY DATA SHEET january 2021 - batch n° 035-Bi - rev.1/18

another hazard class all provisions of this Code relevant to any additional hazards continue to apply.

### IATA

- Packing instruction (cargo aircraft) : 964  
Packing instruction (passenger aircraft) : 964  
Packing group : III  
Labels : 9  
Remarks : IATA: These substances when transported in single or combination packagings containing a net quantity per single or inner packaging of 5 L or less for liquids or having a net mass of 5 kg or less for solids, are not subject to any other provisions of these Regulations provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.

### 14.5 Environmental hazards

#### ADR/RID/ADN

Environmentally hazardous : yes

#### IMDG

Marine pollutant : yes

#### IATA

Environmentally hazardous : yes

### 14.6 Special precautions for user

Remarks : The transport of dangerous goods, including their loading and unloading, must be done by people who received the necessary training required by Modal Regulations.

### 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

---

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Not applicable

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57).

## CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



C-SYSTEMS ET108 component A - SAFETY DATA SHEET january 2021 - batch n° 035-Bi - rev.1/18

REACH - List of substances subject to authorisation : Not applicable  
(Annex XIV)

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

		Quantity 1	Quantity 2
E2	ENVIRONMENTAL HAZARDS	200 t	500 t

### 15.2 Chemical safety assessment

Not applicable

---

### SECTION 16: Other information

#### Full text of H-Statements

H315 : Causes skin irritation.  
H317 : May cause an allergic skin reaction.  
H318 : Causes serious eye damage.  
H319 : Causes serious eye irritation.  
H411 : Toxic to aquatic life with long lasting effects.  
H412 : Harmful to aquatic life with long lasting effects.

#### Full text of other abbreviations

Aquatic Chronic : Chronic aquatic toxicity  
Eye Dam. : Serious eye damage  
Eye Irrit. : Eye irritation  
Skin Irrit. : Skin irritation  
Skin Sens. : Skin sensitisation

#### Further information

Training advice : Provide adequate information, instruction and training for operators.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.