

C-SYSTEMS GELCOAT LIGHT component B

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Relevant identified uses of the substance or mixture and uses advised against

Trade name: **C-SYSTEMS GELCOAT LIGHT component B**

UFI: NG40-809W-400S-2CT6

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture: Resin for Casting

1.3 Details of the supplier of the safety data sheet

Company Cecchi Gustavo & C. srl - Via M. Coppino 253,
55049 Viareggio (LU) ITALY www.cecchi.it - info@cecchi.it

Information in case of emergency: +39 0584 383694 - info@cecchi.it

From monday to friday office hours 8:30 – 12:30, 14:00 – 18:30

1,4 Emergency telephone number

+39 0584 383694 (8,30 -12,30 / 14,00 - 18,00 h)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Skin corrosion, Category 1B	H314: Causes severe skin burns and eye damage.
Serious eye damage, Category 1	H318: Causes serious eye damage.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Long-term (chronic) aquatic hazard, Category 2	H411: Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements : H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



C-SYSTEMS GELCOAT LIGHT comp. B - SAFETY DATA SHEET - february 2021 - n° batch 034-Bi - rev.1/21

	H411	Toxic to aquatic life with long lasting effects.
Supplemental Hazard Statements	: EUH071	Corrosive to the respiratory tract.
Precautionary statements	: Prevention:	
	P261	Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
	P273	Avoid release to the environment.
	P280	Wear protective gloves/ protective clothing/ eye protection/ face protection.
	Response:	
	P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
	P304 + P340 + P310	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/ doctor.
	P305 + P351 + P338 + P310	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.

Hazardous components which must be listed on the label:

4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with m-phenylenebis(methylamine)

m-phenylenebis(methylamine)

3-aminomethyl-3,5,5-trimethylcyclohexylamine

Phenol, styrenated

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Cycloaliphatic amine based mixture

Hazardous components

Chemical name	CAS-No. EC-No./List Registration number	Classification (REGULATION (EC) No	Concentration (%)

		1272/2008)	
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with m-phenylenebis(methylamine)	113930-69-1 01-2119965162-39	Eye Dam.1; H318 Skin Corr.1B; H314 Skin Sens.1; H317 Aquatic Chronic2; H401	>= 50 - <= 100
m-phenylenebis(methylamine)	1477-55-0 216-032-5 01-2119480150-50	Acute Tox.4; H302 Acute Tox.4; H332 Skin Corr.1B; H314 Skin Sens.1B; H317 Aquatic Chronic3; H412	>= 7 - < 10
3-aminomethyl-3,5,5-trimethylcyclohexylamine	2855-13-2 220-666-8 01-2119514687-32	Acute Tox.4; H302 Acute Tox.4; H312 Skin Corr.1B; H314 Eye Dam.1; H318 Skin Sens.1; H317 Aquatic Chronic3; H412	>= 7 - < 10
Phenol, styrenated	61788-44-1 262-975-0 01-2119980970-27	Skin Irrit.2; H315 Skin Sens.1; H317 Aquatic Chronic2; H411	>= 5 - < 7

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Show this safety data sheet to the doctor in attendance.
Keep warm and in a quiet place.
Take off all contaminated clothing immediately.
- If inhaled : Move to fresh air.
Keep patient warm and at rest.
If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
If breathing is irregular or stopped, administer artificial respiration.
- In case of skin contact : Wash off immediately with soap and plenty of water.
Do NOT use solvents or thinners.
If on clothes, remove clothes.
Burns must be treated by a physician.
- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
If eye irritation persists, consult a specialist.
If easy to do, remove contact lens, if worn.



If swallowed : Do NOT induce vomiting.
If a person vomits when lying on his back, place him in the recovery position.
Call a physician immediately.
Give small amounts of water to drink.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Burn
superficial burning sensation
Redness
Severe irritation

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : The first aid procedure should be established in consultation with the doctor responsible for industrial medicine.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Carbon dioxide (CO₂)
Foam
Dry powder
Water mist

Unsuitable extinguishing media : None known.

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : The pressure in sealed containers can increase under the influence of heat.
Cool closed containers exposed to fire with water spray.
Hazardous decomposition products formed under fire conditions.

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.

Further information : In the event of fire and/or explosion do not breathe fumes.
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Immediately evacuate personnel to safe areas.
Prevent fire extinguishing water from contaminating surface water or the ground water system.



SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Refer to protective measures listed in sections 7 and 8.
Evacuate personnel to safe areas.
Use personal protective equipment.
Ensure adequate ventilation.
Inform the responsible authorities in case of gas leakage, or of entry into waterways, soil or drains.

6.2 Environmental precautions

Environmental precautions : Do not allow uncontrolled discharge of product into the environment.
Try to prevent the material from entering drains or water courses.
Local authorities should be advised if significant spillages cannot be contained.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).
Pick up and transfer to properly labelled containers.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Provide sufficient air exchange and/or exhaust in work rooms.
Do not breathe vapours or spray mist.
Avoid inhalation, ingestion and contact with skin and eyes.
Wear personal protective equipment.
Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

Advice on protection against fire and explosion : Keep away from open flames, hot surfaces and sources of ignition.

Hygiene measures : Provide adequate ventilation. Wash hands and face before breaks and immediately after handling the product.

**7.2 Conditions for safe storage, including any incompatibilities**

Requirements for storage areas and containers	: Keep containers tightly closed in a dry, cool and well-ventilated place. Keep in properly labelled containers. To maintain product quality, do not store in heat or direct sunlight.
Further information on storage conditions	: Protect from moisture.
Advice on common storage	: Keep away from isocyanates. Do not store near acids. Keep away from oxidizing agents.
Other data	: Stable at normal ambient temperature and pressure.

7.3 Specific end use(s)

Specific use(s)	: Consult the technical guidelines for the use of this substance/mixture.
-----------------	---

SECTION 8: Exposure controls/personal protection**8.1 Control parameters**

Contains no substances with occupational exposure limit values.

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

3-aminomethyl-3,5,5-trimethylcyclohexylamine	: Fresh water
	Value: 0,06 mg/l
	Marine water
	Value: 0,006 mg/l
	Intermittent releases
	Value: 0,23 mg/l
	Fresh water sediment
	Value: 5,784 mg/kg
	Marine sediment
	Value: 0,578 mg/kg
Sewage treatment plant	
Value: 3,18 mg/l	
Soil	
Value: 1,121 mg/kg	

8.2 Exposure controls**Engineering measures**

Effective exhaust ventilation system
effective ventilation in all processing areas

Personal protective equipment

Eye protection : Safety glasses with side-shields conforming to EN166
Do not wear contact lenses.
Ensure that eyewash stations and safety showers are close to the workstation location.

Hand protection

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



C-SYSTEMS GELCOAT LIGHT comp. B - SAFETY DATA SHEET - february 2021 - n° batch 034-Bi - rev.1/21

Material	: Protective gloves complying with EN 374.
Remarks	: Nitrile rubber
Skin and body protection	: Protective suit Recommended preventive skin protection
Respiratory protection	: Use respirator when performing operations involving potential exposure to vapour of the product. The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used. Recommended Filter type: ABEK-filter Equipment should conform to EN 14387
Protective measures	: Avoid contact with skin. Wear suitable protective equipment.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	: liquid
Colour	: colourless
Odour	: amine-like
Odour Threshold	: not determined
pH	: 11, 1 %
Melting point/freezing point	: Not applicable
Initial boiling point	: 180 °C
Flash point	: 130 °C
Evaporation rate	: not determined
Upper explosion limit	: Not applicable
Lower explosion limit	: Not applicable
Vapour pressure	: Not applicable
Relative vapour density	: not determined
Density	: not determined
Bulk density	: not determined

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



C-SYSTEMS GELCOAT LIGHT comp. B - SAFETY DATA SHEET - february 2021 - n° batch 034-Bi - rev.1/21

Solubility(ies)

Solubility in other solvents : not determined

Partition coefficient: n-
octanol/water : No data available

Ignition temperature : Not applicable

Auto-ignition temperature : Not applicable

Thermal decomposition : Method: No data available

Viscosity

Viscosity, dynamic : 2.000 - 4.000 mPa.s (25 °C)

Viscosity, kinematic : not determined

Explosive properties : Not applicable

Oxidizing properties : Not applicable

9.2 Other information

Surface tension : not determined

Sublimation point : Not applicable

SECTION 10: Stability and reactivity

10.1 Reactivity

Stable under recommended storage conditions.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Reacts with the following substances:
Acids
Strong oxidizing agents

10.4 Conditions to avoid

Conditions to avoid : No decomposition if used as directed.

10.5 Incompatible materials

Materials to avoid : Strong acids
Strong oxidizing agents

**10.6 Hazardous decomposition products**

Hazardous decomposition products : This product may release the following:
Nitrogen oxides (NO_x)
Carbon monoxide
Carbon dioxide (CO₂)

SECTION 11: Toxicological information**11.1 Information on toxicological effects****Acute toxicity****Product:**

Acute oral toxicity : Acute toxicity estimate : > 2.000 mg/kg
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate : > 20 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : > 2.000 mg/kg
Method: Calculation method

Acute toxicity (other routes of administration) :
Remarks: No data available

Skin corrosion/irritation**Product:**

Remarks: No data available

Serious eye damage/eye irritation**Product:**

Remarks: No data available

Respiratory or skin sensitisation**Product:**

Remarks: No data available

Germ cell mutagenicity**Carcinogenicity****Product:**

Remarks: No data available

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



C-SYSTEMS GELCOAT LIGHT comp. B - SAFETY DATA SHEET - february 2021 - n° batch 034-Bi - rev.1/21

Reproductive toxicity

Product:

Effects on fertility : Remarks: No data available
Remarks: No data available

Effects on foetal development : Remarks: No data available
Remarks: No data available

STOT - single exposure

STOT - repeated exposure

Repeated dose toxicity

Product:

Remarks: No data available

Aspiration toxicity

Components:

3-aminomethyl-3,5,5-trimethylcyclohexylamine:

No aspiration toxicity classification

Further information

Product:

Remarks: No data available

SECTION 12: Ecological information

12.1 Toxicity

Product:

Toxicity to fish : Remarks: No data available

Toxicity to daphnia and other aquatic invertebrates : Remarks: No data available

Components:

3-aminomethyl-3,5,5-trimethylcyclohexylamine:

Toxicity to fish : LC50 (Leuciscus idus (Golden orfe)): 110 mg/l
Exposure time: 96 h
Test Type: semi-static test
Method: Directive 67/548/EEC, Annex V, C.1.
GLP: yes

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 23 mg/l
Exposure time: 48 h

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



C-SYSTEMS GELCOAT LIGHT comp. B - SAFETY DATA SHEET - february 2021 - n° batch 034-Bi - rev.1/21

Test Type: static test
Method: OECD Test Guideline 202
GLP: yes

Toxicity to algae : ErC50 (Scenedesmus capricornutum (fresh water algae)): > 50 mg/l
Exposure time: 72 h
Test Type: static test
Method: Directive 67/548/EEC, Annex V, C.3.
GLP: yes

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 3 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Test Type: semi-static test
GLP: yes

12.2 Persistence and degradability

Product:

Biodegradability : Remarks: No data available

Physico-chemical removability : Remarks: No data available

Components:

3-aminomethyl-3,5,5-trimethylcyclohexylamine:

Biodegradability : Test Type: aerobic
Result: Not readily biodegradable.
Method: Directive 67/548/EEC Annex V, C.4.A.
GLP: yes

12.3 Bioaccumulative potential

Product:

Bioaccumulation : Remarks: No data available

Components:

3-aminomethyl-3,5,5-trimethylcyclohexylamine:

Partition coefficient: n-octanol/water : log Pow: 0,99
Method: OECD Test Guideline 107
GLP: yes

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



C-SYSTEMS GELCOAT LIGHT comp. B - SAFETY DATA SHEET - february 2021 - n° batch 034-Bi - rev.1/21

very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Other adverse effects

Product:

Additional ecological information

: Remarks: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

: In accordance with local and national regulations.
Container hazardous when empty.
Do not dispose of with domestic refuse.
Do not mix waste streams during collection.

Contaminated packaging

: Empty containers should be taken to an approved waste handling site for recycling or disposal.

SECTION 14: Transport information

14.1 UN number

ADR/RID/ADN : UN 2735

IMDG : UN 2735

IATA : UN 2735

14.2 UN proper shipping name

ADR/RID/ADN : AMINES, LIQUID, CORROSIVE, N.O.S.
(Reaction Product of BADGE with MXDA)

IMDG : AMINES, LIQUID, CORROSIVE, N.O.S.
(Reaction Product of BADGE with MXDA)

IATA : Amines, liquid, corrosive, n.o.s.
(Reaction Product of BADGE with MXDA)

14.3 Transport hazard class(es)

ADR/RID/ADN : 8

IMDG : 8

IATA : 8

14.4 Packing group

ADR/RID/ADN

Packing group : II

Classification Code : C7

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



C-SYSTEMS GELCOAT LIGHT comp. B - SAFETY DATA SHEET - february 2021 - n° batch 034-Bi - rev.1/21

Hazard Identification Number : 80
Labels : 8
Tunnel restriction code : E

IMDG

Packing group : II
Labels : 8
EmS Code : F-A, S-B
Remarks : IMDG Code segregation group 18 - Alkalis

IATA

Packing instruction (cargo aircraft) : 855
Packing instruction (passenger aircraft) : 851
Packing group : II
Labels : 8

14.5 Environmental hazards

ADR/RID/ADN

Environmentally hazardous : yes

IMDG

Marine pollutant : yes

IATA

Environmentally hazardous : yes

14.6 Special precautions for user

Remarks : The transport of dangerous goods, including their loading and unloading, must be done by people who received the necessary training required by Modal Regulations.

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Not applicable

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57).

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable



Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

E2	ENVIRONMENTAL HAZARDS	Quantity 1 200 t	Quantity 2 500 t
----	-----------------------	---------------------	---------------------

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: 0 %

15.2 Chemical safety assessment

Not applicable

SECTION 16: Other information

Items where relevant changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

Full text of H-Statements

H302 : Harmful if swallowed.
 H312 : Harmful in contact with skin.
 H314 : Causes severe skin burns and eye damage.
 H315 : Causes skin irritation.
 H317 : May cause an allergic skin reaction.
 H318 : Causes serious eye damage.
 H332 : Harmful if inhaled.
 H401 : Toxic to aquatic life.
 H411 : Toxic to aquatic life with long lasting effects.
 H412 : Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox. : Acute toxicity
 Aquatic Chronic : Long-term (chronic) aquatic hazard
 Eye Dam. : Serious eye damage
 Skin Corr. : Skin corrosion
 Skin Irrit. : Skin irritation
 Skin Sens. : Skin sensitisation

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



C-SYSTEMS GELCOAT LIGHT comp. B - SAFETY DATA SHEET - february 2021 - n° batch 034-Bi - rev.1/21

Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Training advice : Provide adequate information, instruction and training for operators.

Classification of the mixture:

Skin Corr. 1B	H314
Eye Dam. 1	H318
Skin Sens. 1	H317
Aquatic Chronic 2	H411

Classification procedure:

Calculation method
Calculation method
Calculation method
Calculation method

The information contained herein is based on the present state of our knowledge and does therefore not guarantee certain properties.

GB / EN