

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS EPOXY PRIMER BLUE Component A – SAFETY DATA SHEET - february 2021 - n°batch 027-BA - rev. 1/2021

Safety data sheet

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name

NAUTILUS EPOXY PRIMER BLUE Component A

Chemical name and synonym

PRODOTTO VERNICIANTE A BASE DI RESINE EPOSSIDICHE p.m.> 700 <1100

UFI:

EA50-A06V-600Q-PSMU

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use

PITTURE VERNICI MARINE.

Identified Uses	Industrial	Professional	Consumer
Prodotto verniciante per nautica outdoor	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Prodotto verniciante per usi industriali	<input checked="" type="checkbox"/>	-	-
Prodotto verniciante per nautica indoor	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Prodotto verniciante per uso professionale	-	<input checked="" type="checkbox"/>	-
Prodotto verniciante per macchine agricole e movimento terra	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>

1.3 Details of the supplier of the safety data sheet Manufacturer/Supplier:

Cecchi Gustavo & C. srl - Via M. Coppino 253,

55049 Viareggio (LU) ITALY www.cecchi.it - info@cecchi.it

1.4 Emergency telephone number:

+39 0584/383694 - info@cecchi.it

From monday to friday office hours 8:30 - 12:30, 14:00 - 18:30

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2015/830. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Flammable liquid, category 2

H225

Highly flammable liquid and vapour.

Serious eye damage, category 1

H318

Causes serious eye damage.

Skin irritation, category 2

H315

Causes skin irritation.

Specific target organ toxicity - single exposure, category 3

H335

May cause respiratory irritation.

Skin sensitization, category 1

H317

May cause an allergic skin reaction.

Hazardous to the aquatic environment, chronic toxicity, category 2

H411

Toxic to aquatic life with long lasting effects.

2.2. Label elements

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS EPOXY PRIMER BLUE Component A – SAFETY DATA SHEET - february 2021 - n°batch 027-BA - rev. 1/2021

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words:

Danger

Hazard statements:

H225	Highly flammable liquid and vapour.
H318	Causes serious eye damage.
H315	Causes skin irritation.
H335	May cause respiratory irritation.
H317	May cause an allergic skin reaction.
H411	Toxic to aquatic life with long lasting effects.

Precautionary statements:

P501	Dispose of contents / container to . . .
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P280	Wear protective gloves/ protective clothing / eye protection / face protection.
P310	Immediately call a POISON CENTER / doctor / . . .

Contains:	ISOBUTYL ALCOHOL RESINA EPOSSIDICA (BISFENOLO A EPICLORIDRINA) p.m. > 700 PRODOTTO DI REAZIONE: BISFENOLO-A-EPICLORIDRINA; RESINE EPOSSIDICHE (PESO MOLECOLARE MEDIO >1100) XYLENE (MIXTURE OF ISOMERS)
------------------	--

Product not intended for uses provided for by Dir. 2004/42/CE.

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

SECTION 3. Composition/information on ingredients

3.2. Mixtures

Contains:

Identification	x = Conc. %	Classification 1272/2008 (CLP)
BARIUM SULFATE		
CAS 7727-43-7	$25 \leq x < 30$	

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS EPOXY PRIMER BLUE Component A – SAFETY DATA SHEET - february 2021 - n°batch 027-BA - rev. 1/2021

EC 231-784-4

INDEX -

Reg. no. 01-2119491274-35-0024

RESINA EPOSSIDICA (BISFENOLO A EPICLORIDRINA)

p.m. > 700

CAS 25036-25-3 16 ≤ x < 19 Eye Irrit. 2 H319, Skin Irrit. 2 H315, Skin Sens. 1 H317

EC

INDEX -

XYLENE (MIXTURE OF ISOMERS)

CAS 1330-20-7 8 ≤ x < 9 Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Asp. Tox. 1 H304,
STOT RE 2 H373, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335,
Aquatic Chronic 3 H412, Classification note according to Annex VI to the CLP
Regulation: C

EC 215-535-7

INDEX 601-022-00-9

Reg. no. 01-2119488216-32-XXXX

ISOBUTYL ALCOHOL

CAS 78-83-1 5 ≤ x < 6 Flam. Liq. 3 H226, Eye Dam. 1 H318, Skin Irrit. 2 H315, STOT SE 3 H335,
STOT SE 3 H336

EC 201-148-0

INDEX 603-108-00-1

Reg. no. 01-2119484609-23

TALC

CAS 14807-96-6 5 ≤ x < 6

EC 238-877-9

INDEX -

REAZIONE DI MASSA DELL'ETILBENZENE E DELLO XILENE

CAS - 5 ≤ x < 6 Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Asp. Tox. 1 H304,
STOT RE 2 H373, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335,
Classification note according to Annex VI to the CLP Regulation: C

EC 905-588-0

INDEX -

Reg. no. 01-2119488216-32-XXXX

1-METOSI-2-PROPANOLO

CAS 107-98-2 4 ≤ x < 5 Flam. Liq. 3 H226, STOT SE 3 H336

EC 203-539-1

INDEX 603-064-00-3

Reg. no. 01-2119457435-35

METILETILCHETONE

CAS 78-93-3 4 ≤ x < 5 Flam. Liq. 2 H225, Eye Irrit. 2 H319, STOT SE 3 H336, EUH066

EC 201-159-0

INDEX 606-002-00-3

Reg. no. 01-2119457290-43

PRODOTTO DI REAZIONE: BISFENOLO-A- EPICLORIDRINA; RESINE EPOSSIDICHE (PESO MOLECOLARE MEDIO >1100)

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it

**NAUTILUS EPOXY PRIMER BLUE Component A** – SAFETY DATA SHEET - february 2021 - n°batch 027-BA - rev. 1/2021

CAS 25068-38-6 3 ≤ x < 4 Eye Irrit. 2 H319, Skin Irrit. 2 H315, Skin Sens. 1B H317, Aquatic Chronic 2 H411

EC 500-033-5

INDEX 603-074-00-8

Reg. no. 01-2119456619-26-XXXX

METILISOBUTILCHETONE

CAS 108-10-1 3 ≤ x < 4 Flam. Liq. 2 H225, Acute Tox. 4 H332, Eye Irrit. 2 H319, STOT SE 3 H335, EUH066

EC 203-550-1

INDEX 606-004-00-4

Reg. no. 01-2119473980-30

FOSFATO IDRATO DI ZINCO**ALLUMINIO**

CAS 7779-90-0 2,5 ≤ x < 3,5 Aquatic Acute 1 H400 M=1, Aquatic Chronic 1 H410 M=1

EC 231-944-3

INDEX 030-011-00-6

Reg. no. 01-2119485044-40-XXXX

TITANIUM DIOXIDE

CAS 13463-67-7 1 ≤ x < 2

EC 236-675-5

INDEX -

Reg. no. 01-2119489379-17-XXXX

N-BUTYL ACETATE

CAS 123-86-4 0,1 ≤ x < 0,4 Flam. Liq. 3 H226, STOT SE 3 H336, EUH066

EC 204-658-1

INDEX 607-025-00-1

Reg. no. 01-2119485493-29-XXXX

4-HYDROXY-4-METHYLPENTAN-2-ONE

CAS 123-42-2 0,1 ≤ x < 0,4 Flam. Liq. 3 H226, Repr. 2 H361, Eye Irrit. 2 H319, STOT SE 3 H335

EC 204-626-7

INDEX 603-016-00-1

Reg. no. 01-2119473975-21-XXXX
2119473975-21**Oleic acid, compound with (Z)-N-octadec-9-enylpropane-1,3-diamine (2:1)**

CAS 34140-91-5 0,1 ≤ x < 0,4 STOT RE 2 H373, Eye Irrit. 2 H319, Skin Irrit. 2 H315, Aquatic Acute 1 H400 M=1, Aquatic Chronic 2 H411

EC 251-846-4

INDEX -

ACETATO DI 1-METIL-2-METOSSETILE

CAS 108-65-6 0 ≤ x < 0,05 Flam. Liq. 3 H226, STOT SE 3 H336

EC 203-603-9

INDEX 607-195-00-7

Reg. no. 01-2119475791-29-XXXX

QUARTZ

CAS 14808-60-7 0 ≤ x < 0,05 Substance with a community workplace exposure limit.

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS EPOXY PRIMER BLUE Component A – SAFETY DATA SHEET - february 2021 - n°batch 027-BA - rev. 1/2021

EC 238-878-4

INDEX -

FORMALDEHYDE

CAS 50-00-0

$0 \leq x < 0,05$

Carc. 1B H350, Muta. 2 H341, Acute Tox. 3 H301, Acute Tox. 3 H311, Skin Corr. 1B H314, Eye Dam. 1 H318, STOT SE 3 H335, Skin Sens. 1B H317, Classification note according to Annex VI to the CLP Regulation: B D

EC 200-001-8

INDEX 605-001-00-5

Reg. no. 01-2119488953-20-XXXX

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately.

INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS EPOXY PRIMER BLUE Component A – SAFETY DATA SHEET - february 2021 - n°batch 027-BA - rev. 1/2021

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

Send away individuals who are not suitably equipped. Use explosion-proof equipment. Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. When performing transfer operations involving large containers, connect to an earthing system and wear antistatic footwear. Vigorous stirring and flow through the tubes and equipment may cause the formation and accumulation of electrostatic charges. In order to avoid the risk of fires and explosions, never use compressed air when handling. Open containers with caution as they may be pressurised. Do not eat, drink or smoke during use. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Store in a cool and well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

Storage class TRGS 510 (Germany):

3

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS EPOXY PRIMER BLUE Component A – SAFETY DATA SHEET - february 2021 - n°batch 027-BA - rev. 1/2021

Regulatory References:

DEU	Deutschland	TRGS 900 - Seite 1 von 69 (Fassung 29.03.2019)- Liste der Arbeitsplatzgrenzwerte und Kurzzeitwerte LÍMITES DE EXPOSICIÓN PROFESIONAL PARA AGENTES QUÍMICOS EN ESPAÑA 2019 (INSST) Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS Decreto Legislativo 9 Aprile 2008, n.81 Regeling van de Staatssecretaris van Sociale Zaken en Werkgelegenheid van 13 juli 2018, 2018-0000118517 tot wijziging van de Arbeidsomstandighedenregeling in verband met de implementatie van Richtlijn 2017/164 in Bijlage XIII
ESP	España	
FRA	France	
ITA	Italia	
NLD	Nederland	
PRT	Portugal	Ministério da Economia e do Emprego Consolida as prescrições mínimas em matéria de protecção dos trabalhadores contra os riscos para a segurança e a saúde devido à exposição a agentes químicos no trabalho - Diário da República, 1.ª série - N.º 111 - 11 de junho de 2018
POL	Polska	ROZPORZĄDZENIE MINISTRA RODZINY, PRACY I POLITYKI SPOŁECZNEJ z dnia 12 czerwca 2018 r
ROU	România	HOTĂRÂRE nr. 584 din 2 august 2018 pentru modificarea Hotărârii Guvernului nr. 1.218/2006 privind stabilirea cerințelor minime de securitate și sănătate în muncă pentru asigurarea protecției lucrătorilor împotriva riscurilor legate de prezența agenților chimici
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Third edition, published 2018)
EU	OEL EU	Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2020

BARIUM SULFATE**Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m ³	ppm	mg/m ³	ppm	
MAK	DEU	0,3				INHAL
MAK	DEU	0,3		1,6		RESP Hinweis
VLA	ESP	10				
NDS/NDSch	POL	0,5				Na Ba
WEL	GBR	10				INHAL
WEL	GBR	4				RESP
TLV-ACGIH		5				

Predicted no-effect concentration - PNEC

Normal value in fresh water	115	µg/L
Normal value in marine water	NPI	
Normal value for fresh water sediment	600,4	mg/kg/d
Normal value for marine water sediment	NPI	
Normal value for water, intermittent release	NPI	
Normal value of STP microorganisms	62,2	mg/l
Normal value for the terrestrial compartment	207,7	mg/kg/d
Normal value for the atmosphere	NPI	

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers			Effects on workers				
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral		NPI		13000 mg/kg bw/d				
Inhalation	NPI	NPI	NPI	10 mg/m ³	NPI	NPI	10 mg/m ³	10 mg/m ³
Skin	NPI	NPI	NPI		NPI	NPI	NPI	NPI

XYLENE (MIXTURE OF ISOMERS)**Threshold Limit Value**

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it

**NAUTILUS EPOXY PRIMER BLUE Component A – SAFETY DATA SHEET - february 2021 - n°batch 027-BA - rev. 1/2021**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	440	100	880	200	SKIN
MAK	DEU	440	100	880	200	SKIN
VLA	ESP	221	50	442	100	SKIN
VLEP	FRA	221	50	442	100	SKIN
VLEP	ITA	221	50	442	100	SKIN
TGG	NLD	210		442		SKIN
NDS/NDSch	POL	100				
WEL	GBR	220	50	441	100	
OEL	EU	221	50	442	100	SKIN
TLV-ACGIH		434	100	651	150	

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,327	mg/l
Normal value in marine water	0,327	mg/l
Normal value for fresh water sediment	12,46	mg/kg
Normal value for marine water sediment	12,46	mg/kg
Normal value of STP microorganisms	6,58	mg/l
Normal value for the terrestrial compartment	2,31	mg/kg

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers			Chronic systemic 1,6 mg/kg bw/d	Effects on workers		
	Acute local	Acute systemic	Chronic local		Acute local	Acute systemic	Chronic local
Inhalation	174 mg/m3	174 mg/m3		14.8 mg/m3	289 mg/m3	289 mg/m3	77 mg/m3
Skin		108 mg/kg bw/d				180 mg/kg bw/d	

ISOBUTYL ALCOHOL**Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	310	100	310 (C)	100 (C)	
MAK	DEU	310	100	310	100	
VLA	ESP	154	50			
VLEP	FRA	150	50			
TGG	NLD	150				
NDS/NDSch	POL	100		200		SKIN
TLV	ROU	100	33	200	66	
WEL	GBR	154	50	231	75	
TLV-ACGIH		152	50			

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,4	mg/l
Normal value in marine water	0,04	mg/l

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it

**NAUTILUS EPOXY PRIMER BLUE Component A – SAFETY DATA SHEET - february 2021 - n°batch 027-BA - rev. 1/2021**

Normal value for fresh water sediment	1,52	mg/kg d.w
Normal value for marine water sediment	0,152	mg/kg d.w.
Normal value for water, intermittent release	11	mg/l
Normal value of STP microorganisms	10	mg/l
Normal value for the terrestrial compartment	0,0699	mg/kg d.w
Normal value for the atmosphere	NPI	

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral		NPI		NPI			25 mg/kg d.w.	VND
Inhalation			310 mg/m ³	VND			55 mg/m ³	VND
Skin		NPI		NPI		NPI		NPI

TALC**Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m ³	ppm	mg/m ³	ppm	
VLA	ESP	2				RESP
TGG	NLD	0,25				
NDS/NDSch	POL	4				INHAL
NDS/NDSch	POL	1				RESP
TLV	ROU	2				
WEL	GBR	1				RESP
TLV-ACGIH		2				

Predicted no-effect concentration - PNEC

Normal value in fresh water	597,97	mg/l
Normal value in marine water	141,26	mg/l
Normal value for fresh water sediment	31,33	mg/kg/d
Normal value for marine water sediment	3,13	mg/kg/d
Normal value for the atmosphere	10	mg/m ³

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral		160 mg/kg bw/d		160 mg/kg bw/d				
Inhalation	1,8 mg/m ³	1,08 mg/m ³	1,8 mg/m ³	1,08 mg/m ³	3,6 mg/m ³	2,16 mg/m ³	3,6 mg/m ³	2,16 mg/m ³
Skin	NPI	NPI	2,27 mg/kg bw/d	26,1 mg/kg bw/d	NPI	NPI	4,54 mg/kg bw/d	43,2 mg/kg bw/d

REAZIONE DI MASSA DELL'ETILBENZENE E DELLO XILENE**Predicted no-effect concentration - PNEC**

Normal value in fresh water	327	µg/L
Normal value in marine water	327	µg/L
Normal value for fresh water sediment	12,46	mg/kg/d
Normal value for marine water sediment	12,46	mg/kg/d

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it

**NAUTILUS EPOXY PRIMER BLUE Component A – SAFETY DATA SHEET - february 2021 - n°batch 027-BA - rev. 1/2021**

Normal value of STP microorganisms	6,58	mg/l
Normal value for the terrestrial compartment	2,31	mg/kg/d

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				12,5 mg/kg bw/d				
Inhalation	260 mg/m3	260 mg/m3	65,3 mg/m3	65,3 mg/m3	442 mg/m3	442 mg/m3	221 mg/m3	221 mg/m3
Skin				125 mg/kg bw/d				212 mg/kg bw/d

1-METOSI-2-PROPANOLO**Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	370	100	740	200	
MAK	DEU	370	100	740	200	
VLA	ESP	375	100	568	150	SKIN
VLEP	FRA	188	50	375	100	SKIN
VLEP	ITA	375	100	568	150	SKIN
TGG	NLD	375		563		SKIN
VLE	PRT	375	100	568	150	
NDS/NDSch	POL	180		360		SKIN
TLV	ROU	375	100	568	150	SKIN
WEL	GBR	375	100	560	150	SKIN
OEL	EU	375	100	568	150	SKIN
TLV-ACGIH		184	50	368	100	

Predicted no-effect concentration - PNEC

Normal value in fresh water	10	mg/l
Normal value in marine water	1	mg/l
Normal value for fresh water sediment	52,3	mg/kg
Normal value for marine water sediment	5,2	mg/kg
Normal value for water, intermittent release	100	mg/l
Normal value of STP microorganisms	100	mg/l
Normal value for the terrestrial compartment	4,59	mg/kg pc/giorno

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			3,3 mg/kg					
Inhalation				43,9 mg/m3	553,5 mg/m3			369 mg/m3
Skin				18,1 mg/kg			50,6 mg/kg	

METILETILCHETONE**Threshold Limit Value**

Type	Country	TWA/8h	STEL/15min	Remarks / Observations
------	---------	--------	------------	------------------------

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it

**NAUTILUS EPOXY PRIMER BLUE Component A – SAFETY DATA SHEET - february 2021 - n°batch 027-BA - rev. 1/2021**

		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	600	200	600	200	SKIN
MAK	DEU	600	200	600	200	SKIN
VLA	ESP	600	200	900	300	
VLEP	FRA	600	200	900	300	SKIN
VLEP	ITA	600	200	900	300	
TGG	NLD	590		500		SKIN
VLE	PRT	600	200	900	300	
NDS/NDSCh	POL	450		900		SKIN
TLV	ROU	600	200	900	300	
WEL	GBR	600	200	899	300	SKIN
OEL	EU	600	200	900	300	
TLV-ACGIH		590	200	885	300	

Predicted no-effect concentration - PNEC

Normal value in fresh water	55,8	mg/l
Normal value in marine water	55,8	mg/l
Normal value for fresh water sediment	284,74	mg/kg
Normal value for marine water sediment	287,7	mg/kg

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers			Effects on workers				
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				31 mg/kg				
Inhalation				406 mg/m3				600 mg/m3
Skin				412 mg/kg				1161 mg/kg

PRODOTTO DI REAZIONE: BISFENOLO-A-EPICLORIDRINA; RESINE EPOSSIDICHE (PESO MOLECOLARE MEDIO >1100)**Predicted no-effect concentration - PNEC**

Normal value in fresh water	0,006	mg/l
Normal value in marine water	0,0006	mg/l
Normal value for fresh water sediment	0,0627	mg/kg
Normal value for marine water sediment	0,00627	mg/kg
Normal value for water, intermittent release	10	mg/l

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers			Effects on workers				
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Inhalation			0,012 mg/kg					0,012 mg/kg
Skin					8,33 mg/kg			8,33 mg/kg

METILISOBUTILCHETONE**Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	83	20	166	40	SKIN

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it

**NAUTILUS EPOXY PRIMER BLUE Component A – SAFETY DATA SHEET - february 2021 - n°batch 027-BA - rev. 1/2021**

MAK	DEU	83	20	166	40	SKIN
VLA	ESP	83	20	208	50	
VLEP	FRA	83	20	208	50	
VLEP	ITA	83	20	208	50	
TGG	NLD	104		208		
VLE	PRT	83	20	208	50	
NDS/NDSch	POL	83		200		
TLV	ROU	83	20	208	50	
WEL	GBR	208	50	416	100	SKIN
OEL	EU	83	20	208	50	
TLV-ACGIH		82	20	307	75	

Predicted no-effect concentration - PNEC

Normal value in fresh water	600	µg/L
Normal value in marine water	60	µg/L
Normal value for fresh water sediment	8,27	mg/kg/d
Normal value for marine water sediment	830	µg/kg/dw
Normal value for water, intermittent release	1,5	mg/l
Normal value of STP microorganisms	27,5	mg/l
Normal value for the food chain (secondary poisoning)	NPI	
Normal value for the terrestrial compartment	1,3	mg/kg/d
Normal value for the atmosphere	NPI	

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral		NPI		4,2 mg/kg/d				
Inhalation	155,2 mg/m3	155,2 mg/m3	14,7 mg/m3	14,7 mg/m3	208 mg/m3	208 mg/m3	83 mg/m3	83 mg/m3
Skin	NPI	NPI		4,2 mg/kg bw/d	NPI	NPI		11,8 mg/kg bw/d

TITANIUM DIOXIDE**Threshold Limit Value**

Type	Country	TWA/8h	STEL/15min	Remarks / Observations
		mg/m3	ppm	
VLA	ESP	10		
VLEP	FRA	10		
NDS/NDSch	POL	10		INHAL
TLV	ROU	10	15	
WEL	GBR	10		INHAL
WEL	GBR	4		RESP
TLV-ACGIH		10		

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,184	mg/l
Normal value in marine water	0,0184	mg/l
Normal value for fresh water sediment	100	mg/kg/d

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it

**NAUTILUS EPOXY PRIMER BLUE Component A – SAFETY DATA SHEET - february 2021 - n°batch 027-BA - rev. 1/2021**

Normal value for marine water sediment	1000	mg/kg/d
Normal value for water, intermittent release	0,193	mg/l
Normal value of STP microorganisms	100	mg/l
Normal value for the terrestrial compartment	100	mg/kg/d

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral		700 mg/kg bw/d		NPI		NPI		NPI
Inhalation	NPI	NPI	NPI	NPI	NPI	NPI	10 mg/m3	NPI
Skin	NPI	NPI	NPI	NPI	NPI	NPI	NPI	NPI

N-BUTYL ACETATE**Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	300	62	600 (C)	124 (C)	
VLA	ESP	724	150	965	200	
VLEP	FRA	710	150	940	200	
TGG	NLD	150				
NDS/NDSch	POL	240		720		
TLV	ROU	715	150	950	200	
WEL	GBR	724	150	966	200	
OEL	EU	241	50	723	150	
TLV-ACGIH			50		150	

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,18	mg/l
Normal value in marine water	0,018	mg/l
Normal value for fresh water sediment	0,981	mg/kg
Normal value for marine water sediment	0,0981	mg/kg
Normal value for water, intermittent release	0,36	mg/l
Normal value of STP microorganisms	35,6	mg/l
Normal value for the terrestrial compartment	0,0903	mg/kg

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral		2 mg/kg bw/d		2 mg/kg bw/d				
Inhalation	300 mg/m3	300 mg/m3	37.5 mg/m3	12 mg/m3	300 mg/m3	48 mg/m3	600 mg/m3	600 mg/m3
Skin	NPI	3.4 mg/kg bw/d	NPI	6 mg/kg bw/d	NPI	11 mg/kg bw/d	NPI	7 mg/kg bw/d

4-HYDROXY-4-METHYLPENTAN-2-ONE**Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	96	20	192	40	SKIN

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it

**NAUTILUS EPOXY PRIMER BLUE Component A – SAFETY DATA SHEET - february 2021 - n°batch 027-BA - rev. 1/2021**

MAK	DEU	96	20	192	40	SKIN
VLA	ESP	241	50			
VLEP	FRA	240	50			
TGG	NLD	120				SKIN
NDS/NDSch	POL	240				
TLV	ROU	150	32	250	53	
WEL	GBR	241	50	362	75	
TLV-ACGIH		238	50			

Predicted no-effect concentration - PNEC

Normal value in fresh water	2	mg/l
Normal value in marine water	0,2	mg/l
Normal value for fresh water sediment	9,06	mg/kg
Normal value for marine water sediment	0,91	mg/kg
Normal value for water, intermittent release	1	mg/l
Normal value for the terrestrial compartment	0,63	mg/kg

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers			Effects on workers				
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral		NPI		1,67 mg/kg				
Inhalation	NPI	NPI	NPI	5.8 mg/m3	240 mg/m3	NPI	NPI	32,6 mg/m3
Skin	NPI	NPI	NPI	167 mg/kg	NPI	NPI	NPI	467 mg/kg

Oleic acid, compound with (Z)-N-octadec-9-enylpropane-1,3-diamine (2:1)**Predicted no-effect concentration - PNEC**

Normal value in fresh water	646	µg/L
Normal value in marine water	646	ng/L
Normal value for fresh water sediment	204	mg/kg/d
Normal value for marine water sediment	20,4	mg/kg/d
Normal value of STP microorganisms	993	mg/l
Normal value for the terrestrial compartment	993	mg/kg/d

ACETATO DI 1-METIL-2-METOSSIETILE**Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	270	50	270	50	
MAK	DEU	270	50	270	50	
VLA	ESP	275	50	550	100	SKIN
VLEP	FRA	275	50	550	100	SKIN
VLEP	ITA	275	50	550	100	SKIN
TGG	NLD	550				
VLE	PRT	275	50	550	100	SKIN
NDS/NDSch	POL	260		520		SKIN
TLV	ROU	275	50	550	100	SKIN

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it

**NAUTILUS EPOXY PRIMER BLUE Component A – SAFETY DATA SHEET - february 2021 - n°batch 027-BA - rev. 1/2021**

WEL	GBR	274	50	548	100	SKIN
OEL	EU	275	50	550	100	SKIN

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,635	mg/l
Normal value in marine water	0,0635	mg/l
Normal value for fresh water sediment	3,29	mg/kg
Normal value for marine water sediment	0,329	mg/kg
Normal value of STP microorganisms	100	mg/l
Normal value for the food chain (secondary poisoning)	NPI	
Normal value for the terrestrial compartment	0,29	mg/kg
Normal value for the atmosphere	NPI	

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral	500 mg/kg bw/d		36 mg/kg bw/d	1,67 mg/kg				
Inhalation	NPI	NPI	33 mg/m3	33 mg/m3	550 mg/m3	NPI	NPI	275 mg/m3
Skin	NPI	NPI	NPI	320 mg/kg bw/d	NPI	NPI	NPI	796 mg/kg bw/d

QUARTZ**Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
VLA	ESP		0,05			RESP
VLEP	FRA	0,1				RESP
VLEP	ITA	0,1				RESP
TGG	NLD	0,075				RESP
NDS/NDSch	POL	0,1				RESP
OEL	EU	0,1				RESP
TLV-ACGIH		0,025				

FORMALDEHYDE**Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	0,37	0,3	0,74	0,6	
VLA	ESP	0,37	0,3	0,74	0,6	
VLEP	FRA		0,5		1	
TGG	NLD	0,15		0,5		
NDS/NDSch	POL	0,37		0,74		SKIN
TLV	ROU	1,2	1	3	2	
WEL	GBR	2,5	2	2,5	2	
OEL	EU	0,37	0,3	0,74	0,6	
TLV-ACGIH			0,1		0,3 (C)	

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS EPOXY PRIMER BLUE Component A – SAFETY DATA SHEET - february 2021 - n°batch 027-BA - rev. 1/2021

Predicted no-effect concentration - PNEC		
Normal value in fresh water	0,47	mg/l
Normal value in marine water	0,47	mg/l
Normal value for fresh water sediment	2,44	mg/kg
Normal value for marine water sediment	2,3	mg/kg/d
Normal value of STP microorganisms	0,19	mg/l
Normal value for the terrestrial compartment	0,21	mg/kg
Normal value for the atmosphere	NPI	

Health - Derived no-effect level - DNEL / DMEL								
Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral		NPI		4.1 mg/kg bw/d				
Inhalation	NPI	NPI	0.1 mg/m3	3.2 mg/m3	NPI	1 mg/m3	0.5 mg/m3	9 mg/m3
Skin	NPI	NPI	NPI	102 mg/kg bw/d	NPI	NPI	NPI	240 mg/kg bw/d

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, wear a mask with a type AX filter, whose limit of use will be defined by the manufacturer (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS EPOXY PRIMER BLUE Component A – SAFETY DATA SHEET - february 2021 - n°batch 027-BA - rev. 1/2021

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	liquid	
Colour	blue	
Odour	characteristic of solvent	
Odour threshold	Not available	
pH	Not available	Reason for missing data:la sostanza/miscela è non polare /aprotica
Melting point / freezing point	Not available	
Initial boiling point	> 35 °C	
Boiling range	Not available	
Flash point	< 23 °C	
Evaporation Rate	Not available	
Flammability of solids and gases	Not available	
Lower inflammability limit	Not available	
Upper inflammability limit	Not available	
Lower explosive limit	Not available	
Upper explosive limit	Not available	
Vapour pressure	24,95 mmHg	
Vapour density	Not available	
Relative density	1,38	
Solubility	immiscible with water	
Partition coefficient: n-octanol/water	Not available	
Auto-ignition temperature	Not available	
Decomposition temperature	Not available	
Viscosity	>20,5 mm ² /sec (40°C)	
Explosive properties	Not available	
Oxidising properties	Not available	

9.2. Other information

Total solids (250°C / 482°F)	65,40 %	
VOC (Directive 2010/75/EC) :	34,60 % - 477,48 g/litre	
VOC (volatile carbon) :	25,52 % - 351,02 g/litre	

SECTION 10. Stability and reactivity

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS EPOXY PRIMER BLUE Component A – SAFETY DATA SHEET - february 2021 - n°batch 027-BA - rev. 1/2021

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

1-METOSI-2-PROPANOLO

Dissolves various plastic materials. Stable in normal conditions of use and storage.

Assorbe e si scioglie in acqua ed in solventi organici. Con l'aria può dare lentamente perossidi esplosivi.

METILETILCHETONE

Reacts with: light metals, strong oxidants. Attacks various types of plastic materials. Decomposes under the effect of heat.

METILISOBUTILCHETONE

Reacts violently with: light metals. Attacks various types of plastic materials.

N-BUTYL ACETATE

Decomposes on contact with: water.

4-HYDROXY-4-METHYLPENTAN-2-ONE

Decomposes at temperatures above 90°C/194°F.

ACETATO DI 1-METIL-2-METOSIETILE

Stable in normal conditions of use and storage.

Con l'aria può dare lentamente perossidi che esplodono per aumento di temperatura.

FORMALDEHYDE

Decomposes under the effect of heat.

Acqueous solutions are stabilised with methanol but tend to polymerise over time.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

XYLENE (MIXTURE OF ISOMERS)

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS EPOXY PRIMER BLUE Component A – SAFETY DATA SHEET - february 2021 - n°batch 027-BA - rev. 1/2021

XYLENE (MIXTURE OF ISOMERS): stable, but may develop violent reactions in the presence of strong oxidising agents such as sulphuric and nitric acids and perchlorates. May form explosive mixtures with the air.

1-METOSI-2-PROPANOLO

May react dangerously with: strong oxidising agents, strong acids.

METILETILCHETONE

May form peroxides with: air, light, strong oxidising agents. Risk of explosion on contact with: hydrogen peroxide, nitric acid, sulphuric acid. May react dangerously with: oxidising agents, trichloromethane, alkalis. Forms explosive mixtures with: air.

METILISOBUTILCHETONE

May react violently with: oxidising agents. Forms peroxides with: air. Forms explosive mixtures with: hot air.

N-BUTYL ACETATE

Risk of explosion on contact with: strong oxidising agents. May react dangerously with: alkaline hydroxides, potassium tert-butoxide. Forms explosive mixtures with: air.

4-HYDROXY-4-METHYLPENTAN-2-ONE

Risk of explosion on contact with: air, sources of heat. May react dangerously with: alkaline metals, amines, oxidising agents, acids.

ACETATO DI 1-METIL-2-METOSIETILE

May react violently with: oxidising substances, strong acids, alkaline metals.

2-BUTANONE OXIME

Above the flash point (69°C/156°F), explosive mixtures can form with air.

FORMALDEHYDE

Risk of explosion on contact with: nitromethane, nitrogen dioxide, hydrogen peroxide, phenoles, performic acid, nitric acid. May polymerise on contact with: strong oxidising agents, alkalis. May react dangerously with: hydrochloric acid, magnesium carbonate, sodium hydroxide, perchloric acid, aniline. Forms explosive mixtures with: air.

10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

1-METOSI-2-PROPANOLO

Avoid exposure to: air.

METILETILCHETONE

Avoid exposure to: sources of heat.

METILISOBUTILCHETONE

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS EPOXY PRIMER BLUE Component A – SAFETY DATA SHEET - february 2021 - n°batch 027-BA - rev. 1/2021

Avoid exposure to: sources of heat.

N-BUTYL ACETATE

Avoid exposure to: moisture, sources of heat, naked flames.

4-HYDROXY-4-METHYLPENTAN-2-ONE

Avoid exposure to: light, sources of heat, naked flames.

FORMALDEHYDE

Avoid exposure to: light, sources of heat, naked flames.

10.5. Incompatible materials

1-METOSI-2-PROPANOLO

Incompatible with: oxidising substances, strong acids, alkaline metals.

METILETILCHETONE

Incompatible with: strong oxidants, inorganic acids, ammonia, copper, chloroform.

METILISOBUTILCHETONE

Incompatible with: oxidising substances, reducing substances.

N-BUTYL ACETATE

Incompatible with: water, nitrates, strong oxidants, acids, alkalis, zinc.

ACETATO DI 1-METIL-2-METOSIETILE

Incompatible with: oxidising substances, strong acids, alkaline metals.

FORMALDEHYDE

Incompatible with: acids, alkalis, ammonia, tannin, strong oxidants, phenols, copper salts, silver, iron.

10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

FORMALDEHYDE

When heated to decomposition releases: methanol, carbon monoxide.

SECTION 11. Toxicological information

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS EPOXY PRIMER BLUE Component A – SAFETY DATA SHEET - february 2021 - n°batch 027-BA - rev. 1/2021

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on toxicological effects

XYLENE (MIXTURE OF ISOMERS)

XYLENE (MIXTURE OF ISOMERS): has a toxic effect on the CNS (encephalopathies). Irritating to the skin, conjunctivae, cornea and respiratory apparatus.

Metabolism, toxicokinetics, mechanism of action and other information

ACETATO DI 1-METIL-2-METOSSIIETILE

La principale via di entrata è quella cutanea, mentre quella respiratoria è meno importante, data la bassa tensione di vapore del prodotto.

Information on likely routes of exposure

1-METOSSII-2-PROPANOLO

LAVORATORI: inalazione; contatto con la cute.

POPOLAZIONE: ingestione di cibo o di acqua contaminati; inalazione aria ambiente; contatto con la cute di prodotti contenenti la sostanza.

N-BUTYL ACETATE

WORKERS: inhalation; contact with the skin.

4-HYDROXY-4-METHYLPENTAN-2-ONE

WORKERS: inhalation; contact with the skin.

ACETATO DI 1-METIL-2-METOSSIIETILE

LAVORATORI: inalazione; contatto con la cute.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

1-METOSSII-2-PROPANOLO

La principale via di entrata è quella cutanea, mentre quella respiratoria è meno importante, data la bassa tensione di vapore del prodotto. Al di sopra di 100 ppm si ha irritazione delle mucose oculari, nasali e orofaringee. A 1000 ppm si notano turbe nell'equilibrio e irritazione severa agli occhi. Gli esami clinici e biologici praticati sui volontari esposti non hanno rivelato anomalie. L'acetato produce maggiore irritazione cutanea ed oculare per contatto diretto. Non vengono riportati effetti cronici sull'uomo.

N-BUTYL ACETATE

In humans, the substance's vapours cause irritation of the eyes and nose. In the event of repeated exposure, skin irritation, dermatitis (dryness and cracking of the skin) and keratitis appear.

4-HYDROXY-4-METHYLPENTAN-2-ONE

Acute toxicity causes irritation of the eyes, nose and throat in humans at 100 ppm (476 mg/kg) and pulmonary disorders at 400 ppm. No chronic effects on humans have been reported. The substance may have a depressive effect on the respiratory centres and cause death from respiratory failure.

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS EPOXY PRIMER BLUE Component A – SAFETY DATA SHEET - february 2021 - n°batch 027-BA - rev. 1/2021

ACETATO DI 1-METIL-2-METOSSJETILE

Al di sopra di 100 ppm si ha irritazione delle mucose oculari, nasali e orofaringee. A 1000 ppm si notano turbe nell'equilibrio e irritazione severa agli occhi. Gli esami clinici e biologici praticati sui volontari esposti non hanno rivelato anomalie. L'acetato produce maggiore irritazione cutanea ed oculare per contatto diretto. Non vengono riportati effetti cronici sull'uomo (INCR, 2010).

Interactive effects

N-BUTYL ACETATE

A case of acute intoxication been reported involving a 33 year old worker while cleaning a tank with a preparation containing xylenes, butyl acetate and ethylene glycol acetate. The person had irritation of the conjunctiva and upper respiratory tract, drowsiness and motor coordination disorders, which disappeared within 5 hours. The symptoms are attributed to poisoning by mixed xylenes and butyl acetate, with a possible synergistic effect responsible for the neurological effects. Cases of vacuolar keratitis are reported in workers exposed to a mixture of butyl acetate and isobutanol vapours, but with uncertainty concerning the responsibility of a particular solvent (INRC, 2011).

ACUTE TOXICITY

ATE (Inhalation) of the mixture:

> 20 mg/l

ATE (Oral) of the mixture:

Not classified (no significant component)

ATE (Dermal) of the mixture:

>2000 mg/kg

TITANIUM DIOXIDE

LD50 (Oral) > 10000 mg/kg Rat

LD50 (Dermal) > 5000 mg/kg CONIGLIO

LC50 (Inhalation) > 6,8 mg/l/4h RATTO

BARIUM SULFATE

LD50 (Oral) > 3000 mg/kg Mouse

ACETATO DI 1-METIL-2-METOSSJETILE

LD50 (Oral) 8500 mg/kg Rat

LD50 (Dermal) > 3160 mg/kg Rat

LC50 (Inhalation) 6193 mg/m³/4h Ratto

ISOBUTYL ALCOHOL

LD50 (Oral) 2460 mg/kg Rat

LD50 (Dermal) 2460 mg/kg Rabbit

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS EPOXY PRIMER BLUE Component A – SAFETY DATA SHEET - february 2021 - n°batch 027-BA - rev. 1/2021

LC50 (Inhalation) 18,18 mg/l/4h Rat

QUARTZ

LD50 (Oral) > 500 mg/kg

4-HYDROXY-4-METHYLPENTAN-2-ONE

LD50 (Oral) 3002 mg/kg Rat

LD50 (Dermal) > 1875 mg/kg RATTO

1-METOSI-2-PROPANOLO

LD50 (Oral) 5300 mg/kg Rat

LD50 (Dermal) 13000 mg/kg Rabbit

LC50 (Inhalation) 54,6 mg/l/4h Rat

FORMALDEHYDE

LD50 (Oral) 100 mg/kg Rat

LD50 (Dermal) 270 mg/kg Rabbit

LC50 (Inhalation) 0,588 mg/l/4h Rat

METILETILCHETONE

LD50 (Oral) 2737 mg/kg Rat

LD50 (Dermal) 6480 mg/kg Rabbit

LC50 (Inhalation) 23,5 mg/l/8h Rat

METILISOBUTILCHETONE

LD50 (Oral) 2080 mg/kg Rat

LD50 (Dermal) > 16000 mg/kg Rabbit

LC50 (Inhalation) > 8,2 mg/l/4h Rat

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS EPOXY PRIMER BLUE Component A – SAFETY DATA SHEET - february 2021 - n°batch 027-BA - rev. 1/2021

N-BUTYL ACETATE

LD50 (Oral) > 6400 mg/kg Rat

LD50 (Dermal) > 5000 mg/kg Rabbit

LC50 (Inhalation) 21,1 mg/l/4h Rat

RESINA EPOSSIDICA (BISFENOLO A EPICLORIDRINA) p.m. > 700

LD50 (Oral) > 2000 mg/kg RATTO

LD50 (Dermal) > 2000 mg/kg RATTO

REAZIONE DI MASSA DELL'ETILBENZENE E DELLO XILENE

LD50 (Oral) > 3500 mg/kg RAT

LD50 (Dermal) > 4350 mg/kg RAT

LC50 (Inhalation) > 29,08 mg/l/4h RAT

XYLENE (MIXTURE OF ISOMERS)

LD50 (Oral) 3500 mg/kg Rat

LD50 (Dermal) 4350 mg/kg Rabbit

LC50 (Inhalation) 26 mg/l/4h Rat

PRODOTTO DI REAZIONE: BISFENOLO-A-EPICLORIDRINA; RESINE EPOSSIDICHE (PESO MOLECOLARE MEDIO >1100)

LD50 (Oral) > 2000 mg/kg ratto

Vinyl chloride copolymère

LD50 (Oral) > 2000 mg/kg RATTO

SKIN CORROSION / IRRITATION

Causes skin irritation

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye damage

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS EPOXY PRIMER BLUE Component A – SAFETY DATA SHEET - february 2021 - n°batch 027-BA - rev. 1/2021

RESPIRATORY OR SKIN SENSITISATION

Sensitising for the skin

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

May cause respiratory irritation

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class Viscosity: >20,5 mm²/sec (40°C)

SECTION 12. Ecological information

This product is dangerous for the environment and is toxic for aquatic organisms. In the long term, it have negative effects on aquatic environment.

12.1. Toxicity

TALC

LC50 - for Fish > 89,581 g/l/96h 89.581 - 110 g/L

TITANIUM DIOXIDE

LC50 - for Fish > 1100 µg/L/96

EC50 - for Crustacea > 103,9 mg/l/48h

EC50 - for Algae / Aquatic Plants > 100 mg/l/72h

BARIUM SULFATE

LC50 - for Fish > 3,5 mg/l/96h 3.5 - 174

EC50 - for Algae / Aquatic Plants > 1,15 mg/l/72h 1.15 - 100 mg/L

ACETATO DI 1-METIL-2-METOSSIETILE

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS EPOXY PRIMER BLUE Component A – SAFETY DATA SHEET - february 2021 - n°batch 027-BA - rev. 1/2021

LC50 - for Fish	> 100 mg/l/96h Oncorhynchus mykiss
EC50 - for Crustacea	> 408 mg/l/48h Daphnia magna
EC50 - for Algae / Aquatic Plants	> 100 mg/l/72h
Chronic NOEC for Fish	47,5 mg/l Oncothynchus mykiss
Chronic NOEC for Crustacea	> 99 mg/l Daphnia magna
Chronic NOEC for Algae / Aquatic Plants	> 999 mg/l Selenastrum capricornutum
ISOBUTYL ALCOHOL	
LC50 - for Fish	> 1,43 mg/l/96h Pimephales promelas
EC50 - for Crustacea	> 1,1 mg/l/48h Daphnia pulex
EC50 - for Algae / Aquatic Plants	> 3,48 mg/l/72h DAFNIE
4-HYDROXY-4-METHYLPENTAN-2-ONE	
LC50 - for Fish	> 100 mg/l/96h ORYZIAS LATIPES
EC50 - for Crustacea	> 1000 mg/l/48h DAFNIA
EC50 - for Algae / Aquatic Plants	> 1000 mg/l/72h PSEUDOKIRCHNERIELLA SUBCAPITATA
FORMALDEHYDE	
LC50 - for Fish	> 6,7 mg/l/96h
EC50 - for Crustacea	> 5,8 mg/l/48h DAFNIE
EC50 - for Algae / Aquatic Plants	> 5,67 mg/l/72h
METILETILCHETONE	
LC50 - for Fish	> 2,993 mg/l/96h Pimephales promelas
EC50 - for Crustacea	> 508 mg/l/48h Daphnia Magna
METILISOBUTILCHETONE	
LC50 - for Fish	> 179 mg/l/96h
EC50 - for Crustacea	> 200 mg/l/48h
N-BUTYL ACETATE	
LC50 - for Fish	> 18 mg/l/96h
EC50 - for Crustacea	> 32 mg/l/48h
EC50 - for Algae / Aquatic Plants	> 246 mg/l/72h
RAZIONE DI MASSA DELL'ETILBENZENE E DELLO XILENE	
LC50 - for Fish	> 2,6 mg/l/96h 2.6 - 8.4
EC50 - for Algae / Aquatic Plants	> 4,6 mg/l/72h 4.6 - 4.9
XYLENE (MIXTURE OF ISOMERS)	
LC50 - for Fish	> 4,2 mg/l/96h Oncorhynchus mykiss
EC50 - for Crustacea	> 2,93 mg/l/48h Daphnia Magna
PRODOTTO DI REAZIONE:BISFENOLO-A-	

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS EPOXY PRIMER BLUE Component A – SAFETY DATA SHEET - february 2021 - n°batch 027-BA - rev. 1/2021

EPICLORIDRINA; RESINE EPOSSIDICHE
(PESO MOLECOLARE MEDIO >1100)

EC50 - for Crustacea > 2 mg/l/48h

Oleic acid, compound with (Z)-N-octadec-9-enylpropane-1,3-diamine (2:1)

LC50 - for Fish > 1,34 mg/l/96h

EC50 - for Algae / Aquatic Plants > 410 µg/L

EC10 for Crustacea > 1,35 mg/l/21d

EC10 for Algae / Aquatic Plants > 323 µg/L 72 h

FOSFATO IDRATO DI ZINCO ALLUMINIO

LC50 - for Fish > 0,5 mg/l/96h

Chronic NOEC for Crustacea > 0,72 mg/l newly hatched larvae to larvae (from unexposed eggs)

Chronic NOEC for Algae / Aquatic Plants > 4,8 mg/l 12 d growth rate

12.2. Persistence and degradability

TALC

Solubility in water < 0,1 mg/l

TITANIUM DIOXIDE

Solubility in water < 0,001 mg/l

Degradability: information not available

BARIUM SULFATE

Solubility in water 0,1 - 100 mg/l

Degradability: information not available

ACETATO DI 1-METIL-2-METOSSITILE

Solubility in water > 10000 mg/l

Rapidly degradable

ISOBUTYL ALCOHOL

Solubility in water > 70 g/l

Rapidly degradable

4-HYDROXY-4-METHYLPENTAN-2-ONE

Solubility in water 1000 - 10000 mg/l

Rapidly degradable

1-METOSI-2-PROPANOLO

Solubility in water 1000 - 10000 mg/l

Rapidly degradable

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS EPOXY PRIMER BLUE Component A – SAFETY DATA SHEET - february 2021 - n°batch 027-BA - rev. 1/2021

FORMALDEHYDE

Solubility in water 55000 mg/l

Rapidly degradable

METILETILCHETONE

Solubility in water > 10000 mg/l

Rapidly degradable

METILISOBUTILCHETONE

Solubility in water > 14,1 g/l

Degradability: information not available

Rapidly degradable

N-BUTYL ACETATE

Solubility in water 5.3 - 14 g/L @ 20 °C mg/l

Rapidly degradable

RAZIONE DI MASSA DELL'ETILBENZENE E DELLO XILENE

Solubility in water > 165,8 mg/l

Rapidly degradable

XYLENE (MIXTURE OF ISOMERS)

Solubility in water 100 - 1000 mg/l

Degradability: information not available

PRODOTTO DI REAZIONE: BISFENOLO-A- EPICLORIDRINA; RESINE EPOSSIDICHE (PESO MOLECOLARE MEDIO >1100)

Solubility in water > 3 mg/l

12.3. Bioaccumulative potential

ACETATO DI 1-METIL-2-METOSSITILE

Partition coefficient: n-octanol/water 1,2

ISOBUTYL ALCOHOL

Partition coefficient: n-octanol/water 1

4-HYDROXY-4-METHYLPENTAN-2-ONE

Partition coefficient: n-octanol/water -0,09

1-METOSI-2-PROPANOLO

Partition coefficient: n-octanol/water < 1

FORMALDEHYDE

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS EPOXY PRIMER BLUE Component A – SAFETY DATA SHEET - february 2021 - n°batch 027-BA - rev. 1/2021

Partition coefficient: n-octanol/water 0,35
BCF < 1

METILETILCHETONE

Partition coefficient: n-octanol/water 0,3

METILISOBUTILCHETONE

Partition coefficient: n-octanol/water 1,9

N-BUTYL ACETATE

Partition coefficient: n-octanol/water 2,3
BCF 15,3

REAZIONE DI MASSA DELL'ETILBENZENE E DELLO XILENE

Partition coefficient: n-octanol/water > 3,16 Log Kow

XYLENE (MIXTURE OF ISOMERS)

Partition coefficient: n-octanol/water 3,12
BCF 25,9

12.4. Mobility in soil

ISOBUTYL ALCOHOL

Partition coefficient: soil/water 0,31

FORMALDEHYDE

Partition coefficient: soil/water 1,202

METILISOBUTILCHETONE

Partition coefficient: soil/water 2,008

N-BUTYL ACETATE

Partition coefficient: soil/water < 3

XYLENE (MIXTURE OF ISOMERS)

Partition coefficient: soil/water 2,73

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

12.6. Other adverse effects

Information not available

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS EPOXY PRIMER BLUE Component A – SAFETY DATA SHEET - february 2021 - n°batch 027-BA - rev. 1/2021

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

14.1. UN number

ADR / RID, IMDG, IATA: 1263

14.2. UN proper shipping name

ADR / RID: PAINT or PAINT RELATED MATERIAL
IMDG: PAINT or PAINT RELATED MATERIAL (PRODOTTO DI REAZIONE: BISFENOLO-A-EPICLORIDRINA; RESINE EPOSSIDICHE (PESO MOLECOLARE MEDIO >1100))
IATA: PAINT or PAINT RELATED MATERIAL

14.3. Transport hazard class(es)

ADR / RID: Class: 3 Label: 3
IMDG: Class: 3 Label: 3
IATA: Class: 3 Label: 3



14.4. Packing group

ADR / RID, IMDG, IATA: II

14.5. Environmental hazards

ADR / RID: Environmentally Hazardous
IMDG: Marine Pollutant
IATA: NO



For Air transport, environmentally hazardous mark is only mandatory for UN 3077 and UN 3082.

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS EPOXY PRIMER BLUE Component A – SAFETY DATA SHEET - february 2021 - n°batch 027-BA - rev. 1/2021

14.6. Special precautions for user

ADR / RID:	HIN - Kemler: 33	Limited Quantities: 5 L	Tunnel restriction code: (D/E)
	Special Provision: 640C		
IMDG:	EMS: F-E, <u>S-E</u>	Limited Quantities: 5 L	
IATA:	Cargo:	Maximum quantity: 60 L	Packaging instructions: 364
	Pass.:	Maximum quantity: 5 L	Packaging instructions: 353
	Special Instructions:	A3, A72, A192	

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EC: P5c-E2

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product Point 3 - 40

Contained substance

Point 72 FORMALDEHYDE
Reg. no.: 01-
2119488953-20-
XXXX

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage \geq than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

Substances subject to the Rotterdam Convention:

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS EPOXY PRIMER BLUE Component A – SAFETY DATA SHEET - february 2021 - n°batch 027-BA - rev. 1/2021

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

German regulation on the classification of substances hazardous to water (AwSV, vom 18. April 2017)

WGK 2: Hazard to waters

15.2. Chemical safety assessment

A chemical safety assessment has been performed for the following contained substances

XYLENE (MIXTURE OF ISOMERS)

ISOBUTYL ALCOHOL

1-METOSI-2-PROPANOLO

METILETILCHETONE

METILISOBUTILCHETONE

N-BUTYL ACETATE

4-HYDROXY-4-METHYLPENTAN-2-ONE

ACETATO DI 1-METIL-2-METOSIETILE

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 2	Flammable liquid, category 2
Flam. Liq. 3	Flammable liquid, category 3
Carc. 1B	Carcinogenicity, category 1B
Muta. 2	Germ cell mutagenicity, category 2
Repr. 2	Reproductive toxicity, category 2
Acute Tox. 3	Acute toxicity, category 3
Acute Tox. 4	Acute toxicity, category 4
Asp. Tox. 1	Aspiration hazard, category 1
STOT RE 2	Specific target organ toxicity - repeated exposure, category 2

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS EPOXY PRIMER BLUE Component A – SAFETY DATA SHEET - february 2021 - n°batch 027-BA - rev. 1/2021

Skin Corr. 1B	Skin corrosion, category 1B
Eye Dam. 1	Serious eye damage, category 1
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
STOT SE 3	Specific target organ toxicity - single exposure, category 3
Skin Sens. 1	Skin sensitization, category 1
Skin Sens. 1B	Skin sensitization, category 1B
Aquatic Acute 1	Hazardous to the aquatic environment, acute toxicity, category 1
Aquatic Chronic 1	Hazardous to the aquatic environment, chronic toxicity, category 1
Aquatic Chronic 2	Hazardous to the aquatic environment, chronic toxicity, category 2
Aquatic Chronic 3	Hazardous to the aquatic environment, chronic toxicity, category 3
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H350	May cause cancer.
H341	Suspected of causing genetic defects.
H361	Suspected of damaging fertility or the unborn child.
H301	Toxic if swallowed.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H332	Harmful if inhaled.
H304	May be fatal if swallowed and enters airways.
H373	May cause damage to organs through prolonged or repeated exposure.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H335	May cause respiratory irritation.
H317	May cause an allergic skin reaction.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS EPOXY PRIMER BLUE Component A – SAFETY DATA SHEET - february 2021 - n°batch 027-BA - rev. 1/2021

- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
 3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
 4. Regulation (EU) 2015/830 of the European Parliament
 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
 13. Regulation (EU) 2017/776 (X Atp. CLP)
 14. Regulation (EU) 2018/669 (XI Atp. CLP)
 15. Regulation (EU) 2018/1480 (XIII Atp. CLP)
 16. Regulation (EU) 2019/521 (XII Atp. CLP)
- The Merck Index. - 10th Edition
 - Handling Chemical Safety
 - INRS - Fiche Toxicologique (toxicological sheet)
 - Patty - Industrial Hygiene and Toxicology
 - N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
 - IFA GESTIS website
 - ECHA website
 - Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Changes to previous review:

The following sections were modified:

01 / 02 / 03 / 04 / 05 / 08 / 09 / 10 / 11 / 12 / 15 / 16.