

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS TWO PACK VARNISH SATIN COMP.A - Safety Data Sheet - february 2021 - batch 025-BA - rev.1/21

NAUTILUS TWO PACK VARNISH SATIN COMP.A

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name

NAUTILUS TWO PACK VARNISH SATIN COMP.A

UFI:

RC60-DOG-M-V00N-MVMM

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use

VERNICE MARINA A BASE DI POLIMERI ALCHIDICI

Identified Uses	Industrial	Professional	Consumer
Prodotto verniciante per mobili	-		-
Prodotto verniciante per nautica - marina	-		-
Prodotto verniciante per usi industriali		-	-
Uses Advised Against			
CONSUMATORE: FAI-DA-TE			

1.3 Details of the supplier of the safety data sheet Manufacturer/Supplier:

Cecchi Gustavo & C. srl - Via M. Coppino 253,

55049 Viareggio (LU) ITALY www.cecchi.it - info@cecchi.it

1.4 Emergency telephone number: +39 0584/383694 - info@cecchi.it

From monday to friday office hours 8:30 – 12:30, 14:00 – 18:30

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2015/830. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Flammable liquid, category 3

H226

Flammable liquid and vapour.

Specific target organ toxicity - repeated exposure, category 2

H373

May cause damage to organs through prolonged or repeated exposure.

Eye irritation, category 2

H319

Causes serious eye irritation.

Skin irritation, category 2

H315

Causes skin irritation.

Specific target organ toxicity - single exposure, category 3

H335

May cause respiratory irritation.

Hazardous to the aquatic environment, chronic toxicity,

H412

Harmful to aquatic life with long lasting effects.

category 3

2.2. Label elements

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS TWO PACK VARNISH SATIN COMP.A - Safety Data Sheet - february 2021 - batch 025-BA - rev.1/21

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words:

Warning

Hazard statements:

H226	Flammable liquid and vapour.
H373	May cause damage to organs through prolonged or repeated exposure.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H335	May cause respiratory irritation.
H412	Harmful to aquatic life with long lasting effects.
EUH208	Contains: Bis (1,2,2,6,6-pentamethyl-4-piperidyl) sebacate, 3- [3- (2H-Benzotriazol-2-yl) -5- (1,1-dimethylethyl) -4-hydroxyphenyl]-1-oxopropyl]-hydroxypoly (oxo-1,2-ethanediyl) May produce an allergic reaction.

Precautionary statements:

P501	Dispose of contents / container to . . .
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe dust / fume / gas / mist / vapours / spray.
P280	Wear protective gloves/ protective clothing / eye protection / face protection.
P271	Use only outdoors or in a well-ventilated area.

Contains: XYLENE (MIXTURE OF ISOMERS)
METILISOBUTILCHETONE

Product not intended for uses provided for by Dir. 2004/42/CE.

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

SECTION 3. Composition/information on ingredients

3.2. Mixtures

Contains:

Identification	x = Conc. %	Classification 1272/2008 (CLP)
XYLENE (MIXTURE OF ISOMERS)		
CAS 1330-20-7	$13 \leq x < 16$	Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335,

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS TWO PACK VARNISH SATIN COMP.A - Safety Data Sheet - february 2021 - batch 025-BA - rev.1/21

Aquatic Chronic 3 H412, Classification note according to Annex VI to the CLP Regulation: C

EC 215-535-7

INDEX 601-022-00-9

Reg. no. 01-2119488216-32-XXXX

ETHYL,3-ETHOXY PROPIONATE

CAS 763-69-9

$10 \leq x < 13$

Flam. Liq. 3 H226, EUH066

EC 212-112-9

INDEX -

N-BUTYL ACETATE

CAS 123-86-4

$8 \leq x < 9$

Flam. Liq. 3 H226, STOT SE 3 H336, EUH066

EC 204-658-1

INDEX 607-025-00-1

Reg. no. 01-2119485493-29-XXXX

ACETATO DI 1-METIL-2-METOSSETILE

CAS 108-65-6

$7 \leq x < 8$

Flam. Liq. 3 H226, STOT SE 3 H336

EC 203-603-9

INDEX 607-195-00-7

Reg. no. 01-2119475791-29-XXXX

METILISOBUTILCHETONE

CAS 108-10-1

$5 \leq x < 6$

Flam. Liq. 2 H225, Acute Tox. 4 H332, Eye Irrit. 2 H319, STOT SE 3 H335, EUH066

EC 203-550-1

INDEX 606-004-00-4

Reg. no. 01-2119473980-30

METILETILCHETONE

CAS 78-93-3

$1 \leq x < 2$

Flam. Liq. 2 H225, Eye Irrit. 2 H319, STOT SE 3 H336, EUH066

EC 201-159-0

INDEX 606-002-00-3

Reg. no. 01-2119457290-43

3- [3- (2H-Benzotriazol-2-yl) -5- (1,1-dimethylethyl) -4-hydroxyphenyl]-1-oxopropyl]-hydroxypoly (oxo-1,2-ethanediy)

CAS 104810-48-2

$0,7 \leq x < 1$

Skin Sens. 1 H317, Aquatic Chronic 2 H411

EC 400-830-7

INDEX 607-176-00-3

Reg. no. 01-2119396032-43-0000

Bis (1,2,2,6,6-penthamethyl-4-piperidyl) sebacate

CAS 41556-26-7

$0,25 \leq x < 0,55$

Skin Sens. 1 H317, Aquatic Acute 1 H400 M=1, Aquatic Chronic 1 H410 M=1

EC 255-437-1

INDEX -

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS TWO PACK VARNISH SATIN COMP.A - Safety Data Sheet - february 2021 - batch 025-BA - rev.1/21

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Wash immediately with plenty of water. If irritation persists, get medical advice/attention. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. In the event of breathing difficulties, get medical advice/attention immediately.

INGESTION: Get medical advice/attention. Induce vomiting only if indicated by the doctor. Never give anything by mouth to an unconscious person, unless authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

Send away individuals who are not suitably equipped. Use explosion-proof equipment. Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site.

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS TWO PACK VARNISH SATIN COMP.A - Safety Data Sheet - february 2021 - batch 025-BA - rev.1/21

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. When performing transfer operations involving large containers, connect to an earthing system and wear antistatic footwear. Vigorous stirring and flow through the tubes and equipment may cause the formation and accumulation of electrostatic charges. In order to avoid the risk of fires and explosions, never use compressed air when handling. Open containers with caution as they may be pressurised. Do not eat, drink or smoke during use. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Store in a cool and well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

Storage class TRGS 510 (Germany):

3

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory References:

DEU	Deutschland	TRGS 900 - Seite 1 von 69 (Fassung 29.03.2019)- Liste der Arbeitsplatzgrenzwerte und Kurzzeitwerte
ESP	España	LÍMITES DE EXPOSICIÓN PROFESIONAL PARA AGENTES QUÍMICOS EN ESPAÑA 2019 (INSST)
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
NLD	Nederland	Regeling van de Staatssecretaris van Sociale Zaken en Werkgelegenheid van 13 juli 2018, 2018-0000118517 tot wijziging van de Arbeidsomstandighedenregeling in verband met de implementatie van Richtlijn 2017/164 in Bijlage XIII
PRT	Portugal	Ministério da Economia e do Emprego Consolida as prescrições mínimas em matéria de protecção dos trabalhadores contra os riscos para a segurança e a saúde devido à exposição a agentes químicos no trabalho - Diário da República, 1.ª série - N.º 111 - 11 de junho de 2018
POL	Polska	ROZPORZĄDZENIE MINISTRA RODZINY, PRACY I POLITYKI SPOŁECZNEJ z dnia 12 czerwca 2018 r
ROU	România	HOTĂRÂRE nr. 584 din 2 august 2018 pentru modificarea Hotărârii Guvernului nr. 1.218/2006 privind

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS TWO PACK VARNISH SATIN COMP.A - Safety Data Sheet - february 2021 - batch 025-BA - rev.1/21

GBR United Kingdom
EU OEL EU

TLV-ACGIH

stabilirea cerințelor minime de securitate și sănătate în muncă pentru asigurarea protecției lucrătorilor împotriva riscurilor legate de prezența agenților chimici
EH40/2005 Workplace exposure limits (Third edition, published 2018)
Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.
ACGIH 2020

XYLENE (MIXTURE OF ISOMERS)**Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	440	100	880	200	SKIN
MAK	DEU	440	100	880	200	SKIN
VLA	ESP	221	50	442	100	SKIN
VLEP	FRA	221	50	442	100	SKIN
VLEP	ITA	221	50	442	100	SKIN
TGG	NLD	210		442		SKIN
NDS/NDSch	POL	100				
WEL	GBR	220	50	441	100	
OEL	EU	221	50	442	100	SKIN
TLV-ACGIH		434	100	651	150	

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,327	mg/l
Normal value in marine water	0,327	mg/l
Normal value for fresh water sediment	12,46	mg/kg
Normal value for marine water sediment	12,46	mg/kg
Normal value of STP microorganisms	6,58	mg/l
Normal value for the terrestrial compartment	2,31	mg/kg

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers			Effects on workers				
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				1.6 mg/kg bw/d				
Inhalation	174 mg/m3	174 mg/m3		14.8 mg/m3	289 mg/m3	289 mg/m3		77 mg/m3
Skin		108 mg/kg bw/d				180 mg/kg bw/d		

ETHYL,3-ETHOXY PROPIONATE**Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	610	100	610 (C)	100 (C)	SKIN
MAK	DEU	610	100	610	100	SKIN
Predicted no-effect concentration - PNEC						
Normal value in fresh water				0,0609		mg/l
Normal value in marine water				0,00609		mg/l

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS TWO PACK VARNISH SATIN COMP.A - Safety Data Sheet - february 2021 - batch 025-BA - rev.1/21

Normal value for fresh water sediment	0,419	mg/kg pc/giorno
Normal value for marine water sediment	0,0419	mg/l
Normal value for water, intermittent release	0,609	mg/l
Normal value of STP microorganisms	50	mg/l

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers			Effects on workers				
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			1,2 mg/m3	1,2 mg/m3				
Inhalation			72,6 mg/m3	72,6 mg/m3			610 mg/m3	610 mg/m3
Skin			24,2 mg/m3	24,2 mg/m3			102 mg/m3	102 mg/m3

AMORPHOUS SILICATE HYDRATE**Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	4				INHAL
MAK	DEU	4				INHAL

Predicted no-effect concentration - PNEC

Normal value for fresh water sediment	NPI
Normal value for marine water sediment	NPI
Normal value for the food chain (secondary poisoning)	NPI
Normal value for the terrestrial compartment	NPI
Normal value for the atmosphere	NPI

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers			Effects on workers				
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Inhalation								4 mg/m3

N-BUTYL ACETATE**Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	300	62	600 (C)	124 (C)	
VLA	ESP	724	150	965	200	
VLEP	FRA	710	150	940	200	
TGG	NLD	150				
NDS/NDSch	POL	240		720		
TLV	ROU	715	150	950	200	
WEL	GBR	724	150	966	200	
OEL	EU	241	50	723	150	
TLV-ACGIH			50		150	

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,18	mg/l
-----------------------------	------	------

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS TWO PACK VARNISH SATIN COMP.A - Safety Data Sheet - february 2021 - batch 025-BA - rev.1/21

Normal value in marine water	0,018	mg/l
Normal value for fresh water sediment	0,981	mg/kg
Normal value for marine water sediment	0,0981	mg/kg
Normal value for water, intermittent release	0,36	mg/l
Normal value of STP microorganisms	35,6	mg/l
Normal value for the terrestrial compartment	0,0903	mg/kg

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral		2 mg/kg bw/d		2 mg/kg bw/d				
Inhalation	300 mg/m3	300 mg/m3	37.5 mg/m3	12 mg/m3	300 mg/m3	48 mg/m3	600 mg/m3	600 mg/m3
Skin	NPI	3.4 mg/kg bw/d	NPI	6 mg/kg bw/d	NPI	11 mg/kg bw/d	NPI	7 mg/kg bw/d

ACETATO DI 1-METIL-2-METOSSIETILE**Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	270	50	270	50	
MAK	DEU	270	50	270	50	
VLA	ESP	275	50	550	100	SKIN
VLEP	FRA	275	50	550	100	SKIN
VLEP	ITA	275	50	550	100	SKIN
TGG	NLD	550				
VLE	PRT	275	50	550	100	SKIN
NDS/NDSch	POL	260		520		SKIN
TLV	ROU	275	50	550	100	SKIN
WEL	GBR	274	50	548	100	SKIN
OEL	EU	275	50	550	100	SKIN

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,635	mg/l
Normal value in marine water	0,0635	mg/l
Normal value for fresh water sediment	3,29	mg/kg
Normal value for marine water sediment	0,329	mg/kg
Normal value of STP microorganisms	100	mg/l
Normal value for the food chain (secondary poisoning)	NPI	
Normal value for the terrestrial compartment	0,29	mg/kg
Normal value for the atmosphere	NPI	

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral	500 mg/kg bw/d		36 mg/kg bw/d	1,67 mg/kg				
Inhalation	NPI	NPI	33 mg/m3	33 mg/m3	550 mg/m3	NPI	NPI	275 mg/m3
Skin	NPI	NPI	NPI	320 mg/kg bw/d	NPI	NPI	NPI	796 mg/kg bw/d

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS TWO PACK VARNISH SATIN COMP.A - Safety Data Sheet - february 2021 - batch 025-BA - rev.1/21

METILISOBUTILCHETONE								
Threshold Limit Value								
Type	Country	TWA/8h		STEL/15min		Remarks / Observations		
		mg/m3	ppm	mg/m3	ppm			
AGW	DEU	83	20	166	40	SKIN		
MAK	DEU	83	20	166	40	SKIN		
VLA	ESP	83	20	208	50			
VLEP	FRA	83	20	208	50			
VLEP	ITA	83	20	208	50			
TGG	NLD	104		208				
VLE	PRT	83	20	208	50			
NDS/NDSch	POL	83		200				
TLV	ROU	83	20	208	50			
WEL	GBR	208	50	416	100	SKIN		
OEL	EU	83	20	208	50			
TLV-ACGIH		82	20	307	75			
Predicted no-effect concentration - PNEC								
Normal value in fresh water				600		µg/L		
Normal value in marine water				60		µg/L		
Normal value for fresh water sediment				8,27		mg/kg/d		
Normal value for marine water sediment				830		µg/kg/dw		
Normal value for water, intermittent release				1,5		mg/l		
Normal value of STP microorganisms				27,5		mg/l		
Normal value for the food chain (secondary poisoning)				NPI				
Normal value for the terrestrial compartment				1,3		mg/kg/d		
Normal value for the atmosphere				NPI				
Health - Derived no-effect level - DNEL / DMEL								
Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral		NPI		4,2 mg/kg/d				
Inhalation	155,2 mg/m3	155,2 mg/m3	14,7 mg/m3	14,7 mg/m3	208 mg/m3	208 mg/m3	83 mg/m3	83 mg/m3
Skin	NPI	NPI		4,2 mg/kg bw/d	NPI	NPI		11,8 mg/kg bw/d
METILETILCHETONE								
Threshold Limit Value								
Type	Country	TWA/8h		STEL/15min		Remarks / Observations		
		mg/m3	ppm	mg/m3	ppm			
AGW	DEU	600	200	600	200	SKIN		
MAK	DEU	600	200	600	200	SKIN		
VLA	ESP	600	200	900	300			
VLEP	FRA	600	200	900	300	SKIN		
VLEP	ITA	600	200	900	300			

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS TWO PACK VARNISH SATIN COMP.A - Safety Data Sheet - february 2021 - batch 025-BA - rev.1/21

TGG	NLD	590		500		SKIN
VLE	PRT	600	200	900	300	
NDS/NDSch	POL	450		900		SKIN
TLV	ROU	600	200	900	300	
WEL	GBR	600	200	899	300	SKIN
OEL	EU	600	200	900	300	
TLV-ACGIH		590	200	885	300	

Predicted no-effect concentration - PNEC	
Normal value in fresh water	55,8 mg/l
Normal value in marine water	55,8 mg/l
Normal value for fresh water sediment	284,74 mg/kg
Normal value for marine water sediment	287,7 mg/kg

Health - Derived no-effect level - DNEL / DMEL								
Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				31 mg/kg				
Inhalation				406 mg/m3				600 mg/m3
Skin				412 mg/kg				1161 mg/kg

3- [3- (2H-Benzotriazol-2-yl) -5- (1,1-dimethylethyl) -4-hydroxyphenyl]-1-oxopropyl]-hydroxypoly (oxo-1,2-ethanediyl)	
Predicted no-effect concentration - PNEC	
Normal value in fresh water	23 µg/L
Normal value in marine water	460 ng/L
Normal value for fresh water sediment	726 mg/kg/dw
Normal value for marine water sediment	726 µg/kg/dw
Normal value of STP microorganisms	100 mg/l
Normal value for the terrestrial compartment	14,52 mg/kg

Health - Derived no-effect level - DNEL / DMEL								
Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				25 µg/kg bw/day				
Inhalation				85 µg/m³			85	350 µg/m³
Skin				25 µg/kg bw/day			25	250 µg/kg bw/day

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS TWO PACK VARNISH SATIN COMP.A - Safety Data Sheet - february 2021 - batch 025-BA - rev.1/21

through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

Exposure levels must be kept as low as possible to avoid significant build-up in the organism. Manage personal protective equipment so as to guarantee maximum protection (e.g. reduction in replacement times).

HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, wear a mask with a type AX filter, whose limit of use will be defined by the manufacturer (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	liquid	
Colour	colourless	
Odour	characteristic of solvent	
Odour threshold	Not available	
pH	Not available	Reason for missing data: la sostanza/miscela è non polare /aprotica
Melting point / freezing point	Not available	
Initial boiling point	> 35 °C	
Boiling range	Not available	
Flash point	23 °C	
Evaporation Rate	Not available	

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS TWO PACK VARNISH SATIN COMP.A - Safety Data Sheet - february 2021 - batch 025-BA - rev.1/21

Flammability of solids and gases	Not available
Lower inflammability limit	Not available
Upper inflammability limit	Not available
Lower explosive limit	Not available
Upper explosive limit	Not available
Vapour pressure	12,84 mmHg
Vapour density	Not available
Relative density	1,08
Solubility	NOT DETECTABLE IN WATER
Partition coefficient: n-octanol/water	Not available
Auto-ignition temperature	Not available
Decomposition temperature	Not available
Viscosity	>20,5 mm ² /sec (40°C)
Explosive properties	Not available
Oxidising properties	Not available

9.2. Other information

Total solids (250°C / 482°F)	54,43 %
VOC (Directive 2010/75/EC) :	45,57 % - 490,43 g/litre
VOC (volatile carbon) :	38,23 % - 409,06 g/litre

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

N-BUTYL ACETATE

Decomposes on contact with: water.

ACETATO DI 1-METIL-2-METOSSIETILE

Stable in normal conditions of use and storage.

Con l'aria può dare lentamente perossidi che esplodono per aumento di temperatura.

METILISOBUTILCHETONE

Reacts violently with: light metals. Attacks various types of plastic materials.

METILETILCHETONE

Reacts with: light metals, strong oxidants. Attacks various types of plastic materials. Decomposes under the effect of heat.

2-ETHYLHEXYL ACRYLATE

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS TWO PACK VARNISH SATIN COMP.A - Safety Data Sheet - february 2021 - batch 025-BA - rev.1/21

Can polymerise, even when stabilised with 20 pm of monomethyl ether hydroquinone.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

XYLENE (MIXTURE OF ISOMERS)

XYLENE (MIXTURE OF ISOMERS): stable, but may develop violent reactions in the presence of strong oxidising agents such as sulphuric and nitric acids and perchlorates. May form explosive mixtures with the air.

N-BUTYL ACETATE

Risk of explosion on contact with: strong oxidising agents. May react dangerously with: alkaline hydroxides, potassium tert-butoxide. Forms explosive mixtures with: air.

ACETATO DI 1-METIL-2-METOSSIETILE

May react violently with: oxidising substances, strong acids, alkaline metals.

METILISOBUTILCHETONE

May react violently with: oxidising agents. Forms peroxides with: air. Forms explosive mixtures with: hot air.

METILETILCHETONE

May form peroxides with: air, light, strong oxidising agents. Risk of explosion on contact with: hydrogen peroxide, nitric acid, sulphuric acid. May react dangerously with: oxidising agents, trichloromethane, alkalis. Forms explosive mixtures with: air.

10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

N-BUTYL ACETATE

Avoid exposure to: moisture, sources of heat, naked flames.

METILISOBUTILCHETONE

Avoid exposure to: sources of heat.

METILETILCHETONE

Avoid exposure to: sources of heat.

10.5. Incompatible materials

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS TWO PACK VARNISH SATIN COMP.A - Safety Data Sheet - february 2021 - batch 025-BA - rev.1/21

N-BUTYL ACETATE

Incompatible with: water,nitrates,strong oxidants,acids,alkalis,zinc.

ACETATO DI 1-METIL-2-METOSSIETILE

Incompatible with: oxidising substances,strong acids,alkaline metals.

METILISOBUTILCHETONE

Incompatible with: oxidising substances,reducing substances.

METILETILCHETONE

Incompatible with: strong oxidants,inorganic acids,ammonia,copper,chloroform.

10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on toxicological effects

XYLENE (MIXTURE OF ISOMERS)

XYLENE (MIXTURE OF ISOMERS): has a toxic effect on the CNS (encephalopathies). Irritating to the skin, conjunctivae, cornea and respiratory apparatus.

Metabolism, toxicokinetics, mechanism of action and other information

ACETATO DI 1-METIL-2-METOSSIETILE

La principale via di entrata è quella cutanea, mentre quella respiratoria è meno importante, data la bassa tensione di vapore del prodotto.

Information on likely routes of exposure

N-BUTYL ACETATE

WORKERS: inhalation; contact with the skin.

ACETATO DI 1-METIL-2-METOSSIETILE

LAVORATORI: inalazione; contatto con la cute.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS TWO PACK VARNISH SATIN COMP.A - Safety Data Sheet - february 2021 - batch 025-BA - rev.1/21

N-BUTYL ACETATE

In humans, the substance's vapours cause irritation of the eyes and nose. In the event of repeated exposure, skin irritation, dermatitis (dryness and cracking of the skin) and keratitis appear.

ACETATO DI 1-METIL-2-METOSSIETILE

Al di sopra di 100 ppm si ha irritazione delle mucose oculari, nasali e orofaringee. A 1000 ppm si notano turbe nell'equilibrio e irritazione severa agli occhi. Gli esami clinici e biologici praticati sui volontari esposti non hanno rivelato anomalie. L'acetato produce maggiore irritazione cutanea ed oculare per contatto diretto. Non vengono riportati effetti cronici sull'uomo (INCR, 2010).

Interactive effects

N-BUTYL ACETATE

A case of acute intoxication been reported involving a 33 year old worker while cleaning a tank with a preparation containing xylenes, butyl acetate and ethylene glycol acetate. The person had irritation of the conjunctiva and upper respiratory tract, drowsiness and motor coordination disorders, which disappeared within 5 hours. The symptoms are attributed to poisoning by mixed xylenes and butyl acetate, with a possible synergistic effect responsible for the neurological effects. Cases of vacuolar keratitis are reported in workers exposed to a mixture of butyl acetate and isobutanol vapours, but with uncertainty concerning the responsibility of a particular solvent (INRC, 2011).

ACUTE TOXICITY

ATE (Inhalation) of the mixture:

> 20 mg/l

ATE (Oral) of the mixture:

Not classified (no significant component)

ATE (Dermal) of the mixture:

>2000 mg/kg

AMORPHOUS SILICATE HYDRATE

LD50 (Oral) > 2000 mg/kg Rat

LD50 (Dermal) > 2000 mg/kg Rat

LC50 (Inhalation) > 2,2 mg/l/1h Rat

ACETATO DI 1-METIL-2-METOSSIETILE

LD50 (Oral) 8500 mg/kg Rat

LD50 (Dermal) > 3160 mg/kg Rat

LC50 (Inhalation) 6193 mg/m³/4h Ratto

METILETILCHETONE

LD50 (Oral) 2737 mg/kg Rat

LD50 (Dermal) 6480 mg/kg Rabbit

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS TWO PACK VARNISH SATIN COMP.A - Safety Data Sheet - february 2021 - batch 025-BA - rev.1/21

LC50 (Inhalation) 23,5 mg//8h Rat

METILISOBUTILCHETONE

LD50 (Oral) 2080 mg/kg Rat

LD50 (Dermal) > 16000 mg/kg Rabbit

LC50 (Inhalation) > 8,2 mg//4h Rat

N-BUTYL ACETATE

LD50 (Oral) > 6400 mg/kg Rat

LD50 (Dermal) > 5000 mg/kg Rabbit

LC50 (Inhalation) 21,1 mg//4h Rat

3- [3- (2H-Benzotriazol-2-yl) -5- (1,1-dimethylethyl) -4-hydroxyphenyl]-1-oxopropyl]-hydroxypoly (oxo-1,2-ethanediyl)

LD50 (Oral) > 5000 mg/kg bw/day RAT

LD50 (Dermal) > 2000 mg/kg bw/day RAT

XYLENE (MIXTURE OF ISOMERS)

LD50 (Oral) 3500 mg/kg Rat

LD50 (Dermal) 4350 mg/kg Rabbit

LC50 (Inhalation) 26 mg//4h Rat

SKIN CORROSION / IRRITATION

Causes skin irritation

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye irritation

RESPIRATORY OR SKIN SENSITISATION

May produce an allergic reaction. Contains: Bis (1,2,2,6,6-penthamethyl-4-piperidyl) sebacate

3- [3- (2H-Benzotriazol-2-yl) -5- (1,1-dimethylethyl) -4-hydroxyphenyl]-1-oxopropyl]-hydroxypoly (oxo-1,2-ethanediyl)

GERM CELL MUTAGENICITY

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS TWO PACK VARNISH SATIN COMP.A - Safety Data Sheet - february 2021 - batch 025-BA - rev.1/21

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

May cause respiratory irritation

STOT - REPEATED EXPOSURE

May cause damage to organs

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class Viscosity: >20,5 mm²/sec (40°C)

SECTION 12. Ecological information

This product is dangerous for the environment and the aquatic organisms. In the long term, it have negative effects on aquatic environment.

12.1. Toxicity

AMORPHOUS SILICATE HYDRATE

LC50 - for Fish	> 1033 mg/l/96h 1.033 - 1.289 g/L
EC50 - for Crustacea	> 5 mg/l/48h
EC50 - for Algae / Aquatic Plants	> 173,1 mg/l/72h

ACETATO DI 1-METIL-2-METOSSIIETILE

LC50 - for Fish	> 100 mg/l/96h Oncorhynchus mykiss
EC50 - for Crustacea	> 408 mg/l/48h Daphnia magna
EC50 - for Algae / Aquatic Plants	> 100 mg/l/72h
Chronic NOEC for Fish	47,5 mg/l Oncothynchus mykiss
Chronic NOEC for Crustacea	> 99 mg/l Daphnia magna
Chronic NOEC for Algae / Aquatic Plants	> 999 mg/l Selenastrum capricornutum

METILETILCHETONE

LC50 - for Fish	> 2,993 mg/l/96h Pimephales promelas
EC50 - for Crustacea	> 508 mg/l/48h Daphnia Magna

METILISOBUTILCHETONE

LC50 - for Fish	> 179 mg/l/96h
-----------------	----------------

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS TWO PACK VARNISH SATIN COMP.A - Safety Data Sheet - february 2021 - batch 025-BA - rev.1/21

EC50 - for Crustacea > 200 mg/l/48h

N-BUTYL ACETATE

LC50 - for Fish > 18 mg/l/96h

EC50 - for Crustacea > 32 mg/l/48h

EC50 - for Algae / Aquatic Plants > 246 mg/l/72h

3- [3- (2H-Benzotriazol-2-yl) -5- (1,1-dimethylethyl) -4-hydroxyphenyl]-1-oxopropyl]-hydroxypoly (oxo-1,2-ethanediyl)

LC50 - for Fish > 2,8 mg/l/96h

EC50 - for Crustacea > 4 mg/l/48h

XYLENE (MIXTURE OF ISOMERS)

LC50 - for Fish > 4,2 mg/l/96h Oncorhynchus mykiss

EC50 - for Crustacea > 2,93 mg/l/48h Daphnia Magna

12.2. Persistence and degradability

AMORPHOUS SILICATE HYDRATE

Solubility in water > 120 mg/l 0,1 - 100

Degradability: information not available

ACETATO DI 1-METIL-2-METOSSIETILE

Solubility in water > 10000 mg/l

Rapidly degradable

ETHYL,3-ETHOXY PROPIONATE

Solubility in water > 10000 mg/l

Rapidly degradable

METILETILCHETONE

Solubility in water > 10000 mg/l

Rapidly degradable

METILISOBUTILCHETONE

Solubility in water > 14,1 g/l

Degradability: information not available

Rapidly degradable

N-BUTYL ACETATE

Solubility in water 5.3 - 14 g/L @ 20 °C mg/l

Rapidly degradable

XYLENE (MIXTURE OF ISOMERS)

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS TWO PACK VARNISH SATIN COMP.A - Safety Data Sheet - february 2021 - batch 025-BA - rev.1/21

Solubility in water 100 - 1000 mg/l

Degradability: information not available

12.3. Bioaccumulative potential

AMORPHOUS SILICATE HYDRATE

Partition coefficient: n-octanol/water 0,53

ACETATO DI 1-METIL-2-METOSSIETILE

Partition coefficient: n-octanol/water 1,2

ETHYL,3-ETHOXY PROPIONATE

Partition coefficient: n-octanol/water 1,47

METILETILCHETONE

Partition coefficient: n-octanol/water 0,3

METILISOBUTILCHETONE

Partition coefficient: n-octanol/water 1,9

N-BUTYL ACETATE

Partition coefficient: n-octanol/water 2,3

BCF 15,3

XYLENE (MIXTURE OF ISOMERS)

Partition coefficient: n-octanol/water 3,12

BCF 25,9

12.4. Mobility in soil

METILISOBUTILCHETONE

Partition coefficient: soil/water 2,008

N-BUTYL ACETATE

Partition coefficient: soil/water < 3

XYLENE (MIXTURE OF ISOMERS)

Partition coefficient: soil/water 2,73

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

12.6. Other adverse effects

Information not available

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS TWO PACK VARNISH SATIN COMP.A - Safety Data Sheet - february 2021 - batch 025-BA - rev.1/21

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

14.1. UN number

ADR / RID, IMDG, 1263
IATA:

14.2. UN proper shipping name

ADR / RID: PAINT or PAINT RELATED MATERIAL
IMDG: PAINT or PAINT RELATED MATERIAL
IATA: PAINT or PAINT RELATED MATERIAL

14.3. Transport hazard class(es)

ADR / RID: Class: 3 Label: 3

IMDG: Class: 3 Label: 3

IATA: Class: 3 Label: 3



14.4. Packing group

ADR / RID, IMDG, III
IATA:

14.5. Environmental hazards

ADR / RID: NO
IMDG: NO
IATA: NO

14.6. Special precautions for user

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS TWO PACK VARNISH SATIN COMP.A - Safety Data Sheet - february 2021 - batch 025-BA - rev.1/21

ADR / RID:	HIN - Kemler: 30	Limited Quantities: 5 L	Tunnel restriction code: (D/E)
	Special Provision: -		
IMDG:	EMS: F-E, <u>S-E</u>	Limited Quantities: 5 L	
IATA:	Cargo:	Maximum quantity: 220 L	Packaging instructions: 366
	Pass.:	Maximum quantity: 60 L	Packaging instructions: 355
	Special Instructions:	A3, A72, A192	

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EC: P5c

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product Point
3 - 40

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage \geq than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS TWO PACK VARNISH SATIN COMP.A - Safety Data Sheet - february 2021 - batch 025-BA - rev.1/21

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

German regulation on the classification of substances hazardous to water (AwSV, vom 18. April 2017)

WGK 2: Hazard to waters

15.2. Chemical safety assessment

A chemical safety assessment has been performed for the following contained substances

XYLENE (MIXTURE OF ISOMERS)

N-BUTYL ACETATE

ACETATO DI 1-METIL-2-METOSSIETILE

METILISOBUTILCHETONE

METILETILCHETONE

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 2	Flammable liquid, category 2
Flam. Liq. 3	Flammable liquid, category 3
Acute Tox. 4	Acute toxicity, category 4
Asp. Tox. 1	Aspiration hazard, category 1
STOT RE 2	Specific target organ toxicity - repeated exposure, category 2
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
STOT SE 3	Specific target organ toxicity - single exposure, category 3
Skin Sens. 1	Skin sensitization, category 1
Aquatic Acute 1	Hazardous to the aquatic environment, acute toxicity, category 1
Aquatic Chronic 1	Hazardous to the aquatic environment, chronic toxicity, category 1
Aquatic Chronic 2	Hazardous to the aquatic environment, chronic toxicity, category 2
Aquatic Chronic 3	Hazardous to the aquatic environment, chronic toxicity, category 3
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H312	Harmful in contact with skin.
H332	Harmful if inhaled.
H304	May be fatal if swallowed and enters airways.
H373	May cause damage to organs through prolonged or repeated exposure.
H319	Causes serious eye irritation.

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS TWO PACK VARNISH SATIN COMP.A - Safety Data Sheet - february 2021 - batch 025-BA - rev.1/21

H315	Causes skin irritation.
H335	May cause respiratory irritation.
H317	May cause an allergic skin reaction.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
 3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
 4. Regulation (EU) 2015/830 of the European Parliament
 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
 13. Regulation (EU) 2017/776 (X Atp. CLP)
 14. Regulation (EU) 2018/669 (XI Atp. CLP)
 15. Regulation (EU) 2018/1480 (XIII Atp. CLP)
 16. Regulation (EU) 2019/521 (XII Atp. CLP)
- The Merck Index. - 10th Edition

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS TWO PACK VARNISH SATIN COMP.A - Safety Data Sheet - february 2021 - batch 025-BA - rev.1/21

- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Changes to previous review:

The following sections were modified:

08 / 09 / 10 / 11 / 12 / 15.