

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it

DECO-DECK GTS - SAFETY DATA SHEET - june 2021 - n° batch 168-BI - rev.1/19

DECO-DECK GTS Gloss Transparent Solvent based

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

Trade name:

DECO-DECK GTS Gloss Transparent Solvent based

UFI:

PJ10-10UD-Q00X-KS00

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance / the mixture: waterproofing coating

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

CECCHI GUSTAVO & C. SRL.

Via M.Coppino, 253 55049 VIAREGGIO (LU) ITALY

TEL. +39 0584 383694 FAX +39 0584 395182

· 1.4 Emergency telephone number:

+39 0584/383694 From monday to friday office hours 8:30 – 12:30, 14:00 – 18:30 - info@cecchi.it

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation EC No 1272/2008 CLP:

GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS08 health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled. STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction. STOT SE 3 H335 May cause respiratory irritation.

2.2 Label elements

Labelling according to Regulation EC No 1272/2008 CLP:

The product is classified and labelled according to the CLP regulation.

GB

(Contd. on page 2)

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it

DECO-DECK GTS - SAFETY DATA SHEET - june 2021 - n° batch 168-BI - rev.1/19

(Contd. of page 1)

Hazard pictograms:



GHS02 GHS07 GHS08

Signal word: Danger

Hazard-determining components of labelling:

Xylene

1,6-hexanediyl-bis(2-(2-(1-ethylpentyl)-3-oxazolidinyl)ethyl)carbamate 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate

3-Isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate, oligomers Distillates (petroleum), hydrotreated light ethylbenzene

Hazard statements:

H226 Flammable liquid and vapour. H315 Causes skin irritation.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled. H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure. H304 May be fatal if swallowed and enters airways.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P260 Do not breathe dust/fume/gas/mist/vapours/spray. P264 Wash hands thoroughly after handling.

P280 Wear protective gloves/protective clothing/eye protection/face protection. P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P331 Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P370+P378 In case of fire: Use for extinction: CO₂, powder or water spray. P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.




2.3 Other hazards

Results of PBT and vPvB

assessment PBT: Not applicable.

vPvB: Not applicable.

SECTION 3: Composition/information on ingredients**3.2 Chemical characterisation: Mixtures****Description:** Mixture: consisting of the following components.

Ingredients according Regulation (EU) 830/2015:		
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32-XXXX	Xylene Flam. Liq. 3, H226; STOT RE 2, H373; Asp. Tox. 1, H304;  Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	10-25%
CAS: 108-65-6 EINECS: 203-603-9 Index number: 607-195-00-7 Reg.nr.: 01-2119475791-29-XXXX	2-methoxy-1-methylethyl acetate Flam. Liq. 3, H226	10-25%
CAS: 140921-24-0 ELINCS: 411-700-4 Index number: 616-079-00-5 Reg.nr.: 01-0000015906-63-XXXX	1,6-hexanediyl-bis(2-(2-(1-ethylpentyl)-3-oxazolidinyl)ethyl) carbamate Skin Sens. 1, H317	2.5-10%
CAS: 53880-05-0 NLP: 500-125-5 Reg.nr.: 01-2119488734-24-XXXX	3-Isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate, oligomers Skin Sens. 1, H317; STOT SE 3, H335	2.5-10%
CAS: 64742-47-8 EINECS: 265-149-8 Index number: 649-422-00-2 Reg.nr.: 01-2119484819-18-XXXX	Distillates (petroleum), hydrotreated light Asp. Tox. 1, H304	≤2.5%
CAS: 100-41-4 EINECS: 202-849-4 Index number: 601-023-00-4	ethylbenzene Flam. Liq. 2, H225; STOT RE 2, H373; Asp. Tox. 1, H304;  Acute Tox. 4, H332	≤2.5%
CAS: 4098-71-9 EINECS: 223-861-6 Index number: 615-008-00-5 Reg.nr.: 01-2119490408-31-XXXX	3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate Acute Tox. 3, H331; Resp. Sens. 1, H334; Aquatic Chronic 2, H411;  Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	≥0.5-<1%

SECTION 4: First aid measures**4.1 Description of first aid measures****General information:**

Take affected persons out into the fresh air.

Seek immediate medical advice.

After inhalation:

Keep patient calm, remove to fresh air.

In case of unconsciousness place patient stably in side position for transportation.

Seek immediate medical advice.

After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Seek immediate medical advice.

After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

Remove contact lenses and continue rinsing for several minutes

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY
tel. +39 0584 383694 fax +39 0584 395182
www.cecchi.it info@cecchi.it

DECO-DECK GTS - SAFETY DATA SHEET - june 2021 - n° batch 168-BI - rev.1/19

(Contd. of page 3)

Avoid strong water jet-risk of cornea damage, consult a doctor.

After swallowing:

Call for a doctor immediately.

Do not induce vomiting; call for medical help immediately.

Drink plenty of water and provide fresh air. Call for a doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

Contact Poison Center or doctor. All treatments should be based on observed signs and symptoms of patient pain.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents: CO₂, powder or water spray. Fight larger fires with water spray.

For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture No further relevant information available.

5.3 Advice for firefighters

Protective equipment:

During fire-fighting wear suitable respiratory device (SCBA) with a full face-piece operated in positive pressure mode.

Cool containers exposed to fire.

Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures:

Wear protective equipment. Keep unprotected persons away.

Keep away from ignition sources.

Avoid contact with spilled material.

Avoid inhalation of vapors.

Ensure adequate ventilation.

Avoid contact with the skin, eyes and clothing.

6.1.1 For non-emergency personnel Avoid contact with dripping or leaking material

6.1.2 For emergency responders Use safety goggles, in case of contact with the eyes.

6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust, silica gel).

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

6.4 Reference to other sections:

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

(Contd. on page 5)

GB

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it

DECO-DECK GTS - SAFETY DATA SHEET - june 2021 - n° batch 168-BI - rev.1/19

(Contd. of page 4)

Keep away from heat and direct sunlight.

Avoid inhaling vapors.

Avoid contact with eyes, hands and clothing.

Ensure good ventilation.

Wash contaminated clothing before reuse.

Wash hands before each break and after finishing work.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

7.2 Conditions for safe storage, including any incompatibilities

Storage: Store the product in closed original containers in a well-ventilated room.

Requirements to be met by storerooms and receptacles:

Store in a cool location.

Provide ventilation for receptacles.

Information about storage in one common storage facility: Store away from oxidizing agents.

Further information about storage conditions:

Store under lock and key and with access restricted to technical experts or their assistants only.

Keep container tightly sealed.

Protect from heat and direct sunlight.

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

CAS: 1330-20-7 Xylene

WEL (Great Britain)	Short-term value: 441 mg/m ³ , 100 ppm Long-term value: 220 mg/m ³ , 50 ppm Sk; BMGV
---------------------	---

IOELV (EU)	Short-term value: 442 mg/m ³ , 100 ppm Long-term value: 221 mg/m ³ , 50 ppm Skin
------------	---

CAS: 108-65-6 2-methoxy-1-methylethyl acetate

WEL (Great Britain)	Short-term value: 548 mg/m ³ , 100 ppm Long-term value: 274 mg/m ³ , 50 ppm Sk
---------------------	---

IOELV (EU)	Short-term value: 550 mg/m ³ , 100 ppm Long-term value: 275 mg/m ³ , 50 ppm Skin
------------	---

CAS: 4098-71-9 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate

WEL (Great Britain)	Short-term value: 0.07 mg/m ³ Long-term value: 0.02 mg/m ³ Sen; as -NCO
---------------------	---

DNELs

xylene(cas: 1330-20-7)

workers

(Contd. on page 6)

GB

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it

DECO-DECK GTS - SAFETY DATA SHEET - june 2021 - n° batch 168-BI - rev.1/19

(Contd. of page 5)

oral, long term systemic effects -
dermal, long term systemic effects 180 mg/kg
bw/day inhalation, long term systemic effects 77
mg/m³ consumers

oral, long term systemic effects 1,6 mg/kg
bw/day dermal, long term systemic effects 108
mg/kg bw/day inhalation, long term systemic
effects 14,8 mg/m³ **PNECs**

Xylol (cas: 1330-20-7)

Fresh water: 0.327 mg / l

(-)

Marine water: 0.327 mg / l (-)

Intermittent releases: 0.327 mg / l (-)

) Fresh water sediment: 12.46 mg /

l (-) Marine water sediment: 12.46

mg / l (-) Soil: 2.31 mg / kg (-)

STP: 6.58 mg / l (-)

Ingredients with biological limit values:	
CAS: 1330-20-7 Xylene	
BMGV (Great Britain)	650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid
CAS: 4098-71-9 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate	
BMGV (Great Britain)	1 µmol creatinine/mol Medium: urine Sampling time: At the end of the period od exposure Parameter: isocyanate-derived diamine

8.2 Exposure controls

8.2.1. Appropriate engineering controls

Take appropriate protective measures with regard to the handling of chemicals and mixtures.

Personal protective equipment

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed. Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin.

Take appropriate protective measures with regard to the handling of chemicals and mixtures. Do not eat, drink or smoke while using the product.

Ensure adequate ventilation during use.

Respiratory protection:



If worker exposure is likely to exceed work exposure levels, wear a respiratory conforming to EN 140 with type A/P2 filter or better.

(Contd. on page 7)

GB

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it

DECO-DECK GTS - SAFETY DATA SHEET - june 2021 - n° batch 168-BI - rev.1/19

(Contd. of page 6)

Protection of hands:

Wear suitable gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

PVC (polyvinyl chloride)

Butyl rubber, BR - 0,7 mm

Nitrile rubber, NBR- 0,4 mm

0.4mm thickness, permeation time > 480 min

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The determined penetration times according to EN 374 part III are not performed under practical conditions.

Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

Eye protection:



Safety glasses with side-shields (frame goggles) (e.g. EN 166)

Body protection:



Chemically resistant, protective work clothing (EN 14605) and boots.
Use protective clothing.

Environmental exposure controls:

Dispose of flushing liquids in accordance with local and national regulations.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Appearance:

Form:	Liquid
Colour:	Transparent
Odour:	Characteristic
Odour threshold:	Not determined

pH value: Not determined

Melting point/freezing point: Not determined

Flash point: 27-32 °C (xylene)

Flammability (solid, gas): Not applicable

(Contd. on page 8)

GB

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it

DECO-DECK GTS - SAFETY DATA SHEET - june 2021 - n° batch 168-BI - rev.1/19

(Contd. of page 7)

Auto-ignition temperature:	Not determined
Decomposition temperature:	Not determined
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
Explosion limits:	
Lower:	Not determined
Upper:	Not determined
Oxidising properties	Not considered as oxidising.
Vapour pressure:	Not determined
Density at 20 °C:	1 g/cm ³
Relative density	Not determined
Vapour density	Not determined
Evaporation rate	Not determined
Solubility in / Miscibility with water:	Fully miscible
Partition coefficient: n-octanol/water:	Not determined
Viscosity:	
Dynamic at 20 °C:	>40 mPas (ISO 2431:1993)
Kinematic:	Not determined
Solvent content:	
VOC (EC)	410 g/l
9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

10.1 Reactivity No further relevant information available.

10.2 Chemical stability

Thermal decomposition / conditions to be avoided Stable at environment temperature.

10.3 Possibility of hazardous reactions No dangerous reactions known.

10.4 Conditions to avoid Avoid heat, sparkles, naked flame or other sources of ignition.

10.5 Incompatible materials No further relevant information available.

10.6 Hazardous decomposition products No dangerous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity Based on available data, the classification criteria are not met.

(Contd. on page 9)

GB

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it

DECO-DECK GTS - SAFETY DATA SHEET - june 2021 - n° batch 168-BI - rev.1/19

(Contd. of page 8)

LD/LC50 values relevant for classification:		
ATE (Acute Toxicity Estimates)		
Dermal	LD50	4,864 mg/kg
Inhalative	LC50/4 h (vapour)	44.2 mg/l
CAS: 108-65-6 2-methoxy-1-methylethyl acetate		
Oral	LD50	8,532 mg/kg (rat)

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.

Sensitisation Sensitization possible through skin contact

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met. **Reproductive toxicity** Based on available data, the classification criteria are not met.

STOT-single exposure

The product is classified as Specific Target Organ Toxicity after single exposure Category 3 May cause respiratory irritation.

STOT-repeated exposure

STOT Repeated Exposure Category 2

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard

The product is classified Aspiration toxicity Category 1

May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity:

CAS: 108-65-6 2-methoxy-1-methylethyl acetate	
EC50 (48h)	>500 mg/l (daphnia magna) 100-180 mg/l (Con)
LC50 (96h)	

12.2 Persistence and degradability No further relevant information available.

12.3 Bioaccumulative potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

12.5 Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

12.6 Other adverse effects No further relevant information available.

GB

(Contd. on page 10)

SECTION 13: Disposal considerations**13.1 Waste treatment methods****Recommendation**

Dispose according to National Regulations.



Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Uncleaned packaging:**Recommendation:**

Disposal must be made according to official regulations.

Packaging may be reused or recycled after cleaning.

SECTION 14: Transport information**14.1 UN-Number****ADR, IMDG, IATA**

UN1866

14.2 UN proper shipping name**ADR**

1866 RESIN SOLUTION

IMDG, IATA

RESIN SOLUTION

14.3 Transport hazard class(es)**ADR, IMDG, IATA****Class**

3 Flammable liquids.

Label

3

14.4 Packing group**ADR, IMDG, IATA**

III

14.5 Environmental hazards:

Not applicable.

14.6 Special precautions for user

Warning: Flammable liquids.

Danger code (Kemler):

30

EMS Number:

F-E,S-D

Stowage Category

A

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable.

Transport/Additional information:**ADR****Limited quantities (LQ)**

5L

Excepted quantities (EQ)

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it

DECO-DECK GTS - SAFETY DATA SHEET - june 2021 - n° batch 168-BI - rev.1/19

(Contd. of page 10)

Transport category	3
Tunnel restriction code	D/E
Remarks:	No goods of grade 3 according to 2.2.3.1.5 ADR and 2.3.2.5 IMDG ADR: Containers >450 l = UN 1866 - 3(F1) - RESIN SOLUTION, flammable IMDG: Containers > 30 l = UN 1866 - 3 (F1) - RESIN SOLUTION, flammable Outside ADR/IMDG = UN 1866 - 3 (F1) - RESIN SOLUTION, flammable
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
Remarks:	No goods of grade 3 according to 2.2.3.1.5 ADR and 2.3.2.5 IMDG ADR: Containers >450 l = UN 1866 - 3(F1) - RESIN SOLUTION, flammable IMDG: Containers > 30 l = UN 1866 - 3 (F1) - RESIN SOLUTION, flammable Outside ADR/IMDG = UN 1866 - 3 (F1) - RESIN SOLUTION, flammable
UN "Model Regulation":	UN 1866 RESIN SOLUTION, 3, III

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH Regulation

1907/2006/EC Regulation (EU)

2015/830

CLP Regulation 1272/2008/EC

Directive 98/24/EC on the protection of health and safety of workers from the risks related to chemicals agents at work.

Directive 94/62/EC on packaging and packaging waste.

Council Directive 94/33/EC on the protection of young people at work, as ammended.

Directive 92/85/EEC on the introduction of measures to encourage improvements in the safety and health at work of pregnant workers and workers who have recently given birth or are breastfeeding, as ammended

Directive 2012/18/EU

Seveso category P5c FLAMMABLE LIQUIDS

Qualifying quantity (tonnes) for the application of lower-tier requirements

5,000 t Qualifying quantity (tonnes) for the application of upper-tier

requirements 50,000 t REGULATION (EC) No 1907/2006 ANNEX XVII Conditions

of restriction: 3

National regulations:

Other regulations, limitations and prohibitive regulations

Substances of very high concern (SVHC) according to REACH, Article 57

It doesn't contain substances of very high concern (SVHC).

(Contd. on page 12)

GB

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H225 Highly flammable liquid and vapour. H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways. H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.

H331 Toxic if inhaled.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled. H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure. H411 Toxic to aquatic life with long lasting effects.

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous

Goods IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of

Chemicals EINECS: European Inventory of Existing Commercial Chemical

Substances ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration

(REACH) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern

vPvB: very Persistent and very

Bioaccumulative Flam. Liq. 2: Flammable

liquids – Category 2 Flam. Liq. 3:

Flammable liquids – Category 3 Acute Tox.

4: Acute toxicity – Category 4 Acute Tox. 3:

Acute toxicity – Category 3

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category

2 Resp. Sens. 1: Respiratory sensitisation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category

3 STOT RE 2: Specific target organ toxicity (repeated exposure) –

Category 2 Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2