



SPINNAKER STANDARD YACHT VARNISH

*SECTION 1 Identification of the substance/preparation and of the company/undertaking

- 1.1 Product identifier
- Trade name: SPINNAKER STANDARD YACHT VARNISH

UFI: SM00-G081-C00H-90K9

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

- Product category PC9a Coatings and paints, thinners, paint removers
 - Process category PROC10 Roller application or brushing
 - Environmental release category
ERC10a Wide dispersive outdoor use of long-life articles and materials with low release
ERC2 Formulation of preparations
 - Application of the substance / the mixture
- See our technical datasheet for application of this product.

· 1.3 Details of the supplier of the safety data sheet

- Manufacturer/Supplier:

Cecchi Gustavo & C. srl - Via M. Coppino 253, 55049 Viareggio (LU) ITALY www.cecchi.it - info@cecchi.it

· 1.4 Emergency telephone number:

: +39 0584/383694 - info@cecchi.it

From monday to friday office hours 8:30 – 12:30, 14:00 – 18:30

SECTION 2: Hazards identification

- 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS07

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H336 May cause drowsiness or dizziness.

(Contd. on page 2)



Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008
The product is classified and labelled according to the CLP regulation.
- Hazard pictograms



GHS02



GHS07

- Signal word **Warning**
- Hazard-determining components of labelling:
Naphtha (petroleum), hydrotreated heavy cobalt bis(2-ethylhexanoate)
- Hazard statements
H226 Flammable liquid and vapour.
H317 May cause an allergic skin reaction.
H336 May cause drowsiness or dizziness.
H412 Harmful to aquatic life with long lasting effects.
- Precautionary statements
P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260 Do not breathe dust/fume/gas/mist/vapours/spray.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- Additional information:
EUH066 Repeated exposure may cause skin dryness or cracking.
Contains cobalt carboxylate, can cause an allergic reaction.
- 2.3 Other hazards
- Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.

* **SECTION 3: Composition/information on ingredients**

- 3.2 Chemical characterisation: Mixtures
- Description: Mixture of substances listed below with nonhazardous additions.

(Contd. on page 3)



· Dangerous components:		
EC number: 919-857-5 Index number: 649-327-00-6 Reg.nr.: 01-2119463258-33	Naphtha (petroleum), hydrotreated heavy Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H336	25-50%
CAS: 34590-94-8 EINECS: 252-104-2 Reg.nr.: 01-2119450011-60	Dipropylene glycol monomethyl ether substance with a Community workplace exposure limit	≤2.5%
CAS: 136-52-7 EINECS: 205-250-6 Reg.nr.: 01-2119524678-29	Cobalt bis(2-ethylhexanoate) Repr. 1B, H360F Aquatic Acute 1, H400; Aquatic Chronic 1, H410 Eye Irrit. 2, H319; Skin Sens. 1A, H317	<0.3%
CAS: 98-54-4 EINECS: 202-679-0 Index number: 604-090-00-8 Reg.nr.: 01-2119489419-21	tert-butylphenol Repr. 2, H361f Eye Dam. 1, H318 Aquatic Chronic 1, H410 Skin Irrit. 2, H315	<0.3%
CAS: 140-66-9 EINECS: 205-426-2 Index number: 604-075-00-6 Reg.nr.: 01-2119541687-29	(1,1,3,3-tetramethylbutyl)phenol Eye Dam. 1, H318 Aquatic Acute 1, H400; Aquatic Chronic 1, H410 Skin Irrit. 2, H315	<0.3%
· SVHC		
· Additional information:		
Note P: The substance does not have to be classified as a carcinogen or mutagen as shown in Part 3.		
Note R: The substance contains less than 0.1% (w / w) benzene (EINECS No 200-753-7.). This note applies only to certain complex oil-derived substances in Part 3.		
For the wording of the listed hazard phrases refer to section 16.		

SECTION 4: First aid measures

- 4.1 Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- After inhalation:
 Supply fresh air and to be sure call for a doctor.
 In case of unconsciousness place patient stably in side position for transportation.
- After skin contact:
 Immediately wash with water and soap and rinse thoroughly.
 Immediately rinse with water.
- After eye contact: Rinse opened eye for several minutes under running water.

(Contd. on page 4)



(Contd. of page 3)

- After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed
No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed
No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents:
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture
During heating or in case of fire poisonous gases are produced.
- 5.3 Advice for firefighters
- Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions:
Prevent seepage into sewage system, workpits and cellars.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- 6.4 Reference to other sections
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- Information about fire - and explosion protection:
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.

(Contd. on page 5)



(Contd. of page 4)

- 7.2 Conditions for safe storage, including any incompatibilities
- Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- 8.1 Control parameters
- Additional information about design of technical facilities:
No further data; see item 7.

- Ingredients with limit values that require monitoring at the workplace:

34590-94-8 Dipropylene glycol monomethyl ether

WEL	Long-term value: 308 mg/m ³ , 50 ppm Sk
-----	---

136-52-7 cobalt bis(2-ethylhexanoate)

WEL	Long-term value: 0.1 mg/m ³ as Co; Carc, Sen
-----	--

34590-94-8 Dipropylene glycol monomethyl ether

WEL	Long-term value: 308 mg/m ³ , 50 ppm Sk
-----	---

136-52-7 cobalt bis(2-ethylhexanoate)

WEL	Long-term value: 0.1 mg/m ³ as Co; Carc, Sen
-----	--

- Regulatory information WEL: EH40/2020

- DNELs

Naphtha (petroleum), hydrotreated heavy

Dermal	Long-term - systemic effects, worker	300 mg/kg bw/day (Werker/Worker)
--------	---	----------------------------------

Inhalative	Long-term - systemic effects, worker	1,500 mg/m ³ (Werker/Worker)
------------	---	---

- Additional information: The lists valid during the making were used as basis.

- 8.2 Exposure controls

- Personal protective equipment:

- General protective and hygienic measures:

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

- Respiratory protection:

Not necessarily with good ventilation, however, use a filter AX when ventilation is inadequate!

(Contd. on page 6)

- **Protection of hands:**
Use gloves of stable material (e.g. Nitrile) - if necessary tricoted to improve the wearability.

**Protective gloves**

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**
The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **For the permanent contact gloves made of the following materials are suitable: nitrile rubber;**
recommended glove thickness > 0.45mm. permeability / permeation time:> 480 min. according to EN 374.
- **As protection from splashes gloves made of the following materials are suitable:**
Cloropene; handglove thickness >0.7mm, penetration time >60min. according EN374.
Nitrilrubber; handglove thickness >0.3mm, penetration time >60min. according EN374.
- **Eye protection:**

**Tightly sealed goggles**

* **SECTION 9: Physical and chemical properties**

- 9.1 Information on basic physical and chemical properties
- General Information
- Appearance:

Form:	Fluid
Colour:	According to product specification
- Odour: Characteristic
- Odour threshold: Not determined.
- pH-value at 20 °C: 7

(Contd. on page 7)



· Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	150 °C
· Flash point:	36 °C
· Flammability (solid, gas):	Not applicable.
· Ignition temperature:	205 °C
· Decomposition temperature:	Not determined.
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
· Vapour pressure:	Not determined.
· Density at 20 °C:	0.91311 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/ water:	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic at 20 °C:	50 s (ISO 4 mm)
· Solvent content:	
Organic solvents:	42.3 %
VOC content:	42.26 %
	VOC content:
	385.8 g/l / 3.22 lb/gal
Solids content:	57.4 %
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:
No decomposition if used according to specifications.

(Contd. on page 8)



- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products:
No dangerous decomposition products known.

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

· Acute toxicity

Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

Naphtha (petroleum), hydrotreated heavy

Oral	LD50	>5,000 mg/kg bw (rat)
Dermal	LD50	>5,000 mg/kg bw (rabbit) ((24h))
Inhalative	LC50	>5,000 mg/m ³ (vapour) (rat) ((8h))

34590-94-8 Dipropylene glycol monomethyl ether

Oral	LD50	5,135 mg/kg bw (rat)
Dermal	LD50	>19,000 mg/kg bw (rab)

136-52-7 cobalt bis(2-ethylhexanoate)

Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50 (Konijn)	5,000 mg/kg (rabbit)

98-54-4 4-tert-butylphenol

Oral	LD50	2,951 mg/kg bw (rat)
Dermal	LD50	2,288 mg/kg bw (rabbit)

140-66-9 4-(1,1,3,3-tetramethylbutyl)phenol

Oral	LD50	3,210 mg/kg bw (mouse)
------	------	------------------------

· Primary irritant effect:

· Skin corrosion/irritation

Based on available data, the classification criteria are not met.

· Serious eye damage/irritation

Based on available data, the classification criteria are not met.

· Respiratory or skin sensitisation

May cause an allergic skin reaction.

· Additional toxicological information:

· CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

· Germ cell mutagenicity

Based on available data, the classification criteria are not met.

· Carcinogenicity

Based on available data, the classification criteria are not met.

· Reproductive toxicity

Based on available data, the classification criteria are not met.

· STOT-single exposure

May cause drowsiness or dizziness.

· STOT-repeated exposure

Based on available data, the classification criteria are not met.

(Contd. on page 9)



(Contd. of page 8)

- Aspiration hazard
Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1 Toxicity

- Aquatic toxicity:

Naphtha (petroleum), hydrotreated heavy

ErL (72h)	>1,000 mg/l (Pseudokirchneriella subcapitata-OECD 201)
EL50 (48h)	>1,000 mg/l ((Daphnia magna-OECD 202))
LL50 (96h)	>1,000 mg/l ((Onorhynchus mykiss OECD 203))
EbL50 (72h)	>1,000 mg/l (Pseudokirchneriella subcapitata-OECD 201)
NOELR (72h)	3 mg/l ((Pseudo. subcapitata-biomass-OECD 201))
	100 mg/l ((Pseudo. subcap. growth rate OECD 201))

136-52-7 cobalt bis(2-ethylhexanoate)

LC50	0.1-1 mg/l (Fish Acute Toxicity Study)
EC50	0.1-1 mg/l (daphnia magna)
EC50	0.1-1 mg/l (Algae, Growth inhibition test)

- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- Ecotoxicological effects:
- Remark: Harmful to fish
- Additional ecological information:
- General notes:
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
Harmful to aquatic organisms
- 12.5 Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- 13.1 Waste treatment methods
- Recommendation
Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- European waste catalogue

08 00 00	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS
----------	---



(Contd. on page 10)



08 01 00	wastes from MFSU and removal of paint and varnish
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances

- Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

· 14.1 UN-Number	UN1263
· ADR, IMDG, IATA	
· 14.2 UN proper shipping name	1263 PAINT
· ADR	1263 PAINT
· IMDG, IATA	PAINT
· 14.3 Transport hazard class(es)	
· ADR	
	
· Class	3 (F1) Flammable liquids.
· Label	3
· IMDG, IATA	
	
· Class	3 Flammable liquids.
· Label	3
· 14.4 Packing group	III
· ADR, IMDG, IATA	
· 14.5 Environmental hazards:	
· Marine pollutant:	No
· 14.6 Special precautions for user	Warning: Flammable liquids.
· Hazard identification number (Kemler code):	30
· EMS Number:	F-E, S-E
· Stowage Category	A
· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging:

(Contd. on page 11)



<ul style="list-style-type: none"> • Transport category • Tunnel restriction code • Remarks: 	<p>30 ml Maximum net quantity per outer packaging: 1000 ml</p> <p>3 D/E Packaging <450L: exemption viscous substances according to 2.2.3.1.5</p>
<ul style="list-style-type: none"> • IMDG • Limited quantities (LQ) • Excepted quantities (EQ) • Remarks: 	<p>5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml</p> <p>≤ 30 l: -</p>
<ul style="list-style-type: none"> • UN "Model Regulation": 	<p>UN 1263 PAINT, 3, III</p>

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
 - Directive 2012/18/EU
 - Named dangerous substances - ANNEX I None of the ingredients is listed.
 - Seveso category P5c FLAMMABLE LIQUIDS
 - Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
 - Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
 - REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
 - DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment - Annex II
- None of the ingredients is listed.

- National regulations:
- Technical instructions (air):

Class	Share in %
NK	25-50

- Waterhazard class:
Water hazard class 1 (Self-assessment): slightly hazardous for water.
- Other regulations, limitations and prohibitive regulations

- Substances of very high concern (SVHC) according to REACH, Article 57

98-54-4	4-tert-butylphenol
140-66-9	4-(1,1,3,3-tetramethylbutyl)phenol

(Contd. on page 12)



- 15.2 Chemical safety assessment:
A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Relevant phrases

- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.
- H360F May damage fertility.
- H361f Suspected of damaging fertility.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.

- Abbreviations and acronyms:

- RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
- ICAO: International Civil Aviation Organisation
- ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- VOC: Volatile Organic Compounds (USA, EU)
- DNEL: Derived No-Effect Level (REACH)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- SVHC: Substances of Very High Concern
- vPvB: very Persistent and very Bioaccumulative
- Flam. Liq. 3: Flammable liquids - Category 3
- Skin Irrit. 2: Skin corrosion/irritation - Category 2
- Eye Dam. 1: Serious eye damage/eye irritation - Category 1
- Eye Irrit. 2: Serious eye damage/eye irritation - Category 2
- Skin Sens. 1: Skin sensitisation - Category 1
- Skin Sens. 1A: Skin sensitisation - Category 1A
- Repr. 1B: Reproductive toxicity - Category 1B
- Repr. 2: Reproductive toxicity - Category 2
- STOT SE 3: Specific target organ toxicity (single exposure) - Category 3
- Asp. Tox. 1: Aspiration hazard - Category 1
- Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1
- Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1
- Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

- * Data compared to the previous version altered.