

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS TWO PACK VARNISH GLOSS Component A - SAFETY DATA SHEET - july 2021 - n°batch 190-BA - rev. 1/2020

Safety data sheet

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name **NAUTILUS TWO PACK VARNISH GLOSS COMP.A**
 UFI: **KH60-DOVE-G00N-XJSR**

1.2. Relevant identified uses of the substance or mixture and uses advised againstIntended use **VERNICE MARINA A BASE DI POLIMERI ALCHIDICI**

Identified Uses	Industrial	Professional	Consumer
Prodotto verniciante per nautica - marina	-	<input type="checkbox"/>	-
Prodotto verniciante per usi industriali	<input type="checkbox"/>	-	-
Prodotto verniciante per uso professionale	-	<input type="checkbox"/>	-
Uses Advised Against			
CONSUMATORE: FAI-DA-TE			

1.3 Details of the supplier of the safety data sheet Manufacturer/Supplier:

Cecchi Gustavo & C. srl - Via M. Coppino 253,
 55049 Viareggio (LU) ITALY www.cecchi.it - info@cecchi.it

1.4 Emergency telephone number:

+39 0584/383694 - info@cecchi.it

From monday to friday office hours 8:30 - 12:30, 14:00 - 18:30

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2015/830. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Flammable liquid, category 3	H226	Flammable liquid and vapour.
Eye irritation, category 2	H319	Causes serious eye irritation.
Specific target organ toxicity - single exposure, category 3	H336	May cause drowsiness or dizziness.
Hazardous to the aquatic environment, chronic toxicity, category 3	H412	Harmful to aquatic life with long lasting effects.

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS TWO PACK VARNISH GLOSS Component A - SAFETY DATA SHEET - july 2021 - n°batch 190-BA - rev. 1/2020

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words:

Warning

Hazard statements:

H226	Flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH208	Contains: Bis (1,2,2,6,6-pentamethyl-4-piperidyl) sebacate, 3- [3- (2H-Benzotriazol-2-yl) -5- (1,1-dimethylethyl) -4-hydroxyphenyl]-1-oxopropyl]-hydroxypoly (oxo-1,2-ethanediyl) May produce an allergic reaction.

Precautionary statements:

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280	Wear protective gloves/ protective clothing / eye protection / face protection.
P370+P378	In case of fire: use . . . to extinguish.
P261	Avoid breathing dust / fume / gas / mist / vapours / spray.
P312	Call a POISON CENTRE / doctor / . . . if you feel unwell.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.

Contains: 2-METHOXY-1-METHYLETHYL ACETATE
N-BUTYL ACETATE

Product not intended for uses provided for by Dir. 2004/42/CE.

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS TWO PACK VARNISH GLOSS Component A - SAFETY DATA SHEET - july 2021 - n°batch 190-BA - rev. 1/2020

SECTION 3. Composition/information on ingredients**3.2. Mixtures**

Contains:

Identification	x = Conc. %	Classification 1272/2008 (CLP)
2-METHOXY-1-METHYLETHYL ACETATE		
CAS 108-65-6	22 ≤ x < 25	Flam. Liq. 3 H226, STOT SE 3 H336
EC 203-603-9		
INDEX 607-195-00-7		
Reg. no. 01-2119475791-29-XXXX		
XYLENE (MIXTURE OF ISOMERS)		
CAS 1330-20-7	9 ≤ x < 10	Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Aquatic Chronic 3 H412, Classification note according to Annex VI to the CLP Regulation: C
EC 215-535-7		
INDEX 601-022-00-9		
Reg. no. 01-2119488216-32-XXXX		
N-BUTYL ACETATE		
CAS 123-86-4	8 ≤ x < 9	Flam. Liq. 3 H226, STOT SE 3 H336, EUH066
EC 204-658-1		
INDEX 607-025-00-1		
Reg. no. 01-2119485493-29-XXXX		
ETHYL,3-ETHOXY PROPIONATE		
CAS 763-69-9	5 ≤ x < 6	Flam. Liq. 3 H226, EUH066
EC 212-112-9		
INDEX -		
4-METHYLPENTAN-2-ONE		
CAS 108-10-1	5 ≤ x < 6	Flam. Liq. 2 H225, Acute Tox. 4 H332, Eye Irrit. 2 H319, STOT SE 3 H335, EUH066
EC 203-550-1		
INDEX 606-004-00-4		
Reg. no. 01-2119473980-30		
3- [3- (2H-Benzotriazol-2-yl) -5- (1,1-dimethylethyl) -4-hydroxyphenyl]-1-oxopropyl]-hydroxypoly (oxo-1,2-ethanediy)		
CAS 104810-48-2	0,7 ≤ x < 1	Skin Sens. 1 H317, Aquatic Chronic 2 H411
EC 400-830-7		
INDEX 607-176-00-3		
Reg. no. 01-2119396032-43-0000		
METHYL ETHYL KETONE		
CAS 78-93-3	0,7 ≤ x < 1	Flam. Liq. 2 H225, Eye Irrit. 2 H319, STOT SE 3 H336, EUH066
EC 201-159-0		
INDEX 606-002-00-3		
Reg. no. 01-2119457290-43		
Bis (1,2,2,6,6-penthamethyl-4-piperidyl) sebacate		
CAS 41556-26-7	0,25 ≤ x < 0,55	Skin Sens. 1 H317, Aquatic Acute 1 H400 M=1, Aquatic Chronic 1 H410 M=1

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS TWO PACK VARNISH GLOSS Component A - SAFETY DATA SHEET - july 2021 - n°batch 190-BA - rev. 1/2020

EC 255-437-1

INDEX -

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Wash immediately with plenty of water. If irritation persists, get medical advice/attention. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. In the event of breathing difficulties, get medical advice/attention immediately.

INGESTION: Get medical advice/attention. Induce vomiting only if indicated by the doctor. Never give anything by mouth to an unconscious person, unless authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS TWO PACK VARNISH GLOSS Component A - SAFETY DATA SHEET - july 2021 - n°batch 190-BA - rev. 1/2020

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

Send away individuals who are not suitably equipped. Use explosion-proof equipment. Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Vapours may catch fire and an explosion may occur; vapour



accumulation is therefore to be avoided by leaving windows and doors open and ensuring good cross ventilation. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. When performing transfer operations involving large containers, connect to an earthing system and wear antistatic footwear. Vigorous stirring and flow through the tubes and equipment may cause the formation and accumulation of electrostatic charges. In order to avoid the risk of fires and explosions, never use compressed air when handling. Open containers with caution as they may be pressurised. Do not eat, drink or smoke during use. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Store in a cool and well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

Storage class TRGS 510 (Germany):

3

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory References:

DEU	Deutschland	TRGS 900 - Seite 1 von 69 (Fassung 29.03.2019)- Liste der Arbeitsplatzgrenzwerte und Kurzzeitwerte
ESP	España	LÍMITES DE EXPOSICIÓN PROFESIONAL PARA AGENTES QUÍMICOS EN ESPAÑA 2019 (INSST)
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Third edition, published 2018)
ITA	Italia	DIRETTIVA (UE) 2017/164 DELLA COMMISSIONE del 31 gennaio 2017
NLD	Nederland	Regeling van de Staatssecretaris van Sociale Zaken en Werkgelegenheid van 13 juli 2018, 2018-0000118517 tot wijziging van de Arbeidsomstandighedenregeling in verband met de implementatie van Richtlijn 2017/164 in Bijlage XIII
POL	Polska	ROZPORZĄDZENIE MINISTRA RODZINY, PRACY I POLITYKI SPOŁECZNEJ z dnia 12 czerwca 2018 r
PRT	Portugal	Ministério da Economia e do Emprego Consolida as prescrições mínimas em matéria de protecção dos trabalhadores contra os riscos para a segurança e a saúde devido à exposição a agentes químicos no trabalho - Diário da República, 1.ª série - N.º 111 - 11 de junho de 2018
ROU	România	HOTĂRÂRE nr. 584 din 2 august 2018 pentru modificarea Hotărârii Guvernului nr. 1.218/2006 privind stabilirea cerințelor minime de securitate și sănătate în muncă pentru asigurarea protecției lucrătorilor împotriva riscurilor legate de prezența agenților chimici
EU	OEL EU	Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2019

2-METHOXY-1-METHYLETHYL ACETATE

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	270	50	270	50	
MAK	DEU	270	50	270	50	
VLA	ESP	275	50	550	100	SKIN
VLEP	FRA	275	50	550	100	SKIN
WEL	GBR	274	50	548	100	SKIN
VLEP	ITA	275	50	550	100	SKIN

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it

**NAUTILUS TWO PACK VARNISH GLOSS Component A - SAFETY DATA SHEET - july 2021 - n°batch 190-BA - rev. 1/2020**

TGG	NLD	550					
NDS/NDSch	POL	260		520			SKIN
VLE	PRT	275	50	550	100		SKIN
TLV	ROU	275	50	550	100		SKIN
OEL	EU	275	50	550	100		SKIN
Predicted no-effect concentration - PNEC							
Normal value in fresh water				0,635		mg/l	
Normal value in marine water				0,0635		mg/l	
Normal value for fresh water sediment				3,29		mg/kg	
Normal value for marine water sediment				0,329		mg/kg	
Normal value of STP microorganisms				100		mg/l	
Normal value for the terrestrial compartment				0,29		mg/kg	
Health - Derived no-effect level - DNEL / DMEL							
	Effects on consumers			Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local Chronic systemic
Oral			VND	1,67 mg/kg			
Inhalation			VND	33 mg/m3			VND 275 mg/m3
Skin			VND	54,8 mg/kg			VND 153,5 mg/kg
XYLENE (MIXTURE OF ISOMERS)							
Threshold Limit Value							
Type	Country	TWA/8h		STEL/15min		Remarks / Observations	
		mg/m3	ppm	mg/m3	ppm		
AGW	DEU	440	100	880	200	SKIN	
MAK	DEU	440	100	880	200	SKIN	
VLA	ESP	221	50	442	100	SKIN	
VLEP	FRA	221	50	442	100	SKIN	
WEL	GBR	220	50	441	100		
VLEP	ITA	221	50	442	100	SKIN	
TGG	NLD	210		442		SKIN	
NDS/NDSch	POL	100					
OEL	EU	221	50	442	100	SKIN	
TLV-ACGIH		434	100	651	150		
Predicted no-effect concentration - PNEC							
Normal value in fresh water				0,327		mg/l	
Normal value in marine water				0,327		mg/l	
Normal value for fresh water sediment				12,46		mg/kg	
Normal value for marine water sediment				12,46		mg/kg	
Normal value of STP microorganisms				6,58		mg/l	
Normal value for the terrestrial compartment				2,31		mg/kg	
Health - Derived no-effect level - DNEL / DMEL							

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it

**NAUTILUS TWO PACK VARNISH GLOSS Component A - SAFETY DATA SHEET - july 2021 - n°batch 190-BA - rev. 1/2020**

Route of exposure	Effects on consumers			Effects on workers				
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				1.6 mg/kg bw/d				
Inhalation	174 mg/m3	174 mg/m3		14.8 mg/m3	289 mg/m3	289 mg/m3		77 mg/m3
Skin		108 mg/kg bw/d				180 mg/kg bw/d		

N-BUTYL ACETATE**Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min	Remarks / Observations
		mg/m3	ppm	mg/m3	ppm
AGW	DEU	300	62	600 (C)	124 (C)
VLA	ESP	724	150	965	200
VLEP	FRA	710	150	940	200
WEL	GBR	724	150	966	200
TGG	NLD	150			
NDS/NDSch	POL	240		720	
TLV	ROU	715	150	950	200
TLV-ACGIH			50		150

Predicted no-effect concentration - PNEC

Normal value in fresh water		0,18		mg/l
Normal value in marine water		0,018		mg/l
Normal value for fresh water sediment		0,981		mg/kg
Normal value for marine water sediment		0,0981		mg/kg
Normal value for water, intermittent release		0,36		mg/l
Normal value of STP microorganisms		35,6		mg/l
Normal value for the terrestrial compartment		0,0903		mg/kg

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers			Effects on workers				
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral		2 mg/kg bw/d		2 mg/kg bw/d				
Inhalation	300 mg/m3	300 mg/m3	37.5 mg/m3	12 mg/m3	300 mg/m3	48 mg/m3	600 mg/m3	600 mg/m3
Skin	NPI	3.4 mg/kg bw/d	NPI	6 mg/kg bw/d	NPI	11 mg/kg bw/d	NPI	7 mg/kg bw/d

4-METHYLPENTAN-2-ONE**Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min	Remarks / Observations
		mg/m3	ppm	mg/m3	ppm
AGW	DEU	83	20	166	40 SKIN
MAK	DEU	83	20	166	40 SKIN
VLA	ESP	83	20	208	50
VLEP	FRA	83	20	208	50

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it

**NAUTILUS TWO PACK VARNISH GLOSS Component A - SAFETY DATA SHEET - july 2021 - n°batch 190-BA - rev. 1/2020**

WEL	GBR	208	50	416	100	SKIN		
VLEP	ITA	83	20	208	50			
TGG	NLD	104		208				
NDS/NDSCh	POL	83		200				
VLE	PRT	83	20	208	50			
OEL	EU	83	20	208	50			
TLV-ACGIH		82	20	307	75			
Predicted no-effect concentration - PNEC								
Normal value in fresh water				600		µg/L		
Normal value in marine water				60		µg/L		
Normal value for fresh water sediment				8,27		mg/kg/d		
Normal value for marine water sediment				830		µg/kg/dw		
Normal value for water, intermittent release				1,5		mg/l		
Normal value of STP microorganisms				27,5		mg/l		
Normal value for the terrestrial compartment				1,3		mg/kg/d		
Health - Derived no-effect level - DNEL / DMEL								
	Effects on consumers				Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral		NPI		4,2 mg/kg/d				
Skin	NPI	NPI			NPI	NPI		
ETHYL,3-ETHOXY PROPIONATE								
Threshold Limit Value								
Type	Country	TWA/8h		STEL/15min		Remarks / Observations		
		mg/m3	ppm	mg/m3	ppm			
AGW	DEU	610	100	610 (C)	100 (C)	SKIN		
MAK	DEU	610	100	610	100	SKIN		
Predicted no-effect concentration - PNEC								
Normal value in fresh water				0,0609		mg/l		
Normal value in marine water				0,00609		mg/l		
Normal value for fresh water sediment				0,419		mg/kg pc/giorno		
Normal value for marine water sediment				0,0419		mg/l		
Normal value for water, intermittent release				0,609		mg/l		
Normal value of STP microorganisms				50		mg/l		
Health - Derived no-effect level - DNEL / DMEL								
	Effects on consumers				Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			1,2 mg/m3	1,2 mg/m3				
Inhalation			72,6 mg/m3	72,6 mg/m3			610 mg/m3	610 mg/m3
Skin			24,2 mg/m3	24,2 mg/m3			102 mg/m3	102 mg/m3

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it

**NAUTILUS TWO PACK VARNISH GLOSS Component A - SAFETY DATA SHEET - july 2021 - n°batch 190-BA - rev. 1/2020**

3- [3- (2H-Benzotriazol-2-yl) -5- (1,1-dimethylethyl) -4-hydroxyphenyl]-1-oxopropyl]-hydroxypoly (oxo-1,2-ethanediyl)								
Predicted no-effect concentration - PNEC								
Normal value in fresh water				23	µg/L			
Normal value in marine water				460	ng/L			
Normal value for fresh water sediment				726	mg/kg/dw			
Normal value for marine water sediment				726	µg/kg/dw			
Normal value of STP microorganisms				100	mg/l			
Normal value for the terrestrial compartment				14,52	mg/kg			
Health - Derived no-effect level - DNEL / DMEL								
Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				25 µg/kg bw/day				
Inhalation				85 µg/m³			85	350 µg/m³
Skin				25 µg/kg bw/day			25	250 µg/kg bw/day
METHYL ETHYL KETONE								
Threshold Limit Value								
Type	Country	TWA/8h		STEL/15min		Remarks / Observations		
		mg/m3	ppm	mg/m3	ppm			
AGW	DEU	600	200	600	200	SKIN		
MAK	DEU	600	200	600	200	SKIN		
VLA	ESP	600	200	900	300			
VLEP	FRA	600	200	900	300	SKIN		
WEL	GBR	600	200	899	300	SKIN		
VLEP	ITA	600	200	900	300			
TGG	NLD	590		500		SKIN		
NDS/NDSch	POL	450		900		SKIN		
VLE	PRT	600	200	900	300			
OEL	EU	600	200	900	300			
TLV-ACGIH		590	200	885	300			
Predicted no-effect concentration - PNEC								
Normal value in fresh water				55,8	mg/l			
Normal value in marine water				55,8	mg/l			
Normal value for fresh water sediment				284,74	mg/kg			
Normal value for marine water sediment				287,7	mg/kg			
Health - Derived no-effect level - DNEL / DMEL								
Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				31 mg/kg				
Inhalation				406 mg/m3				600 mg/m3
Skin				412 mg/kg				1161 mg/kg

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS TWO PACK VARNISH GLOSS Component A - SAFETY DATA SHEET - july 2021 - n°batch 190-BA - rev. 1/2020

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, wear a mask with a type AX filter, whose limit of use will be defined by the manufacturer (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	liquid	
Colour	colourless	
Odour	characteristic of solvent	
Odour threshold	Not available	
pH	Not available	Reason for missing data: Non miscibile con acqua
Melting point / freezing point	Not available	

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS TWO PACK VARNISH GLOSS Component A - SAFETY DATA SHEET - july 2021 - n°batch 190-BA - rev. 1/2020

Initial boiling point	> 35 °C
Boiling range	Not available
Flash point	> 23 °C
Evaporation Rate	Not available
Flammability of solids and gases	Not available
Lower inflammability limit	Not available
Upper inflammability limit	Not available
Lower explosive limit	Not available
Upper explosive limit	Not available
Vapour pressure	9,32 mmHg
Vapour density	Not available
Relative density	1,01
Solubility	immiscible with water
Partition coefficient: n-octanol/water	Not available
Auto-ignition temperature	Not available
Decomposition temperature	Not available
Viscosity	>20,5 mm ² /sec (40°C)
Explosive properties	Not available
Oxidising properties	Not available

9.2. Other information

Total solids (250°C / 482°F)	46,81 %
VOC (Directive 2010/75/EC) :	53,19 % - 537,03 g/litre
VOC (volatile carbon) :	39,89 % - 406,90 g/litre

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

2-METHOXY-1-METHYLETHYL ACETATE

Stable in normal conditions of use and storage.

With the air it may slowly develop peroxides that explode with an increase in temperature.

N-BUTYL ACETATE

Decomposes on contact with: water.

4-METHYLPENTAN-2-ONE

Reacts violently with: light metals. Attacks various types of plastic materials.

METHYL ETHYL KETONE

Reacts with: light metals, strong oxidants. Attacks various types of plastic materials. Decomposes under the effect of heat.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS TWO PACK VARNISH GLOSS Component A - SAFETY DATA SHEET - july 2021 - n°batch 190-BA - rev. 1/2020

The vapours may also form explosive mixtures with the air.

2-METHOXY-1-METHYLETHYL ACETATE

May react violently with: oxidising substances, strong acids, alkaline metals.

XYLENE (MIXTURE OF ISOMERS)

XYLENE (MIXTURE OF ISOMERS): stable, but may develop violent reactions in the presence of strong oxidising agents such as sulphuric and nitric acids and perchlorates. May form explosive mixtures with the air.

N-BUTYL ACETATE

Risk of explosion on contact with: strong oxidising agents. May react dangerously with: alkaline hydroxides, potassium tert-butoxide. Forms explosive mixtures with: air.

4-METHYLPENTAN-2-ONE

May react violently with: oxidising agents. Forms peroxides with: air. Forms explosive mixtures with: hot air.

METHYL ETHYL KETONE

May form peroxides with: air, light, strong oxidising agents. Risk of explosion on contact with: hydrogen peroxide, nitric acid, sulphuric acid. May react dangerously with: oxidising agents, trichloromethane, alkalis. Forms explosive mixtures with: air.

10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

N-BUTYL ACETATE

Avoid exposure to: moisture, sources of heat, naked flames.

4-METHYLPENTAN-2-ONE

Avoid exposure to: sources of heat.

METHYL ETHYL KETONE

Avoid exposure to: sources of heat.

10.5. Incompatible materials

2-METHOXY-1-METHYLETHYL ACETATE

Incompatible with: oxidising substances, strong acids, alkaline metals.

N-BUTYL ACETATE

Incompatible with: water, nitrates, strong oxidants, acids, alkalis, zinc.

4-METHYLPENTAN-2-ONE

Incompatible with: oxidising substances, reducing substances.

METHYL ETHYL KETONE

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS TWO PACK VARNISH GLOSS Component A - SAFETY DATA SHEET - july 2021 - n°batch 190-BA - rev. 1/2020

Incompatible with: strong oxidants, inorganic acids, ammonia, copper, chloroform.

10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on toxicological effects

XYLENE (MIXTURE OF ISOMERS)

XYLENE (MIXTURE OF ISOMERS): has a toxic effect on the CNS (encephalopathies). Irritating to the skin, conjunctivae, cornea and respiratory apparatus.

Metabolism, toxicokinetics, mechanism of action and other information

2-METHOXY-1-METHYLETHYL ACETATE

The main route of entry is the skin, whereas the respiratory route is less important due to the low vapour pressure of the product.

Information on likely routes of exposure

2-METHOXY-1-METHYLETHYL ACETATE

WORKERS: inhalation; contact with the skin.

N-BUTYL ACETATE

WORKERS: inhalation; contact with the skin.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

2-METHOXY-1-METHYLETHYL ACETATE

Above 100 ppm causes irritation of the eye, nose and oropharynx mucous membranes. At 1000 ppm, disturbance of equilibrium and severe eye irritation can be noticed. Clinical and biological examinations carried out on exposed volunteers revealed no anomalies. Acetate produces greater skin and eye irritation with direct contact. No chronic effects on humans have been reported (INCR, 2010).

N-BUTYL ACETATE

In humans, the substance's vapours cause irritation of the eyes and nose. In the event of repeated exposure, skin irritation, dermatitis (dryness and cracking of the skin) and keratitis appear.

Interactive effects

N-BUTYL ACETATE

A case of acute intoxication been reported involving a 33 year old worker while cleaning a tank with a preparation containing xylenes, butyl acetate and ethylene glycol acetate. The person had irritation of the conjunctiva and upper respiratory tract, drowsiness and motor coordination disorders, which disappeared within 5 hours. The symptoms are attributed to poisoning by mixed xylenes and butyl acetate, with a possible synergistic effect responsible for the neurological effects. Cases of vacuolar keratitis are reported in workers exposed to a mixture of butyl acetate and isobutanol vapours, but with uncertainty concerning the responsibility of a particular solvent (INRC, 2011).

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS TWO PACK VARNISH GLOSS Component A - SAFETY DATA SHEET - july 2021 - n°batch 190-BA - rev. 1/2020

ACUTE TOXICITY

LC50 (Inhalation) of the mixture:

> 20 mg/l

LD50 (Oral) of the mixture:

Not classified (no significant component)

LD50 (Dermal) of the mixture:

>2000 mg/kg

2-METHOXY-1-METHYLETHYL ACETATE

LD50 (Oral) 8500 mg/kg Rat

LD50 (Dermal) > 3160 mg/kg Rat

LC50 (Inhalation) 6193 mg/m³/4h Ratto

METHYL ETHYL KETONE

LD50 (Oral) 2737 mg/kg Rat

LD50 (Dermal) 6480 mg/kg Rabbit

LC50 (Inhalation) 23,5 mg/l/8h Rat

4-METHYLPENTAN-2-ONE

LD50 (Oral) 2080 mg/kg Rat

LD50 (Dermal) > 16000 mg/kg Rabbit

LC50 (Inhalation) > 8,2 mg/l/4h Rat

N-BUTYL ACETATE

LD50 (Oral) > 6400 mg/kg Rat

LD50 (Dermal) > 5000 mg/kg Rabbit

LC50 (Inhalation) 21,1 mg/l/4h Rat

3- [3- (2H-Benzotriazol-2-yl) -5- (1,1-dimethylethyl) -4-hydroxyphenyl]-1-oxopropyl]-hydroxypoly (oxo-1,2-ethanediyol)

LD50 (Oral) > 5000 mg/kg bw/day RAT

LD50 (Dermal) > 2000 mg/kg bw/day RAT

XYLENE (MIXTURE OF ISOMERS)

LD50 (Oral) 3500 mg/kg Rat

LD50 (Dermal) 4350 mg/kg Rabbit

LC50 (Inhalation) 26 mg/l/4h Rat

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS TWO PACK VARNISH GLOSS Component A - SAFETY DATA SHEET - july 2021 - n°batch 190-BA - rev. 1/2020

SKIN CORROSION / IRRITATION

Repeated exposure may cause skin dryness or cracking.

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye irritation

RESPIRATORY OR SKIN SENSITISATION

May produce an allergic reaction. Contains: Bis (1,2,2,6,6-pentamethyl-4-piperidyl) sebacate
3- [3- (2H-Benzotriazol-2-yl) -5- (1,1-dimethylethyl) -4-hydroxyphenyl]-1-oxopropyl]-hydroxypoly (oxo-1,2-ethanediy)

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

May cause drowsiness or dizziness

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class Viscosity: >20,5 mm²/sec (40°C)

SECTION 12. Ecological information

This product is dangerous for the environment and the aquatic organisms. In the long term, it have negative effects on aquatic environment.

12.1. Toxicity

2-METHOXY-1-METHYLETHYL ACETATE

LC50 - for Fish	> 100 mg/l/96h Oncorhynchus mykiss
EC50 - for Crustacea	> 408 mg/l/48h Daphnia magna
EC50 - for Algae / Aquatic Plants	> 100 mg/l/72h
Chronic NOEC for Fish	47,5 mg/l Oncothynchus mykiss
Chronic NOEC for Crustacea	> 99 mg/l Daphnia magna
Chronic NOEC for Algae / Aquatic Plants	> 999 mg/l Selenastrum capricornutum

METHYL ETHYL KETONE

LC50 - for Fish	> 2,993 mg/l/96h Pimephales promelas
EC50 - for Crustacea	> 508 mg/l/48h Daphnia Magna

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it

**NAUTILUS TWO PACK VARNISH GLOSS Component A - SAFETY DATA SHEET - july 2021 - n°batch 190-BA - rev. 1/2020****4-METHYLPENTAN-2-ONE**

LC50 - for Fish > 179 mg/l/96h

EC50 - for Crustacea > 200 mg/l/48h

3- [3- (2H-Benzotriazol-2-yl) -5- (1,1-dimethylethyl) -4-hydroxyphenyl]-1-oxopropyl
]-hydroxypoly (oxo-1,2-ethanediy)

LC50 - for Fish > 2,8 mg/l/96h

EC50 - for Crustacea > 4 mg/l/48h

XYLENE (MIXTURE OF ISOMERS)

LC50 - for Fish > 4,2 mg/l/96h Oncorhynchus mykiss

EC50 - for Crustacea > 2,93 mg/l/48h Daphnia Magna

12.2. Persistence and degradability**2-METHOXY-1-METHYLETHYL ACETATE**

Solubility in water > 10000 mg/l

Rapidly degradable

ETHYL,3-ETHOXY PROPIONATE

Solubility in water > 10000 mg/l

Rapidly degradable

METHYL ETHYL KETONE

Solubility in water > 10000 mg/l

Rapidly degradable

4-METHYLPENTAN-2-ONE

Solubility in water > 10000 mg/l

Degradability: information not available

Rapidly degradable

N-BUTYL ACETATE

Solubility in water 1000 - 10000 mg/l

XYLENE (MIXTURE OF ISOMERS)

Solubility in water 100 - 1000 mg/l

Degradability: information not available

12.3. Bioaccumulative potential**2-METHOXY-1-METHYLETHYL ACETATE**

Partition coefficient: n-octanol/water 1,2

ETHYL,3-ETHOXY PROPIONATE

Partition coefficient: n-octanol/water 1,47

METHYL ETHYL KETONE

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS TWO PACK VARNISH GLOSS Component A - SAFETY DATA SHEET - july 2021 - n°batch 190-BA - rev. 1/2020

Partition coefficient: n-octanol/water	0,3
4-METHYLPENTAN-2-ONE	
Partition coefficient: n-octanol/water	1,9
N-BUTYL ACETATE	
Partition coefficient: n-octanol/water	2,3
BCF	15,3
XYLENE (MIXTURE OF ISOMERS)	
Partition coefficient: n-octanol/water	3,12
BCF	25,9

12.4. Mobility in soil

4-METHYLPENTAN-2-ONE	
Partition coefficient: soil/water	2,008
N-BUTYL ACETATE	
Partition coefficient: soil/water	< 3
XYLENE (MIXTURE OF ISOMERS)	
Partition coefficient: soil/water	2,73

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be

evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS TWO PACK VARNISH GLOSS Component A - SAFETY DATA SHEET - july 2021 - n°batch 190-BA - rev. 1/2020

SECTION 14. Transport information**14.1. UN number**ADR / RID, IMDG, 1263
IATA:**14.2. UN proper shipping name**ADR / RID: PAINT or PAINT RELATED MATERIAL
IMDG: PAINT or PAINT RELATED MATERIAL
IATA: PAINT or PAINT RELATED MATERIAL**14.3. Transport hazard class(es)**

ADR / RID: Class: 3 Label: 3

IMDG: Class: 3 Label: 3

IATA: Class: 3 Label: 3

14.4. Packing groupADR / RID, IMDG, III
IATA:**14.5. Environmental hazards**ADR / RID: NO
IMDG: NO
IATA: NO**14.6. Special precautions for user**

ADR / RID:	HIN - Kemler: 30	Limited Quantities: 5 L	Tunnel restriction code: (D/E)
IMDG:	Special Provision: - EMS: F-E, <u>S-E</u>	Limited Quantities: 5 L	
IATA:	Cargo: Pass.:	Maximum quantity: 220 L Maximum quantity: 60 L	Packaging instructions: 366 Packaging instructions: 355
	Special Instructions:	A3, A72, A192	

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Information not relevant

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS TWO PACK VARNISH GLOSS Component A - SAFETY DATA SHEET - july 2021 - n°batch 190-BA - rev. 1/2020

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EC: P5c

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product
Point 3 - 40

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage greater than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

German regulation on the classification of substances hazardous to water (AwSV, vom 18. April 2017)

WGK 2: Hazard to waters

15.2. Chemical safety assessment

A chemical safety assessment has been performed for the following contained substances

2-METHOXY-1-METHYLETHYL ACETATE

XYLENE (MIXTURE OF ISOMERS)

N-BUTYL ACETATE

4-METHYLPENTAN-2-ONE

METHYL ETHYL KETONE



SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 2	Flammable liquid, category 2
Flam. Liq. 3	Flammable liquid, category 3
Acute Tox. 4	Acute toxicity, category 4
Asp. Tox. 1	Aspiration hazard, category 1
STOT RE 2	Specific target organ toxicity - repeated exposure, category 2
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
STOT SE 3	Specific target organ toxicity - single exposure, category 3
Skin Sens. 1	Skin sensitization, category 1
Aquatic Acute 1	Hazardous to the aquatic environment, acute toxicity, category 1
Aquatic Chronic 1	Hazardous to the aquatic environment, chronic toxicity, category 1
Aquatic Chronic 2	Hazardous to the aquatic environment, chronic toxicity, category 2
Aquatic Chronic 3	Hazardous to the aquatic environment, chronic toxicity, category 3
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H312	Harmful in contact with skin.
H332	Harmful if inhaled.
H304	May be fatal if swallowed and enters airways.
H373	May cause damage to organs through prolonged or repeated exposure.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H335	May cause respiratory irritation.
H317	May cause an allergic skin reaction.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS TWO PACK VARNISH GLOSS Component A - SAFETY DATA SHEET - july 2021 - n°batch 190-BA - rev. 1/2020

- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
 3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
 4. Regulation (EU) 2015/830 of the European Parliament
 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
 13. Regulation (EU) 2017/776 (X Atp. CLP)
 14. Regulation (EU) 2018/669 (XI Atp. CLP)
 15. Regulation (EU) 2018/1480 (XIII Atp. CLP)
 16. Regulation (EU) 2019/521 (XII Atp. CLP)
- The Merck Index. - 10th Edition
 - Handling Chemical Safety
 - INRS - Fiche Toxicologique (toxicological sheet)

- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

Product's classification is based on the calculation methods set out in Annex I of the CLP Regulation, unless otherwise indicated in sections 11 and 12.

The data for evaluation of chemical-physical properties are reported in section 9.

Changes to previous review:

The following sections were modified:

02 / 08 / 09 / 11.