

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS ENAMEL RAL 9016 Component A - SAFETY DATA SHEET - august 2021 - n°batch 278-BA - rev. 1/21

Safety Data Sheet

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name

NAUTILUS ENAMEL RAL 9016 Component A

UFI:

EU50-COC8-100P-NU47

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use

MARINA / NAUTICA

Identified Uses	Industrial	Professional	Consumer
Paint product for furniture	-	✓	-
Paint product for boating - marine	-	✓	-
Paint product for industrial uses	✓	-	-
Paint product for professional use	-	✓	-

Uses Advised Against

CONSUMATORE: FAI-DA-TE

1.3 Details of the supplier of the safety data sheet Manufacturer/Supplier:

Cecchi Gustavo & C. srl - Via M. Coppino 253,

55049 Viareggio (LU) ITALY www.cecchi.it - info@cecchi.it

1.4 Emergency telephone number:

+39 0584/383694 - info@cecchi.it

From monday to friday office hours 8:30 - 12:30, 14:00 - 18:30



SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2015/830. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Flammable liquid, category 3	H226	Flammable liquid and vapour.
Specific target organ toxicity - single exposure, category 3	H336	May cause drowsiness or dizziness.

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words: Warning

Hazard statements:

H226	Flammable liquid and vapour.
H336	May cause drowsiness or dizziness.
EUH211	Warning! Hazardous respirable dust may be formed when used. Do not breathe dust.

Precautionary statements:

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280	Wear protective gloves/ protective clothing / eye protection / face protection.
P370+P378	In case of fire: use . . . to extinguish.
P261	Avoid breathing dust / fume / gas / mist / vapours / spray.
P312	Call a POISON CENTRE / doctor / . . . if you feel unwell.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.

Contains:	TITANIUM DIOXIDE [in powder form contain ing 1 % or more of particles with aerodynamic dia meter ≤ 10 µm] ACETATO DI 1-METIL-2-METOSSIIETILE N-BUTYL ACETATE
------------------	--

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS ENAMEL RAL 9016 Component A - SAFETY DATA SHEET - august 2021 - n°batch 278-BA - rev. 1/21

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.**SECTION 3. Composition/information on ingredients****3.2. Mixtures**

Contains:

Identification	x = Conc. %	Classification 1272/2008 (CLP)
TITANIUM DIOXIDE [in powder form containing 1 % or more of particles with aerodynamic diameter \leq 10 μm]		
CAS 13463-67-7	$30 \leq x < 35$	Carc. 2 H351, Classification note/notes according to Annex VI to the CLP Regulation: 10, V, W
EC 236-675-5		
INDEX 022-006-00-2		
ACETATO DI 1-METIL-2-METOSSIETILE		
CAS 108-65-6	$13 \leq x < 16$	Flam. Liq. 3 H226, STOT SE 3 H336
EC 203-603-9		
INDEX 607-195-00-7		
Reg. no. 01-2119475791-29-XXXX		
XYLENE (MIXTURE OF ISOMERS)		
CAS 1330-20-7	$6 \leq x < 7$	Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Aquatic Chronic 3 H412, Classification note/notes according to Annex VI to the CLP Regulation: C
EC 215-535-7		
INDEX 601-022-00-9		
Reg. no. 01-2119488216-32-XXXX		
N-BUTYL ACETATE		
CAS 123-86-4	$4 \leq x < 5$	Flam. Liq. 3 H226, STOT SE 3 H336, EUH066
EC 204-658-1		
INDEX 607-025-00-1		
Reg. no. 01-2119485493-29-XXXX		
ETHYL,3-ETHOXY PROPIONATE		
CAS 763-69-9	$3 \leq x < 4$	Flam. Liq. 3 H226, EUH066
EC 212-112-9		
INDEX -		
TRIMETILOLPROPANO		
CAS 77-99-6	$0,1 \leq x < 0,4$	Repr. 2 H361fd
EC 201-074-9		
INDEX -		
Reg. no. 01-2119486799-10-XXXX		
PHOSPHORIC ACID		
CAS 7664-38-2	$0 \leq x < 0,05$	Skin Corr. 1B H314, Eye Dam. 1 H318, Classification note/notes according to Annex VI to the CLP Regulation: B
EC 231-633-2		

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS ENAMEL RAL 9016 Component A - SAFETY DATA SHEET - august 2021 - n°batch 278-BA - rev. 1/21

INDEX 015-011-00-6

Reg. no. 01-2119485924-24

METHANOL

CAS 67-56-1 $0 \leq x < 0,05$ Flam. Liq. 2 H225, Acute Tox. 3 H301, Acute Tox. 3 H311, Acute Tox. 3 H331, STOT SE 1 H370

EC 200-659-6

INDEX 603-001-00-X

Reg. no. 01-2119433307-44-XXXX

QUARTZ

CAS 14808-60-7 $0 \leq x < 0,05$ Substance with a community workplace exposure limit.

EC 238-878-4

INDEX -

ETHYLBENZENE

CAS 100-41-4 $0 \leq x < 0,05$ Flam. Liq. 2 H225, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373, Aquatic Chronic 3 H412

EC 202-849-4

INDEX 601-023-00-4

Reg. no. 01-2119489370-35-XXXX

The full wording of hazard (H) phrases is given in section 16 of the sheet.

XYLENE (MIXTURE OF ISOMERS)

XYLENE (MIXTURE OF ISOMERS)

*sostanza UVCB, per la quale sono validi anche i seguenti identificatori di prodotto:

Reazione di massa dell'etilbenzene e dello xilene; CE N. : 905-588-0; Nr. REACH: 01-2119486136-34/ Nr. REACH: 01-2119488216-32;

Massa di reazione di etilbenzene e M-xilene e P-xilene; CE N: 905-562-9; Nr. REACH: 01-2119488216-32/ Nr REACH: 01-211955267-33.

SECTION 4. First aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Wash immediately with plenty of water. If irritation persists, get medical advice/attention. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. In the event of breathing difficulties, get medical advice/attention immediately.

INGESTION: Get medical advice/attention. Induce vomiting only if indicated by the doctor. Never give anything by mouth to an unconscious person, unless authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS ENAMEL RAL 9016 Component A - SAFETY DATA SHEET - august 2021 - n°batch 278-BA - rev. 1/21

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

Send away individuals who are not suitably equipped. Use explosion-proof equipment. Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat. Avoid leakage of the product into the environment.



7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store in a cool and well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

Storage class TRGS 510 (Germany):

3

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory References:

DEU	Deutschland	TRGS 900 - Seite 1 von 69 (Fassung 29.03.2019)- Liste der Arbeitsplatzgrenzwerte und Kurzzeitwerte LÍMITES DE EXPOSICIÓN PROFESIONAL PARA AGENTES QUÍMICOS EN ESPAÑA 2019 (INSST) Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS Decreto Legislativo 9 Aprile 2008, n.81 Regeling van de Staatssecretaris van Sociale Zaken en Werkgelegenheid van 13 juli 2018, 2018-0000118517 tot wijziging van de Arbeidsomstandighedenregeling in verband met de implementatie van Richtlijn 2017/164 in Bijlage XIII
ESP	España	
FRA	France	
ITA	Italia	
NLD	Nederland	
PRT	Portugal	Ministério da Economia e do Emprego Consolida as prescrições mínimas em matéria de protecção dos trabalhadores contra os riscos para a segurança e a saúde devido à exposição a agentes químicos no trabalho - Diário da República, 1.ª série - N.º 111 - 11 de junho de 2018
POL	Polska	ROZPORZĄDZENIE MINISTRA RODZINY, PRACY I POLITYKI SPOŁECZNEJ z dnia 12 czerwca 2018 r
ROU	România	HOTĂRÂRE nr. 584 din 2 august 2018 pentru modificarea Hotărârii Guvernului nr. 1.218/2006 privind stabilirea cerințelor minime de securitate și sănătate în muncă pentru asigurarea protecției lucrătorilor împotriva riscurilor legate de prezența agenților chimici
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Third edition, published 2018)
EU	OEL EU	Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2020

TITANIUM DIOXIDE [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 μm]

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
VLA	ESP	10				
VLEP	FRA	10				
NDS/NDSch	POL	10				INHAL
TLV	ROU	10		15		
WEL	GBR	10				INHAL
WEL	GBR	4				RESP
TLV-ACGIH		10				

ACETATO DI 1-METIL-2-METOSSITILE

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it

**NAUTILUS ENAMEL RAL 9016 Component A - SAFETY DATA SHEET - august 2021 - n°batch 278-BA - rev. 1/21**

AGW	DEU	270	50	270	50				
MAK	DEU	270	50	270	50				
VLA	ESP	275	50	550	100	SKIN			
VLEP	FRA	275	50	550	100	SKIN			
VLEP	ITA	275	50	550	100	SKIN			
TGG	NLD	550							
VLE	PRT	275	50	550	100	SKIN			
NDS/NDSch	POL	260		520		SKIN			
TLV	ROU	275	50	550	100	SKIN			
WEL	GBR	274	50	548	100	SKIN			
OEL	EU	275	50	550	100	SKIN			
Predicted no-effect concentration - PNEC									
Normal value in fresh water				0,635		mg/l			
Normal value in marine water				0,0635		mg/l			
Normal value for fresh water sediment				3,29		mg/kg			
Normal value for marine water sediment				0,329		mg/kg			
Normal value of STP microorganisms				100		mg/l			
Normal value for the food chain (secondary poisoning)				NPI					
Normal value for the terrestrial compartment				0,29		mg/kg			
Normal value for the atmosphere				NPI					
Health - Derived no-effect level - DNEL / DMEL									
	Effects on consumers				Effects on workers				
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic	
Oral	500 mg/kg bw/d		36 mg/kg bw/d	1,67 mg/kg					
Inhalation	NPI	NPI	33 mg/m3	33 mg/m3	550 mg/m3	NPI	NPI	275 mg/m3	
Skin	NPI	NPI	NPI	320 mg/kg bw/d	NPI	NPI	NPI	796 mg/kg bw/d	
XYLENE (MIXTURE OF ISOMERS)									
Threshold Limit Value									
Type	Country	TWA/8h		STEL/15min		Remarks / Observations			
		mg/m3	ppm	mg/m3	ppm				
AGW	DEU	440	100	880	200	SKIN			
MAK	DEU	440	100	880	200	SKIN			
VLA	ESP	221	50	442	100	SKIN			
VLEP	FRA	221	50	442	100	SKIN			
VLEP	ITA	221	50	442	100	SKIN			
TGG	NLD	210		442		SKIN			
VLE	PRT	221	50	442	100	SKIN			
NDS/NDSch	POL	100		200		SKIN			
TLV	ROU	221	50	442	100	SKIN			
WEL	GBR	220	50	441	100	SKIN			
OEL	EU	221	50	442	100	SKIN			
TLV-ACGIH		434	100	651	150				

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it

**NAUTILUS ENAMEL RAL 9016 Component A - SAFETY DATA SHEET - august 2021 - n°batch 278-BA - rev. 1/21**

Predicted no-effect concentration - PNEC		
Normal value in fresh water	0,327	mg/l
Normal value in marine water	0,327	mg/l
Normal value for fresh water sediment	12,46	mg/kg
Normal value for marine water sediment	12,46	mg/kg
Normal value of STP microorganisms	6,58	mg/l
Normal value for the terrestrial compartment	2,31	mg/kg

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers			Effects on workers				
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				1.6 mg/kg bw/d				180 mg/kg
Inhalation	174 mg/m3	174 mg/m3		14,8 mg/m3	289 mg/m3	289 mg/m3		77 mg/m3
Skin		108 mg/kg bw/d						180 mg/kg bw/d

N-BUTYL ACETATE**Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	300	62	600 (C)	124 (C)	
VLA	ESP	724	150	965	200	
VLEP	FRA	710	150	940	200	
TGG	NLD	150				
NDS/NDSch	POL	240		720		
TLV	ROU	715	150	950	200	
WEL	GBR	724	150	966	200	
OEL	EU	241	50	723	150	
TLV-ACGIH			50		150	

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,18	mg/l
Normal value in marine water	0,018	mg/l
Normal value for fresh water sediment	0,981	mg/kg
Normal value for marine water sediment	0,0981	mg/kg
Normal value for water, intermittent release	0,36	mg/l
Normal value of STP microorganisms	35,6	mg/l
Normal value for the terrestrial compartment	0,0903	mg/kg

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers			Effects on workers				
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral		2 mg/kg bw/d		2 mg/kg bw/d				
Inhalation	300 mg/m3	300 mg/m3	37.5 mg/m3	12 mg/m3	300 mg/m3	48 mg/m3	600 mg/m3	600 mg/m3
Skin	NPI	3.4 mg/kg bw/d	NPI	6 mg/kg bw/d	NPI	11 mg/kg bw/d	NPI	7 mg/kg bw/d

ETHYL,3-ETHOXY PROPIONATE**Threshold Limit Value**

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it

**NAUTILUS ENAMEL RAL 9016 Component A - SAFETY DATA SHEET - august 2021 - n°batch 278-BA - rev. 1/21**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations		
		mg/m3	ppm	mg/m3	ppm			
AGW	DEU	610	100	610 (C)	100 (C)	SKIN		
MAK	DEU	610	100	610	100	SKIN		
Predicted no-effect concentration - PNEC								
Normal value in fresh water				0,0609	mg/l			
Normal value in marine water				0,00609	mg/l			
Normal value for fresh water sediment				0,419	mg/kg pc/giorno			
Normal value for marine water sediment				0,0419	mg/l			
Normal value for water, intermittent release				0,609	mg/l			
Normal value of STP microorganisms				50	mg/l			
Health - Derived no-effect level - DNEL / DMEL								
		Effects on consumers			Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			1,2 mg/m3	1,2 mg/m3				
Inhalation			72,6 mg/m3	72,6 mg/m3			610 mg/m3	610 mg/m3
Skin			24,2 mg/m3	24,2 mg/m3			102 mg/m3	102 mg/m3
TRIMETILOLPROPANO								
Predicted no-effect concentration - PNEC								
Normal value in fresh water				NPI				
Normal value in marine water				NPI				
Normal value for fresh water sediment				NPI				
Normal value for marine water sediment				NPI				
Normal value for water, intermittent release				NPI				
Normal value of STP microorganisms				NPI				
Normal value for the food chain (secondary poisoning)				NPI				
Normal value for the terrestrial compartment				NPI				
Health - Derived no-effect level - DNEL / DMEL								
		Effects on consumers			Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral		NPI		340 µg/kg bw/day				
Inhalation	NPI	NPI	NPI	580 µg/m³	NPI	NPI	NPI	3,3 mg/m3
Skin	NPI	NPI	NPI	340 µg/kg bw/day	NPI	NEA	NPI	940 µg/kg bw/day
PHOSPHORIC ACID								
Threshold Limit Value								
Type	Country	TWA/8h		STEL/15min		Remarks / Observations		
		mg/m3	ppm	mg/m3	ppm			
AGW	DEU	2		4 (C)		INHAL		
MAK	DEU	2		4		INHAL		
VLA	ESP	1		2				
VLEP	FRA	1	0,2	2	0,5			

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it

**NAUTILUS ENAMEL RAL 9016 Component A - SAFETY DATA SHEET - august 2021 - n°batch 278-BA - rev. 1/21**

VLEP	ITA	1	2					
TGG	NLD	1	2					
VLE	PRT	1	2					
NDS/NDSch	POL	1	2					
TLV	ROU	1	2					
WEL	GBR	1	2					
OEL	EU	1	2					
TLV-ACGIH		1	3					
Predicted no-effect concentration - PNEC								
Normal value in fresh water		NPI						
Normal value in marine water		NPI						
Normal value for fresh water sediment		NPI						
Normal value for marine water sediment		NPI						
Normal value for water, intermittent release		NPI						
Normal value of STP microorganisms		NPI						
Normal value for the food chain (secondary poisoning)		NPI						
Normal value for the terrestrial compartment		NPI						
Normal value for the atmosphere		NPI						
Health - Derived no-effect level - DNEL / DMEL								
	Effects on consumers			Effects on workers				
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			100 µg/kg bw/day					
Inhalation			360 µg/m ³	4.57 mg/m ³	2 mg/m ³		1 mg/m ³	10,7 mg/m ³
METHANOL								
Threshold Limit Value								
Type	Country	TWA/8h		STEL/15min		Remarks / Observations		
		mg/m ³	ppm	mg/m ³	ppm			
AGW	DEU	270	200	1080	800	SKIN		
MAK	DEU	130	100	260	200	SKIN		
VLA	ESP	266	200			SKIN		
VLEP	FRA	260	200	1300	1000	SKIN 11		
VLEP	ITA	260	200			SKIN		
TGG	NLD	133				SKIN		
VLE	PRT	260	200			SKIN		
NDS/NDSch	POL	100		300		SKIN		
TLV	ROU	260	200			SKIN		
WEL	GBR	266	200	333	250	SKIN		
OEL	EU	260	200			SKIN		
TLV-ACGIH		262	200	328	250	SKIN		
Predicted no-effect concentration - PNEC								
Normal value in fresh water				20,8	mg/l			
Normal value in marine water				2,08	mg/l			



Normal value for fresh water sediment	77	mg/kg/d
Normal value for marine water sediment	7,7	mg/kg/d
Normal value for water, intermittent release	1,54	mg/l
Normal value of STP microorganisms	100	mg/l
Normal value for the terrestrial compartment	100	mg/kg/d
Normal value for the atmosphere	NPI	

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral		4 mg/kg bw/d		4 mg/kg bw/d				
Inhalation	26 mg/m3	26 mg/m3	26 mg/m3	26 mg/m3	130 mg/m3	130 mg/m3	130 mg/m3	130 mg/m3
Skin	NPI	4 mg/kg bw/d	NPI	4 mg/kg bw/d	NPI	20 mg/kg bw/d	NPI	20 mg/kg bw/d

QUARTZ

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
VLA	ESP		0,05			RESP
VLEP	FRA	0,1				RESP
VLEP	ITA	0,1				RESP
TGG	NLD	0,075				RESP
NDS/NDSch	POL	0,1				RESP
OEL	EU	0,1				RESP
TLV-ACGIH		0,025				

ETHYLBENZENE

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	88	20	176	40	SKIN
MAK	DEU	88	20	176	40	SKIN
VLA	ESP	441	100	884	200	SKIN
VLEP	FRA	88,4	20	442	100	SKIN
VLEP	ITA	442	100	884	200	SKIN
TGG	NLD	215		430		SKIN
VLE	PRT	442	100	884	200	SKIN
NDS/NDSch	POL	200		400		SKIN
TLV	ROU	442	100	884	200	SKIN
WEL	GBR	441	100	552	125	SKIN
OEL	EU	442	100	884	200	SKIN
TLV-ACGIH		87	20			

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,1	mg/l
Normal value in marine water	0,01	mg/l



Normal value for fresh water sediment	13,7	mg/l
Normal value for marine water sediment	13,7	mg/l
Normal value of STP microorganisms	9,6	mg/l
Normal value for the food chain (secondary poisoning)	20	mg/kg
Normal value for the terrestrial compartment	2,68	mg/kg
Normal value for the atmosphere	NPI	

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral		NPI		1,6 mg/kg				
Inhalation	NPI		NPI	15 mg/m ³	293 mg/m ³		442 mg/m ³	77 mg/m ³
Skin	NPI	NPI	NPI	NPI	NPI	NPI	NPI	180 mg/kg/d

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.



SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	liquid	
Colour	white	
Odour	characteristic of solvent	
Odour threshold	Not available	
pH	Not available	Reason for missing data: la sostanza/miscela è non polare /aprotica
Melting point / freezing point	Not available	
Initial boiling point	Not available	
Boiling range	Not available	
Flash point	23 ≤ T ≤ 60 °C	
Evaporation Rate	Not available	
Flammability of solids and gases	Not available	
Lower inflammability limit	Not available	
Upper inflammability limit	Not available	
Lower explosive limit	Not available	
Upper explosive limit	Not available	
Vapour pressure	25,44 mmHg	
Vapour density	Not available	
Relative density	1,40	
Solubility	insoluble in water	
Partition coefficient: n-octanol/water	Not available	
Auto-ignition temperature	Not available	
Decomposition temperature	Not available	
Viscosity	>20,5 mm ² /sec (40°C)	
Explosive properties	Not available	
Oxidising properties	Not available	

9.2. Other information

Total solids (250°C / 482°F)	70,85 %
VOC (Directive 2010/75/EC) :	29,14 % - 406,74 g/litre
VOC (volatile carbon) :	19,04 % - 265,75 g/litre

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

ACETATO DI 1-METIL-2-METOSSIETILE

Stable in normal conditions of use and storage.

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS ENAMEL RAL 9016 Component A - SAFETY DATA SHEET - august 2021 - n°batch 278-BA - rev. 1/21

Con l'aria può dare lentamente perossidi che esplodono per aumento di temperatura.

N-BUTYL ACETATE

Decomposes on contact with: water.

PHOSPHORIC ACID

Decomposes at temperatures above 200°C/392°F.

2-ETHYLHEXYL ACRYLATE

Can polymerise, even when stabilised with 20 pm of monomethyl ether hydroquinone.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

ACETATO DI 1-METIL-2-METOSSIETILE

May react violently with: oxidising substances, strong acids, alkaline metals.

XYLENE (MIXTURE OF ISOMERS)

Stable in normal conditions of use and storage. Reacts violently with: strong oxidants, strong acids, nitric acid, perchlorates. May form explosive mixtures with: air.

N-BUTYL ACETATE

Risk of explosion on contact with: strong oxidising agents. May react dangerously with: alkaline hydroxides, potassium tert-butoxide. Forms explosive mixtures with: air.

PHOSPHORIC ACID

Risk of explosion on contact with: nitromethane. May react dangerously with: alkalis, sodium borohydride.

ETHYLBENZENE

Reacts violently with: strong oxidants. Attacks various types of plastic materials. May form explosive mixtures with: air.

10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

N-BUTYL ACETATE

Avoid exposure to: moisture, sources of heat, naked flames.

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS ENAMEL RAL 9016 Component A - SAFETY DATA SHEET - august 2021 - n°batch 278-BA - rev. 1/21

10.5. Incompatible materials

ACETATO DI 1-METIL-2-METOSSIETILE

Incompatible with: oxidising substances, strong acids, alkaline metals.

N-BUTYL ACETATE

Incompatible with: water, nitrates, strong oxidants, acids, alkalis, zinc.

PHOSPHORIC ACID

Incompatible with: metals, strong alkalis, aldehydes, organic sulphides, peroxides.

10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

PHOSPHORIC ACID

May develop: phosphoryl oxides.

ETHYLBENZENE

May develop: methane, styrene, hydrogen, ethane.

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on toxicological effects

Metabolism, toxicokinetics, mechanism of action and other information

ACETATO DI 1-METIL-2-METOSSIETILE

La principale via di entrata è quella cutanea, mentre quella respiratoria è meno importante, data la bassa tensione di vapore del prodotto.

Information on likely routes of exposure

ACETATO DI 1-METIL-2-METOSSIETILE

LAVORATORI: inalazione; contatto con la cute.

XYLENE (MIXTURE OF ISOMERS)

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; inhalation of ambient air.

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS ENAMEL RAL 9016 Component A - SAFETY DATA SHEET - august 2021 - n°batch 278-BA - rev. 1/21

N-BUTYL ACETATE

WORKERS: inhalation; contact with the skin.

METHANOL

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; contact with the skin of products containing the substance.

ETHYLBENZENE

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; contact with the skin of products containing the substance.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

ACETATO DI 1-METIL-2-METOSSIETILE

Al di sopra di 100 ppm si ha irritazione delle mucose oculari, nasali e orofaringee. A 1000 ppm si notano turbe nell'equilibrio e irritazione severa agli occhi. Gli esami clinici e biologici praticati sui volontari esposti non hanno rivelato anomalie. L'acetato produce maggiore irritazione cutanea ed oculare per contatto diretto. Non vengono riportati effetti cronici sull'uomo (INCR, 2010).

XYLENE (MIXTURE OF ISOMERS)

Toxic effect on the central nervous system (encephalopathy); irritating for the skin, conjunctiva, cornea and respiratory apparatus.

N-BUTYL ACETATE

In humans, the substance's vapours cause irritation of the eyes and nose. In the event of repeated exposure, skin irritation, dermatitis (dryness and cracking of the skin) and keratitis appear.

METHANOL

The minimum lethal dose for humans by ingestion is considered to be in the range from 300 to 1000 mg/kg. Ingestion of 4-10 ml of the substance may cause permanent blindness in adult humans (IPCS).

ETHYLBENZENE

As the counterparts of benzene, may have an acute effect on the central nervous system, with depression, narcosis, often preceded by dizziness and associated with headache (Ispesl). Is irritating for skin, conjunctiva and respiratory tract.

Interactive effects

XYLENE (MIXTURE OF ISOMERS)

Intake of alcohol interferes with the metabolism of the substance, inhibiting it. Ethanol consumption (0.8 g/kg) before a 4-hour exposure to xylene vapours (145 and 280 ppm) causes a 50% reduction in the excretion of methyl hippuric acid, whereas the concentration of xylenes in the blood increases approx. 1.5-2 times. At the same time there is an increase in the secondary side effects of the ethanol. The metabolism of the xylenes is increased by phenobarbital and 3-methyl-colantrene type enzyme inducers. Aspirin and xylenes mutually inhibit their conjugation with the glycine, which results in a decrease in urinary excretion of methyl hippuric acid. Other industrial products can interfere with the metabolism of xylenes.

N-BUTYL ACETATE

A case of acute intoxication been reported involving a 33 year old worker while cleaning a tank with a preparation containing xylenes, butyl acetate and ethylene glycol acetate. The person had irritation of the conjunctiva and upper respiratory tract, drowsiness and motor coordination disorders, which disappeared within 5 hours. The symptoms are attributed to poisoning by mixed xylenes and butyl acetate, with a possible synergistic effect responsible for the neurological effects. Cases of vacuolar keratitis are reported in workers exposed to a mixture of butyl acetate and isobutanol vapours, but with

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS ENAMEL RAL 9016 Component A - SAFETY DATA SHEET - august 2021 - n°batch 278-BA - rev. 1/21

uncertainty concerning the responsibility of a particular solvent (INRC, 2011).

ACUTE TOXICITY

ATE (Inhalation) of the mixture:

> 20 mg/l

ATE (Oral) of the mixture:

Not classified (no significant component)

ATE (Dermal) of the mixture:

>2000 mg/kg

PHOSPHORIC ACID

LD50 (Oral) 1530 mg/kg Rat

LD50 (Dermal) 2740 mg/kg Rabbit

LC50 (Inhalation) > 0,85 mg/l/1h Rat

XYLENE (MIXTURE OF ISOMERS)

LD50 (Oral) 3523 mg/kg Rat

LD50 (Dermal) 4350 mg/kg Rabbit

LC50 (Inhalation) 26 mg/l/4h Rat

TITANIUM DIOXIDE [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$]

LD50 (Oral) > 10000 mg/kg Rat

ACETATO DI 1-METIL-2-METOSSITILE

LD50 (Oral) 8500 mg/kg Rat

LD50 (Dermal) > 3160 mg/kg Rat

LC50 (Inhalation) 6193 mg/m³/4h Ratto

QUARTZ

LD50 (Oral) > 500 mg/kg

ETHYLBENZENE

LD50 (Oral) 3500 mg/kg Rat

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS ENAMEL RAL 9016 Component A - SAFETY DATA SHEET - august 2021 - n°batch 278-BA - rev. 1/21

LD50 (Dermal) 15354 mg/kg Rabbit

LC50 (Inhalation) 17,2 mg/l/4h Rat

METHANOL

LD50 (Oral) > 5628 mg/kg RAT

LD50 (Dermal) > 15800 mg/kg RAT

LC50 (Inhalation) > 64000 ppm/4h rat

N-BUTYL ACETATE

LD50 (Oral) > 6400 mg/kg Rat

LD50 (Dermal) > 5000 mg/kg Rabbit

LC50 (Inhalation) 21,1 mg/l/4h Rat

TRIMETILOLPROPANO

LD50 (Oral) > 14700 mg/kg RATTO

LD50 (Dermal) > 10000 mg/kg RATTO

LC50 (Inhalation) > 850 mg/l/4h RATTO

SKIN CORROSION / IRRITATION

Does not meet the classification criteria for this hazard class

SERIOUS EYE DAMAGE / IRRITATION

Does not meet the classification criteria for this hazard class

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS ENAMEL RAL 9016 Component A - SAFETY DATA SHEET - august 2021 - n°batch 278-BA - rev. 1/21

TITANIUM DIOXIDE [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$]

The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1% or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter $\leq 10 \mu\text{m}$.

XYLENE (MIXTURE OF ISOMERS)

Classified in Group 3 (not classifiable as a human carcinogen) by the International Agency for Research on Cancer (IARC).
The US Environmental Protection Agency (EPA) affirms that "the data is inadequate for an assessment of the carcinogenic potential".

ETHYLBENZENE

Classified in Group 2B (possible human carcinogen) by the International Agency for Research on Cancer (IARC) - (IARC, 2000).
Classified in Group D (not classifiable as a human carcinogen) by the US Environmental Protection Agency (EPA) - (US EPA file on-line 2014).

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

May cause drowsiness or dizziness

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class Viscosity: $>20,5 \text{ mm}^2/\text{sec}$ (40°C)

SECTION 12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

12.1. Toxicity

PHOSPHORIC ACID

EC50 - for Crustacea $> 100 \text{ mg/l/48h}$

EC50 - for Algae / Aquatic Plants $> 100 \text{ mg/l/72h}$

XYLENE (MIXTURE OF ISOMERS)

LC50 - for Fish $> 4,2 \text{ mg/l/96h}$ Oncorhynchus mykiss

EC50 - for Crustacea $> 2,93 \text{ mg/l/48h}$ Daphnia Magna

ACETATO DI 1-METIL-2-METOSSIIETILE

LC50 - for Fish $> 100 \text{ mg/l/96h}$ Oncorhynchus mykiss

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS ENAMEL RAL 9016 Component A - SAFETY DATA SHEET - august 2021 - n°batch 278-BA - rev. 1/21

EC50 - for Crustacea	> 408 mg/l/48h Daphnia magna
EC50 - for Algae / Aquatic Plants	> 100 mg/l/72h
Chronic NOEC for Fish	47,5 mg/l Oncorhynchus mykiss
Chronic NOEC for Crustacea	> 99 mg/l Daphnia magna
Chronic NOEC for Algae / Aquatic Plants	> 999 mg/l Selenastrum capricornutum

ETHYLBENZENE

LC50 - for Fish	> 4,2 mg/l/96h 4.2 - 5.1 mg/L
EC50 - for Crustacea	> 1,8 mg/l/48h 1.8 - 2.4 mg/L
EC50 - for Algae / Aquatic Plants	> 4,9 mg/l/72h 4.9 - 5.4 mg/L

METHANOL

LC50 - for Fish	> 15,4 mg/l/96h
-----------------	-----------------

N-BUTYL ACETATE

LC50 - for Fish	> 18 mg/l/96h
EC50 - for Crustacea	> 32 mg/l/48h
EC50 - for Algae / Aquatic Plants	> 246 mg/l/72h

TRIMETILOLPROPANO

LC50 - for Fish	> 1 mg/l/96h
EC50 - for Crustacea	> 13 mg/l/48h
EC50 - for Algae / Aquatic Plants	> 1 mg/l/72h

12.2. Persistence and degradability

PHOSPHORIC ACID

Solubility in water	> 850000 mg/l
Degradability: information not available	

XYLENE (MIXTURE OF ISOMERS)

Solubility in water	100 - 1000 mg/l
Rapidly degradable	

TITANIUM DIOXIDE [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$]

Solubility in water	< 0,001 mg/l
Degradability: information not available	

ACETATO DI 1-METIL-2-METOSSIETILE

Solubility in water	> 10000 mg/l
Rapidly degradable	

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it

**NAUTILUS ENAMEL RAL 9016 Component A** - SAFETY DATA SHEET - august 2021 - n°batch 278-BA - rev. 1/21

ETHYL,3-ETHOXY PROPIONATE

Solubility in water > 10000 mg/l

Rapidly degradable

ETHYLBENZENE

Solubility in water 1000 - 10000 mg/l

Rapidly degradable

METHANOL

Solubility in water > 1000000 mg/l

Rapidly degradable

N-BUTYL ACETATE

Solubility in water 5.3 - 14 g/L @ 20 °C mg/l

Rapidly degradable

TRIMETILOLPROPANO

Solubility in water > 100 mg/l

Entirely degradable

12.3. Bioaccumulative potential

XYLENE (MIXTURE OF ISOMERS)

Partition coefficient: n-octanol/water 3,12

BCF 25,9

ACETATO DI 1-METIL-2-METOSSIETILE

Partition coefficient: n-octanol/water 1,2

ETHYL,3-ETHOXY PROPIONATE

Partition coefficient: n-octanol/water 1,47

ETHYLBENZENE

Partition coefficient: n-octanol/water 3,6

METHANOL

Partition coefficient: n-octanol/water -0,77

BCF 0,2

N-BUTYL ACETATE

Partition coefficient: n-octanol/water 2,3

BCF 15,3

TRIMETILOLPROPANO

Partition coefficient: n-octanol/water > -0,47 Log Kow @26°C

12.4. Mobility in soil

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS ENAMEL RAL 9016 Component A - SAFETY DATA SHEET - august 2021 - n°batch 278-BA - rev. 1/21

XYLENE (MIXTURE OF ISOMERS)

Partition coefficient: soil/water 2,73

N-BUTYL ACETATE

Partition coefficient: soil/water < 3

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

12.6. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

14.1. UN number

ADR / RID, IMDG, 1263
IATA:

14.2. UN proper shipping name

ADR / RID: PAINT
IMDG: PAINT
IATA: PAINT

14.3. Transport hazard class(es)

ADR / RID: Class: 3 Label: 3

IMDG: Class: 3 Label: 3

IATA: Class: 3 Label: 3

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS ENAMEL RAL 9016 Component A - SAFETY DATA SHEET - august 2021 - n°batch 278-BA - rev. 1/21

14.4. Packing group

ADR / RID, IMDG, III
IATA:

14.5. Environmental hazards

ADR / RID: NO
IMDG: NO
IATA: NO

14.6. Special precautions for user

ADR / RID:	HIN - Kemler: 30	Limited Quantities: 5 L	Tunnel restriction code: (D/E)
IMDG:	Special Provision: - EMS: F-E, <u>S-E</u>	Limited Quantities: 5 L	
IATA:	Cargo:	Maximum quantity: 220 L	Packaging instructions: 366
	Pass.:	Maximum quantity: 60 L	Packaging instructions: 355
	Special Instructions:	A3, A72, A192	

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EC: P5c

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product
Point 3 - 40

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage \geq than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS ENAMEL RAL 9016 Component A - SAFETY DATA SHEET - august 2021 - n°batch 278-BA - rev. 1/21

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

German regulation on the classification of substances hazardous to water (AwSV, vom 18. April 2017)

WGK 2: Hazard to waters

15.2. Chemical safety assessment

A chemical safety assessment has been performed for the following contained substances

ACETATO DI 1-METIL-2-METOSSIETILE

XYLENE (MIXTURE OF ISOMERS)

N-BUTYL ACETATE

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 2	Flammable liquid, category 2
Flam. Liq. 3	Flammable liquid, category 3
Carc. 2	Carcinogenicity, category 2
Repr. 2	Reproductive toxicity, category 2
Acute Tox. 3	Acute toxicity, category 3
STOT SE 1	Specific target organ toxicity - single exposure, category 1
Acute Tox. 4	Acute toxicity, category 4
Asp. Tox. 1	Aspiration hazard, category 1
STOT RE 2	Specific target organ toxicity - repeated exposure, category 2
Skin Corr. 1B	Skin corrosion, category 1B
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
STOT SE 3	Specific target organ toxicity - single exposure, category 3
Aquatic Chronic 3	Hazardous to the aquatic environment, chronic toxicity, category 3

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS ENAMEL RAL 9016 Component A - SAFETY DATA SHEET - august 2021 - n°batch 278-BA - rev. 1/21

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H351	Suspected of causing cancer.
H361fd	Suspected of damaging fertility. Suspected of damaging the unborn child.
H301	Toxic if swallowed.
H311	Toxic in contact with skin.
H331	Toxic if inhaled.
H370	Causes damage to organs.
H312	Harmful in contact with skin.
H332	Harmful if inhaled.
H304	May be fatal if swallowed and enters airways.
H373	May cause damage to organs through prolonged or repeated exposure.
H314	Causes severe skin burns and eye damage.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH211	Warning! Hazardous respirable dust may be formed when used. Do not breathe dust.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY

tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it



NAUTILUS ENAMEL RAL 9016 Component A - SAFETY DATA SHEET - august 2021 - n°batch 278-BA - rev. 1/21

3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
4. Regulation (EU) 2015/830 of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
12. Regulation (EU) 2016/1179 (IX Atp. CLP)
13. Regulation (EU) 2017/776 (X Atp. CLP)
14. Regulation (EU) 2018/669 (XI Atp. CLP)
15. Regulation (EU) 2018/1480 (XIII Atp. CLP)
16. Regulation (EU) 2019/521 (XII Atp. CLP)

- The Merck Index. - 10th Edition

- Handling Chemical Safety

- INRS - Fiche Toxicologique (toxicological sheet)

- Patty - Industrial Hygiene and Toxicology

- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition

- IFA GESTIS website

- ECHA website

- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.