Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY tel. +39 0584 383694 fax +39 0584 395182 www.cecchi.it info@cecchi.it



NAUTILUS EPOXY LIGHT FILLER component A – SAFETY DATA SHEET - may 2022 n°batch 2210010 - rev. 1/2022

Safety data sheet

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: NAUTILUS EPOXY LIGHT FILLER component A

UFI: 2H2V-T2H0-W00Y-E1W0

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Filler for industrial or professional application. For information regarding additional possible application please email us or dial the indicated phone number as shown below. We will connect you with our responsible technical personnel.

1.3 Details of the supplier of the safety data sheet Manufacturer/Supplier:

Cecchi Gustavo & C. srl - Via M. Coppino 253, 55049 Viareggio (LU) ITALY www.cecchi.it - info@cecchi.it

1.4 Emergency telephone number:

+39 0584/383694 - info@cecchi.it

From monday to friday office hours 8:30 – 12:30, 14:00 – 18:30

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

corrosion

Eye Dam. 1 H318 Causes serious eye damage.

environment

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY tel. +39 0584 383694 fax +39 0584 395182 www.cecchi.it info@cecchi.it



NAUTILUS EPOXY LIGHT FILLER component A – SAFETY DATA SHEET - may 2022 n°batch 2210010 - rev. 1/2022

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

· 2.2 Label elements

- · Labelling according to Regulation (EC) No 1272/2008

 The product is classified and labelled according to the CLP regulation.
- · Hazard pictograms
- · Pittogrammi di pericolo





GHS05 GHS07



GHS05

· Signal word Danger

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it

NAUTILUS EPOXY LIGHT FILLER component A – SAFETY DATA SHEET - may 2022 n°batch 2210010 - rev. 1/2022



(Contd. of page 1)

· Hazard-determining components of labelling:

1,4-bis(2,3-epoxypropoxy)butane

Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight =< 700) Bisphenol F-(epichlorhydrin) epoxy resin

Hazard statements

H315 Causes skin irritation.

H318 Causes serious eye damage.

H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P280 Wear protective gloves / eye protection / face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P321 Specific treatment (see on this label).

P362+P364 Take off contaminated clothing and wash it before reuse.

· Additional information:

EUH205 Contains epoxy constituents. May produce an allergic reaction.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · **vPvB**: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

· **Description**: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 25068-38-6 NLP: 500-033-5	Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight =< 700)	25-50%
Reg.nr.: 01-2119456619-26	Aquatic Chronic 2, H411; — Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	
CAS: 2425-79-8 EINECS: 219-371-7 Reg.nr.: 01-2119494060-45	1,4-bis(2,3-epoxypropoxy)butane	≥10-<25%
	➡ Eye Dam. 1, H318; — Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Skin Sens. 1, H317; Aquatic Chronic 3, H412	
CAS: 28064-14-4	Bisphenol F-(epichlorhydrin) epoxy resin H-, Aquatic Chronic 2, H411; — Skin Irrit. 2, H315; Eye Irrit. 2,	≥10-<25%
	H319; Skin Sens. 1, H317	

[·] Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately rinse with water.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

(Contd. on page 3)

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY tel. +39 0584 383694 fax +39 0584 395182 www.cecchi.it info@cecchi.it



NAUTILUS EPOXY LIGHT FILLER component A – SAFETY DATA SHEET - may 2022 n°batch 2210010 - rev. 1/2022

(Contd. of page 2)

- · After swallowing: If symptoms persist consult doctor.
- 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralising agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- · Information about fire and explosion protection: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Store away from foodstuffs.
- Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 10
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Additional information about design of technical facilities: No further data; see item 7.
- · Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· Additional information: The lists valid during the making were used as basis.

(Contd. on page 4)

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY tel. +39 0584 383694 fax +39 0584 395182 www.cecchi.it info@cecchi.it



NAUTILUS EPOXY LIGHT FILLER component A – SAFETY DATA SHEET - may 2022 n°batch 2210010 - rev. 1/2022

- · 8.2 Exposure controls
- Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Avoid contact with the eyes.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Breakthrough time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:

Tightly sealed goggles

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

Form: Fluid

Colour: According to product specification

Odour: CharacteristicOdour threshold: Not determined.

· **pH-value**: Not determined.

· Change in condition

Melting point/freezing point: Undetermined. **Initial boiling point and boiling range:** >200 °C

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY tel. +39 0584 383694 fax +39 0584 395182 www.cecchi.it info@cecchi.it



NAUTILUS EPOXY LIGHT FILLER component A – SAFETY DATA SHEET - may 2022 n°batch 2210010 - rev. 1/2022

· Flash point:	140 °C (DIN EN ISO 1523:2002)
· Flammability (solid, gas):	Not applicable.
· Decomposition temperature:	Not determined.
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product does not present an explosion hazard.
· Explosion limits: Lower: Upper:	Not determined. Not determined.
· Vapour pressure at 20 °C:	<0.1 hPa
 Density at 20 °C: Relative density Vapour density Evaporation rate 	0.663 g/cm³ (DIN EN ISO 2811-1) Not determined. Not determined. Not determined.
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity: Dynamic at 20 °C: Kinematic:	168,000-192,000 mPas Not determined.
· Solvent content: VOC (EC)	0.00 %
Solids content (weight-%):	100.0 %
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products:

Possible in traces.

Nitrogen oxides

Hydrogen chloride (HCI)

Carbon monoxide

Nitrogen oxides (NOx)

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

(Contd. on page 6)

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY tel. +39 0584 383694 fax +39 0584 395182 www.cecchi.it info@cecchi.it



NAUTILUS EPOXY LIGHT FILLER component A – SAFETY DATA SHEET - may 2022 n°batch 2210010 - rev. 1/2022

· LD/LC5	· LD/LC50 values relevant for classification:			
25068-38-6 Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight =< 700)				
Oral	LD50	>5,000 mg/kg (rat)		
Dermal	LD50	>2,000 mg/kg (rabbit)		
2425-79	2425-79-8 1,4-bis(2,3-epoxypropoxy)butane			
Oral	LD50	1,118 mg/kg (rat)		
Dermal	LD50	2,150 mg/kg (rat)		

- · Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation

Causes serious eye damage.

· Respiratory or skin sensitisation

May cause an allergic skin reaction.

- · Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are notmet.
- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Must not reach sewage water or drainage ditch undiluted or unneutralised.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

(Contd. on page 7)

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY tel. +39 0584 383694 fax +39 0584 395182 www.cecchi.it info@cecchi.it



NAUTILUS EPOXY LIGHT FILLER component A – SAFETY DATA SHEET - may 2022 n°batch 2210010 - rev. 1/2022

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- Recommendation:

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

SECTION 14: Transport information	
· 14.1 UN-Number	
· ADR, IMDG, IATA	UN3082
· 14.2 UN proper shipping name	
· ADR	UN 30 82 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenolresins)
·IMDG	ENVIRONMENTALLY HAZARDOUS SUBSTANCE,
	LIQUID, N.O.S. (Bisphenolresins), MARINE
·IATA	POLLUTANT ENVIRONMENTALLY HAZARDOUS SUBSTANCE,
	LIQUID, N.O.S. (Bisphenolresins)
· 14.3 Transport hazard class(es)	
· ADR	
· Class	9 (M6) Miscellaneous dangerous substances and
· Label	articles. 9
	3
· IMDG, IATA	
· Class	9 Miscellaneous dangerous substances and articles.
· Label	9
· 14.4 Packing group	
· ADR, IMDG, IATA	III
· 14.5 Environmental hazards:	O what (fat and the c)
· Marine pollutant: · Special marking (ADR):	Symbol (fish and tree) Symbol (fish and tree)
· Special marking (IATA):	Symbol (fish and tree)
· 14.6 Special precautions for user	Warning: Miscellaneous dangerous substances and
	articles.

(Contd. on page 8)

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY tel. +39 0584 383694 fax +39 0584 395182 www.cecchi.it info@cecchi.it



NAUTILUS EPOXY LIGHT FILLER component A – SAFETY DATA SHEET - may 2022 n°batch 2210010 - rev. 1/2022

 Hazard identification number (Kemler code): EMS Number: Stowage Category 	90 F-A,S-F A
· 14.7 Transport in bulk according to Annex II o Marpol and the IBC Code	of Not applicable.
· Transport/Additional information:	
 ADR Limited quantities (LQ) Transport category Tunnel restriction code Remarks: 	5L 3 (-) ≤ 5l: SV 375 ADR
· IMDG · Limited quantities (LQ) · Remarks:	5L ≤ 5l: 2.10.2.7 IMDG-Code
· IATA · Remarks:	≤ 5I: A 197
· UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (BISPHENOLRESINS), 9, III

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category E2 Hazardous to the Aquatic Environment
- Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

(Contd. on page 9)

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY tel. +39 0584 383694 fax +39 0584 395182 www.cecchi.it info@cecchi.it



NAUTILUS EPOXY LIGHT FILLER component A – SAFETY DATA SHEET - may 2022 n°batch 2210010 - rev. 1/2022

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3