

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY
tel. +39 0584 383694 fax +39 0584 395182
www.cecchi.it info@cecchi.it



SPINNAKER STANDAR YACHT VARNISH – Safety Data Sheet - september 2022 - batch 296-B2 - rev.2/21

SPINNAKER STANDARD YACHT VARNISH

*SECTION 1 Identification of the substance/preparation and of the company/undertaking

- 1.1 Product identifier
- Trade name: SPINNAKER STANDARD YACHT VARNISH
- UFI: SM00-G081-C00H-90K9

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

- Product category PC9a Coatings and paints, thinners, paint removers
 - Process category PROC10 Roller application or brushing
 - Environmental release category
ERC10a Wide dispersive outdoor use of long-life articles and materials with low release
ERC2 Formulation of preparations
 - Application of the substance / the mixture
- See our technical datasheet for application of this product.

· 1.3 Details of the supplier of the safety data sheet

- Manufacturer/Supplier:
Cecchi Gustavo & C. srl - Via M. Coppino 253, 55049 Viareggio (LU) ITALY www.cecchi.it - info@cecchi.it

· 1.4 Emergency telephone number:

- +39 0584/383694 - info@cecchi.it
- From monday to friday office hours 8:30 – 12:30, 14:00 – 18:30

SECTION 2: Hazards identification

- 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

(Contd. on page 2)

- **2.2 Label elements**
- Labelling according to Regulation (EC) No 1272/2008
The product is classified and labelled according to the CLP regulation.
- Hazard pictograms



GHS02



GHS07

- Signal word **Warning**
- Hazard-determining components of labelling:
Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclic, < 2% aromatics. (Note-P)
cobalt bis(2-ethylhexanoate)
- Hazard statements
H226 **Flammable liquid and vapour.**
H317 **May cause an allergic skin reaction.**
H336 **May cause drowsiness or dizziness.**
H412 **Harmful to aquatic life with long lasting effects.**
- Precautionary statements
P102 **Keep out of reach of children.**
P210 **Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.**
P260 **Do not breathe dust/fume/gas/mist/vapours/spray.**
P271 **Use only outdoors or in a well-ventilated area.**
P280 **Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.**
P301+P310 **IF SWALLOWED: Immediately call a POISON CENTER/ doctor.**
P303+P361+P353 **IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].**
P501 **Dispose of contents/container in accordance with local/regional/national/international regulations.**
- Additional information:
EUH066 **Repeated exposure may cause skin dryness or cracking.**
Contains cobalt carboxylate, can cause an allergic reaction.
- **2.3 Other hazards**
- Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- **3.2 Mixtures**
- Description: Mixture of substances listed below with nonhazardous additions.

(Contd. on page 3)



· Dangerous components:		
CAS: 64742-48-9 EC number: 919-857-5 Index number: 649-327-00-6 Reg.nr.: 01-2119463258-33	Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclic, < 2% aromatics. (Note-P) Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H336	25-50%
CAS: 34590-94-8 EINECS: 252-104-2 Reg.nr.: 01-2119450011-60	Dipropylene glycol monomethyl ether substance with a Community workplace exposure limit	≤2.5%
CAS: 22464-99-9 EINECS: 245-018-1 Reg.nr.: 01-2119979088-21	Zirconium 2-ethylhexanoate Repr. 2, H361d	≤0.5%
CAS: 136-52-7 EINECS: 205-250-6 Reg.nr.: 01-2119524678-29	cobalt bis(2-ethylhexanoate) Repr. 1B, H360F Aquatic Acute 1, H400; Aquatic Chronic 1, H410 Eye Irrit. 2, H319; Skin Sens. 1A, H317	≥0.1-<0.25%
CAS: 98-54-4 EINECS: 202-679-0 Index number: 604-090-00-8 Reg.nr.: 01-2119489419-21	4-tert-butylphenol Repr. 2, H361f Eye Dam. 1, H318 Aquatic Chronic 1, H410 Skin Irrit. 2, H315	≥0.025-<0.25%
CAS: 140-66-9 EINECS: 205-426-2 Index number: 604-075-00-6 Reg.nr.: 01-2119541687-29	4-(1,1,3,3-tetramethylbutyl)phenol Eye Dam. 1, H318 Aquatic Acute 1, H400 (M=10); Aquatic Chronic 1, H410 (M=10) Skin Irrit. 2, H315	≥0.025-<0.25%
· SVHC		
98-54-4	4-tert-butylphenol	
140-66-9	4-(1,1,3,3-tetramethylbutyl)phenol	

· Additional information:

Note P: The substance does not have to be classified as a carcinogen or mutagen as can be shown that the substance contains less than 0.1% (w / w) benzene (EINECS No 200-753-7.). This note applies only to certain complex oil-derived substances in Part 3.

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- 4.1 Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.

(Contd. on page 4)



(Contd. of page 3)

- **After inhalation:**
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:**
Immediately wash with water and soap and rinse thoroughly.
Immediately rinse with water.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **5.2 Special hazards arising from the substance or mixture**
No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**
Prevent seepage into sewage system, workpits and cellars.
Inform respective authorities in case of seepage into water course or sewage system.
Dilute with plenty of water.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.

(Contd. on page 5)



- Prevent formation of aerosols.
- Information about fire - and explosion protection:
 Keep ignition sources away - Do not smoke.
 Protect against electrostatic charges.
 Keep respiratory protective device available.
- 7.2 Conditions for safe storage, including any incompatibilities
- Storage:
 Requirements to be met by storerooms and receptacles: No special requirements.
 Information about storage in one common storage facility: Not required.
 Further information about storage conditions: Keep container tightly sealed.
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

- Ingredients with limit values that require monitoring at the workplace:

34590-94-8 Dipropylene glycol monomethyl ether

WEL	Long-term value: 308 mg/m ³ , 50 ppm Sk
-----	---

136-52-7 cobalt bis(2-ethylhexanoate)

WEL	Long-term value: 0.1 mg/m ³ as Co; Carc, Sen
-----	--

34590-94-8 Dipropylene glycol monomethyl ether

WEL	Long-term value: 308 mg/m ³ , 50 ppm Sk
-----	---

136-52-7 cobalt bis(2-ethylhexanoate)

WEL	Long-term value: 0.1 mg/m ³ as Co; Carc, Sen
-----	--

- Regulatory information WEL: EH40/2020

- DNEL (Derived No Effect Level) voor professionals

64742-48-9 Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclic, < 2% aromatics. (Note-P)

Oral	Long-term - systemic effects.	125 mg/kg bw/day (General population)
Inhalative	Long-term - systemic effects.	185 mg/m ³ (General population)

34590-94-8 Dipropylene glycol monomethyl ether

Dermal	Long-term - systemic effects.	65 mg/kg/day (Employees)
Inhalative	Long-term - systemic effects.	310 mg/m ³ (Employees)

22464-99-9 Zirconium 2-ethylhexanoate

Dermal	Long-term - systemic effects.	6.49 mg/kg/day (Employees)
Inhalative	Long-term - systemic effects.	32.97 mg/m ³ (Employees)

136-52-7 cobalt bis(2-ethylhexanoate)

Inhalative	Long-term - local effects.	0.037 mg/m ³ (General population)
	Long-term - systemic effects.	0.2351 mg/m ³ (Employees)

(Contd. on page 6)

98-54-4 4-tert-butylphenol		
Oral	Long-term - systemic effects.	0.1 mg/kg bw/day (General population)
Dermal	Short-term - systemic effects.	16.8 mg/kg (General population) 33 mg/kg (Employees)
Inhalative	Acute - systemic effects. Long-term - systemic effects.	1.8 mg/m ³ (General population) 0.6 mg/m ³ (General population)
140-66-9 4-(1,1,3,3-tetramethylbutyl)phenol		
Inhalative	Long-term - systemic effects.	0.8 mg/m ³ (General population)
· DNEL (Derived No Effect Level) for general audience		
64742-48-9 Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclic, < 2% aromatics. (Note-P)		
Dermal	Long-term - systemic effects.	208 mg/kg bw/day (Employees)
Inhalative	Long-term - systemic effects. Long term - systemic effects.	871 mg/m ³ (Employees) 125 mg/kg bw/day (General population)
34590-94-8 Dipropylene glycol monomethyl ether		
Oral	Long-term systemic effects.	1.67 mg/kg bw/day (General population)
Dermal	Long-term - systemic effects.	15 mg/kg bw/day (General population)
Inhalative	Long-term - systemic effects.	37.2 mg/m ³ (General population)
22464-99-9 Zirconium 2-ethylhexanoate		
Oral	Long-term systemic effects.	4.51 mg/kg bw/day (General population)
Dermal	Long-term - systemic effects.	3.25 mg/kg bw/day (General population)
Inhalative	Long-term - systemic effects.	8.13 mg/m ³ (General population)
136-52-7 cobalt bis(2-ethylhexanoate)		
Oral	Long-term systemic effects.	0.0558 mg/kg bw/day (General population)
98-54-4 4-tert-butylphenol		
Oral	Short-term - systemic effects.	0.5 mg/kg bw/day (General population)
Dermal	Long-term - systemic effects.	11.3 mg/kg bw/day (Employees)
Inhalative	Acute - systemic effects. Long-term - systemic effects. Long term - systemic effects.	2.4 mg/m ³ (Employees) 0.8 mg/m ³ (Employees) 5.6 mg/kg bw/day (General population)
· PNECs		
34590-94-8 Dipropylene glycol monomethyl ether		
	Aquatic compartment.	19 mg/l (Freshwater)

(Contd. on page 7)



	Aquatic compartment. STP Soil Intermittent Soil Sediment	1.9 mg/l (Seawater) 4,168 mg/l (Segmentation, Targeting and Positioning) 70.2 mg/kg (Freshwater) 190 mg/l (Intermittent) 2.74 mg/kg (soil) 7.02 mg/kg (Seawater)
136-52-7 cobalt bis(2-ethylhexanoate)		
	Aquatic compartment. Aquatic compartment. STP Soil Soil Sediment	0.00051 mg/l (Freshwater) 0.00236 mg/l (Seawater) 0.37 mg/l (Segmentation, Targeting and Positioning) 9.5 mg/kg (Freshwater) 7.9 mg/kg (soil) 9.5 mg/kg (Seawater)
98-54-4 4-tert-butylphenol		
Oral	Oral Aquatic compartment. Aquatic compartment. Aquatic compartment - sediment in freshwater Aquatic compartment - sediment in marine water STP Intermittent Soil	0.04667 g/kg (Oral) 0.01 mg/l (Freshwater) 0.001 mg/l (Seawater) 0.27 mg/kg sed dw (Freshwater) 0.027 mg/kg sed dw (Seawater) 1.5 mg/l (Segmentation, Targeting and Positioning) 0.048 mg/l (Intermittent) 0.25 mg/kg (soil)
140-66-9 4-(1,1,3,3-tetramethylbutyl)phenol		
Oral	Oral Aquatic compartment. Aquatic compartment. Aquatic compartment - sediment in freshwater Aquatic compartment - sediment in marine water STP Soil Intermittent	0.00236 g/kg (Oral) 0.001 mg/l (Seawater) 0.001 mg/l (Seawater) 4.62 mg/kg sed dw (Freshwater) 1.23 mg/kg sed dw (Seawater) 0.1 mg/l (Segmentation, Targeting and Positioning) 2.3 mg/kg (soil) 0 mg/l (Intermittent)

· Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

· Appropriate engineering controls No further data; see item 7.

(Contd. on page 8)

- Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
- Respiratory protection:
In case of short or low load, breathing filter device; in the case of intensive or prolonged exposure, use a breathing apparatus independent of the surrounding air. A half-face mask for organic vapours and solvents according to EN140 type A1 or A2 is recommended.
- Hand protection
Use gloves of stable material (e.g. Nitrile) - if necessary tricoted to improve the wearability.



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- Material of gloves
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- Penetration time of glove material
The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
- For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:
Butyl rubber, BR
- As protection from splashes gloves made of the following materials are suitable:
Cloropene; handglove thickness >0.7mm, penetration time >60min. according EN374.
Nitrilrubber; handglove thickness >0.3mm, penetration time >60min. according EN374.
- Eye/face protection



Tightly sealed goggles



(Contd. of page 8)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

· Physical state	Fluid
· Colour:	Brown
· Odour:	Solvent-like
· Odour threshold:	Not determined.
· Melting point/freezing point:	Undetermined.
· Boiling point or initial boiling point and boiling range	154 °C (64742-48-9 Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclic, < 2% aromatics. (Note-P))
· Flammability	Not applicable.
· Lower and upper explosion limit	
· Lower:	Not determined.
· Upper:	Not determined.
· Flash point:	41 °C
· Auto-ignition temperature:	Product is not selfigniting.
· Decomposition temperature:	Not determined.
· pH at 20 °C	7
· Viscosity:	
· Kinematic viscosity at 20 °C	50 s (ISO 4 mm)
· Dynamic:	Not determined.
· Solubility	
· water:	Fully miscible.
· Partition coefficient n-octanol/water (log value)	Not determined.
· Vapour pressure:	Not determined.
· Density and/or relative density	
· Density at 20 °C:	0.91311 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.

9.2 Other information

· Appearance:	
· Form:	Fluid
· Important information on protection of health and environment, and on safety.	
· Ignition temperature:	205 °C
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Solvent content:	
· Organic solvents:	40.5 %
· VOC content:	40.51 % VOC content: 369.9 g/l / 3.09 lb/gal
· Solids content:	59.5 %
· Change in condition	
· Evaporation rate	Not determined.

(Contd. on page 10)



(Contd. of page 9)

- Information with regard to physical hazard classes
- Explosives Void
- Flammable gases Void
- Aerosols Void
- Oxidising gases Void
- Gases under pressure Void
- Flammable liquids Flammable liquid and vapour.
- Flammable solids Void
- Self-reactive substances and mixtures Void
- Pyrophoric liquids Void
- Pyrophoric solids Void
- Self-heating substances and mixtures Void
- Substances and mixtures, which emit flammable gases in contact with water Void
- Oxidising liquids Void
- Oxidising solids Void
- Organic peroxides Void
- Corrosive to metals Void
- Desensitised explosives Void

SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:
 No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products:
 No dangerous decomposition products known.

SECTION 11: Toxicological information

- 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- Acute toxicity

- LD/LC50 values relevant for classification:

34590-94-8 Dipropylene glycol monomethyl ether

Oral	LD50	5,135 mg/kg bw (rat)
Dermal	LD50	>19,000 mg/kg bw (rab)
	Long-term exposure (8 hours TWA): 50 ppm	308 mg/m ³ (Occupational exposure limits)

136-52-7 cobalt bis(2-ethylhexanoate)

Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50 (Konijn)	5,000 mg/kg (rabbit)

(Contd. on page 11)



98-54-4 4-tert-butylphenol		
Oral	LD50	2,951 mg/kg bw (rat)
Dermal	LD50	2,288 mg/kg bw (rabbit)
140-66-9 4-(1,1,3,3-tetramethylbutyl)phenol		
Oral	LD50	3,210 mg/kg bw (mouse)
<ul style="list-style-type: none"> Respiratory or skin sensitisation May cause an allergic skin reaction. STOT-single exposure May cause drowsiness or dizziness. 11.2 Information on other hazards 		
<ul style="list-style-type: none"> Endocrine disrupting properties 		
98-54-4	4-tert-butylphenol	List I, II
140-66-9	4-(1,1,3,3-tetramethylbutyl)phenol	List I

*

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity:

136-52-7 cobalt bis(2-ethylhexanoate)

LC50 0.1-1 mg/l (Fish Acute Toxicity Study)

EC50 0.1-1 mg/l (daphnia magna)

EC50 0.1-1 mg/l (Algae, Growth inhibition test)

- 12.2 Persistence and degradability** No further relevant information available.
- 12.3 Bioaccumulative potential** No further relevant information available.
- 12.4 Mobility in soil** No further relevant information available.
- 12.5 Results of PBT and vPvB assessment**
- PBT:** Not applicable.
- vPvB:** Not applicable.
- 12.6 Endocrine disrupting properties**
For information on endocrine disrupting properties see section 11.
- 12.7 Other adverse effects**
- Remark:** Harmful to fish
- Additional ecological information:**
- General notes:**
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
Harmful to aquatic organisms

*



SECTION 13: Disposal considerations

- 13.1 Waste treatment methods**
- Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- Uncleaned packaging:**
- Recommendation:** Disposal must be made according to official regulations.
(Contd. on page 12)



- Recommended cleansing agents:
Water, if necessary together with cleansing agents.

SECTION 14: Transport information

· 14.1 UN number or ID number	UN1263
· ADR, IMDG, IATA	
· 14.2 UN proper shipping name	1263 PAINT
· ADR	PAINT
· IMDG, IATA	
· 14.3 Transport hazard class(es)	
· ADR	
	
· Class	3 (F1) Flammable liquids.
· Label	3
· IMDG, IATA	
	
· Class	3 Flammable liquids.
· Label	3
· 14.4 Packing group	III
· ADR, IMDG, IATA	
· 14.5 Environmental hazards:	
· Marine pollutant:	No
· 14.6 Special precautions for user	Warning: Flammable liquids.
· Hazard identification number (Kemler code):	30
· EMS Number:	F-E, S-E
· Stowage Category	A
· 14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml



· Transport category	3
· Tunnel restriction code	D/E
· Remarks:	Packaging <450L: exemption viscous substances according to 2.2.3.1.5
<hr/>	
· IMDG	5L
· Limited quantities (LQ)	Code: E1
· Excepted quantities (EQ)	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· Remarks:	≤ 30 l: -
· UN "Model Regulation":	UN 1263 PAINT, 3, III

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Directive 2012/18/EU
- Named dangerous substances - ANNEX I None of the ingredients is listed.
- Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements
5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements
50,000 t
- National regulations:
- Technical instructions (air):

Class	Share in %
NK	25-50

- Waterhazard class:
Water hazard class 1 (Self-assessment): slightly hazardous for water.
- Other regulations, limitations and prohibitive regulations

- Substances of very high concern (SVHC) according to REACH, Article 57

98-54-4	4-tert-butylphenol
140-66-9	4-(1,1,3,3-tetramethylbutyl)phenol

- 15.2 Chemical safety assessment:
A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 14)

**· Relevant phrases**

- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.
- H360F May damage fertility.
- H361d Suspected of damaging the unborn child.
- H361f Suspected of damaging fertility.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.

· Abbreviations and acronyms:

- RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
- ICAO: International Civil Aviation Organisation
- ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- VOC: Volatile Organic Compounds (USA, EU)
- DNEL: Derived No-Effect Level (REACH)
- PNEC: Predicted No-Effect Concentration (REACH)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- SVHC: Substances of Very High Concern
- vPvB: very Persistent and very Bioaccumulative
- Flam. Liq. 3: Flammable liquids - Category 3
- Skin Irrit. 2: Skin corrosion/irritation - Category 2
- Eye Dam. 1: Serious eye damage/eye irritation - Category 1
- Eye Irrit. 2: Serious eye damage/eye irritation - Category 2
- Skin Sens. 1: Skin sensitisation - Category 1
- Skin Sens. 1A: Skin sensitisation - Category 1A
- Repr. 1B: Reproductive toxicity - Category 1B
- Repr. 2: Reproductive toxicity - Category 2
- Repr. 2: Reproductive toxicity - Category 2
- STOT SE 3: Specific target organ toxicity (single exposure) - Category 3
- Asp. Tox. 1: Aspiration hazard - Category 1
- Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1
- Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1
- Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

· * Data compared to the previous version altered.