

## CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY  
tel. +39 0584 383694 fax +39 0584 395182  
www.cecchi.it info@cecchi.it



NAUTILUS DRIVE PRIMER B WINTER CL210 - SAFETY DATA SHEET - January 2020 - batch 031-B0 - rev.1/15

# NAUTILUS DRIVE PRIMER comp. B CL210 (winter)

## 1. Identification of the substance or mixture and the company/enterprise

### 1.1. Product identifier

Name **Nautilus Drive Primer COMP. B CL210 (winter)**

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Description/Purpose product for marine and professional use - **component for epoxy system**  
**- Antifouling primer for propellers, axles and stern feet**

### 1.3. Information about the supplier of the safety data sheet

Business Name **CECCHI GUSTAVO & C. LTD.**  
Address **M.Coppino Street, 253**  
Location and State **55049 VIAREGGIO(LU) ITALY**  
**TEL. +39 0584 383694**  
**FAX +39 0584 395182**

Email of the competent person, responsible for the safety data sheet: **info@cecchi.it**

Responsible for placing on the market: **CECCHI GUSTAVO & C. srl**

### 1.4. Emergency telephone number

For urgent inquiries contact: 0584/383694 office hours 8:30 a.m.-12:30 p.m., 2 p.m.-6:30 p.m. Monday1 through Friday1

## SECTION 2: Hazard Identification.

### 2.1 Classification of the substance or mixture

#### Classification (REGULATION (EC) No. 1272/2008)

Flammable liquids, Category 3 H226:Flammable liquid and vapors. Skin irritation, Category 2 H315: Causes skin irritation.  
Serious eye injury, Category 1 H318: Causes serious eye injury.  
Skin sensitization, Category 1 H317: May cause an allergic skin reaction. Specific target organ toxicity - single exposure, Category 3 H335: May irritate the respiratory tract.

#### Classification (67/548/EEC, 1999/45/EC)

Flammable R10: Flammable.  
Harmful R20/21: Harmful by inhalation and skin contact.  
Sensitizing R43: May cause sensitization by skin contact. Irritant R41: Risk of serious eye injury.  
R37/38: Irritating to respiratory tract and skin.

### 2.2 Label elements

#### Labeling (REGULATION (EC) No. 1272/2008)

Danger pictograms :



Warning : Danger

Hazard statements : H226 Flammable liquid and vapors.

H315 Causes skin irritation.

H317 May cause allergic skin reaction. H318 Causes severe eye injury.

H335 May irritate the respiratory tract.

Precautionary statements : **Prevention:**

P210 Keep away from heat, hot surfaces, sparks, open flames or other sources of ignition. Do not smoke.

P261 Avoid breathing the vapors.

#### **Reaction:**

P303 + P361 + P353 IF ON SKIN (or hair): remove all contaminated clothing immediately.

Rinse skin/take a shower.

P305 + P351 + P338 + P310 IN CASE OF CONTACT WITH

EYES: rinse thoroughly to

## CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY  
tel. +39 0584 383694 fax +39 0584 395182  
www.cecchi.it info@cecchi.it



NAUTILUS DRIVE PRIMER B WINTER CL210 - SAFETY DATA SHEET - January 2020 - batch 031-B0 - rev.1/15

several minutes. Remove any contact lenses if it is comfortable to do so. Continue to rinse.

Contact an ANTIVENTION CENTER or physician immediately.

P362 + P364 Remove all contaminated clothing and wash before wearing again. P370 + P378

In case of fire: use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Hazardous components to be reported on the label:

78-83-1 2-methylpropan-1-ol.

112-24-3 3,6-diazaottano-1,8-diamina

### 2.3 Other hazards

Unknown.

No risk from the material cos1 provided.

The information requested and mentioned in this Safety Sheet.

## SECTION 3: Composition/information on ingredients.

### 3.2 Mixtures

Chemical nature : Liquid solution

#### Hazardous Components

Chemical Name	N. CAS N. EC Registration number	Classification (67/548/EEC)	Classification (REGULATION (EC) No. 1272/2008)	Concentration [%]
2-methylpropan-1-ol	78-83-1 201-148-0 01- 2119484609- 23	R10 Xi; R37/38-R41 R67	Flam. Liq. 3; H226 STOT SE 3; H335, H336 Skin Irrit. 2; H315 Eye Dam. 1; H318	>= 17,5 - < 20
xylene	1330-20-7 215-535-7 01- 2119488216- 32	R10 Xn; R20/21 Xi; R38 Note C	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315	>= 17,5 - < 20
2,4,6- tri(dimethylaminomethy l) phenol	90-72-2 202-013-9  01- 2119560597- 27	Xn; R22 Xi; R36/38	Acute Tox. 4; H302 Skin Irrit. 2; H315  Eye Irrit. 2; H319	>= 5 - < 10
4-Hydroxy-4- methylpentan- 2-one	123-42-2 204-626-7 01- 2119473975- 21	Xi; R36/37	Flam. Liq. 3; H226 Eye Irrit. 2; H319 STOT SE 3; H335	>= 1 - < 5
3,6-diazaoctane-1,8- heck	112-24-3 203-950-6	C; R34 Xn; R21 R43 R52-R53	Acute Tox. 4; H312 Skin Corr. 1B; H314 Skin Sens. 1; H317 Aquatic Chronic 3; H412	>= 1 - < 5
4-methyl-pentan-2-one	108-10-1 203-550-1 01- 2119473980- 30	F; R11 Xn; R20 Xi; R36/37 R66	EUH066 Flam. Liq. 2; H225 Acute Tox. 4; H332 Eye Irrit. 2; H319 STOT SE 3; H335	>= 1 - < 5
Substances with an occupational exposure limit :				
2-methoxy-1- methylethylacetate	108-65-6 203-603-9	R10	Flam. Liq. 3; H226	>= 5 - < 10

## CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY  
tel. +39 0584 383694 fax +39 0584 395182  
www.cecchi.it info@cecchi.it



NAUTILUS DRIVE PRIMER B WINTER CL210 - SAFETY DATA SHEET - January 2020 - batch 031-B0 - rev.1/15

	01- 2119475791- 29			
--	--------------------------	--	--	--

For the full text of the R-phrases mentioned in this section, refer to Section 16.

For the full text of the hazard statements mentioned in this paragraph, refer to paragraph 16.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

General Information : If symptoms persist or if there is any doubt, consult a physician.

Do not administer anything to an unconscious person. If inhaled : Take the casualty to fresh air.

Place the affected person in the resting position and keep warm.

In case of irregular breathing or respiratory arrest give artificial respiration. In case of unconsciousness place on the side in a stable position and consult a doctor.

In case of skin contact: Remove all contaminated clothing immediately.

Wash skin thoroughly with soap and water or use a cleanser approved by medical authorities. Do not use solvents or thinners.

Arrange showers in the workplace

In case of eye contact

: Keep eyelids open and rinse copiously with clean water for at least 10 minutes. Consult a physician.

Arrange eyewash at the workplace

Remove contact lenses.

If swallowed : If swallowed, seek medical attention immediately. DO NOT induce vomiting.

Keep at rest.

#### 4.2 Main symptoms and effects, both acute and delayed

Symptoms : No information available. Risks : No information available.

#### 4.3 Indication of whether immediate medical attention and special treatment are needed

Treatment : First Aid procedure should be agreed upon in consultation with the competent occupational physician.

Consult a physician.

### SECTION 5: Fire-fighting measures

#### 5.1 Extinguishing media

Suitable extinguishing media : Use water fog, alcohol-resistant foam, dry chemicals or carbon dioxide.

Cool the containers and surroundings with water spray. Unsuitable extinguishing media

: DO NOT use water jets.

#### 5.2 Special hazards arising from the substance or mixture

Specific hazards against fire

: Because the product contains combustible organic components, its combustion will produce a dense black smoke containing hazardous combustion products (see Section 10). Inhalation of decomposition products can cause health damage.

Cool closed containers near flames with water spray.

Collect contaminated water used to extinguish the fire separately. Do not discharge it into the sewage system.

Dispose of contaminated water used for extinguishment and fire residue according to current regulations.

#### 5.3 Recommendations for firefighters.

## CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY  
tel. +39 0584 383694 fax +39 0584 395182  
www.cecchi.it info@cecchi.it



NAUTILUS DRIVE PRIMER B WINTER CL210 - SAFETY DATA SHEET - January 2020 - batch 031-B0 - rev.1/15

Special protective equipment for firefighters

: If necessary, wear a self-contained breathing apparatus to extinguish the fire.

### **SECTION 6: Measures in case of accidental release**

**6.1 Personal precautions, protective equipment and emergency procedures** Individual precautions : Solvent vapors are heavier than air and spread to the ground. Provide adequate ventilation.

Use personal protective equipment.

Evacuate personnel to safe areas.

Keep people away from the leak, upwind. Air the premises.

### **6.2 Environmental precautions**

Environmental precautions : Prevent the material from seeping into drains or waterways.

In case of pollution of rivers, lakes or sewers, inform the relevant authorities in accordance with local laws.

### **6.3 Methods and materials for containment and remediation**

Cleaning methods : Clean with detergents. Avoid the use of solvents.

Contain and collect accidental spills with non-combustible absorbent material (such as sand, soil, kieselguhr, vermiculite) and place in a container for disposal according to local or national guidelines (refer to Section 13).

Pick up and transfer to an appropriately labeled container. Thoroughly clean the contaminated surface.

Curb.

Impregnate with inert absorbent material and dispose of as waste (see SEC. 13).

### **6.4 References to other sections**

Refer to Section 15 for specific national guidelines.

## **SECTION 7: Handling and Storage.**

### **7.1 Precautions for safe handling**

Warnings for safe use

: Do not exceed the occupational exposure limit (Cf.Sect.8). Use only in areas provided with appropriate ventilation systems. Avoid contact with skin, eyes and clothing. Do not eat, drink or smoke while working.

Do not inhale vapors or mists.

See Section 8 for personal protective equipment. Mix well before use

Keep container tightly closed after use Fire and explosion directions

: Prevent the formation of concentrations of explosive or flammable vapors and prevent these concentrations from exceeding the

Expected occupational exposure limits.

In the decants, check the grounding and if necessary

Take appropriate measures; use only conductive piping. Employ non-sparking tools.

The product cannot be used in areas where there are unprotected lights or other sources of flame or spark.

Prohibited Smoking.

### **7.2 Conditions for safe storage, including any incompatibilities**

Warehouse and container requirements

: Observe the directions on the label.

Close open containers carefully and store them upright to prevent leakage. Solvent vapors are heavier than air and propagate to the ground.

Vapors can form explosive mixtures with air. Electrical installations and working materials must comply with current safety and technical standards.

Store away from flames and sparks. Do not smoke.

Store at a temperature between 5° and 35°C, in an airy room, protected from heat sources, flames and direct light

Store in compliance with special national guidelines.

## CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY  
tel. +39 0584 383694 fax +39 0584 395182  
www.cecchi.it info@cecchi.it



NAUTILUS DRIVE PRIMER B WINTER CL210 - SICURE SHEET - January 2020 - batch 031-B0 - rev.1/15

Indications for storage together with other products.

: Keep away from oxidizing agents, strong acids or bases.

### 7.3 Specific end uses

: This information is not available.

## SECTION 8: Exposure control/personal protection.

### 8.1 Control parameters Control parameters

Components	N. CAS	Value	Control parameters	Update	Base
Isobutanol	78-83-1	TWA	50 ppm 152 mg/m <sup>3</sup>		
xylene	1330-20-7	TWA	50 ppm 221 mg/m <sup>3</sup>	2000-06-16	2000/39/EC
More information	Skin: Identify the possibility of significant absorption through the pelleIndicative				
		STEL	100 ppm 442 mg/m <sup>3</sup>	2000-06-16	2000/39/EC
More information	Skin: Identify the possibility of significant absorption through the pelleIndicative				
2-methoxy-1-methylethyl acetate	108-65-6	TWA	50 ppm 275 mg/m <sup>3</sup>	2000-06-16	2000/39/EC
More information	Skin: Identify the possibility of significant absorption through the pelleIndicative				
		STEL	100 ppm 550 mg/m <sup>3</sup>	2000-06-16	2000/39/EC
More information	Skin: Identify the possibility of significant absorption through the pelleIndicative				
Diacetonalcool	123-42-2	TWA	50 ppm 238 mg/m <sup>3</sup>		
methyl isobutyl ketone	108-10-1	TWA	20 ppm 83 mg/m <sup>3</sup>	2000-06-16	2000/39/EC
More information	Indicative				
		STEL	50 ppm 208 mg/m <sup>3</sup>	2000-06-16	2000/39/EC
More information	Indicative				

### DNEL

2,4,6-tri(dimethyl-aminomethyl) phenol

: End use: Industrial use

Route of exposure: Inalation

Potential health consequences: Local effects Value:

0.31 mg/m<sup>3</sup>

### PNEC

2,4,6-tri(dimethyl-aminomethyl)

phenol

: Fresh water Value:

0.84 mg/l

### 8.2 Exposure controls

#### Personal protection

Respiratory protection : Apply the necessary technical measures not to exceed the values

## CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY  
tel. +39 0584 383694 fax +39 0584 395182  
www.cecchi.it info@cecchi.it



NAUTILUS DRIVE PRIMER B WINTER CL210 - SAFETY DATA SHEET - January 2020 - batch 031-B0 - rev.1/15

occupational exposure limit.

This is achievable by good general air exchange or, separable, by local exhaust ventilation. If for technical reasons the exposure limit value cannot be met, temporarily use an appropriate protective breathing apparatus.

Respiratory apparatus with integrated dust/particle filter (EN 141).

Hand protection : Solvent resistant gloves (butyl rubber) In case of prolonged or repeated contact use gloves. Protective gloves according to EN 374.

Please observe the instructions regarding permeability and penetration time that are provided by the glove supplier. Please also want to consider the specific local conditions under which the product is used, such as danger of cuts, abrasion and duration of contact.

If used in solution, or mixed with other substances, and under conditions other than those mentioned in EN 374, contact the supplier of CE-approved gloves.

Protective creams can increase the protective screen on exposed areas of the skin; however, they should not be

Apply once the skin has already been exposed. After contact, wash the skin thoroughly.

Wash hands and put on protective creams before starting work  
Eye protection : Use goggles suitable for chemical hazards. Skin and body protection

: After contact, wash the skin thoroughly.

Do not wear work clothes whose fibers may melt in case of fire. Personnel should wear protective clothing.

Workers must use antistatic shoes.

### Environmental exposure controls

General Information : Prevent material from seeping into drains or waterways.

In case of pollution of rivers, lakes or sewers, inform the relevant authorities in accordance with local laws.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Appearance :	liquid
Odor :	solvent
Flash point.:	> 23 - 55 °C
Ignition temperature :	notdetermined
Lower explosive limit :	No data available Upper
explosive limit :	No data available Auto-ignition
temperature :	not applicable
pH :	not determined
Freezing point :	not applicable
Boiling point :	notdetermined
Vapor pressure :	1,000 hPa at 50 °C
Density :	0.9212 g/cm <sup>3</sup>
Water solubility :	not determined
Partition coefficient: nottanol/water :	No data available Solubility in other
solvents :	not determined
Flow time :	55 s4
	mm
	Method: ASTM D 1200 '82
Relative vapor density :	not applicable
Evaporation rate :	notdetermined

### 9.2 More information

Dry Residue :	49.54 %
Content of compounds volatile organics (VOCs):	50.45 %.

## CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY  
tel. +39 0584 383694 fax +39 0584 395182  
www.cecchi.it info@cecchi.it



NAUTILUS DRIVE PRIMER B WINTER CL210 - SAFETY DATA SHEET - January 2020 - batch 031-B0 - rev.1/15

### SECTION 10: Stability and responsiveness.

#### 10.1 Reactivity

None reasonably foreseeable.

#### 10.2 Chemical stability

The product is chemically stable.

#### 10.3 Possibility of dangerous reactions

Hazardous reactions : No hazardous reaction is known when used under normal conditions.

#### 10.4 Conditions to avoid

Conditions to avoid : Our products are formulated by taking the necessary precautions to avoid decomposition and degradation under the prescribed conditions of use.

Due to the nature of the product, it is recommended that it be left in its original packaging avoiding decanting

#### 10.5 Incompatible materials

Materials to avoid : Store away from oxidizing agents and strongly alkaline or acidic materials in order to avoid exothermic reactions.

#### 10.6 Hazardous decomposition products

Hazardous decomposition products

: Coal dioxide, (CO<sub>2</sub>), coal monoxide (CO), nitrogen oxides (NO<sub>x</sub>), dense black smoke. Thermal decomposition : not applicable

### SECTION 11: Toxicological Information.

#### 11.1 Information on toxicological effects

##### Product

Acute oral toxicity : Acute toxicity estimate: > 2,000 mg/kg, Calculation method Acute inhalation

toxicity : Acute toxicity estimate: > 20 mg/l, 4 h, vapor, Calculation method Acute dermal toxicity :

Acute toxicity estimate: > 2,000 mg/kg, Calculation method

Skin corrosion/irritation : Repeated or prolonged contact with the product may cause removal of the skin's natural fat and its subsequent dehydration., The product may be adsorbed through the skin. Severe eye injury/irritation.

severe ocular

: Splashing into the eyes can cause irritation and reversible damage.

Additional Information : Keep in mind the concentration of individual substances in order to evaluate the toxicological effects resulting from exposure to the preparation.

##### Components:

##### xylene :

Acute dermal toxicity : Acute toxicity estimate: 1,100 mg/kg, Conversion to point estimate of acute toxicity

##### 2,4,6-tri(dimethyl-aminomethyl) phenol :

Acute oral toxicity : Acute toxicity estimate: 500 mg/kg, Conversion to point estimate of acute toxicity

##### 4-idrossi-4-metil-pentan-2-one :

Acute oral toxicity : LD50: 3,002 mg/kg, rat Acute inhalation

toxicity : LC0: >= 7.6 mg/l, rat Acute dermal toxicity : LD50:

> 1,875 mg/kg, rat **3,6-diazaoctane-1,8-diamine** :

Acute dermal toxicity : Acute toxicity estimate: 1,100 mg/kg, Conversion to point estimate of acute toxicity

### SECTION 12: Ecological Information

#### 12.1 Toxicity

Fish toxicity :

Remarks:

No specific product information is available. Fish toxicity

4-idrossi-4-metil-pentan-2-one

: LC50: > 100 mg/l

Exposure time: 96 h

Species: Oryzias latipes (Orange-red cypriniformes)

## CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY  
tel. +39 0584 383694 fax +39 0584 395182  
www.cecchi.it info@cecchi.it



NAUTILUS DRIVE PRIMER B WINTER CL210 - SAFETY DATA SHEET - January 2020 - batch 031-B0 - rev.1/15

### 12.2 Persistence and degradability

Biodegradability : No data available

### 12.3 Bioaccumulation potential

Bioaccumulation : No data available

### 12.4 Mobility in soil

Mobility : No data available

### 12.5 Results of PBT and vPvB assessment

The mixture does not contain any substance considered to be persistent, bioaccumulative or toxic (PBT), The mixture does not contain any substance considered to be very persistent or very bioaccumulative (vPvB).

This substance/mixture contains no components that are considered either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at concentrations of 0.1% or higher.

### 12.6 Other adverse

**effects** Additional  
ecological information

: The product contains substances (listed in Chapter 3) that are hazardous to the environment  
Keep in mind the concentration of individual substances in order to assess the toxicological effects resulting from exposure to the preparation.

## SECTION 13: Disposal considerations.

### 13.1 Waste treatment methods

Product : Product must not enter sewers, waterways or soil. Disposal with household waste is not permitted.

Special disposal must be carried out according to local legislation.

Contaminated containers : Empty containers should be transported to an approved site for recycling or disposal.

According to the European Waste Catalog, waste codes are not product-specific, but application-specific. The waste code should be assigned followed discussion between the user, the producer and the waste disposal company.

The following waste codes are only suggestions: 150110\*

## SECTION 14: Transportation Information

### 14.1 UN number

ADR : UN 3469

IMDG : UN 3469

IATA : UN 3469

### 14.2 UN proper shipping name

ADR PAINT RELATED MATERIAL, FLAMMABLE,  
CORROSIVE

IMDG PAINT RELATED MATERIAL, FLAMMABLE,  
CORROSIVE

IATA PAINT RELATED MATERIAL, FLAMMABLE,  
CORROSIVE

### 14.3 ADR transport-related hazard classes:3

(8)

IMDG : 3 (8)

IATA : 3 (8)

### 14.4 ADR Packaging

#### Group

Packing group : III

Classification code : FC

Hazard Identification No. :38

Labels : 3 (8)



## CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY  
tel. +39 0584 383694 fax +39 0584 395182  
www.cecchi.it info@cecchi.it



NAUTILUS DRIVE PRIMER B WINTER CL210 - SICURE SHEET - January 2020 - batch 031-B0 - rev.1/15

### IMDG

Packing group :III Labels :

EmS Code : 3(8)  
F-E,S-D

### IATA

Packing group :III Labels :

3(8)

### 14.5 Environmental

#### Hazards ADR

Dangerous for the environment : no

#### IMDG

Marine pollutant : no

#### IATA

Dangerous for the environment : no

### 14.6 Special precautions for users

not applicable

### 14.7 Transportation of bulk cargo according to MARPOL Annex II 73/78 and the IBC Code.

Not applicable to the product in its supplied form.

## SECTION 15: Regulatory Information

**15.1 Health, safety and environmental regulations and legislation specific to the substance or mixture** REACH - Candidate List of Substances of Very High Concern for Authorization (Article 59). : not applicable

MAL code number (DK) : 4-5 (1993)

2,243-m3 air/10 g

Risk classification, according to the VbF

: Exempt

: Exempt

Refer to the user's defined free text Class of contamination

of water (Germany)

: water contaminant VVVWS

A4

This MSDS complies with the requirements of Regulation (EC) No. 1907/2006 Regulation (EC)

No. 1272/2008 on classification, labeling and packaging of substances and mixtures

The product is classified and labeled according to Directive 1999/45/EC.

### 15.2 Chemical safety assessment

No specific product information is available.

## SECTION 16: Other information.

### Full text of R sentences quoted in Chapters 2 and 3

R10 Flammable.

R11 Highly flammable. R20

Harmful by inhalation.

R20/21 Harmful by inhalation and skin contact. R21

Harmful in contact with skin.

R22 Harmful if swallowed.

R34 Causes burns.

R36/37 Irritating to eyes and respiratory tract. R36/38

Irritating to eyes and skin.

R37/38 Irritating to respiratory tract and skin.

R38 Irritating to skin.

## CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY  
tel. +39 0584 383694 fax +39 0584 395182  
www.cecchi.it info@cecchi.it



NAUTILUS DRIVE PRIMER B WINTER CL210 - SAFETY DATA SHEET - January 2020 - batch 031-B0 - rev.1/15

R41 Risk of serious eye injury.

R43 May cause sensitization by skin contact. R52 Harmful to aquatic organisms.

R53 May cause long-term adverse effects to the aquatic environment. R66 Repeated exposure may cause skin dryness and cracking. R67 Inhalation of vapors may cause drowsiness and dizziness.

**Full text of hazard statements (H) cited in sections 2 - 3.** EUH066 Repeated exposure may cause skin dryness or cracking. H225 Highly flammable liquid and vapors.

H226 Flammable liquid and vapors. H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and serious eye injury.

H315 Causes skin irritation.

H317 May cause allergic skin reaction. H318 Causes severe eye injury.

H319 Causes severe eye irritation. H332 Harmful if inhaled.

H335 May irritate the respiratory tract.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic organisms with long-lasting effects.

The information in this Safety Data Sheet is correct to the best of our knowledge of the product at the time of publication. This information is provided for the sole purpose of enabling the product to be used, stored, transported, and disposed of in the most proper and safe manner. This information should not be considered a guarantee or specification of the quality of the product. It relates only to the material specifically indicated and does not apply to the same when used in combination with other materials or in other processes not specifically indicated in the text of the Material Safety Data Sheet.