



## SPINNAKER EGGSHELL YACHT VARNISH

### \* SECTION 1 Identification of the substance/preparation and of the company/undertaking

#### 1.1 Product identifier

Trade name: **SPINNAKER EGGSHELL**

UFI: **GS00-G0MT-Y00G-MPRE**

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Product category **PC9a Coatings and paints, thinners, paint removers**

Process category **PROC10 Roller application or brushing**

Environmental release category

**ERC10b Wide dispersive outdoor use of long-life articles and materials with high or intended release (including abrasive processing)**

**ERC2 Formulation of preparations**

Application of the substance / the mixture

See our technical datasheet for application of this product.

#### 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

**Cecchi Gustavo & C. srl** - Via M. Coppino 253, 55049 Viareggio (LU) ITALY [www.cecchi.it](http://www.cecchi.it) - [info@cecchi.it](mailto:info@cecchi.it)

#### 1.4 Emergency telephone number:

: +39 0584/383694 - [info@cecchi.it](mailto:info@cecchi.it)

From monday to friday office hours 8:30 – 12:30, 14:00 – 18:30

\*

- 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



flame

**Flam. Liq. 3 H226 Flammable liquid and vapour.**

**STOT SE 3 H336 May cause drowsiness or dizziness.**

(Contd. on page 2)

GB



- 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008  
The product is classified and labelled according to the CLP regulation.
- Hazard pictograms



GHS02



GHS07

- Signal word Warning
- Hazard-determining components of labelling:  
Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclic, < 2% aromatics. (Note-P)
- Hazard statements  
H226 Flammable liquid and vapour.  
H336 May cause drowsiness or dizziness.
- Precautionary statements  
P102 Keep out of reach of children.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P260 Do not breathe dust/fume/gas/mist/vapours/spray.  
P271 Use only outdoors or in a well-ventilated area.  
P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.  
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.  
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].  
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- Additional information:  
EUH066 Repeated exposure may cause skin dryness or cracking.  
Contains cobalt carboxylate, can cause an allergic reaction.
- 2.3 Other hazards
- Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.

\*

- 3.2 Mixtures
- Description:  
Resin mixture  
Solvent mixture with additives  
Mixture of synthetic binders, matting agent, additives  
and organic solvents

(Contd. on page 3)

GB



· Dangerous components:		
CAS: 64742-48-9 EC number: 919-857-5 Index number: 649-327-00-6 Reg.nr.: 01-2119463258-33	Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclic, < 2% aromatics. (Note-P)	25-50%
	Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H336	
CAS: 107-98-2 EINECS: 203-539-1 Index number: 603-064-00-3 Reg.nr.: 01-2119457435-35	1-methoxy-2-propanol	≤2.5%
	Flam. Liq. 3, H226 STOT SE 3, H336	
CAS: 136-52-7 EINECS: 205-250-6 Reg.nr.: 01-2119524678-29	Cobalt bis(2-ethylhexanoate)	<0.3%
	Repr. 1B, H360F Aquatic Acute 1, H400; Aquatic Chronic 1, H410 Eye Irrit. 2, H319; Skin Sens. 1A, H317	

## · Additional information:

Note P: The substance does not have to be classified as a carcinogen or mutagen as can be shown that the substance contains less than 0.1% (w / w) benzene (EINECS No 200-753-7.). This note applies only to certain complex oil-derived substances in Part 3.

For the wording of the listed hazard phrases refer to section 16.

\*

- 4.1 Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Immediately rinse with water.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed  
No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed  
No further relevant information available.

\*

- 5.1 Extinguishing media
- Suitable extinguishing agents:  
CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture  
During heating or in case of fire poisonous gases are produced.

(Contd. on page 4)



- 5.3 Advice for firefighters
- Protective equipment: Mouth respiratory protective device.

\*

- 6.1 Personal precautions, protective equipment and emergency procedures  
Ensure adequate ventilation  
Mount respiratory protective device.  
Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions:  
Prevent seepage into sewage system, workpits and cellars.  
Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.
- 6.4 Reference to other sections  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

\*

- 7.1 Precautions for safe handling  
Keep away from heat and direct sunlight.  
Ensure good ventilation/exhaustion at the workplace.  
Prevent formation of aerosols.
- Information about fire - and explosion protection:  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.  
Keep respiratory protective device available.
- 7.2 Conditions for safe storage, including any incompatibilities
- Storage:  
Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- 7.3 Specific end use(s) No further relevant information available.

\*

- 8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:		
107-98-2 1-methoxy-2-propanol		
WEL	Short-term value: 560 mg/m <sup>3</sup> , 150 ppm Long-term value: 375 mg/m <sup>3</sup> , 100 ppm	
Sk		

(Contd. on page 5)

GB



136-52-7 cobalt bis(2-ethylhexanoate)		
WEL	Long-term value: 0.1 mg/m <sup>3</sup> as Co; Carc, Sen	
107-98-2 1-methoxy-2-propanol		
WEL	Short-term value: 560 mg/m <sup>3</sup> , 150 ppm Long-term value: 375 mg/m <sup>3</sup> , 100 ppm Sk	
136-52-7 cobalt bis(2-ethylhexanoate)		
WEL	Long-term value: 0.1 mg/m <sup>3</sup> as Co; Carc, Sen	

- Regulatory information WEL: EH40/2020
- Additional information: The lists valid during the making were used as basis.
- 8.2 Exposure controls
- Appropriate engineering controls No further data; see item 7.
- Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:  
Immediately remove all soiled and contaminated clothing  
Wash hands before breaks and at the end of work.
- Respiratory protection:  
Not necessarily with good ventilation, however, use a filter AX when ventilation is inadequate!
- Hand protection

#### Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- Material of gloves  
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- Penetration time of glove material  
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:  
Butyl rubber, BR
- As protection from splashes gloves made of the following materials are suitable:  
Cloropene; handglove thickness >0.7mm, penetration time >60min. according EN374.  
Nitrilrubber; handglove thickness >0.3mm, penetration time >60min. according EN374.

(Contd. on page 6)



- Eye/face protection

Tightly sealed goggles

★

- 9.1 Information on basic physical and chemical properties
- General Information
- Physical state Fluid
- Colour: According to product specification
- Odour: Characteristic
- Odour threshold: Not determined.
- Melting point/freezing point: Undetermined.
- Boiling point or initial boiling point and boiling range 150 °C
- Flammability Not applicable.
- Lower and upper explosion limit
- Lower: 0.6 Vol %
- Upper: 7 Vol %
- Flash point: >42 °C
- Auto-ignition temperature: Product is not selfigniting.
- Decomposition temperature: Not determined.
- pH Not determined.
- Viscosity:
- Kinematic viscosity at 20 °C 35 s (ISO 6 mm)
- Dynamic: Not determined.
- Solubility
- water: Not miscible or difficult to mix.
- Partition coefficient n-octanol/water (log value) Not determined.
- Vapour pressure at 20 °C: 1 hPa
- Density and/or relative density
- Density at 20 °C: 0.92854 g/cm<sup>3</sup>
- Relative density Not determined.
- Vapour density Not determined.
- 9.2 Other information
- Appearance:
- Form: Fluid
- Important information on protection of health and environment, and on safety.
- Ignition temperature: 240 °C
- Explosive properties: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

(Contd. on page 7)

GB



· Solvent content:	
· Organic solvents:	51.0 %
· VOC content:	50.95 %
	VOC content:
	473.1 g/l / 3.95 lb/gal
· Solids content:	51.9 % (SC % 1h150 C)
· Change in condition	
· Evaporation rate	Not determined.
· Information with regard to physical hazard classes	
· Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Flammable liquid and vapour.
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

## SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:  
No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products:  
No dangerous decomposition products known.

## SECTION 11: Toxicological information

- 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- Acute toxicity

· LD/LC50 values relevant for classification:

107-98-2 1-methoxy-2-propanol

Oral	LD50	5,660 mg/kg bw (rat)
------	------	----------------------

(Contd. on page 8)



Dermal	LD50	13,000 mg/kg bw (rabbit)
Inhalative	LC50/4 h	6 mg/l (rat)
136-52-7 cobalt bis(2-ethylhexanoate)		
Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50 (Konijn)	5,000 mg/kg (rabbit)

- STOT-single exposure May cause drowsiness or dizziness.
- 11.2 Information on other hazards

- Endocrine disrupting properties

None of the ingredients is listed.

## SECTION 12: Ecological information

- 12.1 Toxicity

- Aquatic toxicity:

136-52-7 cobalt bis(2-ethylhexanoate)

LC50	0.1-1 mg/l (Fish Acute Toxicity Study)
EC50	0.1-1 mg/l (daphnia magna)
EC50	0.1-1 mg/l (Algae, Growth inhibition test)

- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.
- 12.6 Endocrine disrupting properties  
The product does not contain substances with endocrine disrupting properties.
- 12.7 Other adverse effects
- Additional ecological information:
- General notes:  
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water  
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

## SECTION 13: Disposal considerations



- 13.1 Waste treatment methods
- Recommendation  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.

GB

(Contd. on page 9)



**SECTION 14: Transport information**

· 14.1 UN number or ID number	UN1263
· ADR, IMDG, IATA	
· 14.2 UN proper shipping name	1263 PAINT
· ADR	PAINT
· IMDG, IATA	
· 14.3 Transport hazard class(es)	
· ADR	
	
· Class	3 (F1) Flammable liquids.
· Label	3
· IMDG, IATA	
	
· Class	3 Flammable liquids.
· Label	3
· 14.4 Packing group	III
· ADR, IMDG, IATA	
· 14.5 Environmental hazards:	
· Marine pollutant:	No
· 14.6 Special precautions for user	Warning: Flammable liquids.
· Hazard identification number (Kemler code):	30
· EMS Number:	F-E, <u>S-E</u>
· Stowage Category	A
· 14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· Transport category	3
· Tunnel restriction code	D/E
· Remarks:	Packaging <450L: exemption viscous substances according to 2.2.3.1.5

(Contd. on page 10)



(Contd. of page 9)

· IMDG	5L
· Limited quantities (LQ)	Code: E1
· Excepted quantities (EQ)	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· Remarks:	≤ 30 l: -
· UN "Model Regulation":	UN 1263 PAINT, 3, III

**SECTION 15: Regulatory information**

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Directive 2012/18/EU
- Named dangerous substances - ANNEX I None of the ingredients is listed.
- Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- National regulations:
- Technical instructions (air):

Class	Share in %
NK	50-100
- Waterhazard class:  
Water hazard class 1 (Self-assessment): slightly hazardous for water.
- 15.2 Chemical safety assessment:  
A Chemical Safety Assessment has not been carried out.

**SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

## Relevant phrases

- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.
- H360F May damage fertility.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.

(Contd. on page 11)



· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of

Chemicals EINECS: European Inventory of Existing Commercial Chemical

Substances ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids - Category 3

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Skin Sens. 1A: Skin sensitisation - Category 1A

Repr. 1B: Reproductive toxicity - Category 1B

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

· **\* Data compared to the previous version altered.**