Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it

C-SYSTEMS 10 10 UV PROTECTION comp. A - Scheda dati sicurezza - marzo 2022 - nº batch 084-B2 - rev.1/22



C-SYSTEMS 10 10 UV PROTECTION componente A

SEZIONE 1: Identificazione della sostanza o della miscela e della società/ impresa

1.1 Identificatore del prodotto

Nome commerciale: C-SYSTEMS 10 10 UV PROTECTION component A

UFI : 7Y10-K09D-800E-VFWA

1.2 Usi pertinenti identificati della sostanza o miscela e usi sconsigliati

Utilizzazione della sostanza/della miscela

1.3 Informazioni sul fornitore della scheda di dati di sicurezza

Società Cecchi Gustavo & C. srl - Via M. Coppino 253,

55049 Viareggio (LU) ITALY www.cecchi.it - info@cecchi.it

1.4 Numero telefonico di emergenza: +39 0584 383694 - info@cecchi.it

orario ufficio da lunedì a martedì 8:30 - 12:30, 14:00 - 18:30

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Skin irritation, Category 2 H315: Causes skin irritation.

Serious eye damage, Category 1 H318: Causes serious eye damage.

Skin sensitisation, Category 1 H317: May cause an allergic skin reaction.

Long-term (chronic) aquatic hazard, H411: Toxic to aquatic life with long lasting effects.

Category 2

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :





Signal word : Danger

Hazard statements : H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it

C-SYSTEMS 10 10 UV PROTECTION comp. A - Scheda dati sicurezza - marzo 2022 - nº batch 084-B2 - rev.1/22



H318 Causes serious eye damage.

H411 Toxic to aquatic life with long lasting effects.

Prevention: Precautionary statements

> P261 Avoid breathing dust/ fume/ gas/ mist/

> > vapours/ spray.

P264 Wash skin thoroughly after handling. P273 Avoid release to the environment.

P280 Wear protective gloves/ eye protection/ face

protection.

Response:

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously

> with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a

POISON CENTER/ doctor.

P391 Collect spillage.

Hazardous components which must be listed on the label: bis-[4-(2,3-epoxipropoxi)phenyl]propane

1,4-bis(2,3 epoxypropoxy)butane

Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-({2-[4-(oxiran-2ylmethoxy)benzyl]phenoxy}methyl)oxirane

oxirane, mono[(C12-14-alkyloxy)methyl] derivs.

Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6pentamethyl-4-piperidyl Sebacate

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Modified epoxy resin

Hazardous components

Chemical name	CAS-No.	Classification	Concentration
	EC-No./List	(REGULATION	(%)
	Registration number	(EC) No	` ,
		1272/2008)	
bis-[4-(2,3-	1675-54-3	Skin Irrit.2; H315	>= 50 - <= 100

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it

C-SYSTEMS 10 10 UV PROTECTION comp. A - Scheda dati sicurezza - marzo 2022 - nº batch 084-B2 - rev.1/22



epoxipropoxi)phenyl]propane	216-823-5 01-2119456619-26	Eye Irrit.2; H319 Skin Sens.1; H317 Aquatic Chronic2; H411	
1,4-bis(2,3 epoxypropoxy)butane	2425-79-8 219-371-7 01-2119494060-45	Acute Tox.4; H302 Acute Tox.4; H312 Acute Tox.4; H332 Eye Dam.1; H318 Skin Irrit.2; H315 Skin Sens.1; H317 Aquatic Chronic3; H412	>= 12,5 - < 20
Reaction mass of 2,2'- [methylenebis(2,1- phenyleneoxymethylene)]bis(oxiran e) and 2,2'-[methylenebis(4,1- phenyleneoxymethylene)]bis(oxiran e) and 2-({2-[4-(oxiran-2- ylmethoxy)benzyl]phenoxy}methyl)o xirane	9003-36-5 01-2119454392-40	Skin Irrit.2; H315 Skin Sens.1; H317 Aquatic Chronic2; H411	>= 7 - < 10
oxirane, mono[(C12-14- alkyloxy)methyl] derivs.	- 271-846-8 01-2119485289-22	Skin Irrit.2; H315 Skin Sens.1; H317	>= 1 - < 3
Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl Sebacate	1065336-91-5 01-2119491304-40	Skin Sens.1A; H317 Repr.2; H361f Aquatic Acute1; H400 Aquatic Chronic1; H410	>= 0,25 - < 0,5

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Keep warm and in a quiet place.

Show this safety data sheet to the doctor in attendance.

Take off all contaminated clothing immediately.

If inhaled : Move to fresh air.

Keep patient warm and at rest.

If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

If breathing is irregular or stopped, administer artificial

respiration.

In case of skin contact : Wash off immediately with soap and plenty of water.

Do NOT use solvents or thinners. If on clothes, remove clothes.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it

C-SYSTEMS 10 10 UV PROTECTION comp. A - Scheda dati sicurezza - marzo 2022 - nº batch 084-B2 - rev.1/22



If skin irritation persists, call a physician.

In case of eye contact : Rinse immediately with plenty of water, also under the eyelids,

for at least 15 minutes.

If eye irritation persists, consult a specialist. If easy to do, remove contact lens, if worn.

If swallowed : Keep at rest.

Do not induce vomiting without medical advice.

Keep respiratory tract clear.

If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : irritant effects

Redness

sensitising effects

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : The first aid procedure should be established in consultation

with the doctor responsible for industrial medicine.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Foam

Sand

Carbon dioxide (CO2)

Water mist

Unsuitable extinguishing

media

: Water spray jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during

firefighting

: The pressure in sealed containers can increase under the

influence of heat.

Cool closed containers exposed to fire with water spray.

5.3 Advice for firefighters

Special protective equipment

for firefighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

Further information : In the event of fire and/or explosion do not breathe fumes.

Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment. Immediately evacuate personnel to safe areas.

Prevent fire extinguishing water from contaminating surface

water or the ground water system.

Fire residues and contaminated fire extinguishing water must

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it

C-SYSTEMS 10 10 UV PROTECTION comp. A - Scheda dati sicurezza - marzo 2022 - nº batch 084-B2 - rev.1/22



be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Refer to protective measures listed in sections 7 and 8.

Evacuate personnel to safe areas. Use personal protective equipment. Ensure adequate ventilation.

Inform the responsible authorities in case of gas leakage, or of

entry into waterways, soil or drains.

6.2 Environmental precautions

Environmental precautions : Do not allow uncontrolled discharge of product into the

environment.

Try to prevent the material from entering drains or water

courses.

Local authorities should be advised if significant spillages

cannot be contained.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to

local / national regulations (see section 13).

Pick up and transfer to properly labelled containers.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Provide sufficient air exchange and/or exhaust in work rooms.

Avoid inhalation, ingestion and contact with skin and eyes.

Wear personal protective equipment.

Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is

being used.

Advice on protection against

fire and explosion

Keep away from open flames, hot surfaces and sources of

ignition.

Hygiene measures : Provide adequate ventilation. Wash hands and face before

breaks and immediately after handling the product.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it

C-SYSTEMS 10 10 UV PROTECTION comp. A - Scheda dati sicurezza - marzo 2022 - nº batch 084-B2 - rev.1/22



7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: Keep containers tightly closed in a dry, cool and well-ventilated place. Keep in properly labelled containers.

Advice on common storage

: Keep away from oxidizing agents, strongly acid or alkaline

materials and amines.

Keep product and empty container away from heat and

sources of ignition.

Keep away from food and drink.

Other data : Stable at normal ambient temperature and pressure.

7.3 Specific end use(s)

Specific use(s) : Consult the technical guidelines for the use of this

substance/mixture.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Contains no substances with occupational exposure limit values.

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

bis-[4-(2,3- : End Use: Workers

epoxipropoxi)phenyl]propane Exposure routes: Skin contact

Potential health effects: Acute systemic effects, Long-term

systemic effects Value: 8,33 mg/kg End Use: Workers

Exposure routes: Inhalation

Potential health effects: Acute systemic effects, Long-term local

effects

Value: 12,25 mg/m3 End Use: Consumers

Exposure routes: Skin contact

Potential health effects: Acute systemic effects, Long-term

systemic effects Value: 3,571 mg/kg End Use: Consumers Exposure routes: Ingestion

Potential health effects: Acute systemic effects, Long-term

systemic effects Value: 0,75 mg/kg : End Use: Workers

oxirane, mono[(C12-14-alkyloxy)methyl] derivs.

Exposure routes: Skin contact

Potential health effects: Long-term systemic effects

Value: 3,9 mg/kg End Use: Workers

Exposure routes: Inhalation

Potential health effects: Long-term systemic effects

Value: 13,8 mg/m3

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it

C-SYSTEMS 10 10 UV PROTECTION comp. A - Scheda dati sicurezza - marzo 2022 - nº batch 084-B2 - rev.1/22



Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

bis-[4-(2,3- : Fresh water

epoxipropoxi)phenyl]propane Value: 0,006 mg/l

Marine water
Value: 0,0006 mg/l
Intermittent releases
Value: 0,018 mg/l

Sewage treatment plant

Value: 10 mg/l

Fresh water sediment Value: 0,996 mg/kg Marine sediment Value: 0,0996 mg/kg

Soil

Value: 0,196 mg/kg

oxirane, mono[(C12-14- : Sewage treatment plant

alkyloxy)methyl] derivs. Value: 10 mg/l

Fresh water Value: 0,0072 mg/l Marine water Value: 0,00072 mg/l Fresh water sediment Value: 66,77 mg/kg

Marine sediment Value: 6,677 mg/kg

/-I.... 00

Value: 80,12 mg/kg

8.2 Exposure controls

Engineering measures

Effective exhaust ventilation system effective ventilation in all processing areas

Personal protective equipment

Eye protection : Do not wear contact lenses.

Safety glasses with side-shields conforming to EN166

Ensure that eyewash stations and safety showers are close to

the workstation location.

Hand protection

Material : Protective gloves complying with EN 374.

Skin and body protection : Protective suit

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. In the case of vapour formation use a respirator with an

approved filter.

Equipment should conform to EN 14387

Apply technical measures to comply with the occupational

exposure limits.

This should be achieved by a good general extraction and -if practically feasible- by the use of a local exhaust ventilation.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it

C-SYSTEMS 10 10 UV PROTECTION comp. A - Scheda dati sicurezza - marzo 2022 - nº batch 084-B2 - rev.1/22



Protective measures : Avoid contact with skin.

Wear suitable protective equipment.

Environmental exposure controls

General advice : Do not allow uncontrolled discharge of product into the

environment.

Try to prevent the material from entering drains or water

courses.

Local authorities should be advised if significant spillages

cannot be contained.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : liquid

Colour : light yellow

Odour : slight

Odour Threshold : not determined

pH : 4 - 6, 1 %

Melting point/freezing point : Not applicable

Boiling point/boiling range : > 200 °C

Flash point : 150 °C

Evaporation rate : not determined

Upper explosion limit : Not applicable

Lower explosion limit : Not applicable

Vapour pressure : Not applicable

Relative vapour density : not determined

Density : 1,15 g/cm3 (25 °C)

Bulk density : not determined

Solubility(ies)

Solubility in other solvents : not determined

Partition coefficient: n-

octanol/water

: No data available

8 / 18

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it

C-SYSTEMS 10 10 UV PROTECTION comp. A - Scheda dati sicurezza - marzo 2022 - nº batch 084-B2 - rev.1/22



Ignition temperature : Not applicable

Auto-ignition temperature : Not applicable

Thermal decomposition : Method: No data available

Viscosity

Viscosity, dynamic : 800 - 1.200 mPa.s (25 °C)

Viscosity, kinematic : not determined

Explosive properties : Not applicable

Oxidizing properties : Not applicable

9.2 Other information

Surface tension : not determined

Sublimation point : Not applicable

SECTION 10: Stability and reactivity

10.1 Reactivity

Stable under recommended storage conditions.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Reacts with the following substances:

Bases

Strong oxidizing agents

Avoid amines.

10.4 Conditions to avoid

Conditions to avoid : No decomposition if used as directed.

10.5 Incompatible materials

Materials to avoid : Incompatible with oxidizing agents.

10.6 Hazardous decomposition products

Hazardous decomposition

products

: This product may release the following:

Carbon monoxide, carbon dioxide and unburned

hydrocarbons (smoke).

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it

C-SYSTEMS 10 10 UV PROTECTION comp. A - Scheda dati sicurezza - marzo 2022 - nº batch 084-B2 - rev.1/22



SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product:

Acute oral toxicity : Acute toxicity estimate : > 2.000 mg/kg

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate : > 20 mg/l

Exposure time: 4 h

Test atmosphere: vapour Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : > 2.000 mg/kg

Method: Calculation method

Acute toxicity (other routes of :

administration) Remarks: No data available

Components:

bis-[4-(2,3-epoxipropox i)pheny propane:

Acute oral toxicity : LD50 (Rat, female): > 2.000 mg/kg

Method: OECD Test Guideline 420

GLP: yes

Acute dermal toxicity : LD50 (Rat, male and female): > 2.000 mg/kg

Method: OECD Test Guideline 402

GLP: yes

Skin corrosion/irritation

Product:

Remarks: No data available

Components:

bis-[4-(2,3-epoxipropoxi)phenyl]propane:

Species: Rabbit Exposure time: 4 h

Method: OECD Test Guideline 404

Result: Skin irritation

GLP: yes


Serious eye damage/eye irritation

Product:

Remarks: No data available

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it





Respiratory or skin sensitisation

Product:

Remarks: No data available

Components:

bis-[4-(2,3-epoxipropoxi)phenyl]propane:

Test Type: Mouse Local Lymph Node assay (LLNA)

Species: Mouse

Method: OECD Test Guideline 429

Result: May cause sensitisation by skin contact.

GLP: yes

Germ cell mutagenicity

Carcinogenicity

Product:

Remarks: No data available

Reproductive toxicity

Product:

Effects on fertility : Remarks: No data available

Remarks: No data available

Effects on foetal : Remarks: No data available development : Remarks: No data available

STOT - single exposure

Product:

Remarks: No data available

STOT - repeated exposure

Repeated dose toxicity

Product:

Remarks: No data available

Aspiration toxicity

Components:

bis-[4-(2,3-epoxipropoxi)phenyl]propane:

No aspiration toxicity classification

Further information

Product:

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it

C-SYSTEMS 10 10 UV PROTECTION comp. A - Scheda dati sicurezza - marzo 2022 - nº batch 084-B2 - rev.1/22



Remarks: No data available

SECTION 12: Ecological information

12.1 Toxicity

Product:

Toxicity to fish : Remarks: No data available

aquatic invertebrates

Toxicity to daphnia and other : Remarks: No data available

Components:

bis-[4-(2,3-epoxipropoxi)phenyl]propane:

Toxicity to daphnia and other

aquatic invertebrates

: EC50 (Daphnia (water flea)): 1,7 mg/l

Exposure time: 48 h Test Type: static test

Method: OECD Test Guideline 202

GLP: yes

Toxicity to daphnia and other

aquatic invertebrates (Chronic toxicity)

: NOEC: 0,3 mg/l Exposure time: 21 d

Species: Daphnia magna (Water flea)

Test Type: semi-static test

Method: OECD Test Guideline 211

GLP: ves

Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6pentamethyl-4-piperidyl Sebacate:

M-Factor (Short-term (acute)

aquatic hazard)

M-Factor (Long-term (chronic) aquatic hazard) : 1

12.2 Persistence and degradability

Product:

Biodegradability : Remarks: No data available

Physico-chemical

removability

: Remarks: No data available

Components:

bis-[4-(2,3-epoxipropoxi)phenyl]propane:

Biodegradability : Result: Not readily biodegradable.

Method: OECD Test Guideline 301F

GLP: yes

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it

C-SYSTEMS 10 10 UV PROTECTION comp. A - Scheda dati sicurezza - marzo 2022 - nº batch 084-B2 - rev.1/22



12.3 Bioaccumulative potential

Product:

Bioaccumulation : Remarks: No data available

Components:

bis-[4-(2,3-epoxipropoxi)p heny propane:

Partition coefficient: n- : log Pow: 3,242 (25 °C)

octanol/water pH: 7,1

Method: OECD Test Guideline 117

GLP: yes

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher...

12.6 Other adverse effects

Product:

Further information : The substance/mixture does not contain components

considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

Additional ecological

information

: Remarks: An environmental hazard cannot be excluded in the

event of unprofessional handling or disposal.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : In accordance with local and national regulations.

Container hazardous when empty.

Do not dispose of with domestic refuse.

Do not mix waste streams during collection.

Contaminated packaging : Empty containers should be taken to an approved waste

handling site for recycling or disposal.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it

C-SYSTEMS 10 10 UV PROTECTION comp. A - Scheda dati sicurezza - marzo 2022 - nº batch 084-B2 - rev.1/22



SECTION 14: Transport information

14.1 UN number

 ADR/RID/ADN
 : UN 3082

 IMDG
 : UN 3082

 IATA
 : UN 3082

14.2 UN proper shipping name

ADR/RID/ADN : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(bis-[4-(2,3-epoxipropoxi)phenyl]propane)

IMDG : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(bis-[4-(2,3-epoxipropoxi)phenyl]propane)

IATA : Environmentally hazardous substance, liquid, n.o.s.

(bis-[4-(2,3-epoxipropoxi)phenyl]propane)

14.3 Transport hazard class(es)

 ADR/RID/ADN
 : 9

 IMDG
 : 9

 IATA
 : 9

14.4 Packing group

ADR/RID/ADN

Packing group : III
Classification Code : M6
Hazard Identification Number : 90
Labels : 9
Tunnel restriction code : -

Remarks : ADR: These substances when carried in single or

combination packagings containing a net quantity per single or inner packaging of 5 I or less for liquids or having a net mass per single or inner packaging of 5 kg or less for solids, are not

subject to any other provisions of ADR provided the

packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and

4.1.1.4 to 4.1.1.8.

IMDG

Packing group : III
Labels : 9
EmS Code : F-A, S-F

Remarks : IMDG: Marine pollutants packaged in single or combination

packagings containing a net quantity per single or inner packaging of 5 I or less for liquids or having a net mass per single or inner packaging of 5 kg or less for solids are not subject to any other provisions of this Code relevant to marine

pollutants provided the packagings meet the general

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY tel. +39 0584 383694 fax +39 0584 395182 www.cecchi.it info@cecchi.it



C-SYSTEMS 10 10 UV PROTECTION comp. A - Scheda dati sicurezza - marzo 2022 - nº batch 084-B2 - rev.1/22

: 964

provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8. In thecase of marine pollutants also meeting the criteria for inclusion in another hazard class all provisions of this Code relevant to

any additional hazards continue to apply.

IMDG Code segregation group - none

IATA

Packing instruction (cargo

aircraft)

Packing instruction : 964

(passenger aircraft)

Packing group : III Labels : 9

Remarks : IATA: These substances when transported in single or

combination packagings containing a net

quantity per single or inner packaging of 5 L or less far liquids

or having a net mass of 5 kg or less for

solids, are not subject to any other provisions of these Regulations provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.

14.5 Environmental hazards

ADR/RID/ADN

Environmentally hazardous : yes

IMDG

Marine pollutant : yes

IATA

Environmentally hazardous : yes

14.6 Special precautions for user

Remarks : The transport of dangerous goods, including their loading and

unloading, must be done by people who received the necessary training required by Modal Regulations.

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances,

preparations and articles (Annex XVII)

: Not applicable

REACH - Candidate List of Substances of Very High : This product does not contain

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it

C-SYSTEMS 10 10 UV PROTECTION comp. A - Scheda dati sicurezza - marzo 2022 - nº batch 084-B2 - rev.1/22



Concern for Authorisation (Article 59). substances of very high concern

(Regulation (EC) No

1907/2006 (REACH), Article 57).

REACH - List of substances subject to authorisation : Not applicable

(Annex XIV)

Regulation (EC) No 649/2012 of the European : Not applicable

Parliament and the Council concerning the export and

import of dangerous chemicals

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of

major-accident hazards involving dangerous substances.

Quantity 1 Quantity 2

E2 ENVIRONMENTAL 200 t 500 t

HAZARDS

Other regulations : For the product composition, we do not add any of the

substances listed in the European Directive 2011/65/EU

(RoHS 2, RoHS 3, and China RoHS).

The product is thus in line with those directives. We do not add Conflict minerals to the product.

15.2 Chemical safety assessment

Not applicable

SECTION 16: Other information

Items where relevant changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

Full text of H-Statements

H302 : Harmful if swallowed.

H312 : Harmful in contact with skin.

H315 : Causes skin irritation.

H317 : May cause an allergic skin reaction.
H318 : Causes serious eye damage.
H319 : Causes serious eye irritation.

H332 : Harmful if inhaled.

H361f : Suspected of damaging fertility.

H400 : Very toxic to aquatic life.

H410 : Very toxic to aquatic life with long lasting effects.
H411 : Toxic to aquatic life with long lasting effects.
H412 : Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox. : Acute toxicity

Aquatic Acute : Short-term (acute) aquatic hazard
Aquatic Chronic : Long-term (chronic) aquatic hazard

Eye Dam. : Serious eye damage

Eye Irrit. : Eye irritation

Repr. : Reproductive toxicity

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY tel. +39 0584 383694 fax +39 0584 395182

www.cecchi.it info@cecchi.it

C-SYSTEMS 10 10 UV PROTECTION comp. A - Scheda dati sicurezza - marzo 2022 - nº batch 084-B2 - rev.1/22



Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitisation

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN -Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx -Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS -Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP -Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO -International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC -No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD -Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID -Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Training advice : Provide adequate information, instruction and training for

operators.

Classification of the mixture: Classification procedure:

Skin Irrit. 2 H315 Calculation method
Eye Dam. 1 H318 Calculation method
Skin Sens. 1 H317 Calculation method
Aquatic Chronic 2 H411 Calculation method

The information contained herein is based on the present state of our knowledge and does therefore not guarantee certain properties.

GB / EN

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY tel. +39 0584 383694 fax +39 0584 395182 www.cecchi.it info@cecchi.it



C-SYSTEMS 10 10 UV PROTECTION comp. A - Scheda dati sicurezza - marzo 2022 - nº batch 084-B2 - rev.1/22