

CECCHI GUSTAVO & C. s.r.l.

Via M. Coppino 253, 55049 Viareggio (LU) ITALY

Tel. +39 0584 383694

www.cecchi.it info@cecchi.it



C-EPOXY THINNER

TECHNICAL NAME	THINNER FOR BI-COMPONENT EPOXY ENAMELS
EMPLOYMENT	AND PAINTS
SECTORS	C-Epoxy Thinner is used for the dilution of two-component
CHARACTERISTICS	epoxy enamels and paints
GENERAL	

Color:	Colorless transparent
Use:	Dilution of paint products and cleaning of tools
Specific weight:	860 ± 10 g/L at 20°C
VOC content:	860 g/L
Flash point	24°C Abel-Pensky closed cup
packs	0.5 liters
Standards in stock	Avoid exposure to the sun and heat sources. Keep in a cold and dry place
Shelf life	Minimum 12 months in original sealed packaging.
Safety standards	All handling of the products must comply with the hygiene standards for the use of solvent-based paint products and the safety standards shown on the "safety data sheet" according to EEC regulations 89/379 and subsequent amendments
IMPORTANT	The company CECCHI GUSTAVO & C. s.r.l. does not assume responsibility in the case of use of the products, whether the rules of the relative technical data sheets and the conditions of use are not respected or due to manipulation, mixtures with other products, preparation of dyes or other. The product meets our quality standards. In case of particular uses, the responsibility for choosing the product belongs to the user. See general conditions of sale. All data and information provided in this technical data sheet are given in good faith based on our experience at the date of printing of this document, but in any case not binding on our part.